1.B) Consider the following database that maintain information about employees & Departments.

Employee (empid: int, ename:string, age:int, salary:int, deptno:int)
Department (deptno:int, dname: string, manager-id: int)

i. Create the above tables by properly specifying the primary keys & foreign keys.
ii. Enter at least 5 tuples for each relation.
iii. Display emp-id & emp name whose salary lies between 5,000 and 10,000.
iv. List empname & salary for all the employee working for BCA Dept.
v. Display empname & deptname for all the managers.

---

i. Create the above tables by properly specifying the primary keys & foreign keys.

create table employee (empid int, ename varchar(10), age int, salary int , deptno int primary key);

create table dept(deptno references employee, dname varchar(10), mid varchar(10));

ii. Enter at least 5 tuples for each relation.

insert into employee values(1, 'abc' ,20, 10000, 101);
insert into employee values(2, 'abd' ,21, 10000, 102);
insert into employee values(3, 'abe' ,20, 10300, 103);
insert into employee values(4, 'abx' ,21, 10300, 104);
insert into employee values(5, 'abde' ,21, 7000, 105);

select * from employee;

EMPID	ENAME	AGE	SALARY	DEPTNO
1	abc	20	10000	101
2	abd	21	10000	102
3	abe	20	10300	103
4	abx	21	10300	104
5	abde	21	7000	105

insert into dept values(101, 'bca', 80);
insert into dept values(103, 'bcom', 81);
insert into dept values(102, 'bcom', 83);
insert into dept values(104, 'bcom', 84);
insert into dept values(104, 'bcom', 85);

select * from dept;

```
    DEPTNO DNAME        MID
---------- ----------  ----------
       101  bca          80
       103  bcom         81
       102  bcom         83
       104  bcom         84
       104  bcom         85
```

iii. Display emp-id & emp name whose salary lies between 5,000 and 10,000.

select empid,ename from employee where salary between 5000 and 10000;

```
EMPID ENAME
---------- ----------
         1 abc
         2 abd
         5 abde
```

iv. List empname & salary for all the employee working for BCA Dept.

select e.ename,e.salary from employee e,dept d where e.deptno=d.deptno and dname='bca';

```
ENAME        SALARY
----------   ----------
abc          10000
```

v. Display empname & deptname for all the managers.

select e.ename,d.dname,d.mid from employee e,dept d where e.deptno=d.deptno;

```
ENAME      DNAME      MID
---------- ----------  ----------
abc        bca          80
abe        bcom         81
abd        bcom         83
abx        bcom         84
abx        bcom         85
```