



CS 111

Introduction to C Programming

Instructor: Wei Hong (MAE)
Lab: Jiawei Huang (EE)
TA: TBD

About the course



Office Hours:

4:00-5:30 Tue
303 SUSTech Center
(1008 N. Eng. Bldg.)

Credit Distribution:

- In-class performance /quizzes – 10%
- Homework/projects – 50%
- Final Exam – 40%



ChatGPT

ChatGPT knows coding



Write a Java Method to find the largest and smallest number from array



Here is an example Java method that finds the largest and smallest number from an array:

java Copy code

```
public static void findLargestAndSmallest(int[] arr) {  
    int largest = arr[0];  
    int smallest = arr[0];  
  
    for (int i = 1; i < arr.length; i++) {  
        if (arr[i] > largest) {  
            largest = arr[i];  
        } else if (arr[i] < smallest) {  
            smallest = arr[i];  
        }  
    }  
  
    System.out.println("Largest number in the array is: " + largest);  
    System.out.println("Smallest number in the array is: " + smallest);  
}
```

Regenerate response



What does "arr[i] > largest" do in this code?



The expression `arr[i] > largest` in this code is a conditional statement that compares the value of the `i`th element in the `arr` array to the current value of the `largest` variable.

In the method I provided in my previous answer, the loop iterates through the array and compares each element to the current `largest` and `smallest` values. If an element is greater than the current `largest` value, the `largest` variable is updated to that element. The comparison is performed using the greater than (`>`) operator.

So, when the expression `arr[i] > largest` evaluates to `true`, it means that the value of the `i`th element in the `arr` array is greater than the current value of the `largest` variable. In this case, the `largest` variable is updated to the value of the `i`th element.

If the expression `arr[i] > largest` evaluates to `false`, it means that the value of the `i`th element in the `arr` array is not greater than the current value of the `largest` variable. In this case, the value of the `largest` variable remains the same.

Regenerate response

ChatGPT can debug



Sure, here's an example of buggy Python code with some flaws:



python

Copy code

```
def calculate_average(numbers):  
    total = 0  
    count = 0  
  
    for number in numbers:  
        total += number  
    average = total / count  
  
    return average  
  
numbers = [3, 5, 7, 9]  
result = calculate_average(numbers)  
print("The average is: " + str(result))
```

This code has a few flaws:

1. The `count` variable is never incremented, so its value is always 0. As a result, the `average` variable will be assigned a value of `NaN` (Not a Number) because dividing by zero is not a valid operation.
2. The `print()` function call tries to concatenate a string and a number, which is not a valid operation. We need to convert the result to a string using the `str()` function before concatenating it with the rest of the string.
3. The `calculate_average()` function does not handle the case where the `numbers` parameter is an empty list. In this case, dividing by zero will also result in a `NaN` value.

To fix these issues, we can modify the code as follows:

python

Copy code

```
def calculate_average(numbers):  
    total = 0  
    count = len(numbers)  
  
    if count == 0:  
        return None  
  
    for number in numbers:  
        total += number  
  
    average = total / count  
  
    return average  
  
numbers = [3, 5, 7, 9]  
result = calculate_average(numbers)  
if result is not None:  
    print("The average is: " + str(result))  
else:  
    print("The list is empty.")
```

In this fixed version of the code, we:

1. Initialize `count` to the length of the `numbers` list, so we can properly calculate the average.
2. Check if `count` is zero, and return `None` if it is. This way, the caller of the function can handle the `None` value as appropriate.

Regenerate response



The background features a series of overlapping, semi-transparent orange rectangular planes that create a sense of depth and perspective. These planes are arranged in a way that suggests a 3D architectural space. At the bottom of the image, there is a grid of thin orange lines on a light blue-grey surface, which also recedes into the distance, enhancing the perspective effect. The overall color palette is dominated by warm oranges and soft whites, with a cool blue-grey at the base.

**Then why do we
have to learn
programming?**

ChatGPT makes mistakes

which are usually hard to tell



用Python写个解挠曲方程 ($d^4w/dx^4=f(x)$, $x \in (0, 1)$, 边界条件为 $w=d^2w/dx^2=0$) 的有限差分程序



以下是使用有限差分的 Python 代码来解决挠曲方程:

less

Copy code

```
import numpy as np

def beam_bending(f, N):
    h = 1.0/(N+1) # grid size
    x = h*np.arange(1, N+1) # grid points

    # Stiffness matrix
    A = (2 + h**2)*np.eye(N) - np.eye(N, k=1) - np.eye(N, k=-1)

    # Right-hand side vector
    b = h**2*np.array([f(xi) for xi in x])

    # Impose boundary conditions
    b[0] -= 0
    b[-1] -= 0
    A[0,1] = 0
    A[-1,-2] = 0
    A[0,0] = 1
    A[-1,-1] = 1

    # Solve linear system
    w = np.linalg.solve(A, b)
    return w
```

使用方法:

python

Copy code

```
def f(x):
    return np.sin(np.pi*x)

N = 10 # number of grid points
w = beam_bending(f, N) # solve the equation
```

How to master programming?

Practice

Programing languages are also languages

Examples of grammatically correct but **senseless** sentences

Colorless green ideas sleep furiously.

John is a married bachelor.

Examples of syntactically correct but **semantically undefined** codes


```
complex *p = NULL;
```

```
complex abs_p = sqrt(*p >> 4 + p->im);
```

Syntax & Semantics


Chomsky, Noam (September 1956). "Three Models for the Description of Language". *IRE Transactions on Information Theory*. **2** (3): 113–124.

The Turing Machine



Example of a “program” for the Turing Machine


State	Symbol Read	Write Instruction	Move Instruction	Next State
State 0	Blank	Write 'Blank'	Move tape right	State 1
	0	Write '0'	Move tape left	State 0
	1	Write '1'	Move tape left	State 0
State 1	Blank	Write '1'	Move tape left	State 2
	0	Write '1'	Move tape right	State 2
	1	Write '0'	Move tape right	State 1
State 2	Blank	Write 'Blank'	Move tape right	Stop State
	0	Write '0'	Move tape left	State 2
	1	Write '1'	Move tape left	State 2



Alan Turing
(1912 – 1954)




Is human brain a Turing Machine?



Atanasoff-Berry computer (ABC)
the first automatic electronic
digital computer, 1942
Non-programmable,
non-Turing-complete

Early Digital Computers



ENIAC (Electronic Numerical Integrator and
Computer) the first programmable, electronic,
general-purpose digital computer, completed in
1945.
Cost: \$487,000 (~\$6,600,000 in 2022)







EDVAC (Electronic Discrete
Variable Automatic Computer),
1949
Binary, stored-program computer
Cost: \$500,000

Analog

VS.

Digital



Boolean logic

Digital computers use binary numbers

Decimal Number System

5

$$10^2 = 100$$

$$5 = *100$$

Five hundred

7

$$10^1 = 10$$

$$7 = *10$$

seventy

8

$$10^0 = 1$$

$$8 = *1$$

eight

Binary Number System

1

$$2^3 = 8$$

$$1 * 8$$

8

1

$$2^2 = 4$$

$$1 * 4$$

4

0

$$2^1 = 2$$

$$0 * 2$$

0

1

$$2^0 = 1$$


$$1 * 1$$

1

13

Hexadecimal: 0x0D


Von Neumann Architecture (Princeton Architecture)



John von Neumann
(1903-1957)

The First Draft of a Report on the EDVAC, John von Neumann (1945)


Machine code & Assembly language



8086/8088 instructions

Instruction	Meaning	Opcode
ADD	Add	0x00...0x05, 0x80/0...0x81/0, 0x82/0...0x83/0 (since 80186)
ADC	Add with carry	0x10...0x15, 0x80...0x81/2, 0x82...0x83/2 (since 80186)
AND	Logical and	0x20...0x25, 0x80...0x81/4, 0x82...0x83/4 (since 80186)
JMP	Jump	0xE9...0xEB, 0xFF/4, 0xFF/5
MOV	Move	0xA0...0xA3
MUL	Unsigned multiply	0xF7/4, 0xF6/4
SUB	Subtraction	0x28...0x2D, 0x80...0x81/5, 0x82...0x83/5 (since 80186)

High level programming languages



FORTRAN

FORmula TRANslating System

```
C AREA OF A TRIANGLE WITH A STANDARD SQUARE ROOT FUNCTION
C INPUT - TAPE READER UNIT 5, INTEGER INPUT
C OUTPUT - LINE PRINTER UNIT 6, REAL OUTPUT
C INPUT ERROR DISPLAY ERROR OUTPUT CODE 1 IN JOB CONTROL LISTING
  READ INPUT TAPE 5, 501, IA, IB, IC
  501 FORMAT (3I5)
C IA, IB, AND IC MAY NOT BE NEGATIVE OR ZERO
C FURTHERMORE, THE SUM OF TWO SIDES OF A TRIANGLE
C MUST BE GREATER THAN THE THIRD SIDE, SO WE CHECK FOR THAT, TOO
  IF (IA) 777, 777, 701
  701 IF (IB) 777, 777, 702
  702 IF (IC) 777, 777, 703
  703 IF (IA+IB-IC) 777, 777, 704
  704 IF (IA+IC-IB) 777, 777, 705
  705 IF (IB+IC-IA) 777, 777, 799
  777 STOP 1
C USING HERON'S FORMULA WE CALCULATE THE
C AREA OF THE TRIANGLE
  799 S = FLOATF (IA + IB + IC) / 2.0
  AREA = SQRTF( S * (S - FLOATF(IA)) * (S - FLOATF(IB)) *
+ (S - FLOATF(IC)))
  WRITE OUTPUT TAPE 6, 601, IA, IB, IC, AREA
  601 FORMAT (4H A= ,I5,5H B= ,I5,5H C= ,I5,8H AREA= ,F10.2,
+ 13H SQUARE UNITS)
  STOP
END
```

IBM

FORTRAN Coding Form

PROGRAM _____ DATE _____ PUNCHING INSTRUCTIONS _____ GRAPHIC PUNCH _____ PAGE OF _____ CARD ELECTRO NUMBER* _____


STATEMENT NUMBER _____ FORTRAN STATEMENT _____ IDENTIFICATION SEQUENCE _____

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80

* A standard card form, IBM electro 888187, is available for punching statements from this form.



keypuncher operators in 1940s



A Fortran punched card

The B (Bell Lab) language

```
/* The following program will calculate the constant e-2 to about
4000 decimal digits, and print it 50 characters to the line in
groups of 5 characters. The method is simple output conversion
of the expansion
  1/2! + 1/3! + ... = .111....
where the bases of the digits are 2, 3, 4, . . . */

main() {
    extrn putchar, n, v;
    auto i, c, col, a;

    i = col = 0;
    while(i<n)
        v[i++] = 1;
    while(col<2*n) {
        a = n+1;
        c = i = 0;
        while (i<n) {
            c =+ v[i] *10;
            v[i++] = c%a;
            c =/ a--;
        }

        putchar(c+'0');
        if(!(++col%5))
            putchar(col%50?' ': '*n');
    }
    putchar('*n*n');
}
v[2000];
n 2000;
```

The C language

```
1  /*
2   * This line basically imports the "stdio" header file, part of
3   * the standard library. It provides input and output functionality
4   * to the program.
5   */
6  #include <stdio.h>
7
8  /*
9   * Function (method) declaration. This outputs "Hello, world\n" to
10  * standard output when invoked.
11  */
12 void sayHello(void) {
13     // printf() in C outputs the specified text (with optional
14     // formatting options) when invoked.
15     printf("Hello, world!\n");
16 }
17
18 /*
19  * This is a "main function". The compiled program will run the code
20  * defined here.
21  */
22 int main(void)
23 {
24     // Invoke the sayHello() function.
25     sayHello();
26     return 0;
27 }
```

“B and the old old C were very very similar languages except for all the **types**”
- Ken Thompson in *Users’ reference to B*

Standardization/development of C

- *K&R C*
 - Described in Kernighan and Ritchie, *The C Programming Language* (1978)
 - De facto standard
- *C89/C90*
 - ANSI standard X3.159-1989 (completed in 1988; formally approved in December 1989)
 - International standard ISO/IEC 9899:1990
- *C99*
 - International standard ISO/IEC 9899:1999
 - Incorporates changes from Amendment 1 (1995)
- *C11*
 - International standard ISO/IEC 9899:2011
 - Incorporates features already supported by common contemporary compilers, and includes a detailed memory model to better support multi-thread execution
- *C17*
 - International standard ISO/IEC 9899:2018
 - Fixes numerous minor defects without introducing new features
- *To be superseded by C23 (ISO/IEC 9899:2023) in 2024*


The differences between the different versions aren't huge, and the compilers are usually backward compatible.

Decedents of C

- **C++** includes all the features of C, but adds classes and other features to support object-oriented programming.
- **Java** is based on C++ and therefore inherits many C features.
- **C#** is a more recent language derived from C++ and Java.
- **Perl** has adopted many of the features of C.
- ...

Compiled Language


- Faster
- Closer to OS
- Platform dependent
- Steeper learning curves
- Difficult to debug / modify



e.g. Fortran, C, C++, C#, COBOL, Rust...

Interpreted Language

- Cross-platform
- Run directly
- Usually easier
- Run-time debugging
- Slower
- Source code visible to user



e.g. Python, matlab, Java script, PHP, BASIC...

vs.

The way C works

rocks.c

```
#include <stdio.h>
int main()
{
    puts("C Rocks!");
    return 0;
}
```



```
Command Prompt
Microsoft Windows [Version 10.0.22631.3155]
(c) Microsoft Corporation. All rights reserved.

C:\Users\HONG>gcc rocks.c -o rocks.exe
```



rocks.exe



Source

Edit a source file (with a file name ending by **.c**)

Compile (& Link)

Executable

A file containing machine codes, ending by **.exe** in Windows.