
Fusion Data Framework Documentation

Release 0.0.0

John Schmitt, David R. Smith, Kevin Tritz, Howard Yuh

February 04, 2016

CONTENTS

1	Introduction	1
1.1	Fusion Data Platform	1
2	Getting Started	3
2.1	User Guide	3
2.2	Developer Guide	4
3	Usage Examples	8
3.1	Initiate a machine instance	8
3.2	Load shots and XPs	8
4	Package Reference	10
4.1	Module factory.py	10
4.2	Class factory.Machine	10
4.3	Class factory.Shot	10
4.4	Class factory.Logbook	10
4.5	Module fdf_signal.py	10
4.6	Class fdf_signal.Signal	10
4.7	Module fdf_globals.py	10
5	Project Documents	11

INTRODUCTION

About FDF

1.1 Fusion Data Platform

Fusion Data Platform (FDP) is a data framework in Python for magnetic fusion experiments. FDP streamlines data discovery, access, management, and visualization.

1.1.1 Resources

- Github repository: <https://github.com/Fusion-Data-Platform/fdp>
- Documentation: <http://fusion-data-platform.readthedocs.org/>
- Google Group: <https://groups.google.com/forum/#!forum/fusion-data-platform>

1.1.2 Example

```
In [1]: import fdp

In [2]: dir(fdp.nstx.s140000)
Precaching MDS server connections...
Finished.
Out[2]:
['bes',
 'chers',
 'equilibria',
 'filterscopes',
 'ip',
 'magnetics',
 'mpts',
 'mse',
 'usxr',
 'vloop']

In [3]: dir(fdp.nstx.s140000.mpts)
Out[3]: ['comment', 'ne', 'shot', 'spline', 'te', 'valid']
```

```
In [4]: fdp.nstx.s140000.mpts.te.plot()

In [5]: fdp.nstx.s140000.logbook()

Logbook entries for 140000
*****
140000 on 2010-08-17 in XP 1048
adiallo in topic PHYS OPS

Small increase of the SPA current by 50 A.
Good.
*****
```

1.1.3 Created by

- John Schmitt, Princeton Plasma Physics Lab
- David R. Smith, U. Wisconsin-Madison
- Kevin Tritz, The Johns Hopkins U.
- Howard Yuh, Nova Photonics

License

The MIT License (MIT)

Copyright (c) 2015 John Schmitt, David R. Smith, Kevin Tritz, Howard Yuh

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the “Software”), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED “AS IS”, WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

GETTING STARTED

2.1 User Guide

This guide is for people who want to use FDF on the PPPL Linux cluster. If you wish to contribute to the FDF project as a developer, see the developer guide.

HTML documentation is also available: <http://fusion-data-framework.github.io/fdf/>

To use FDF on the PPPL Linux cluster, load the module `nstx/fdf` (you may need to unload other `nstx` modules):

```
[sunfire06:~] % module load nstx/fdf

[sunfire06:~] % module list
Currently Loaded Modulefiles:
1) torque/2.5.2          5) idl/8.2              9) java/v1.6
2) moab/5.4.0           6) nstx/treedefs       10) nstx/mdsplus5
3) ppplcluster/1.1      7) nstx/epics          11) nstx/fdf
4) freetds/0.91         8) nstx/idldirs
```

Verify that python points to `/p/fdf/anaconda/bin/python`:

```
[sunfire06:~] % which python
/p/fdf/anaconda/bin/python
```

If python does not point to `/p/fdf/anaconda/bin/python`, then `PATH` contains to a different python distribution. In this case, you need to modify `PATH` so `/p/fdf/anaconda/bin` is the first python distribution in `PATH`.

Finally, you can launch python and import the FDF package:

```
[sunfire06:~] % python
Python 2.7.10 |Anaconda 2.3.0 (64-bit)| (default, Sep 15 2015, 14:50:01)
[GCC 4.4.7 20120313 (Red Hat 4.4.7-1)] on linux2
Type "help", "copyright", "credits" or "license" for more information.
Anaconda is brought to you by Continuum Analytics.
Please check out: http://continuum.io/thanks and https://anaconda.org
>>> import fdf
>>>
```

See Usage Examples to learn about the capabilities of FDF.

2.2 Developer Guide

This guide is for developers who want to contribute to the FDF project, and this guide describes the development workflow on the PPPL Linux cluster. If you simply want to use FDF on the PPPL Linux cluster, see the user guide.

HTML documentation is also available: <http://fusion-data-framework.github.io/fdf/>

The FDF code repository is hosted on GitHub: <https://github.com/Fusion-Data-Framework/fdf>

To participate in the FDF project as a developer, you must create a GitHub account. The FDF project uses GitHub and Git for collaborative development and version control.

Configure Git

On the PPPL Linux cluster, load the module git/1.8.0.2 (on Red Hat 6 systems, use git/2.4.2):

```
[sunfire08:~] % module avail git
----- /usr/pppl/Modules/modulefiles -----
git/1.7.4.1(default)      git/1.8.0.2      git/2.4.2

[sunfire08:~] % module load git/1.8.0.2

[sunfire08:~] % module list
Currently Loaded Modulefiles:
1) torque/2.5.2          3) ppplcluster/1.1
2) moab/5.4.0           4) git/1.8.0.2
```

You may want to add the module load command to your shell start-up files: `~/.cshrc` for `csh/tcsh` or `~/.bash_profile` for `bash`.

Next, you must configure Git with your name and email (the same email associated with your GitHub account):

```
[sunfire08:~] % git config --global user.name "John Doe"
[sunfire08:~] % git config --global user.email "JohnDoe@email.com"
```

Also, we recommend setting an editor (e.g. `vi`, `emacs`, `nedit`) for Git comments:

```
[sunfire08:~] % git config --global core.editor nedit
```

You can inspect your Git configuration in the file `~/.gitconfig`. For more information about Git configuration, see <https://help.github.com/articles/set-up-git/> or <https://git-scm.com/book/en/v2/Getting-Started-First-Time-Git-Setup>

Clone the FDF repository

Git clones repositories into a new directory in your current directory. In the right column of the FDF repo page (<https://github.com/Fusion-Data-Framework/fdf>), you can find the HTTPS URL (<https://github.com/Fusion-Data-Framework/fdf.git>) to clone FDF to your local directory

```
[sunfire08:~] % ls -d fdf
ls: fdf: No such file or directory

[sunfire08:~] % git clone https://github.com/Fusion-Data-Framework/fdf.git
```

```
Cloning into 'fdf'...
remote: Counting objects: 619, done.
remote: Total 619 (delta 0), reused 0 (delta 0), pack-reused 619
Receiving objects: 100% (619/619), 783.01 KiB, done.
Resolving deltas: 100% (279/279), done.

[sunfire08:~] % ls -d fdf
fdf/
```

Cloning via SSH is also feasible: <https://help.github.com/articles/set-up-git/#next-steps-authenticating-with-github-from-git>

Finally, add your new fdf directory to the PYTHONPATH environment variable:

```
[sunfire08:~] % setenv PYTHONPATH ${HOME}/fdf:$PYTHONPATH

[sunfire08:~] % echo $PYTHONPATH
/u/drsmith/fdf:<other directories>
```

You may want to add this action to your shell start-up files, as described above. In bash, use the export command to set PYTHONPATH.

Git workflow for FDF development

(1) Create a development branch (here, we call it devbranch) and checkout the new branch:

```
[sunfire08:~] % cd fdf

[sunfire08:~/fdf] % git branch
* master

[sunfire08:~/fdf] % git branch devbranch

[sunfire08:~/fdf] % git branch
devbranch
* master

[sunfire08:~/fdf] % git checkout devbranch
Switched to branch 'devbranch'

[sunfire08:~/fdf] % git branch
* devbranch
master
```

Devbranch initializes as a copy of master. git branch lists branches in your local repository, and the asterisk denotes the active branch. You can switch between local branches with git checkout <LocalBranchName>.

(2) Push devbranch to the remote FDF repository at GitHub (you may need to enter your GitHub username and password):

```
[sunfire08:~/fdf] % git push origin devbranch
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/Fusion-Data-Framework/fdf.git
 * [new branch]      devbranch -> devbranch
```


devbranch is now listed in the FDF repository at GitHub. `origin` is the alias for the remote GitHub repository. You can view your remote repositories and aliases with `git remote -v`.

(3) Proceed with FDF development within devbranch: commit changes, add/delete files, and push updates to GitHub.

As you complete small tasks, you should commit changes to your local repository with `git commit -a -m '<mymessage>'`. Also, each commit requires a short message describing the changes:

```
[sunfire02:~/fdf] % git commit -a -m 'added dictionary rows in logbook.py'
[devbranch bb6c58a] added dictionary rows in logbook.py
1 file changed, 16 insertions(+), 21 deletions(-)
```

If you do not specify a commit message with `-m` option, then Git will open your default editor and ask for a commit message (see Configure Git above). The `-a` option commits all file changes throughout the branch index, not simply your current directory. The branch index is the list of files Git tracks in the branch. `git commit -a` tracks changes to files in the branch index, so you must add new files to the index and remove deleted files from the index. You can view the branch index with `git ls-files`, and you can add new files to the index and remove deleted files from the index with `git add -A`:

```
[sunfire02:~/fdf] % touch temp.py

[sunfire02:~/fdf] % ls temp.py
temp.py

[sunfire02:~/fdf] % git ls-files temp.py

[sunfire02:~/fdf] % git add -A

[sunfire02:~/fdf] % git ls-files temp.py
temp.py
```

Note that `temp.py` appeared in the index only after the command `git add -A`. Similarly, deleted files stay in the index until the `git add -A` is given.

When you complete a large task, you should “push” changes to the devbranch on GitHub with `git push`:

```
[sunfire05:~/fdf] % git push origin devbranch
Counting objects: 10, done.
Delta compression using up to 8 threads.
Compressing objects: 100% (6/6), done.
Writing objects: 100% (6/6), 1.30 KiB, done.
Total 6 (delta 3), reused 0 (delta 0)
To https://github.com/Fusion-Data-Framework/fdf.git
129c5d9..a166825 devbranch -> devbranch
```

Again, “origin” signifies the branches on the remote GitHub repo.

(4) While you are working locally in devbranch, others may be modifying master at GitHub. When you are ready to merge devbranch into master, you should first merge the latest version of master from GitHub into your local devbranch. To retrieve the latest version of master from GitHub, use `git fetch`:

```
[sunfire05:~/fdf] % git fetch origin master
From https://github.com/Fusion-Data-Framework/fdf
```

```
* branch          master      -> FETCH_HEAD
```

Next, verify that you are in devbranch and merge origin/master into devbranch:

```
[sunfire08:~/fdf] % git branch
* devbranch
master

[sunfire05:~/fdf] % git merge origin/master
```

Next, push your local devbranch to devbranch on GitHub:

```
[sunfire05:~/fdf] % git push origin devbranch
```

Finally, on the GitHub website, in the devbranch area, submit a *pull request* to pull devbranch into master.

USAGE EXAMPLES

First, import the FDF module:

```
>>> import fdf
```

3.1 Initiate a machine instance

Define a NSTX machine instance:

```
>>> nstx = fdf.Machine('nstx')
```

or pre-load a shotlist:

```
>>> nstx = fdf.Machine('nstx', [140000, 140001])
```

or pre-load an XP:

```
>>> nstx = fdf.Machine('nstx', xp=1013)
```

3.2 Load shots and XPs

Shots are added as referenced. For instance, without previous reference to 139980, you can enter:

```
>>> nstx.s139980.chers.plot()
```

Add shots to the NSTX instance:

```
>>> nstx.addshot(140000)
```

or a shotlist:

```
>>> nstx.addshot([141400, 141401, 141402])
```

or by XP:

```
>>> nstx.addshot(xp=1048)
```

or by date (string or int YYYYMMDD):

```
>>> nstx.addshot(date=20100817)
```

List shots presently loaded:

```
>>> dir(nstx)
```

or:

```
>>> nstx.listshot()
```

Get a custom **shotlist**:

```
>>> my_shotlist = nstx.get_shotlist(xp=1032) # returns numpy.ndarray
```

PACKAGE REFERENCE

4.1 Module factory.py

4.2 Class factory.Machine

4.3 Class factory.Shot

4.4 Class factory.Logbook

4.5 Module fdf_signal.py

4.6 Class fdf_signal.Signal

4.7 Module fdf_globals.py

PROJECT DOCUMENTS

October 9, 2015 meeting