

Automatic Placement with Madonna

30th September 2019

The job of placing the instances can be performed by an automatic tool which was called after one of the most famous singers of the 1980'ies¹. She places the instances such that the total wire length is (hopefully) minimized. As we all know, *madonna* is rather unpretentious; If you like, you can improve her results manually using the other commands in the instance menu. A circuit which was placed using *madonna* can be routed automatically, since *madonna* makes sure that all instances are present in the layout.

1 What is required before I can call Madonna?

Madonna is very sensitive to errors in her input. To prevent offending her the following data must be present:

- A proper circuit description in the database. *Seadali* complains if a circuit description with the specified name doesn't exist. Do not forget to convert your *sls* network description into the database using *csls*.
- For each of the son-cells (instances) in the circuit description a layout must exist which has the same name. We made sure that this is always the case for all library cells.

If there is an error in the netlist description *madonna* opens a window to explain what you did wrong.

2 Running *madonna*

Just like *fish*, *madonna* can be called both from *seadali* and the command shell.

2.1 From *seadali*

Calling her by pressing the button Madonna in the instances menu is the most convenient for you. Pressing this button will overwrite the design which you are currently editing in *seadali*. Therefore you will be asked whether you are sure to continue in case the workspace is not empty.

¹And 90'ies.

As next step you must enter the name of the circuit which has to be placed. A small menu will appear, in which you just click **DO IT !** to start *madonna*. In the menu some optional features of can be set for *madonna*:

set box Set the box within which *madonna* has to place the instances. Click the right-top corner. In this way you can control the shape and the size of the placement. Specifying a big box will leave quite some unused transistors. Specifying a very small box will squeeze the instances on minimum area. If the box is too small, *madonna* will expand it in either the x- or the y-direction, depending on what you specified. It is better not to make the box much too small, because *madonna* will have a hard time recovering from that.

If the workspace was empty, *seadali* will make an empty image array before you can specify the box. In this way you have some reference for the size of the box.

X-expand Force *madonna* to expand horizontally if the box was too small. This is default.

Y-expand Expand vertically if the box was too small.

Channels Create a placement with routing channels. If this feature is active, *madonna* computes the amount of space that *trout* needs to complete the routing process successfully. This computation actually involves a call to *madonna*'s internal global router. A report of the global routing process is written to the file `seadif/groutes`.

Note that the routing channels increase the layout area in both the X and the Y direction, regardless of the preferences indicated by means of the **X/Y-expand** buttons or the **set box** button.

Options Set any other (unofficial) option which you want to propagate to *madonna*. Don't touch this button unless you know what you are doing.

DO IT! Start *madonna*. This may take anywhere from 30 seconds up to 10 minutes, depending on the number of instances and the system load. You can kill *madonna* using the **KILL**-button.

You can try to place the circuit with various shapes and sizes.

Can I pre-place some instances? No, *madonna* is quite possessive. She wants to do everything herself. She will always place all instances in your circuit description. Pressing **Madonna** a second time will overwrite the existing placement. You can only request her to place the instances in a certain box. Obviously, you can modify *madonna*'s placement manually using the buttons in the instance menu.

2.2 Calling *madonna* from the command line using *sea*

The non-interactive way to call her is by using the tool *sea* from the command line:

```
[op5u9/myproject] sea -p name
```

in which *name* is the name of the circuit cell. As a result, the output placement will be written into the layout database. The program *sea* is a kind of bodyguard to *madonna*, it checks the correctness of your input. Only if everything is correct, it calls *madonna* to look at your circuit.

Sea also allows you to place and route a circuit in one step:

```
[op5u9/myproject] sea hotelLogic
```

for instance, will place and route the cell `hotelLogic` and write the result into the layout database under the name `hotelLogic` (use the `'-o name'` option to write it under a different name). Just type

```
[op5u9/myproject] sea -h
```

to see all the options.

