


Pablo Slavkin
dci


Sheet: /ethernet/
File: ethernet.sch


Title: ethernet


Size: A4 Date: 25 10 2019
KiCad E.D.A. kicad 5.0.2+dfsg1-1

Rev: 1.0
Id: 2/15












Multipurpose LEDs



Boot Mode to Flash/USB



SCI leds



Pablo Slavkin
dci


Sheet: /clk/
File: clk.sch



Title: clk

Size: A4
KiCad E.D.A. kicad 5.0.2+dfsg1-1

Date: 25 10 2019

Rev: 1.0
Id: 6/15





I've decided to use LEM, nor shunt, it's a little expensive, but less
 bum, isolated and easy to change ranges. Without sigma delta issues..
 3 fases included but should work with only 2


Pablo Slavkin
 dci



Sheet: /lem/
 File: lem.sch

Title: LEM current measurement

Size: A4 Date: 25 10 2019
 KiCad E.D.A. kicad 5.0.2+dfsg1-1

Rev: 1.0
 Id: 8/15






Pablo Slavkin
dci

Sheet: /endat/
File: endat.sch

Title: ENDAT/BISS Interface

Size: A4 Date: 25 10 2019
KiCad E.D.A. kicad 5.0.2+dfsg1-1

Rev: 1.0
Id: 11/15



Pablo Slavkin
dci

Sheet: /qep/
File: qep.sch


Title: QEP encoder Interfase

Size: A4 Date: 25 10 2019

KiCad E.D.A. kicad 5.0.2+dfsg1-1

Rev: 1.0

Id: 12/15



Pablo Slavkin
dci

Sheet: /rs485/
File: rs485.sch


Title: RS485

Size: A4 Date: 25 10 2019

KiCad E.D.A. kicad 5.0.2+dfsg1-1

Rev: 1.0

Id: 13/15



Sheet: /can/
File: can.sch

Title:

Size: A4
KiCad E.D.A. kicad 5.0.2+dfsg1-1

Date:

Rev:
Id: 14/15

