pi_ager install on Raspberry Pi 3/Pi 4/ Pi zero w under Pi OS (32-bit) with desktop and recommended software or Pi OS Lite

- For Pi 4/3: Download and install Raspberry Pi OS with desktop and recommended software from https://www.raspberrypi.org/software/operating-systems/

- For Pi zero: Download and install Raspberry Pi OS Lite from https://www.raspberrypi.org/software/operating-systems/

- Enable SSH for remote access
  sudo touch /boot/ssh

- Setup WLAN configuration
  Generate file wpa_supplicant.conf in /boot:

```
country=DE
ctrl_interface=DIR=/var/run/wpa_supplicant GROUP=netdev
update_config=1
network={
    ssid="WLAN SSID"
    psk="WLAN PASSWORT"
}
```

- Edit config.txt in /boot to support I2C and SPI devices:

```
# Additional overlays and parameters are documented /boot/overlays/README
# Use Pi-Ager Pins 11/13 GPIO 17/27 for I2C
dtoverlay=i2c-gpio,bus=3,i2c_gpio_sda=17,i2c_gpio_scl=27
# Use Pi-Ager Pin 16 for MCP3204
dtoverlay=spi1-1cs,cs0_pin=16
```

- Add in /boot/cmdline.txt at the end of line this to enable USB camera with fswebcam :
  dwc_otg.fiq_fsm_mask=0x3

- Reboot system

- Edit /etc/modules to load i2c-dev at boot, add this line :
  i2c-dev

- Add file :
  sudo touch /etc/modprob.d/raspi-blacklist.conf

- Get a copy from Pi-Ager repository to your local system:
  git clone –b entwicklung https://github.com/Tronje-the-Falconer/Pi-Ager
  All project file are now in the folder ./Pi-Ager/

- Copy setup.txt from local repository to /boot/ and edit it as needed.

- Copy /etc/modprobe.d/Pi-Ager_i2c_off.conf.on from local repository to /etc/modprobe.d/

- Reboot system

- Install lighttpd:
  sudo apt-get update
  sudo apt-get upgrade
  sudo apt-get install lighttpd
  sudo systemctl status lighttpd

  sudo nano /etc/lighttpd/lighttpd.conf
  and change Parameter

  server.document-root = "/var/www/html"
  to
  server.document-root = "/var/www"

  sudo usermod -G www-data -a pi
  sudo chown -R www-data:www-data /var/www
  sudo chmod -R 755 /var/www

- Reboot system

  For testing the web server, generate html-page:

  sudo nano /var/www/test.html
  with content:

  ```
  <html>
  <head><title>Test-Seite</title></head>
  <body>
  <h1>Das ist eine Test-Seite.</h1>
  </body>
  </html>
  ```
  Enter your IP Address (or localhost) into the browser followed by /test.html

  In addition we need .htcredentials to contain user and password.

  Fort that we use the Online-Tool https://websistent.com/tools/htdigest-generator-tool/

  Username: pi-ager
  REALM: Pi-Ager
  Password: raspberry
  Caution! All entries are case sensitive!

  Open this file now

  sudo nano /var/.htcredentials

  and fill in the string output from the generator tool.

  Save file with “STRG+o”, “RETURN” and close with “STRG+x”

  Now we have to setup the password authentification in lighttpd:

sudo nano /etc/lighttpd/conf-available/05-auth.conf
The following lines are added under server.modules += („mod_auth“) :

```
auth.backend               = "htdigest"
auth.backend.htdigest.userfile     = "/var/.htcredentials"

auth.require               = ( "/settings.php" =>
                           (
                            "method" => "digest",
                            "realm" => "Pi-Ager",
                            "require" => "user=pi-ager"
                           ),
                            "/admin.php" =>
                           (
                            "method"  => "digest",
                            "realm"   => "Pi-Ager",
                            "require" => "valid-user"
                            ),
                            "/webcam.php" =>
                           (
                            "method"  => "digest",
                            "realm"   => "Pi-Ager",
                            "require" => "valid-user"
                            ),
                            "/notification.php" =>
                           (
                            "method"  => "digest",
                            "realm"   => "Pi-Ager",
                            "require" => "valid-user"
                            )
                           )
```

Then we activate this modul:
sudo lighty-enable-mod auth

In addition we have to edit :

sudo nano /etc/lighttpd/conf-available/15-fastcgi-php.conf
add at the end of the line

"broken-scriptfilename" => "enable"
a “,” and in a new line

"allow-x-send-file" => "enable"
Save end exit nano.

Now enable these modules:
sudo lighty-enable-mod fastcgi
sudo lighty-enable-mod fastcgi-php

Now reload the the webserver:
sudo service lighttpd force-reload

Now continue to install additional modules:

- Install Git
  sudo apt install git

- Install smbus
  sudo apt-get install python3-smbus

- Install sqlite3:
  sudo apt-get install sqlite3

- Install DHT sensor support
  sudo pip3 install Adafruit-DHT

- Install SHT1x sensors
  sudo pip3 install pi-sht1x

- Install fswebcam:
  sudo apt-get install fswebcam

- Install influxdb
  sudo pip3 install influxdb

- Install php 7.3
  sudo apt-get install php7.3-common php7.3-cgi php7.3 php7.3-sqlite3

- Install additional modules for php7.3:
  sudo apt-get install php7.3-apcu php7.3-fpm php7.3-mbstring php7.3-phpdebug

- Install wiringpi:
  sudo apt-get install wiringpi

- Install wiringpi new version with Pi4 support :
  cd /tmp
  wget https://project-downloads.drogon.net/wiringpi-latest.deb
  sudo dpkg -i wiringpi-latest.deb

- Copy gpio to /usr/local/bin
  sudo cp /usr/bin/gpio /usr/local/bin
  sudo chmod 4755 /usr/local/bin/gpio

- Install PiShrink
  wget https://raw.githubusercontent.com/Drewsif/PiShrink/master/pishrink.sh
  chmod +x pishrink.sh
  sudo mv pishrink.sh /usr/local/bin

- Nextion serial client (HMI Dislplay support)
  sudo pip3 install nextion

- php zip support:
  sudo apt-get update
  sudo apt-get install php-zip

- Install lsof command:
  sudo apt update
  sudo apt install lsof

- Install Locale en-GB and de-DE UTF-8 using
  sudo raspi-config

- Enable Serial Interface, disable login, needed for HMI Nextion Display
  sudo raspi-config

- Install zip and unzip:
  sudo apt install zip unzip

- Workaround for Adafruit_DHT for Pi4:
  In "/usr/local/lib/python3.7/dist-packages/Adafruit_DHT/platform_detect.py", you can add the followings at line #112 in the elif ladder, so it should workaround the issue.

```
elif match.group(1) == 'BCM2711':
    return 3
```



- Unblock wifi for Pi4, add rfkill unblock wifi:
  cd /etc
  sudo nano rc.local

```
#!/bin/sh -e
#
# rc.local
#
# This script is executed at the end of each multiuser runlevel.
# Make sure that the script will "exit 0" on success or any other
# value on error.
#
# In order to enable or disable this script just change the execution
# bits.
#
# By default this script does nothing.

# Print the IP address
_IP=$(hostname -I) || true
if [ "$_IP" ]; then
  printf "My IP address is %s\n" "$_IP"
fi

rfkill unblock wifi

exit 0
```

- Generate/edit crontab to prepare for automatic enable pi-ager_backup.sh

```
pi@pi-ager:~ $ sudo crontab -l
#---------------------------------------------------------------------
# Shell variable for cron
SHELL=/bin/bash
# PATH variable for cron
PATH=/usr/local/bin:/usr/local/sbin:/sbin:/usr/sbin:/bin:/usr/bin:/usr/bin/X11
#M   S     T M W   Befehl
#---------------------------------------------------------------------
#*    */6   * * *   /usr/bin/flock -w 0 /var/run/pi-ager_backup.pid /usr/local/bin/pi-ager_backup.sh >> /var/log/pi-ager_backup
.log 2>&1
#*/2 *     * * *   logger "greetings from the crontab" > /dev/null 2>&1
```

Use visudo to edit /etc/sudoers, so that the www-data User (User of Website) can execute /var/sudowebscript.sh :

sudo visudo

and then in sudoers following

...

#User privilege specification

root ALL=(ALL:ALL) ALL

...

adding:

www-data ALL=NOPASSWD:/var/sudowebscript.sh

Save and exit.

- Now copy alle files and folders from your local git repository /var/www to /var/www/
- from local repository /opt/pi-ager/ to /opt/pi-ager/
- from local repository /var/sudowebscript.sh to /var/
- sudo chown –R www-data:www-data /var/www
- sudo chown root:root /var/www/
- sudo usermod –G gpio –a www-data
- sudo chmod 666 /var/www/logs/logfile.txt
- sudo chown –R root:root /var/www/logs

- sudo chmod 755 /var/www/logs/
- sudo chmod 664 /var/www/config/pi-ager.sqlite3
- sudo chown -R www-data:www-data /var/www/config/
- sudo chmod 555 /var/sudowebscript.sh
- from local repository /usr/local/bin/*.sh copy all to /usr/local/bin/
  (pi-ager_backup.sh, pi-ager_image.sh,setup_pi-ager.sh)
  Set +x mode to the scripts :
  sudo chmod +x /usr/local/bin/*.sh

- from local repository /lib/systemd/system copy the following files to
  /lib/systemd/system/ :
  pi-ager_main.service
  setup_pi-ager.service

- Enable setup_pi-ager.service to initialize system with data from /boot/setup.txt after next reboot:
  sudo systemctl enable setup_pi-ager
  sudo reboot