

Therefore DB Codes

Therefore 2020

The Therefore database schema contains several columns which hold integer values (codes). This document describes the meaning of these codes.

TheActno*.TypeNo

- 1 Server
- 2 Document
- 3 Category
- 4 Category Field
- 5 Datatype
- 6 Media Pool
- 7 Media
- 8 Parser Profile
- 9 Spool Type
- 10 Query
- 11 User
- 12 Group
- 13 Capture Profile
- 14 Preprocessor
- 15 COLD Form
- 16 Query Template
- 17 Folder
- 18 Document Loader Profile
- 19 Workflow Process
- 20 Workflow Task
- 21 Workflow Instance
- 22 Keyword Dictionary
- 23 Storage Policy
- 24 Device
- 25 Storage Area
- 26 Retention Policy
- 27 MFP Device
- 28 Tree View
- 29 Universal Connector Profile
- 30 Task
- 31 SharePoint Profile
- 32 Automatic Counter
- 33 Data Extractor
- 34 Content Connector source
- 35 Replication connection
- 36 Replication table
- 37 Case definition
- 38 Case Header

- 39 Office Profile
- 40 Stamp
- 41 SQL Reporting Definition
- 42 PowerBI Table
- 43 PowerBI Dataset
- 44 SharePoint Connector: connection to SharePoint
- 45 Cloud Storage
- 46 Common Script
- 47 EForm
- 48 EForm Submission
- 49 ESignature Provider
- 50 Dashboard
- 51 Role

TheCaptBarcode.BarType

- 1 3 of 9
- 2 Interleaved 2 of 5
- 4 Code 128
- 8 EAN
- 16 UPC-A
- 32 UPC-E
- 64 Codabar
- 128 Code 93
- 256 Postnet
- 512 Linear 2 of 5
- 1024 Aztek
- 2048 PDF 417
- 4096 Datamatrix
- 16384 QR
- 1048576 EAN-5 Addon

The database column can contain a combination of these flags. (See note on flags).

TheCaptBarcode.Encoding

- 0 Automatic
- 1 UTF-8
- 2 UTF-16

TheCaptBarcode.Frequency

- 0 None – no barcode used
- 1 The barcode exists on exactly one page of the document
- 2 The barcode exists on some pages of the document – if a second page has the same barcode, no document break is made
- 3 The barcode exists on each page of the document – if there is one page without barcode, a warning is reported.

TheCaptBarcode.Orientation

- 1 0°
- 2 90°

- 4 180°
- 8 270°

The database column can contain a combination of these flags. (See note on flags).

TheCaptBarcode.Quality

- 0 Good
- 1 Normal
- 2 Poor

TheCaptBarcode.Ratio

- 0 3:1
- 1 2:1

TheCaptGrid.TypeNo

- 1 Display the document counter
- 2 Display the category name
- 3 Display the page count
- 4 Display a category field
- 5 Display information

TheCaptProfile.ColorMode

- 1 Black & white
- 2 24-bit Color
- 4 256 colors
- 8 256-Level gray
- 16 16-Level gray
- 32 4-Level gray
- 64 3-bit color
- 128 6-bit color
- 256 12-bit color

TheCaptProfile.DocBreak

- 1 Single page documents
- 2 Use separator pages (e.g.: DR 3020)
- 3 Manual – scan all pages into one document
- 4 Barcode/OCR
- 5 Barcode – skip page with barcode

TheCaptProfile:ScanDropOutColor

- 0 None
- 1 Red
- 2 Green
- 4 Blue

TheCaptProfile.ScanMode

- 1 Panel
- 2 Line
- 4 Photo

- 8 Mixed

TheCaptProfile.ScanRotate

- 0 None
- 1 90° (rotate right)
- 2 180°
- 3 270° (rotate left)

TheCaptProfile.ScanSize

Decimal value	Hex value	
1	0x00000001	A0
2	0x00000002	A1
4	0x00000004	A2
8	0x00000008	A3
16	0x00000010	A4
32	0x00000020	A5
64	0x00000040	B
128	0x00000080	Letter
256	0x00000100	B0
512	0x00000200	B1
1024	0x00000400	B2
2048	0x00000800	B3
4096	0x00001000	B4
8192	0x00002000	B5
16384	0x00004000	B6
32768	0x00008000	Legal
65536	0x00010000	Panel
131072	0x00020000	Coupon
262144	0x00040000	Personal
524288	0x00080000	Business
4194304	0x00400000	Maximum
33554432	0x02000000	Minimum
67108864	0x04000000	Auto-Detect
134217728	0x08000000	Custom

TheCaptProfile.ScanSource

- 1 Flatbed
- 2 ADF
- 4 Panel
- 8 Manual

TheCaptProfile.StorageCompression

- 1 JPEG 2000
- 2 JPEG
- 3 Packbits
- 4 LZW
- 5 ZIP

TheCaptProfile.StorageMode

- 0 Original
- 1 Single TIFF
- 2 Single PDF
- 3 Multipage TIFF
- 4 Multipage PDF
- 5 Searchable PDF
- 6 Searchable PDF/A
- 7 Multipage PDF Jpeg2000
- 8 Multipage PDF/A

TheCaptStep.TypeNo

- 1 Scan
- 2 Barcode
- 3 OCR
- 4 Define Category
- 5 Automatically set index data
- 6 Set index data via dll
- 7 Call verification dll
- 8 Archive
- 9 Call trigger dll (after archive)
- 10 Image enhancement
- 11 Nuance OCR

TheCaptVerify.VerifyMode

- 1 Ascending
- 2 Descending
- 3 Constant

TheCase.Security

See TheDocument.Security

TheCategory.AutoApndMode

- 0 Default
- 1 Insert at beginning
- 2 Append to end
- 3 Replace
- 4 Disabled

TheCategory.CheckInMode

- 0 Check-In comment is not allowed
- 1 Check-In comment is optional
- 2 Check-In comment is mandatory

TheCategory.CoverMode

- 0 Never show a cover sheet
- 1 Cover sheet shown for empty documents
- 2 Always show the cover sheet

TheCategory.EmptyDocMode

- 0 No empty documents allowed
- 1 Documents can be empty
- 2 All documents must be empty

TheCategory.FulltextMode

- 0 Full-text indexing is disabled
- 1 Full-text indexing is turned on for all documents
- 2 Full-text indexing is turned on for all documents newer than the date in THECategory.FulltextDate

TheCategory.WMMode

- 0 Normal mode
- 1 Secure mode – deny printing if the watermark image is not available

TheCatSpool.Status

- 0 Original input file archived
- 1 Preprocessed
- 2 Processing completed
- 4 Faulty – may be combined with one of the previous status flags

TheCloudStorage.CloudProvider

- 1 Dropbox
- 2 Google Drive
- 3 One Drive
- 4 Box

TheCntConnError.Status

- 1 Unknown
- 0 Normal error status: error reported
- 1 Queued for retry
- 2 Retry failed – the file already exists
- 3 Retry failed – other reasons
- 4 Too many OCR threads are running within the conversion service

TheCntConnJob.StorageMode

See TheCaptProfile.StorageMode

TheCntConnSource.SourceMode

- 1 Folder
- 2 Mailbox
- 3 Signature Provider

TheCommonScript.ScriptLang

- 1 VBScript
- 2 JScript

TheCounter.CounterType

- 1 Integer

- 2 Text (formatted)

TheCtgrFields.CounterMode

- 1 Client-side counter, filled before displaying index information
- 2 Server-side counter, filled by the server when saving the document

TheCtgrFields.DependencyMode

- 0 Referenced
- 1 Synchronized redundant
- 2 Editable redundant

TheCtgrFields.IndexType

- 0 None – no index
- 1 Normal index
- 2 Unique index

TheCtgrFields.TypeNo

- 1 String
 - 2 Integer
 - 3 Date
 - 4 Label
 - 5 Decimal
 - 6 Logical
 - 7 Datetime (internal use only)
 - 8 Counter (integer)
 - 9 Counter (formatted)
 - 10 Table field
 - 11 Integer, 64-bit
 - 12 Image
 - 13 Tab
- other User defined datatypes; get data type information from TheDatatype

TheDataExtractor.ModeNo

- 1 Text, line-based
- 2 Text, page-based
- 3 PDF
- 4 XML
- 5 OCR
- 6 Existing Doc

TheDataExtractorItem.DocBreakMode

- 0 None
- 1 On change
- 2 On value

TheDataExtractorItem.TypeNo

- 1 Text, line-based
- 2 Text, page-based
- 3 PDF zone

- 4 XML tag
- 5 OCR
- 6 PDF attachment
- 7 PDF signature

TheDataType.TypeGroup

- 1 Standard – predefined datatype (String, Integer, Date, ...)
- 2 Keyword
- 3 User defined datatype; primary index column of referenced table is of type integer
- 4 User defined datatype; primary index column of referenced table is of type ansi-text
- 5 User defined datatype; primary index column of referenced table is of type date
- 6 User defined datatype; primary index column of referenced table is of type float
- 7 User defined datatype; primary index column of referenced table is of type unicode-text
- 8 Case definition

TheDemigrate.Action

- 1 After copying the document back to the buffer, primary migration to the new storage group is scheduled (requires CopyToBuffer)
- 2 After copying the document back to the buffer, backup migration to the new storage group is scheduled (requires CopyToBuffer)
- 4 Copy the document from the medium to the buffer
- 8 Delete the document on the primary media
- 16 Delete the document on the backup media
- 32 Delete the document on the primary media after it has been migrated to the new primary media
- 64 Delete the document on the backup media after it has been migrated to the new backup media
- 128 Set TheDocument.MediaNo to 0
- 256 Set TheDocument.BackMediaNo to 0
- 512 Set TheDocument.ServerNo to the demigrate server (useful with CopyToBuffer)

The database column can contain a combination of these flags. (See note on flags).

TheDevice.Type

- 1 ~~Jukebox~~
- 2 RAID (local folder)
- 3 ~~Optical drive~~
- 4 Network Share

TheDocument.Security

- 0 Standard security as defined on category and sub-category level
- 1 Use ACL of the document only - no inheritance from (sub-)category
- 2 Use ACL of the document and inherit permissions from (sub-)category

TheEFormSubmission.SubmissionType

- 1 Default
- 2 User
- 3 Draft

TheFolder.FolderType

See TheActno.TypeNo

TheForm.FormType

- 0 TIFF
- 3 Greenbar
- 4 XML

TheForm.PageOrder

- 0 Cyclic (1,2,3,... n,1,2,...)
- 1 Special first and last page (1, 2, 2, 2, 2, ..., 3)
- 2 Special first page (1, 2, 3, ... n, 2, 3, ...)
- 3 Special last page (1, 2, 3, ... n-1, 1, 2, ..., n)

TheFulltextQueue.Action

- 1 Rebuild the complete catalog
- 2 Remove document from catalog
- 3 Add document to catalog
- 4 Update document
- 5 Compress the catalog

TheIndexingAssignment.ErrorMode

- 1 Abort
- 2 Ignore
- 3 Use fall back
- 4 Report error

TheIndexingProfile.AutoAppendMode

- 0 Category default
- 1 Insert
- 2 Append
- 3 Replace
- 4 No check
- 5 Error
- 6 Skip document

TheIndexingProfile.ModeNo

- 1 File
- 2 Mail
- 3 Word
- 4 Excel
- 5 Capture Client
- 6 Office
- 7 Workflow – update index data
- 8 Workflow – change category
- 9 New form
- 10 Signature
- 11 Workflow – Update case header

TheIndexingProfile.ScriptLang

- 1 VBScript
- 2 JScript

TheMedia.DirStruct

Example document: document number is 1777187, coded in base36: '0123ab'; document number mod 100 = 87; the category table is TWC3

- 1 Classic – TWC3\3\2\1\0123ab; each page is stored in a separate file
- 2 Base36CF – b\3\2\1\0123ab.ados; the document is stored as a compound file
- 3 Buffer – 87\0123ab.ados; the document is stored as a compound file
- 6 UDO – 01\77\71\0123ab.ados; there are 100 documents per folder and 3 levels of folders, each having 100 sub folders.

TheMedia.Status

- 0 Raw (not formatted)
- 1 Formatted (not assigned to a storage group)
- 2 Assigned to a storage group
- 4 Full
- 8 Damaged

TheMediaPool.DirStruct

See TheMedia.DirStruct.

TheMediaPool.FileSystem

- 1 FAT
- 2 NTFS
- 3 NTFS compressed

TheMFPDevice.Color

- 0 Undefined
- 1 Black & white
- 2 Gray
- 4 Color

TheMFPDevice.ImageType (Quality)

- 0 Undefined
- 1 Text
- 2 Text/image
- 4 Image
- 8 Photo
- 16 Text/photo
- 32 Text/map/photo
- 64 Map
- 128 Second copy

TheMFPDevice.ScanOrientation

- 0 Undefined
- 1 Automatic

- 2 Long-edge feed
- 4 Short-edge feed

TheMFPDevice.ScanSize

- 0 Undefined
- 1 Any
- 2 A3
- 4 A4
- 8 A5
- 16 A6
- 32 SRA3
- 64 B4
- 128 B5
- 256 Letter
- 512 Legal
- 1024 Statement
- 2048 K8
- 4096 K16
- 8192 Hagaki
- 16384 Inch 12x18
- 32768 Ledger

TheMigrate.Action

- 1 The server will do the primary migration of the document
- 2 The server will do the backup migration of the document
- 4 The server will pre-fetch the document
- 8 The server has to delete the document from its local buffer when the document has been migrated to the primary disk (TheDocument.MediaNo is set)
- 16 The server has to delete the document from its local buffer when the document has been migrated to primary and backup disks (TheDocument.MediaNo and BackMediaNo is set)

The database column can contain a combination of these flags. (See note on flags).

TheObjLinks.DestTypeNo

See TheActno.TypeNo

TheObjLinks.SrcTypeNo

See TheActno.TypeNo

TheOfficeAction.ActionType

- 0 Undefined
- 1 Base
- 2 New document
- 3 Save
- 4 Send
- 5 Print
- 6 Script

TheOfficeAssignment.AssignmentType

- 0 Undefined
- 1 Content control
- 2 Form field
- 3 Cell
- 4 Mail basic
- 5 Mail advanced
- 10 Document property

TheOfficeProfile.ProfileType

- 0 Undefined
- 1 Word
- 2 Excel
- 3 Template only (For example non office templates - replaces the Template feature)
- 4 Mail

ThePowerBITable.FrequencyType

- 1 Hourly
- 2 Daily

ThePowerBITable.TableType

- 1 Category
- 2 Workflow

TheQuery.VersionNo

- 0 Therefore 2017 or earlier
- 1 Therefore 2018 or later

TheQueryField.Alignment

- 0 Default
- 1 Left
- 2 Center
- 3 Right

TheRecycleBin.BelongsToType

See TheActno.TypeNo

TheReplColumn.ColType

- 1 Int
- 2 Date
- 3 Text
- 4 Float
- 5 Short
- 6 Bool
- 7 Datetime
- 8 ANSI text
- 9 NText
- 10 Int64
- 11 GUID

TheReplConn.DBBrand

- 1 SQL Server
- 2 Oracle
- 6 SQL Server via ODBC

TheReporting.EventType

- 1 WF process start
- 2 WF task start
- 3 WF instance claimed
- 4 WF instance unclaimed
- 5 WF instance delegated
- 6 WF instance rerouted
- 7 WF task finished
- 8 WF process finished
- 9 WF instance deleted

TheRetentionQueue.Action

- 1 Delete single version of document
- 2 Delete document (with all versions)
- 4 Ignore media (Before final delete from the TheDocument table is performed, the retention algorithm checks whether document TheDocVersion.MediaNo and TheDocVersion.BackMediaNo is 0. If this flag is set, then the media are not checked.)

TheRole.Permission

Decimal value	Hex value	
1	0x01	Operator
2	0x02	Administrator
4	0x04	Set Permissions
8	0x08	Access/Read
16	0x10	<not used>
32	0x20	<not used>
64	0x40	Category/Case: add documents
128	0x80	Manage searches
256	0x100	Execute searches
512	0x200	Manage keyword dictionary
1 024	0x400	Document/Case: create tasks
2 048	0x800	<not used>
4 096	0x1000	Document/Case: view in hit list
8 192	0x2000	Document/Case: open and view
16 384	0x4000	Document/Case: print
32 768	0x8000	Document/Case: export and send
65 536	0x1 0000	<not used>
131 072	0x2 0000	<not used>
262 144	0x4 0000	Document/Case: view history
524 288	0x8 0000	Document: add annotations
1 048 576	0x10 0000	Document: delete annotations
2 097 152	0x20 0000	Document: edit document

4 194 304	0x40 0000	Document: update index data
8 388 608	0x80 0000	Document: add file
16 777 216	0x100 0000	Document: delete file
33 554 432	0x200 0000	Document: delete document
67 108 864	0x400 0000	Document: retention protection
134 217 728	0x800 0000	Document/Case: manage links
268 435 456	0x1000 0000	Case: create
536 870 912	0x2000 0000	Case: delete
1 073 741 824	0x4000 0000	Case: close
2 147 483 648	0x8000 0000	Read permission
4 294 967 296	0x1 0000 0000	Case: reopen
8 589 934 592	0x2 0000 0000	Workflow: participate
17 179 869 184	0x4 0000 0000	Workflow: add a document
34 359 738 368	0x8 0000 0000	Workflow: view history
68 719 476 736	0x10 0000 0000	Workflow: delegate
137 438 953 472	0x20 0000 0000	Workflow: view all
274 877 906 944	0x40 0000 0000	Workflow: delete
549 755 813 888	0x80 0000 0000	Workflow: start manually
1 099 511 627 776	0x100 0000 0000	Case: update index data

The database column can contain a combination of these flags. (See note on flags).

TheRoleAssignments.ObjectType

See TheActno.ObjType

TheRoleAssignments.SubObjNo

Normally, this column holds the sub-object number of the object (e.g.: sub category). However, if ObjType=17 (Folder) and ObjNo=0 the entry holds the access mask for a pre-defined folder and SubObjNo specifies the folder. SubObjNo can have the following values in this case:

- 1000 Therefore System – root folder
- 1001 Content Connector – root folder
- 1002 Exchange Connector – root folder
- 1004 SAP Connector – root folder
- 1005 User Management – root folder
- 1006 Portal – root folder

TheSigningStatus.Status

- 0 Uploaded
- 1 Completed, ready for download
- 2 Declined, ready for download
- 3 Processed
- 4 Declined
- 5 Error, completed
- 6 Error, declined
- 7 Error, unknown

TheSPProfile.Conversion

- 0 Original

- 1 Single-page TIFF
- 2 Single-page PDF
- 3 Multi-page TIFF
- 4 Multi-page PDF
- 5 Searchable PDF
- 6 Searchable PDF/A
- 50 JPEG

TheSPProfile.Direction

- 1 From SharePoint to Therefore
- 2 From Therefore to SharePoint

TheSPProfile.OPMode

- 1 Copy
- 2 Move

TheSPProfile.Versioning

- 3 Latest version

TheStamp.StampType

- 0 PDF
- 1 PNG

TheStatistics.TypeNo

- 1 Retrieve
- 2 Connect
- 4 Archive
- 8 COLD processing

TheStorageFiles.Status

The status can contain any error code generated by Therefore and is 0 for all normal documents. An explanation for the error code is found in the Eventlog when Therefore generates the error and sets this column (typically during Verification in Therefore Console). Some typical values are listed here

- 0 Normal – no error reported
- 304 Document not found on Therefore medium
- 306 No index information found for the document
- 311 The document is corrupt on the primary disk and on the backup disk
- 312 The document is corrupt on the primary disk
- 313 The document is corrupt on the backup disk
- 314 The document is corrupt on the buffer

TheStorageFiles.Type

- 0 Unknown
- 1 Thex files (.thex)
- 2 Content files (.thec)
- 3 Compressed content file (.zip)
- 4 ADOS file (.ados)

TheString.MainObjType

See TheActno.TypeNo

TheString.StringType

- 1 Category name
- 2 Category description
- 3 Category header
- 4 Category footer
- 5 Field caption
- 6 Tab caption
- 7 Regular expression: help text
- 8 Workflow process name
- 9 Workflow process description
- 10 Workflow task name
- 11 Workflow transition name
- 12 Workflow transition: description
- 13 Workflow transition: condition error text
- 14 Workflow task: checklist text
- 15 Keyword dictionary
- 16 Keyword
- 17 Folder name
- 18 Case definition name
- 19 Query template name
- 20 Label field caption

TheTask.TaskMode

- 1 Complete
- 2 Complete / decline
- 3 Approve / reject
- 4 Yes / No

TheTaskUser.TaskState

- 1 Not started
- 2 In progress
- 3 Waiting on someone else
- 4 Deferred
- 5 Completed
- 6 Revoked

TheTreeViewLevel.LevelFunction

- 0 No function
- 1 Month
- 2 Year
- 3 Month/Year
- 4 First character
- 5 First character grouped
- 6 Range

TheTreeViewLevel.SortOrder

- 1 Ascending
- 2 Descending

TheUCAction.ActionFlags

- 1 Show index data
- 2 View document
- 4 Capture: auto-save
- 8 Select profile
- 16 Open on single hit

TheUCAction.ActionType

- 1 Search
- 2 Save
- 3 Scan with Capture client
- 4 Full-text search
- 5 Scan with Viewer
- 6 Cross-category search
- 7 Search case
- 8 Run executable

TheUCControl.CompProps

- 1 ID
- 2 Class
- 4 Top
- 8 Left
- 16 Width
- 32 Height
- 64 Position
- 128 Caption

TheUCProfile.ClassCompMode

- 1 Exact
- 2 Starts with
- 3 Ends with
- 4 Contains

TheUCProfile.CompMode

See TheUCProfile.ClassCompMode

TheUsageStats.StatType

- 1 Condition in category search
- 2 Condition in case search
- 3 Index field when saving into a category
- 4 Index field when creating a new case

TheUser.UserType

- 1 User
- 2 Group

- 3 System
- 4 Portal user

TheUserFavorites.ObjectType

See TheActno.ObjType

TheUserSync.UserType

See TheUser.UserType

TheUserSync.SyncState

- 0 Synced – no action needed
- 1 Dirty – needs to be synced (new or changed)
- 2 Deleted
- 3 Error after trying to synchronize a dirty entry
- 4 Error after trying to synchronize a deleted entry

TheWFHistory.Type

- 1 Started
- 2 Finished
- 3 Saved
- 4 Routed
- 5 Claimed
- 6 Unclaimed
- 7 Reclaimed
- 8 Delegated
- 9 Document linked to Instance
- 10 Document link removed from Instance
- 11 Overdue Mail sent for Instance
- 12 Overdue transition applied
- 13 Rerouted
- 14 Split
- 15 Merged
- 16 Exception merge
- 17 User split
- 18 Error
- 99 User defined Entry

TheWFInstAccess.EntryType

- 1 Instance claimed by user
- 2 Instance originally assigned to user

TheWFTasks.Type

- 1 Start
- 2 End
- 3 Manual Task
- 4 Automatic Task

TheWFTasks.UserChoice

- 0 Instance is routed to all specified users/groups

- 1 User has to choose one user/group from the specified list

Notes

Flags

Some codes are marked as flags and it is stated that the column value can contain a combination of these flags. This is possible, because each code corresponds to exactly 1 bit in the binary representation of a number, e.g.:

Decimal value	Binary value
1	00000001
2	00000010
4	00000100
8	00001000
16	00010000
32	00100000
64	01000000
128	10000000

To decode a specific value (e.g.: 99), convert the value into its binary representation (in this case: 01100011). In the binary value one can easily see that the value 99 is built from the flags 64+32+2+1. So, these four flags are combined in this one value.