

Workflow Transition Conditions

www.therefore.net
© 2024 Therefore Corporation

All rights reserved. No parts of this work may be reproduced in any form or by any means - graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems - without the written permission of the publisher.

Any other 3rd party products that are referred to in this document may be either trademarks and/or registered trademarks of the respective owners. The publisher and the author make no claim to these trademarks.

While care has been taken in the preparation of this document, the publisher and the author assume no responsibility for errors or omissions, or for damages resulting from the use of information contained in this document.

VERSION: 2024 - 01

Table of Contents

1. Introduction	4
2. Samples	5
2.1 Document with the same index data in one category	5
2.2 Document with the same index data in two categories	5
2.3 Document is present in another category	6
2.4 Check if a multi-keyword field is empty	6
3. Legal	7

1. Introduction

Therefore™ Workflows contain transitions between different tasks in a process. Conditions can be set on these transitions so the workflow will only proceed down that path if certain criteria are fulfilled. For example, you can set a condition to check if a document with the same index data already exists in a category.

Basic transition conditions such as routing based on a certain index field (i.e. amount) are outlined in the Administrator manual. This document covers more advanced scenarios which involve querying the Therefore™ database.

Note that the examples included in this document are based on a SQL database. If you are using another database brand, you must adjust the syntax to suit your database type/version.

2. Samples

2.1 Document with the same index data in one category

The following conditions check whether a document with the same index data already exists in a category.

1. EXISTS (SELECT NULL FROM TheCatXXX c WHERE c.<col1> = TheCatXXX.<col1> AND c.<col2> = TheCatXXX.<col2> AND c.DocNo <> TheCatXXX.DocNo)

This will return TRUE regardless of the number of existing documents. If no document with the same index data exists, it will return FALSE.

2. 1 = (SELECT count(*) FROM TheCatXXX c WHERE c.<col1> = TheCatXXX.<col1> AND c.DocNo <> TheCatXXX.DocNo)

This will return TRUE only if there is one document in the category with the same index data.

3. (SELECT count(*) FROM TheCatXXX c WHERE c.<col1> = TheCatXXX.<col1> AND c.DocNo <> TheCatXXX.DocNo) >= 2

This will return TRUE only if there are 2 or more documents in the category with the same index data.

Legend:

XXX is the ID of the category

<col1> and <col2> are the column names of the index fields to be checked

2.2 Document with the same index data in two categories

Pre-2015:

[Info] is not NULL and EXISTS (Select NULL from TheCat551, TheCat622 as Source where Source.DocNo = TheCat622.DocNo and Source.Info = TheCat551.Info)

2015 +:

[Info] is not NULL and EXISTS (Select NULL from TheCat551, TheCat622 where TheCat622 .DocNo = T0.DocNo and TheCat622 .Info = TheCat551.Info)

LEGEND:

[Info] is the index data field to check for

TheCat551 and TheCat622 are the tables to check (source and target table)

TheCat622.Info and TheCat551.Info are again the index data fields to check

T0.DocNo or TheCat622.DocNo is needed to restrict to the current document

2.3 Document is present in another category

The following condition checks whether a document is present in another category within the same case.

Pre-2015:

```
(SELECT COUNT(0) FROM dbo.TheCat609 cat WHERE cat.CaseNo = dbo.TheCase23.CaseNo) > 0
```

OR

```
EXISTS (SELECT NULL FROM TheCat609 WHERE TheCat609.CaseNo = TheCase23.CaseNo)
```

These statements assume Category 609 exists and belongs to the case definition (in this example Case Definition 23).

2015 +:

```
(SELECT COUNT(0) FROM dbo.TheCat609 cat WHERE cat.CaseNo = T0.CaseNo) > 0
```

OR

```
EXISTS (SELECT NULL FROM TheCat609 WHERE TheCat609.CaseNo = T0.CaseNo)
```

LEGEND:

609 is the ID of the category

23 is the ID of the case definition

T0.CaseNo or TheCase23.CaseNo are needed to restrict to the current case

2.4 Check if a multi-keyword field is empty

The following condition checks whether a multiple keyword field is empty or not.

```
(SELECT count(*) FROM TheDocuKeyXX WHERE DocNo=T0.DocNo)>0
```

This will return TRUE if at least one keyword is stored in the multiple keyword field and FALSE if the field is empty.

Legend:

XX is the ID of the Keyword used in the category.

3. Legal

All rights reserved. No parts of this work may be reproduced in any form or by any means - graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems - without the written permission of the publisher.

Any other 3rd party products that are referred to in this document may be either trademarks and/or registered trademarks of the respective owners. The publisher and the author make no claim to these trademarks.

While care has been taken in the preparation of this document, the publisher and the author assume no responsibility for errors or omissions, or for damages resulting from the use of information contained in this document.

VERSION: 2024 - 01