

STONE PATTERN SERIES

Size: 457.2*914.4*3mm

PLAST LAMINO

LVT Tiles

PM-3001

PM-3002

PM-3003

PM-3004

SCENE PICTURE

PLAST LAMINO

LVT Tiles

Luxury Vinyl Tile

FLOORING

Type of Floor Classification

EN ISO 10582
EN ISO 10874

Dimensions

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Total Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Wear Layer Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Dimensions

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Total Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Wear Layer Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Total weight

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Wear-resistant layer

Sealguard floor design and color is not worn for a long time, the floor is durable

Color film

1:1 restore the real wood grain, waterproof and non-fading

Base layer

PVC+Calcium composite, the floor has a high strength of pressure resistance

Place Makers

Luxury Vinyl Tile

EN 434
EN 12501-1
EN 433
DIN 51130
EN 13893
EN 6602
EN ISO 26987
EN 6018:EN 425
EN 424

Long 0.02%-Trans 0.4%
IP 3, glued over concrete substrate
0.4mm
Longitudinal 0.3 - Extremely Safe
Transverse 0.05 - Extremely Safe
Average Mass Loss (10% - 15 mg/100 Cycles
Average Volume Loss (PV) 1.8 mm/100 Cycles
No damage
No damage
No damage
No damage

Luxury Vinyl Tile

FLOORING

Type of Floor Classification

EN ISO 10582
EN ISO 10874

Dimensions

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Total Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Wear Layer Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Dimensions

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Total Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Wear Layer Thickness

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Total weight

EN ISO 24342
EN ISO 24346
EN ISO 24340
EN ISO 23997

Wear-resistant layer

Sealguard floor design and color is not worn for a long time, the floor is durable

Color film

1:1 restore the real wood grain, waterproof and non-fading

Base layer

PVC+Calcium composite, the floor has a high strength of pressure resistance

Place Makers

Luxury Vinyl Tile

EN 434
EN 12501-1
EN 433
DIN 51130
EN 13893
EN 6602
EN ISO 26987
EN 6018:EN 425
EN 424

Long 0.02%-Trans 0.4%
IP 3, glued over concrete substrate
0.4mm
Longitudinal 0.3 - Extremely Safe
Transverse 0.05 - Extremely Safe
Average Mass Loss (10% - 15 mg/100 Cycles
Average Volume Loss (PV) 1.8 mm/100 Cycles
No damage
No damage
No damage
No damage

WOOD GRAIN SERIES

Size: 152.4*914.3mm

PLAST LAMINO

LVT Tiles

PM-1001

PM-1002

PM-1003

PM-1004

WOOD GRAIN SERIES

Size: 152.4*914.4*3mm

PLAST LAMINO

LVT Tiles

PM-1005

PM-1006

PM-1007

PM-1008

WOOD GRAIN SERIES

Size: 152.4*914.4*3mm

PLAST LAMINO

LVT Tiles

PM-1009

PM-1010

PM-1011

PM-1012

WOOD GRAIN SERIES

Size: 152.4*914.4*3mm

PLAST LAMINO

LVT Tiles

PM-1013

PM-1014

PM-1015

PM-1016

STONE PATTERN SERIES

Size: 610*610*3mm

PLAST LAMINO

LVT Tiles

PM-2001

PM-2002

PM-2003

PM-2004

STONE PATTERN SERIES

Size: 610*610*3mm

PLAST LAMINO

LVT Tiles

PM-2005

PM-2006

PM-2007

PM-2008