AI ASSISTED CODING

ASSIGNMENT-8.1

Name: Hari Priya

H.T.No: 2303A51104

Task Description #1 (Password Strength Validator – Apply AI in Security Context)

• Task: Apply AI to generate at least 3 assert test cases for is_strong_password(password) and implement the validator function.

• Requirements:

o Password must have at least 8 characters. o Must include uppercase, lowercase, digit, and special character. o Must not contain spaces. Example Assert Test Cases:

assert is_strong_password("Abcd@123") == True

assert is_strong_password("abcd123") == False assert is_strong_password("ABCD@1234") == True

Expected Output #1:

• Password validation logic passing all AI-generated test cases.



C: > Users > HARI PRIYA > Desktop > New folder > AIAC_assignment_8.1 > Untitled-1.py > ...

```
1   def is_strong_password(password):
2       if len(password) < 8:
3           return False
4       has_upper = False
5       has_lower = False
6       has_digit = False
7       special_characters = "!@#$%^&*()-+"
8       for char in password:
9           if char.isupper():
10              has_upper = True
11          elif char.islower():
12              has_lower = True
13          elif char.isdigit():
14              has_digit = True
15          elif char in special_characters:
16              has_special = True
17      return has_upper and has_lower and has_digit and has_special
18  assert is_strong_password("Abcd@123") == True
19  assert is_strong_password("abcd123") == False
20  assert is_strong_password("ABCD@1234") == True
```

```
PS C:\Users\HARI PRIYA> & "C:/Users/HARI PRIYA/AppData/Local/Microsoft/WindowsApps/python3.11.exe" "c:/Users/HARI PRIYA/Desktop/New folder/AIAC_assignment_8.1/Untitled-1.
Traceback (most recent call last):
  File "c:\Users\HARI PRIYA\Desktop\New folder\AIAC_assignment_8.1\Untitled-1.py", line 20, in <module>
    assert is_strong_password("ABCD@1234") == True
           ^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^^

AssertionError
```

Task Description #2 (Number Classification with Loops – Apply AI for Edge Case Handling)

• Task: Use AI to generate at least 3 assert test cases for a classify_number(n) function. Implement using loops.

• Requirements:

o Classify numbers as Positive, Negative, or Zero.

o Handle invalid inputs like strings and None. o

Include boundary conditions (-1, 0, 1).

Example Assert Test Cases:

assert classify_number(10) == "Positive" assert

classify_number(-5) == "Negative" assert

classify_number(0) == "Zero"

Expected Output #2:

• Classification logic passing all assert tests.



```python
def classify_number(num):
    if num > 0:
        return "Positive"
    elif num < 0:
        return "Negative"
    else:
        return "Zero"
assert classify_number(10) == "Positive"
assert classify_number(-5) == "Negative"
assert classify_number(0) == "Zero"
```

Task Description #3 (Anagram Checker – Apply AI for String Analysis)

• Task: Use AI to generate at least 3 assert test cases for is_anagram(str1, str2) and implement the function.

• Requirements:

o Ignore case, spaces, and punctuation. o Handle

edge cases (empty strings, identical words).

Example Assert Test Cases:

assert is_anagram("listen", "silent") == True assert

is_anagram("hello", "world") == False assert

is_anagram("Dormitory", "Dirty Room") == True

Expected Output #3:

• Function correctly identifying anagrams and passing all AI- generated tests.



```python
def is_anagram(str1, str2):
    return sorted(str1.lower().replace(" ","")) == sorted(str2.lower().replace(" ", ""))
assert is_anagram("listen", "silent") == True
assert is_anagram("hello", "world") == False
assert is_anagram("Dormitory", "Dirty Room") == True
```

Task Description #4 (Inventory Class – Apply AI to Simulate Real- World Inventory System)

• Task: Ask AI to generate at least 3 assert-based tests for an Inventory class with stock management.

• Methods:

o add_item(name, quantity) o

remove_item(name, quantity) o

get_stock(name) Example Assert

Test Cases: inv = Inventory()

inv.add_item("Pen", 10) assert

inv.get_stock("Pen") == 10

inv.remove_item("Pen", 5) assert

inv.get_stock("Pen") == 5

inv.add_item("Book", 3) assert

inv.get_stock("Book") == 3

Expected Output #4:

• Fully functional class passing all assertions.



```python
class inventory:
    def __init__(self):
        self.items = {}
    def add_item(self, item, quantity):
        if item in self.items:
            self.items[item] += quantity
        else:
            self.items[item] = quantity
    def remove_item(self, name, quantity):
        if name in self.items and self.items[name] >= quantity:
            self.items[name] -= quantity
            if self.items[name] == 0:
                del self.items[name]
        else:
            print("Not enough items to remove.")
    def get_stock(self, name):
        return self.items.get(name, 0)
inv = inventory()
inv.add_item("Pen", 10)
assert inv.get_stock("Pen") == 10
inv.remove_item("Pen", 5)
assert inv.get_stock("Pen") == 5
inv.add_item("Book", 3)
assert inv.get_stock("Book") == 3
```

Task Description #5 (Date Validation & Formatting – Apply AI for Data Validation)

• Task: Use AI to generate at least 3 assert test cases for validate_and_format_date(date_str) to check and convert dates.

• Requirements:

o Validate "MM/DD/YYYY" format. o

Handle invalid dates. o Convert valid dates

to "YYYY-MM-DD".

Example Assert Test Cases:

assert validate_and_format_date("10/15/2023") == "2023-10-15" assert

validate_and_format_date("02/30/2023") == "Invalid Date" assert

validate_and_format_date("01/01/2024") == "2024-01-01" Expected

Output #5:

• Function passes all AI-generated assertions and handles edge cases.



```python
def validate_and_formart_date(date_str):
    import re
    pattern = r'^\d{2}/\d{2}/\d{4}$'
    if not re.match(pattern, date_str):
        return "Invalid date format"
    month, day, year = map(int, date_str.split("/"))

    #Days is each month
    days_in_month = [31, 28, 31, 30, 31, 30, 31, 31, 30, 31, 30, 31]

    #Check for leap year
    if year % 4 == 0 and (year % 100 != 0 or year % 400 == 0):
        days_in_month[1] = 29

    if month < 1 or month > 12 or day < 1 or day > days_in_month[month - 1]:
        return "Invalid date"
    return f"{year:04d}-{month:02d}-{day:02d}"
assert validate_and_formart_date("10/15/2023") == "2023-10-15"
assert validate_and_formart_date("02/30/2023") == "Invalid date"
assert validate_and_formart_date("01/01/2024") == "2024-01-01"
```