

ichem® Introduction

ichem was established in Cairo, Egypt.

Team business with values that include: experience , do the right thing and work hard.

As the manufacturer, we verify that only the best products are shipped out to your project.

We constantly test and review our systems for continuous innovation to provide you with the best solutions.

Yeah, we're obsessed, but in a good way **ichem** classified as a class A contractor and have built a strong reputation and growing business in Egypt.

we are able to undertake multidisciplinary projects of scale and complexity.

Fast growth in business and revenue is a testimony to our proven capability to deliver quality products and services with speed and cost effectiveness.

CONSTRUCTION CHEMICALS
SOLUTIONS



ichem[®]

Welcome to ichem[®]

A trailblazer in the construction industry, where innovation, expertise, and unwavering commitment converge to redefine the standards of excellence.

As a distinguished provider of construction solutions, we take pride in delivering cutting-edge products designed to elevate your projects to unprecedented levels of success.

GENERAL INFORMATION

Why Choose ichem for Your Construction Endeavors:

Elevate your projects with our avant-garde construction chemicals solutions. Our portfolio includes state-of-the-art admixtures and expertly formulated joint sealants that not only meet but exceed industry standards, ensuring the durability, resilience, and longevity of your structures.

Our Journey – Shaping the Future of Construction:

ichem was founded with a vision to not just meet but exceed construction standards. Throughout our journey, we have consistently pushed boundaries, set industry benchmarks, and introduced cutting-edge construction chemicals that redefine what's possible in construction



ichem[®]
CONSTRUCTION CHEMICALS

INDEX

01 | CONCRETE ADMIXTURES AND ADDITIVES

02 | ADDITIVES FOR STAPE

03 | WATERPROOFING

04 | THERMAL INSULATION

05 | CONCRETE REPAIR

06 | PROTECTIVE COATING

07 | FLOORING SOLUTIONS

08 | TILING SOLUTIONS

09 | JOINT SOLUTIONS

10 | EXTERIOR COATING

11 | TOOLS



CONCRETE ADMIXTURES AND ADDITIVES

CATEGORY

Super Plasticizers

AddChem G305	2
AddChem G307	2
AddChem G309	3
AddChem G309 Plus	4
AddChem G310	5
AddChem G311	6
AddChem G312	12
AddChem G406	10
AddChem G418	11
AddChem G249	12
AddChem G250	12
AddChem G260	11
AddChem G270	12
AddChem G271	12
AddChem G273	12
AddChem G275	11
AddChem G285	12
AddChem F388.....	12
AddChem F389.....	12
AddChem F390.....	12
AddChem F391.....	12
AddChem F393.....	12
AddChem F395.....	11
AddChem F400.....	12

Self Compact Early Strength Super Plasticizers

AddChem Row 5055	2
AddChem Row 4000A	2
AddChem Row 4030A	2
AddChem Flow 4070A.....	7
AddChem Flow 5000A.....	9
AddChem Flow 525RA	10
AddChem Flow 535RA	11
AddChem Row 540RA.....	2
AddChem Flow 2020R.....	12
AddChem Flow 2025R.....	12
AddChem Flow 2030R.....	11
AddChem Flow 2035R.....	12

Foam Forming Admixtures

AddChem Foam LC 100.....	12
--------------------------	----

Plasticizers For Ready Mix

AddChem D103	12
--------------------	----

Release Agent

AddChem Form 4	12
AddChem Form GP	12

Concrete Curing

ChemCure WB	5
ChemCure WX	5
ChemCure SB.....	5
ChemCure AR	5

Retarders

AddChem Stap25.....	12
---------------------	----

Stabilizers

AddChem Staplizier RH	12
-----------------------------	----

Accelerators

AddChem Quick R100.....	3
-------------------------	---

Additives For Concrete

AddChem Slurry S50.....	2
-------------------------	---

Air Entraining Agent

AddChem AIR 333	4
-----------------------	---

Tunnel & Underground

AddChem Tard T109	4
AddChem T111.....	4

Waterproofing Admixtures

AddChem 103 WP.....	12
AddChem 110 WP	12

Fiber

AddChem FG	12
AddChem PPF.....	12
AddChem MF	12

ADDITIVES FOR STAPE

Waterproofing Additives

AddChem WPL	12
AddChem WPP	12

Waterproofing & Bonding Agent Additives

iLatex SBR	12
iBond SBR.....	12
iBond AR	12
iBond PVA	12

Accelerating & Waterproofing Admixtures

AddChem Q2	12
AddChem Q4	12

Mortar Expanding Admixtures

AddChem EX	12
------------------	----

WATER PROOFING SYSTEMS

Damp Proofing

BituCoat WB	1
BituCoat R10.....	2
BituCoat S.....	3
BituCoat RS.....	3
BituCoat XS.....	3

Waterproofing Membrane

ChemGuard SBS.....	2
ChemGuard AR.....	3
ChemGuard P2.....	2
ChemGuard FG	3
ChemGuard PVC	2
ChemGuard EPDM	3
ChemGuard TPO	3
ChemSheet PE	3

Cementitious Waterproofing

ChemProof 1.....	5
ChemProof 110	5
ChemProof 120	5
ChemProof 120 El	9

ChemProof 520	9
---------------------	---

Acrylic Waterproofing

AcryShield 60	7
ChemShield PF	8

Epoxy Waterproofing

ChemProof CT	10
--------------------	----

Water Repellent Agents

ChemShield WR	11
ChemShield WRS	11
ChemShield WRX	11

Waterstop Profiles

isoFlex 300	13
isoFlex PVC	12
isoFlex SB	12
Waterstop Clip	2

Protective Sheets

ChemGeotex PP	13
ChemGeotex PE	12
ChemShield PC	2

THERMAL INSULATION

Foam

ChemFoam XPS	14
ChemFoam EPS	14

Mineral Wool Insulation

ChemRock	14
ChemGlass	14

CONCRETE REPAIR

Cementitious Repairing

CemGrout 920	3
CemGrout NS	3
ChemFlow MC	3
MasterCem R20	4

MasterCem RF	3
ChemCrack C.....	3

Acrylic Repairing

ChemCrack AR	7
--------------------	---

Cementitious Rapid Setting Mortar

ChemPlug.....	7
---------------	---

Epoxy Repairing

EpoGrout.....	3
EpoMortar SF	5
EpoMortar PU.....	5
ChemPutty	4
EpoBond SF	4

Surface Trearment

ChemPaste C	5
-------------------	---

Reinforcement Matrial

ChemNet FG.....	5
-----------------	---

PROTECTIVE COATING

Steel Protection

ChemSheild Pro	5
ChemZinc 1	5
ChemZinc 2	5

Chemical Resistance Coating

ChemCoat NO	12
ChemCoat PUR	12
ChemCoat AR	12
ChemCarpo Shield	12

FLOORING SOLUTIONS

Epoxy Coating

ChemFloor 100	1
ChemPrime EP	1
ChemFloor EP200	3
ChemFloor EP400	3

Multi Components Epoxy System

ChemFloor SL 100	7
ChemFloor SL 300	8
ChemFloor M50	9

Cementitious Flooring Systems

ChemFloor C10	13
ChemFloor C30	12

Stamped Concrete

ChemColor C	13
ChemReverse.....	13
ChemSeler WB.....	13
ChemSeler AR.....	13

Road Marking

ChemRoad	12
ChemTraffic AC	12

Dry Shake Surface Hardner

ChemHard C.....	13
ChemHard M.....	13

TILING SOLUTIONS**Cementitious Tile Adhesive**

ChemTile C100.....	15
ChemTile C120.....	11
ChemTile WP.....	17
ChemTile G.....	18

Epoxy Tile Adhesive

ChemTile EP.....	19
ChemTile EPG.....	19

JOINT SOLUTIONS**Sealing Materials**

ChemSeal PU	12
ChemSeal 1.....	13
ChemSeal 2.....	13
ChemJoint	1
ChemSeal AR	13

ChemSeal PS.....13

ChemSeal FS.....13

Vapor Barriers

iFlex PVC.....13

iFlex EPDM.....13

Joint Fillers

iFlex RS.....13

iFlex BR.....13

EXTERIOR COATING

Cementitious Coating

ChemDecor15

ChemDecor Plus16

Acrylic Coating

ChemDecor AR15

ChemDecor AR Plus16

Seler

ChemSeler PVA.....16

TOOLS

WaterStop Welding..... 2

Spiked Shoes..... 2

Spiked Roll 2

Notched Trowel..... 2

Sealant Gun 600ML 2

Injection Gun 300ML..... 2



Concrete Admixtures and Additives

ChemProof 110®

Economical Cementitious Waterproofing Coating



Description

The **ChemProof 110®** is a two-component cement-based multi-purpose water proofing slurry.

Key Features

- Impermeable.
- Non-toxic-suitable for contact with potable water.
- Brush or trowel applied.
- Very good adhesion to most construction materials.
- Hardens without shrinkage.
- Easy to apply.
- Excellent resistance to a wide range of chemicals.
- Non-corrosive to steel or iron & over-paintable.

Technical Properties

Density	2.0 kg/l (mixed)
Compressive Strength	at +25C (28 days) 30 - 35 N/mm ²
Flexural Strength	at +25C (28 days) 8 - 10 N/mm ²
Coverage	Depending on the type of surface to be insulated. 2 : 2.5 kg/ m ² for two coats
Bond Strength	2 - 3 N/mm ² after 28 days
Mixing Ratio	1: 4.5 by weight
Colour	Grey and White
Base	Part A : liquid polymer and additive. Part B : Portland cement selected aggregate and admixtures.
Packaging	25 kg (A+B) (5 kg pails of component A and 20 kg bags of component B)

Application Instructions

Surface Preparation:

All loose particles, laitance, dust and grease etc., must be removed prior to application of

ChemProof 110®. Concrete must be at least 4 - 6 weeks old, depending on climate, wire-brush, sand- or waterblasted or grind substrates.

Mixing:

Use a low speed electric drill fitted with a paint mixer a wing type paddle. In hot weather, use cool water to bring the mixed grout temperature to <30°C. In cold weather, use warm water to raise the mixed grout temperature to >10°C.

Application:

While the surface is still damp (no standing water) apply the first coat and leave to harden (2-6 hours). apply, using a short, stiff bristle brush or roller. Where more than one coat is found necessary, to achieve the desired thickness, apply the second or subsequent coats after the previous coat has dried

ChemProof 110®

Economical Cementitious Waterproofing Coating



Description

The **ChemProof 110®** is a two-component cement-based multi-purpose water proofing slurry.

Key Features

- Impermeable.
- Non-toxic-suitable for contact with potable water.
- Brush or trowel applied.
- Very good adhesion to most construction materials.
- Hardens without shrinkage.
- Easy to apply.
- Excellent resistance to a wide range of chemicals.
- Non-corrosive to steel or iron & over-paintable.

Technical Properties

Density	2.0 kg/l (mixed)
Compressive Strength	at +25C (28 days) 30 - 35 N/mm ²
Flexural Strength	at +25C (28 days) 8 - 10 N/mm ²
Coverage	Depending on the type of surface to be insulated. 2 : 2.5 kg/ m ² for two coats
Bond Strength	2 - 3 N/mm ² after 28 days
Mixing Ratio	1: 4.5 by weight
Colour	Grey and White
Base	Part A : liquid polymer and additive. Part B : Portland cement selected aggregate and admixtures.
Packaging	25 kg (A+B) (5 kg pails of component A and 20 kg bags of component B)

Application Instructions

Surface Preparation:

All loose particles, laitance, dust and grease etc., must be removed prior to application of

ChemProof 110®. Concrete must be at least 4 - 6 weeks old, depending on climate, wire-brush, sand- or waterblasted or grind substrates.

Mixing:

Use a low speed electric drill fitted with a paint mixer a wing type paddle. In hot weather, use cool water to bring the mixed grout temperature to <30°C. In cold weather, use warm water to raise the mixed grout temperature to >10°C.

Application:

While the surface is still damp (no standing water) apply the first coat and leave to harden (2-6 hours). apply, using a short, stiff bristle brush or roller. Where more than one coat is found necessary, to achieve the desired thickness, apply the second or subsequent coats after the previous coat has dried

OUR COMPANY'S GROWTH

