

Work & documentation notes of various wargames

Galen Rowell

July 14, 2020

1 Bandit

1.1 Levels

1.1.1 bandit0

Password to enter: *bandit0*

Challenge: Solved using the **ssh** command, which included use of flags to set user & port.

```
ssh bandit0@bandit.labs.overthewire.org -p 2220
```

1.1.2 bandit1

Password to enter: *boJ9jbbUNNfktD78OOpsqOltutMc3MY1*

Challenge: Reading a file named '-', this was problematic due to many common shell commands using '-' to prefix an option or flag.

```
cat ./-
```

1.1.3 bandit2

Password to enter: *CV1DtqXWVFXTvM2F0k09SHz0YwRINYA9*

Challenge: With spaces in a filename, shell programs will interpret the input as several arguments (instead of one space-delimited string). This issue can be solved two ways.

```
cat 'spaced filename'
```

```
cat spaced\ filename
```

1.1.4 bandit3

Password to enter: *UmHadQclWmgdLOKQ3YNgjWxGoRMb5luK*

Challenge: The file is prepended by a '.', which causes it to be hidden from most views. The **-A** flag for **ls** will show all hidden files except '.' & '..', which are part of the directory itself.

```
ls -A1
```

1.1.5 bandit4

Password to enter: *pIwrPrtPN36QITSp3EQaw936yaFoFgAB*

Challenge: The file is hidden in one of '/inhere/-file0,9'. They contain special characters that interfere with the terminal environment. The use of **file** aids as it lists the encoding of a given file.

```
file ./*
```

1.1.6 bandit5

Password to enter: *koReBOKuIDDepwhWk7jZC0RTdopnAYKh*

Challenge: The file is within one of many sub-folders, with human readable encoding and a file size of '1033' bytes. The use of **ls** with the recursive flag **-R**, combined with **grep** to select the file with the given size solves this problem.

```
ls -Al -R | grep --color -C 5 -e '1033'
```

1.1.7 bandit6

Password to enter: *DXjZPULLxYr17uwoI01bNLQbtFemEgo7*

Challenge: The file is somewhere on the server, so we should search recursively from the root of the drive. We are given the owner name, group name and size of the file, which we can plug into **find** to find the file.

```
find / -group bandit6 -size 33c 2>&1 | grep -v "Permission denied"
```

*Note: The use of a terminal redirect and **grep** remove the output of excessive file permission warnings*

1.1.8 bandit7

Password to enter: *HKBPTKQnIay4Fw76bEy8PVxKEDQRKTzs*

Challenge: This level is a simple grep search for the word *millionth* in a large keyword text file.

1.1.9 bandit8

Password to enter: *cvX2JJJa4CFALtqS87jk27qwqGhBM9plV*

Challenge: The password is the only line that occurs once within an unordered text file.

```
sort data.txt | uniq -u
```

*Note: The -u flag of **uniq** ensures only lines of 1 occurrence are printed*

1.1.10 bandit9

Password to enter: *UsvVyFSfZZWbi6wgC7dAFyFuR6jQQUhR*

Challenge: The given file is a binary encoded file, IE. it is not in plaintext or easy to read. **strings** will only print human-readable strings from a given input, and the use of **grep** will limit the output to a manageable size.

```
strings data.txt | grep -Ee [=]+
```

*Note: The [=]+ pattern of **grep** searches for one or more occurrences of = in each line, EG. =, ===== or =====*

1.1.11 bandit10

Password to enter: *truKLdjsbJ5g7yyJ2X2R0o3a5HQQJFuLk*

Challenge: The file is encoded in base 64, which can be encoded and decoded using the **base64** program.

```
base64 -d data.txt
```

1.1.12 bandit11

Password to enter: *IFukwKGsFW8MOq3IRFqrxE1hxTNEbUPR*

Challenge: The file is encoded in a ROT-13 cipher, meaning that all letters in the alphabet have been shifted 13 places. **tr** is a unix program which is used to translate various sets of text.

```
cat data.txt | tr "n-za-mN-ZA-M" "a-zA-Z"
```

1.1.13 bandit12

Password to enter: *5Te8Y4drgCRfCx8ugdwuEX8KFC6k2EUu*

Challenge: The given file is a hexdump of a binary file, which is a compressed **gzip** file. The **gzip** file is itself compressed many times with **gzip**, **bzip2** & **tar**. One of the best ways to discover what encoding a file has is to run **file** on the given file, as well as visual inspection with **less**.

The methodology used to solve the level was to inspect the file encoding using **file**, find the appropriate decompression program, then repeat until the end result was the final plain-text.

gzip has a 'unix-pipe' program version named **zcat**.

bzip2 has a 'unix-pipe' program version named **bzcat**.

tar acts like a 'unix-pipe' program with the arguments **tar xO**.

The use of these *unix-pipe* versions allow use to pipe the input through *std-in* and have the decompressed output sent to *std-out*.

to uncompress a hexdump

```
xxd -r data.txt a.bin
```

to test the file encoding/type from std-in

```
file -
```

the series of decompression required

```
xxd -r data.txt a.bin
```

```
zcat a.bin | bzcat | zcat | tar xO | tar xO | bzcat | tar xO | zcat
```

1.1.14 bandit13

Password to enter: *8ZjyCRiBWFYkneahHwxCv3wb2a1ORpYL*

Challenge: This is a small challenge regarding SSH keys, a private key to access the next level is given. **ssh**'s **-i** flag uses the given key to authenticate the connection.

```
ssh bandit14@localhost -i sshkey.private
```

1.1.15 bandit14

Password to enter: *4wcYUJFw0k0XLShlDzztnTBHiqxU3b3e*

Challenge: This passwords for the next level is retrieved by sending the password for the current level to port 30,000 of the machine (*IE. localhost*). This was solved by using a dated, but universal, shell program called **net cat**.

```
1 nc localhost 30000
2 4wcYUJFw0k0XLShlDzztnTBHiqxU3b3e
3 Correct!
4 BfMYroe26WYalil77FoDi9qh59eK5xNr
```

Note: Line #2 was entered manually, lines #3-4 were a 'response' from port 30,000

1.1.16 bandit15

Password to enter: *BfMYroe26WYalil77FoDi9qh59eK5xNr*

Challenge: This challenge covers the use of **openssl**, and it's broad uses as a cryptographic tool for certificate and key generation/management. **openssl** has many sub-commands, of particular note is the **s_client** sub-command.

```
cat bandit15 | openssl s_client -connect localhost:30001 -ign_eof
```

Note: the flag '-ign_eof' is used to allow the piping from cat into the session, alternatively the text can be manually input.

1.1.17 bandit16

Password to enter: *cluFn7wTiGryunymYOu4RcfftSxQluehd*

Challenge: This challenge expands more upon basic TCP/IP technologies, and covers port scanning with the use of **nmap**. **nmap** is an extremely powerful and ubiquitous ip & port scanning tool. It can be used to detect open ports and what they are running to detecting the OS a given machine is running.

scan ports 31000 32000 of localhost and attempt to discover what they are running

```
nmap -sV -p 31000-32000 localhost
```

1.1.18 bandit17

Password to enter: *xLYVMN9WE5zQ5vHacb0sZEVqbrp7nBTn*

Challenge: This challenge is a simple use of **diff**, to find the password which is the one line of difference between the two files.

```
diff passwords.new passwords.old
```

1.1.19 bandit18

Password to enter: *kfBf3eYk5BPBRzwjqutbbfE887SVc5Yd*

Challenge: The login shell environment for level 18 automatically logs the user out. This prevents users from entering in any commands but is solved by using a feature of **ssh**, in which a command can be specified (instead of invoking a login shell).

```
ssh [... various flags/options ...] destination [command]
ssh bandit18@bandit.labs.overthewire.org -p 2220 /bin/sh
```

1.1.20 bandit19

Password to enter: *IueksS7Ubh8G3DCwVzrTd8rAVOwq3M5x*

Challenge: This covers the shell programs **setuid** & **setgid**.

According to Wikipedia: **setuid** and **setgid** (short for "set user ID" and "set group ID") are Unix access rights flags that allow users to run an executable with the permissions of the executable's owner or group respectively and to change behaviour in directories. They are often used to allow users on a computer system to run programs with temporarily elevated privileges in order to perform a specific task

In essence they allow a user to execute a file as if they were a different (possibly higher-privileged) user.

1.1.21 bandit20

Password to enter: *GbKksEFF4yrVs6il55v6gwY5aVje5f0j*

Challenge: This level covers LINUX jobs, which enable the pausing of an active process, sending it to the background and other various features. This allows us to do things like set a server running in the background and connect to it all from the same terminal. The main issue here is a self-imposed limitation of using one **ssh** connection, it would be far more trivial if we used multiple connections.

1. set up the server for the given executable to connect to, place it in the background
2. connect the executable to the server, place it in the background
3. bring the server into the foreground, send the password to our executable

```
1 nc -l -p 30101 &
2 ./suconnect 30101 &
3 fg 1
4 nc -l -b -p 30101
5 GbKksEFF4yrVs6il55v6gwY5aVje5f0j
6 Read: GbKksEFF4yrVs6il55v6gwY5aVje5f0j
7 Password matches, sending next password
8 gE269g2h3mw3pwgrj0Ha9Uoqen1c9DGr
```

Note: Line #5 was entered by the user

*Note: **nc** or **netcat** varies by system and has oddities which had to be worked around for the script to function*

Links & resources

1. The bandit wargame is run on a remote server, accessed by ssh. In order to write scripts to log what I executed and re-run/solve the level then a tool is needed to be able to feed the password during the handshake process. SSHpass is great for this: [SSHPass tutorial](#)
2. When scripting, it is often useful to have a temporary directory where files can be created & modified without the risk of littering such files about the filesystem. So a temporary directory (often in /tmp/) is useful, **mktemp** does this:

move to the new temporary directory

```
cd $(mktemp -d)
```

store the new temporary directory path

```
tmp_dir=$(mktemp -d)
```