



Natural Language Processing

Anoop Sarkar

`anoopsarkar.github.io/nlp-class`

September 16, 2014

Smoothing n -gram Models

- Event Space for n -gram Models

- Smoothing Counts

 - Add-one Smoothing

 - Additive Smoothing

 - Good-Turing Smoothing

- Smoothing by Interpolation

 - Interpolation: Jelinek-Mercer Smoothing

- Backoff Smoothing

 - Katz Backoff

 - Backoff Smoothing with Discounting

Cross-Entropy and Perplexity

Trigram Models

- ▶ The trigram model:

$$\begin{aligned} P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1}) \end{aligned}$$

Trigram Models

- ▶ The trigram model:

$$\begin{aligned} P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1}) \end{aligned}$$

- ▶ Notice that the length of the sentence n is variable

Trigram Models

- ▶ The trigram model:

$$P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1})$$

- ▶ Notice that the length of the sentence n is variable
- ▶ What is the event space?

The stop symbol

- ▶ Let $\mathcal{V} = \{a, b\}$ and the language L be \mathcal{V}^*

The stop symbol

- ▶ Let $\mathcal{V} = \{a, b\}$ and the language L be \mathcal{V}^*
- ▶ Consider a unigram model: $P(a) = P(b) = 0.5$

The stop symbol

- ▶ Let $\mathcal{V} = \{a, b\}$ and the language L be \mathcal{V}^*
- ▶ Consider a unigram model: $P(a) = P(b) = 0.5$
- ▶ So strings in this language L are:

a stop 0.5

b stop 0.5

aa stop 0.5^2

bb stop 0.5^2

\vdots

The stop symbol

- ▶ Let $\mathcal{V} = \{a, b\}$ and the language L be \mathcal{V}^*
- ▶ Consider a unigram model: $P(a) = P(b) = 0.5$
- ▶ So strings in this language L are:

a stop	0.5
b stop	0.5
aa stop	0.5^2
bb stop	0.5^2
\vdots	

- ▶ The sum over all strings in L should be equal to 1:

$$\sum_{w \in L} P(w) = 1$$

The stop symbol

- ▶ Let $\mathcal{V} = \{a, b\}$ and the language L be \mathcal{V}^*
- ▶ Consider a unigram model: $P(a) = P(b) = 0.5$
- ▶ So strings in this language L are:

a stop	0.5
b stop	0.5
aa stop	0.5^2
bb stop	0.5^2
\vdots	

- ▶ The sum over all strings in L should be equal to 1:

$$\sum_{w \in L} P(w) = 1$$

- ▶ But $P(a) + P(b) + P(aa) + P(bb) = 1.5$!!

The stop symbol

- ▶ What went wrong?
We need to model variable length sequences

The stop symbol

- ▶ What went wrong?
We need to model variable length sequences
- ▶ Add an explicit probability for the stopsymbol:

$$P(a) = P(b) = 0.25$$

$$P(\text{stop}) = 0.5$$

The stop symbol

- ▶ What went wrong?
We need to model variable length sequences
- ▶ Add an explicit probability for the stopsymbol:

$$P(a) = P(b) = 0.25$$

$$P(\text{stop}) = 0.5$$

- ▶ $P(\text{stop}) = 0.5$, $P(a \text{ stop}) = P(b \text{ stop}) = 0.25 \times 0.5 = 0.125$,
 $P(aa \text{ stop}) = 0.25^2 \times 0.5 = 0.03125$ (now the sum is no longer greater than one)

The stop symbol

- ▶ With this new stop symbol we can show that $\sum_w P(w) = 1$
Notice that the probability of any sequence of length n is $0.25^n \times 0.5$

Also there are 2^n sequences of length n

$$\begin{aligned}\sum_w P(w) &= \\&= \sum_{n=0}^{\infty} 2^n \times 0.25^n \times 0.5 \\&= \sum_{n=0}^{\infty} 0.5^n \times 0.5 = \sum_{n=0}^{\infty} 0.5^{n+1} \\&= \sum_{n=1}^{\infty} 0.5^n = 1\end{aligned}$$

Bigram Models

- In practice:

$$\begin{aligned} P(\text{Mork read a book}) = & \\ & P(\text{Mork} \mid <\text{start}>) \times P(\text{read} \mid \text{Mork}) \times \\ & P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times \\ & P(<\text{stop}> \mid \text{book}) \end{aligned}$$

Bigram Models

- In practice:

$$P(\text{Mork read a book}) =$$

$$P(\text{Mork} \mid \langle \text{start} \rangle) \times P(\text{read} \mid \text{Mork}) \times$$

$$P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times$$

$$P(\langle \text{stop} \rangle \mid \text{book})$$

- $P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$

On unseen data, $c(w_{i-1}, w_i)$ or worse $c(w_{i-1})$ could be zero

$$\sum_{w_i} \frac{c(w_{i-1}, w_i)}{c(w_{i-1})} = ?$$

Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times

Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times
- ▶ Smoothing algorithms also tend to improve the accuracy of the model

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times
- ▶ Smoothing algorithms also tend to improve the accuracy of the model

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Not just unobserved events: what about events observed once?

Add-one Smoothing

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Add-one Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{1 + c(w_{i-1}, w_i)}{V + c(w_{i-1})}$$

Add-one Smoothing

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Add-one Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{1 + c(w_{i-1}, w_i)}{V + c(w_{i-1})}$$

- Let V be the number of words in our vocabulary
Assign count of 1 to unseen bigrams

Add-one Smoothing

$$\begin{aligned} P(\text{Mindy read a book}) = & \\ & P(\text{Mindy} \mid \langle \text{start} \rangle) \times P(\text{read} \mid \text{Mindy}) \times \\ & P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times \\ & P(\langle \text{stop} \rangle \mid \text{book}) \end{aligned}$$

- Without smoothing:

$$P(\text{read} \mid \text{Mindy}) = \frac{c(\text{Mindy, read})}{c(\text{Mindy})} = 0$$

Add-one Smoothing

$$\begin{aligned} P(\text{Mindy read a book}) = & \\ & P(\text{Mindy} \mid \langle \text{start} \rangle) \times P(\text{read} \mid \text{Mindy}) \times \\ & P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times \\ & P(\langle \text{stop} \rangle \mid \text{book}) \end{aligned}$$

- ▶ Without smoothing:

$$P(\text{read} \mid \text{Mindy}) = \frac{c(\text{Mindy, read})}{c(\text{Mindy})} = 0$$

- ▶ With add-one smoothing (assuming $c(\text{Mindy}) = 1$ but $c(\text{Mindy, read}) = 0$):

$$P(\text{read} \mid \text{Mindy}) = \frac{1}{V + 1}$$

Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Add-one smoothing works horribly in practice. Seems like 1 is too large a count for unobserved events.

Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Add-one smoothing works horribly in practice. Seems like 1 is too large a count for unobserved events.
- ▶ Additive Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{\delta + c(w_{i-1}, w_i)}{(\delta \times V) + c(w_{i-1})}$$

Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Add-one smoothing works horribly in practice. Seems like 1 is too large a count for unobserved events.
- ▶ Additive Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{\delta + c(w_{i-1}, w_i)}{(\delta \times V) + c(w_{i-1})}$$

- ▶ $0 < \delta \leq 1$
Still works horribly in practice, but better than add-one smoothing.

Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Imagine you're sitting at a sushi bar with a conveyor belt.

Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Imagine you're sitting at a sushi bar with a conveyor belt.
- ▶ You see going past you 10 plates of tuna, 3 plates of unagi, 2 plates of salmon, 1 plate of shrimp, 1 plate of octopus, and 1 plate of yellowtail

Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Imagine you're sitting at a sushi bar with a conveyor belt.
- ▶ You see going past you 10 plates of tuna, 3 plates of unagi, 2 plates of salmon, 1 plate of shrimp, 1 plate of octopus, and 1 plate of yellowtail
- ▶ Chance you will observe a new kind of seafood: $\frac{3}{18}$

Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Imagine you're sitting at a sushi bar with a conveyor belt.
- ▶ You see going past you 10 plates of tuna, 3 plates of unagi, 2 plates of salmon, 1 plate of shrimp, 1 plate of octopus, and 1 plate of yellowtail
- ▶ Chance you will observe a new kind of seafood: $\frac{3}{18}$
- ▶ How likely are you to see another plate of salmon: should be $< \frac{2}{18}$

Good-Turing Smoothing

- ▶ How many types of seafood (words) were seen once? Use this to predict probabilities for unseen events

Let n_1 be the number of events that occurred once: $p_0 = \frac{n_1}{N}$

Good-Turing Smoothing

- ▶ How many types of seafood (words) were seen once? Use this to predict probabilities for unseen events

Let n_1 be the number of events that occurred once: $p_0 = \frac{n_1}{N}$

- ▶ The Good-Turing estimate states that for any n -gram that occurs r times, we should pretend that it occurs r^* times

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

Good-Turing Smoothing

- ▶ How many types of seafood (words) were seen once? Use this to predict probabilities for unseen events

Let n_1 be the number of events that occurred once: $p_0 = \frac{n_1}{N}$

- ▶ The Good-Turing estimate states that for any n -gram that occurs r times, we should pretend that it occurs r^* times

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

- ▶ n_r : number of different objects seen r times

Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail

Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is new data? Let n_1 be the number of items occurring once, which is 3 in this case. N is the total, which is 18.

$$p_0 = \frac{n_1}{N} = \frac{3}{18} = 0.166$$

Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail

Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is *octopus*? Since $c(\text{octopus}) = 1$ The GT estimate is 1^* .

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

$$p_{GT} = \frac{r^*}{N}$$

Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is *octopus*? Since $c(\text{octopus}) = 1$ The GT estimate is 1^* .

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

$$p_{GT} = \frac{r^*}{N}$$

- ▶ To compute 1^* , we need $n_1 = 3$ and $n_2 = 1$

$$1^* = 2 \times \frac{1}{3} = \frac{2}{3}$$

$$p_1 = \frac{1^*}{18} = 0.037$$

Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is *octopus*? Since $c(\text{octopus}) = 1$ The GT estimate is 1^* .

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

$$p_{GT} = \frac{r^*}{N}$$


- ▶ To compute 1^* , we need $n_1 = 3$ and $n_2 = 1$

$$1^* = 2 \times \frac{1}{3} = \frac{2}{3}$$

$$p_1 = \frac{1^*}{18} = 0.037$$

- ▶ What happens when $n_{r+1} = 0$? (smoothing before smoothing)

Simple Good-Turing: linear interpolation for missing n_{r+1}



$$f(r) = a + b * r$$

$$a = 2.3$$

$$b = -0.17$$

r	$n_r = f(r)$
1	2.14
2	1.97
3	1.80
4	1.63
5	1.46
6	1.29
7	1.12
8	0.95
9	0.78
10	0.61
11	0.44

Comparison between Add-one and Good-Turing

freq r	num with freq r n_r	NS p_r	Add1 p_r	SGT p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

► $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$

Comparison between Add-one and Good-Turing

freq	num with freq r	NS	Add1	SGT
r	n_r	p_r	p_r	p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$
- ▶ $V = 1 + 3 + 2 + 1 + 1 + 1 = 9$

Comparison between Add-one and Good-Turing

freq r	num with freq r n_r	NS p_r	Add1 p_r	SGT p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$
- ▶ $V = 1 + 3 + 2 + 1 + 1 + 1 = 9$
- ▶ Important: we added a new word type for unseen words. Let's call it UNK, the unknown word.

Comparison between Add-one and Good-Turing

freq r	num with freq r n_r	NS p_r	Add1 p_r	SGT p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$
- ▶ $V = 1 + 3 + 2 + 1 + 1 + 1 = 9$
- ▶ Important: we added a new word type for unseen words. Let's call it UNK, the unknown word.
- ▶ Check that: $1.0 == \sum_r n_r \times p_r$
 $0.12 + (3 * 0.03079) + (2 * 0.06719) + 0.1045 + 0.1797 + 0.3691 = 1.0$

Comparison between Add-one and Good-Turing

freq r	num with freq r n_r	NS p_r	Add1 p_r	SGT p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- NS = No smoothing: $p_r = \frac{r}{N}$

Comparison between Add-one and Good-Turing

freq r	num with freq r n_r	NS p_r	Add1 p_r	SGT p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ NS = No smoothing: $p_r = \frac{r}{N}$
- ▶ Add1 = Add-one smoothing: $p_r = \frac{1+r}{V+N}$

Comparison between Add-one and Good-Turing

freq r	num with freq r n_r	NS p_r	Add1 p_r	SGT p_r
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ NS = No smoothing: $p_r = \frac{r}{N}$
- ▶ Add1 = Add-one smoothing: $p_r = \frac{1+r}{V+N}$
- ▶ SGT = Simple Good-Turing: $p_0 = \frac{n_1}{N}$, $p_r = \frac{(r+1) \frac{n_{r+1}}{n_r}}{N}$
with linear interpolation for missing values where $n_{r+1} = 0$
(Gale and Sampson, 1995) <http://www.grsampson.net/AGtf1.html>

Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- In add-one or Good-Turing:

$$P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$$

Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ In add-one or Good-Turing:
 $P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$
- ▶ If $c(w_{i-1}, w_i) = 0$, then use $P(w_i)$ (back off)

Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ In add-one or Good-Turing:
 $P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$
- ▶ If $c(w_{i-1}, w_i) = 0$, then use $P(w_i)$ (back off)
- ▶ Works for trigrams too: back off to bigrams and then unigrams

Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ In add-one or Good-Turing:
 $P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$
- ▶ If $c(w_{i-1}, w_i) = 0$, then use $P(w_i)$ (back off)
- ▶ Works for trigrams too: back off to bigrams and then unigrams
- ▶ Problem: probabilities get mixed up (unseen bigrams, for example will get higher probabilities than seen bigrams)

Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$
where, $0 \leq \lambda \leq 1$

Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$
where, $0 \leq \lambda \leq 1$
- ▶ Notice that $P_{JM}(\text{the} \mid \text{string}) > P_{JM}(\text{Fonz} \mid \text{string})$ as we wanted

Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$
where, $0 \leq \lambda \leq 1$
- ▶ Notice that $P_{JM}(\text{the} \mid \text{string}) > P_{JM}(\text{Fonz} \mid \text{string})$ as we wanted
- ▶ Jelinek-Mercer (1980) describe an elegant form of this **interpolation**:

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$
where, $0 \leq \lambda \leq 1$
- ▶ Notice that $P_{JM}(\text{the} \mid \text{string}) > P_{JM}(\text{Fonz} \mid \text{string})$ as we wanted
- ▶ Jelinek-Mercer (1980) describe an elegant form of this **interpolation**:

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

- ▶ What about $P_{JM}(w_i)$?
For missing unigrams: $P_{JM}(w_i) = \lambda P_{ML}(w_i) + (1 - \lambda)\frac{\delta}{V}$

Interpolation: Finding λ

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

- ▶ Deleted Interpolation (Jelinek, Mercer)
compute λ values to minimize cross-entropy on **held-out** data
which is **deleted** from the initial set of training data

Interpolation: Finding λ

$$P_{JM}(ngram) = \lambda P_{ML}(ngram) + (1 - \lambda)P_{JM}(n - 1gram)$$

- ▶ Deleted Interpolation (Jelinek, Mercer)
compute λ values to minimize cross-entropy on **held-out** data
which is **deleted** from the initial set of training data
- ▶ Improved JM smoothing, a separate λ for each w_{i-1} :

$$P_{JM}(w_i \mid w_{i-1}) = \lambda(w_{i-1})P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda(w_{i-1}))P_{ML}(w_i)$$

$$\text{where } \sum_i \lambda(w_i) = 1 \text{ because } \sum_{w_i} P(w_i \mid w_{i-1}) = 1$$

Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.

Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.
- ▶ Also called discounting since we remove some probability from observed events.

Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.
- ▶ Also called discounting since we remove some probability from observed events.
- ▶ Katz Backoff (include Good-Turing with Backoff Smoothing)

$$P_{katz}(y \mid x) = \begin{cases} \frac{c^*(xy)}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x)P_{katz}(y) & \text{otherwise} \end{cases}$$

Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.
- ▶ Also called discounting since we remove some probability from observed events.
- ▶ Katz Backoff (include Good-Turing with Backoff Smoothing)

$$P_{katz}(y \mid x) = \begin{cases} \frac{c^*(xy)}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x)P_{katz}(y) & \text{otherwise} \end{cases}$$

- ▶ where $\alpha(x)$ is chosen to make sure that $P_{katz}(y \mid x)$ is a proper probability

$$\alpha(x) = 1 - \sum_y \frac{c^*(xy)}{c(x)}$$

Backoff Smoothing: Katz Backoff

x	$c(x)$	$c^*(x)$	$\frac{c^*(x)}{c(the)}$
the	48		
the,dog	15	14.5	14.5/48
the,woman	11	10.5	10.4/48
the,man	10	9.5	9.5/48
the,park	5	4.5	4.5/48
the,job	2	1.5	4.5/48
the,telescope	1	0.5	0.5/48
the>manual	1	0.5	0.5/48
the,afternoon	1	0.5	0.5/48
the,country	1	0.5	0.5/48
the,street	1	0.5	0.5/48
TOTAL			0.9479
the,UNK	0		0.052

Backoff Smoothing with Discounting

- ▶ Witten-Bell discounting
use the $n - 1$ gram model when the n gram model has too few unique words in the n gram context

Backoff Smoothing with Discounting

- ▶ Witten-Bell discounting
use the $n - 1$ gram model when the n gram model has too few unique words **in the n gram context**
- ▶ Absolute discounting (Ney, Essen, Kneser)

$$P_{abs}(y \mid x) = \begin{cases} \frac{c(xy) - D}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x) P_{abs}(y) & \text{otherwise} \end{cases}$$

compute $\alpha(x)$ as was done in Katz smoothing

Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing
 $P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$

Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing
$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$
 - ▶ *Francisco* is common, so interpolation gives $P(\text{Francisco} \mid \text{eggplant})$ a high value

Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing

$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$

- ▶ *Francisco* is common, so interpolation gives $P(\text{Francisco} \mid \text{eggplant})$ a high value
- ▶ But *Francisco* occurs in few contexts (only after *San*)

Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing

$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$

- ▶ *Francisco* is common, so interpolation gives $P(\text{Francisco} \mid \text{eggplant})$ a high value
- ▶ But *Francisco* occurs in few contexts (only after *San*)
- ▶ *stew* is common, **and** occurs in many contexts

Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing

$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$

- ▶ *Francisco* is common, so interpolation gives $P(\text{Francisco} \mid \text{eggplant})$ a high value
- ▶ But *Francisco* occurs in few contexts (only after *San*)
- ▶ *stew* is common, **and** occurs in many contexts
- ▶ Hence weight the interpolation based on number of contexts for the word using discounting

Smoothing n -gram Models

- Event Space for n -gram Models

- Smoothing Counts

 - Add-one Smoothing

 - Additive Smoothing

 - Good-Turing Smoothing

- Smoothing by Interpolation

 - Interpolation: Jelinek-Mercer Smoothing

- Backoff Smoothing

 - Katz Backoff

 - Backoff Smoothing with Discounting

Cross-Entropy and Perplexity

How good is a model

- ▶ So far we've seen the probability of a sentence: $P(w_0, \dots, w_n)$

How good is a model

- ▶ So far we've seen the probability of a sentence: $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of a corpus

How good is a model

- ▶ So far we've seen the probability of a sentence: $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of a corpus
- ▶ Let $T = s_0, \dots, s_m$ be a text corpus with sentences s_0 through s_m

How good is a model

- ▶ So far we've seen the probability of a sentence: $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of a corpus
- ▶ Let $T = s_0, \dots, s_m$ be a text corpus with sentences s_0 through s_m
- ▶ What is $P(T)$?
Let us assume that we trained $P(\cdot)$ on some *training data*, and T is the *test data*

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences
- ▶ $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences
- ▶ $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶ $P(s_i) = P(w_0^i, \dots, w_n^i)$

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences
- ▶ $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶ $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let W_T be the length of the text T measured in words

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences
- ▶ $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶ $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let W_T be the length of the text T measured in words
- ▶ Then for the unigram model, $P(T) = \prod_{w \in T} P(w)$

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences
- ▶ $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶ $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let W_T be the length of the text T measured in words
- ▶ Then for the unigram model, $P(T) = \prod_{w \in T} P(w)$
- ▶ A problem: we want to compare two different models P_1 and P_2 on T

How good is a model

- ▶ $T = s_0, \dots, s_m$ is the text corpus with sentences s_0 through s_m
- ▶ $P(T) = P(s_0, s_1, s_2, \dots, s_m)$ – but each sentence is independent from the other sentences
- ▶ $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶ $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let W_T be the length of the text T measured in words
- ▶ Then for the unigram model, $P(T) = \prod_{w \in T} P(w)$
- ▶ A problem: we want to compare two different models P_1 and P_2 on T
- ▶ To do this we use the *per word* perplexity of the model:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}} = \sqrt[W_T]{\frac{1}{P(T)}}$$

How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}}$$

How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{w_T}}$$

- ▶ Recall that $PP_P(T) = 2^{H_P(T)}$ where $H_P(T)$ is the cross-entropy of P for text T .

How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}}$$

- ▶ Recall that $PP_P(T) = 2^{H_P(T)}$ where $H_P(T)$ is the cross-entropy of P for text T .
- ▶ Therefore, $H_P(T) = \log_2 PP_P(T) = -\frac{1}{W_T} \log_2 P(T)$

How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}}$$

- ▶ Recall that $PP_P(T) = 2^{H_P(T)}$ where $H_P(T)$ is the cross-entropy of P for text T .
- ▶ Therefore, $H_P(T) = \log_2 PP_P(T) = -\frac{1}{W_T} \log_2 P(T)$
- ▶ Above we use a unigram model $P(w)$, but the same derivation holds for bigram, trigram, ...

How good is a model

- ▶ Lower cross entropy values and perplexity values are better
Lower values mean that the model is *better*
Correlation with performance of the language model in various applications

How good is a model

- ▶ Lower cross entropy values and perplexity values are better
Lower values mean that the model is *better*
Correlation with performance of the language model in various applications
- ▶ Performance of a language model is its cross-entropy or perplexity on *test data* (unseen data)
corresponds to the number bits required to encode that data

How good is a model

- ▶ Lower cross entropy values and perplexity values are better
Lower values mean that the model is *better*
Correlation with performance of the language model in various applications
- ▶ Performance of a language model is its cross-entropy or perplexity on *test data* (unseen data)
corresponds to the number bits required to encode that data
- ▶ On various real life datasets, typical perplexity values yielded by n -gram models on English text range from about 50 to almost 1000 (corresponding to cross entropies from about 6 to 10 bits/word)