



# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

September 22, 2017

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

Part 1: Probability models of Language

# The Language Modeling problem

## Setup

- ▶ Assume a (finite) vocabulary of words:  
 $\mathcal{V} = \{killer, crazy, clown\}$

# The Language Modeling problem

## Setup

- ▶ Assume a (finite) vocabulary of words:

$$\mathcal{V} = \{killer, crazy, clown\}$$

- ▶ Use  $\mathcal{V}$  to construct an infinite set of *sentences*

$$\mathcal{V}^+ = \left\{ \begin{array}{l} clown, killer clown, crazy clown, \\ crazy killer clown, killer crazy clown, \\ \dots \end{array} \right\}$$

# The Language Modeling problem

## Setup

- ▶ Assume a (finite) vocabulary of words:

$$\mathcal{V} = \{killer, crazy, clown\}$$

- ▶ Use  $\mathcal{V}$  to construct an infinite set of *sentences*

$$\mathcal{V}^+ = \left\{ \begin{array}{l} clown, killer clown, crazy clown, \\ crazy killer clown, killer crazy clown, \\ \dots \end{array} \right\}$$

- ▶ A *sentence* is **defined** as each  $s \in \mathcal{V}^+$

# The Language Modeling problem

## Data

Given a training data set of example sentences  $s \in \mathcal{V}^+$

# The Language Modeling problem

## Data

Given a training data set of example sentences  $s \in \mathcal{V}^+$

## Language Modeling problem

Estimate a probability model:

$$\sum_{s \in \mathcal{V}^+} p(s) = 1.0$$

- ▶  $p(\text{clown}) = 1\text{e-}5$
- ▶  $p(\text{killer}) = 1\text{e-}6$
- ▶  $p(\text{killer clown}) = 1\text{e-}12$
- ▶  $p(\text{crazy killer clown}) = 1\text{e-}21$
- ▶  $p(\text{crazy killer clown killer}) = 1\text{e-}110$
- ▶  $p(\text{crazy clown killer killer}) = 1\text{e-}127$

Why do we want to do this?

# Scoring Hypotheses in Speech Recognition

## From acoustic signal to candidate transcriptions

| Hypothesis                                   | Score  |
|----------------------------------------------|--------|
| the station signs are in deep in english     | -14732 |
| the stations signs are in deep in english    | -14735 |
| the station signs are in deep into english   | -14739 |
| the station 's signs are in deep in english  | -14740 |
| the station signs are in deep in the english | -14741 |
| the station signs are indeed in english      | -14757 |
| the station 's signs are indeed in english   | -14760 |
| the station signs are indians in english     | -14790 |
| the station signs are indian in english      | -14799 |
| the stations signs are indians in english    | -14807 |
| the stations signs are indians and english   | -14815 |



# Scoring Hypotheses in Machine Translation

From source language to target language candidates

| Hypothesis                          | Score  |
|-------------------------------------|--------|
| we must also discuss a vision .     | -29.63 |
| we must also discuss on a vision .  | -31.58 |
| it is also discuss a vision .       | -31.96 |
| we must discuss on greater vision . | -36.09 |
| ⋮                                   | ⋮      |

# Scoring Hypotheses in Decryption

## Character substitutions on ciphertext to plaintext candidates

| Hypothesis                            | Score |
|---------------------------------------|-------|
| Heopaj, zk ukq swjp pk gjks w oaynap? | -93   |
| Urbcnw, mx hxd fjwc cx twxf j bnanc?  | -92   |
| Wtdepy, oz jzf hlye ez vyzh l dpncpe? | -91   |
| Mjtufo, ep zpv xbou up lopx b tfdsfu? | -89   |
| Nkuvgp, fq aqw ycpv vq mpqy c ugetgv? | -87   |
| Gdnozi, yj tjp rvio oj fijr v nzxmzo? | -86   |
| Czjkve, uf pfl nrek kf befn r jvtivk? | -85   |
| Yvfgra, qb lbh jnag gb xabj n frperg? | -84   |
| Zwghsb, rc mci kobh hc ybck o gsqfsh? | -83   |
| Byijud, te oek mqdj je adem q iushuj? | -77   |
| Jgqrcl, bm wms uylr rm ilmu y qcapcr? | -76   |
| Listen, do you want to know a secret? | -25   |

# Scoring Hypotheses in Spelling Correction

Substitute spelling variants to generate hypotheses

| Hypothesis                                                                                         | Score  |
|----------------------------------------------------------------------------------------------------|--------|
| ... stellar and versatile <b>acress</b> whose combination of sass and glamour has defined her ...  | -18920 |
| ... stellar and versatile <b>acres</b> whose combination of sass and glamour has defined her ...   | -10209 |
| ... stellar and versatile <b>actress</b> whose combination of sass and glamour has defined her ... | -9801  |

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.
- ▶ Write down a new model over  $\mathcal{V}^+$  such that  $P(s \mid \ell)$  is in the model

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.
- ▶ Write down a new model over  $\mathcal{V}^+$  such that  $P(s \mid \ell)$  is in the model
- ▶ **And** the model should be equal to  $\sum_{s \in \mathcal{V}^+} P(s)$ .



# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.
- ▶ Write down a new model over  $\mathcal{V}^+$  such that  $P(s \mid \ell)$  is in the model
- ▶ **And** the model should be equal to  $\sum_{s \in \mathcal{V}^+} P(s)$ .
- ▶ Write down the model

$$\sum_{s \in \mathcal{V}^+} P(s) = \dots$$

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

Part 2:  $n$ -grams for Language Modeling

## Language models

### $n$ -grams for Language Modeling

#### Smoothing $n$ -gram Models

##### Smoothing Counts

- Add-one Smoothing

- Additive Smoothing

- Interpolation: Jelinek-Mercer Smoothing


##### Backoff Smoothing with Discounting

- Backoff Smoothing with Discounting

#### Evaluating Language Models

# $n$ -gram Models

Google  $n$ -gram viewer



# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs

# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values

# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values
- ▶ Problem: does not generalize to new sentences unseen in the training data.



# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values
- ▶ Problem: does not generalize to new sentences unseen in the training data.
- ▶ What are the chances you will see a sentence: crazy killer clown crazy killer?

# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values
- ▶ Problem: does not generalize to new sentences unseen in the training data.
- ▶ What are the chances you will see a sentence: crazy killer clown crazy killer?
- ▶ In NLP applications we often need to assign non-zero probability to previously unseen sentences.

# Learning Language Models

Apply the Chain Rule: the unigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2) \dots p(w_n) \\ &= \prod_i p(w_i) \end{aligned}$$

# Learning Language Models

Apply the Chain Rule: the unigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2) \dots p(w_n) \\ &= \prod_i p(w_i) \end{aligned}$$

Big problem with a unigram language model

$p(\text{the the the the the the the}) > p(\text{we must also discuss a vision .})$

# Learning Language Models

Apply the Chain Rule: the bigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2 \mid w_1) \dots p(w_n \mid w_{n-1}) \\ &= p(w_1) \prod_{i=2}^n p(w_i \mid w_{i-1}) \end{aligned}$$

# Learning Language Models

Apply the Chain Rule: the bigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2 \mid w_1) \dots p(w_n \mid w_{n-1}) \\ &= p(w_1) \prod_{i=2}^n p(w_i \mid w_{i-1}) \end{aligned}$$

Better than unigram

$p(\text{the the the the the the the}) < p(\text{we must also discuss a vision .})$

# Learning Language Models

Apply the Chain Rule: the trigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx \\ &p(w_1)p(w_2 \mid w_1)p(w_3 \mid w_1, w_2) \dots p(w_n \mid w_{n-2}, w_{n-1}) \\ &p(w_1)p(w_2 \mid w_1) \prod_{i=3}^n p(w_i \mid w_{i-2}, w_{i-1}) \end{aligned}$$

# Learning Language Models

Apply the Chain Rule: the trigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx \\ &p(w_1)p(w_2 \mid w_1)p(w_3 \mid w_1, w_2) \dots p(w_n \mid w_{n-2}, w_{n-1}) \\ &p(w_1)p(w_2 \mid w_1) \prod_{i=3}^n p(w_i \mid w_{i-2}, w_{i-1}) \end{aligned}$$

Better than bigram, but ...

p(we must also discuss a vision .) might be zero because we have not seen p(discuss | must also)



# Maximum Likelihood Estimate

Using training data to learn a trigram model

- ▶ Let  $c(u, v, w)$  be the count of the trigram  $u, v, w$ , e.g.  $c(\text{crazy}, \text{killer}, \text{clown})$

# Maximum Likelihood Estimate

## Using training data to learn a trigram model

- ▶ Let  $c(u, v, w)$  be the count of the trigram  $u, v, w$ , e.g.  $c(\text{crazy}, \text{killer}, \text{clown})$
- ▶ Let  $c(u, v)$  be the count of the bigram  $u, v$ , e.g.  $c(\text{crazy}, \text{killer})$

# Maximum Likelihood Estimate

## Using training data to learn a trigram model

- ▶ Let  $c(u, v, w)$  be the count of the trigram  $u, v, w$ , e.g.  $c(\text{crazy}, \text{killer}, \text{clown})$
- ▶ Let  $c(u, v)$  be the count of the bigram  $u, v$ , e.g.  $c(\text{crazy}, \text{killer})$
- ▶ For any  $u, v, w$  we can compute the conditional probability of generating  $w$  given  $u, v$ :

$$p(w \mid u, v) = \frac{c(u, v, w)}{c(u, v)}$$

# Maximum Likelihood Estimate

## Using training data to learn a trigram model

- ▶ Let  $c(u, v, w)$  be the count of the trigram  $u, v, w$ , e.g.  $c(\text{crazy}, \text{killer}, \text{clown})$
- ▶ Let  $c(u, v)$  be the count of the bigram  $u, v$ , e.g.  $c(\text{crazy}, \text{killer})$
- ▶ For any  $u, v, w$  we can compute the conditional probability of generating  $w$  given  $u, v$ :

$$p(w \mid u, v) = \frac{c(u, v, w)}{c(u, v)}$$

- ▶ For example:

$$p(\text{clown} \mid \text{crazy}, \text{killer}) = \frac{c(\text{crazy}, \text{killer}, \text{clown})}{c(\text{crazy}, \text{killer})}$$

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

## Question

How many unigram probabilities:  $P(x)$  for  $x \in \mathcal{V}$ ?

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

Question

How many unigram probabilities:  $P(x)$  for  $x \in \mathcal{V}$ ?

4

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$



# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

## Question

How many bigram probabilities:  $P(y|x)$  for  $x, y \in \mathcal{V}$ ?

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

## Question

How many bigram probabilities:  $P(y|x)$  for  $x, y \in \mathcal{V}$ ?

$$4^2 = 16$$

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

## Question

How many trigram probabilities:  $P(z|x, y)$  for  $x, y, z \in \mathcal{V}$ ?

# Number of Parameters

How many probabilities in each  $n$ -gram model

- ▶ Assume  $\mathcal{V} = \{killer, crazy, clown, UNK\}$

## Question

How many trigram probabilities:  $P(z|x, y)$  for  $x, y, z \in \mathcal{V}$ ?

$$4^3 = 64$$

# Number of Parameters

## Question

- ▶ Assume  $|\mathcal{V}| = 50,000$  (a realistic vocabulary size for English)
- ▶ What is the minimum size of training data in tokens?
  - ▶ If you wanted to observe all unigrams at least once.
  - ▶ If you wanted to observe all trigrams at least once.

Some trigrams should be zero since they do not occur in the language,  $P(\textit{the} \mid \textit{the}, \textit{the})$ .

But others are simply unobserved in the training data,  $P(\textit{idea} \mid \textit{colourless}, \textit{green})$ .

# Number of Parameters

## Question

- ▶ Assume  $|\mathcal{V}| = 50,000$  (a realistic vocabulary size for English)
- ▶ What is the minimum size of training data in tokens?
  - ▶ If you wanted to observe all unigrams at least once.
  - ▶ If you wanted to observe all trigrams at least once.

125,000,000,000,000 (125 Ttokens)

Some trigrams should be zero since they do not occur in the language,  $P(\textit{the} \mid \textit{the}, \textit{the})$ .

But others are simply unobserved in the training data,  $P(\textit{idea} \mid \textit{colourless}, \textit{green})$ .

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

Part 3: Smoothing Probability Models



## Language models

### $n$ -grams for Language Modeling

#### Smoothing $n$ -gram Models

##### Smoothing Counts

Add-one Smoothing

Additive Smoothing

Interpolation: Jelinek-Mercer Smoothing

##### Backoff Smoothing with Discounting

Backoff Smoothing with Discounting

### Evaluating Language Models

# Bigram Models

- In practice:

$$\begin{aligned} P(\text{crazy killer clown}) = \\ P(\text{crazy} \mid \langle s \rangle) \times P(\text{killer} \mid \text{crazy}) \times \\ P(\text{clown} \mid \text{killer}) \times P(\langle /s \rangle \mid \text{clown}) \end{aligned}$$

# Bigram Models

- In practice:

$$\begin{aligned} P(\text{crazy killer clown}) = \\ P(\text{crazy} \mid \langle s \rangle) \times P(\text{killer} \mid \text{crazy}) \times \\ P(\text{clown} \mid \text{killer}) \times P(\langle /s \rangle \mid \text{clown}) \end{aligned}$$

- $P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$   
On unseen data,  $c(w_{i-1}, w_i)$  or worse  $c(w_{i-1})$  could be zero

$$\sum_{w_i} \frac{c(w_{i-1}, w_i)}{c(w_{i-1})} = ?$$

# Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times

# Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times
- ▶ Smoothing algorithms also tend to improve the accuracy of the model

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

# Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times
- ▶ Smoothing algorithms also tend to improve the accuracy of the model

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Not just unobserved events: what about events observed once?

## Add-one Smoothing

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Add-one Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{1 + c(w_{i-1}, w_i)}{V + c(w_{i-1})}$$

## Add-one Smoothing

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Add-one Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{1 + c(w_{i-1}, w_i)}{V + c(w_{i-1})}$$

- Let  $V$  be the number of words in our vocabulary  
Assign count of 1 to unseen bigrams



## Add-one Smoothing

$$\begin{aligned} P(\text{insane killer clown}) = \\ P(\text{insane} \mid \langle s \rangle) \times P(\text{killer} \mid \text{insane}) \times \\ P(\text{clown} \mid \text{killer}) \times P(\langle /s \rangle \mid \text{clown}) \end{aligned}$$

- Without smoothing:

$$P(\text{killer} \mid \text{insane}) = \frac{c(\text{insane}, \text{killer})}{c(\text{insane})} = 0$$

## Add-one Smoothing

$$\begin{aligned} P(\text{insane killer clown}) = \\ P(\text{insane} \mid \langle s \rangle) \times P(\text{killer} \mid \text{insane}) \times \\ P(\text{clown} \mid \text{killer}) \times P(\langle /s \rangle \mid \text{clown}) \end{aligned}$$

- ▶ Without smoothing:

$$P(\text{killer} \mid \text{insane}) = \frac{c(\text{insane}, \text{killer})}{c(\text{insane})} = 0$$

- ▶ With add-one smoothing (assuming initially that  $c(\text{insane}) = 1$  and  $c(\text{insane}, \text{killer}) = 0$ ):

$$P(\text{killer} \mid \text{insane}) = \frac{1}{V + 1}$$

## Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i) + 1}{c(w_{i-1}) + V}$$

- Why add 1? 1 is an overestimate for unobserved events.

## Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Why add 1? 1 is an overestimate for unobserved events.
- ▶ Additive Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{\delta + c(w_{i-1}, w_i)}{(\delta \times V) + c(w_{i-1})}$$

## Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Why add 1? 1 is an overestimate for unobserved events.
- ▶ Additive Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{\delta + c(w_{i-1}, w_i)}{(\delta \times V) + c(w_{i-1})}$$

- ▶  $0 < \delta \leq 1$

## Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$

# Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$
- ▶ Jelinek and Mercer (1980) describe an elegant form of this **interpolation**:

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

## Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$
- ▶ Jelinek and Mercer (1980) describe an elegant form of this **interpolation**:

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

- ▶ What about  $P_{JM}(w_i)$ ?  
For missing unigrams:  $P_{JM}(w_i) = \lambda P_{ML}(w_i) + (1 - \lambda)\frac{\delta}{V}$



## Interpolation: Finding $\lambda$

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

- ▶ Deleted Interpolation (Jelinek, Mercer)  
compute  $\lambda$  values to minimize cross-entropy on **held-out** data  
which is **deleted** from the initial set of training data

## Interpolation: Finding $\lambda$

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

- ▶ Deleted Interpolation (Jelinek, Mercer)  
compute  $\lambda$  values to minimize cross-entropy on **held-out** data  
which is **deleted** from the initial set of training data
- ▶ Improved JM smoothing, a separate  $\lambda$  for each  $w_{i-1}$ :

$$P_{JM}(w_i \mid w_{i-1}) = \lambda(w_{i-1})P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda(w_{i-1}))P_{ML}(w_i)$$

# Backoff Smoothing with Discounting

- Discounting (Ney, Essen, Kneser)

$$P_{abs}(y \mid x) = \begin{cases} \frac{c(xy)-D}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x)P_{abs}(y) & \text{otherwise} \end{cases}$$

# Backoff Smoothing with Discounting

- ▶ Discounting (Ney, Essen, Kneser)

$$P_{abs}(y \mid x) = \begin{cases} \frac{c(xy) - D}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x) P_{abs}(y) & \text{otherwise} \end{cases}$$

- ▶ where  $\alpha(x)$  is chosen to make sure that  $P_{katz}(y \mid x)$  is a proper probability

$$\alpha(x) = 1 - \sum_y \frac{c(xy) - D}{c(x)}$$

# Backoff Smoothing with Discounting

| $x$           | $c(x)$ | $c(x) - D$ | $\frac{c(x)-D}{c(the)}$ |
|---------------|--------|------------|-------------------------|
| the           | 48     |            |                         |
| the,dog       | 15     | 14.5       | 14.5/48                 |
| the,woman     | 11     | 10.5       | 10.5/48                 |
| the,man       | 10     | 9.5        | 9.5/48                  |
| the,park      | 5      | 4.5        | 4.5/48                  |
| the,job       | 2      | 1.5        | 4.5/48                  |
| the,telescope | 1      | 0.5        | 0.5/48                  |
| the>manual    | 1      | 0.5        | 0.5/48                  |
| the,afternoon | 1      | 0.5        | 0.5/48                  |
| the,country   | 1      | 0.5        | 0.5/48                  |
| the,street    | 1      | 0.5        | 0.5/48                  |
| TOTAL         |        |            | 0.9479                  |
| the,UNK       | 0      |            | 0.052                   |

## Language models

### $n$ -grams for Language Modeling

### Smoothing $n$ -gram Models

#### Smoothing Counts

- Add-one Smoothing

- Additive Smoothing

- Interpolation: Jelinek-Mercer Smoothing

#### Backoff Smoothing with Discounting

- Backoff Smoothing with Discounting

## Evaluating Language Models

# Evaluating Language Models

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$

# Evaluating Language Models

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of an unseen test corpus  $T$



# Evaluating Language Models

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of an unseen test corpus  $T$
- ▶ Let  $T = s_0, \dots, s_m$  be a test corpus with sentences  $s_i$

# Evaluating Language Models

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of an unseen test corpus  $T$
- ▶ Let  $T = s_0, \dots, s_m$  be a test corpus with sentences  $s_i$
- ▶  $T$  is assumed to be separate from the training data used to train our language model  $P(s)$

# Evaluating Language Models

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of an unseen test corpus  $T$
- ▶ Let  $T = s_0, \dots, s_m$  be a test corpus with sentences  $s_i$
- ▶  $T$  is assumed to be separate from the training data used to train our language model  $P(s)$
- ▶ What is  $P(T)$ ?

## Evaluating Language Models: Independence assumption

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$

# Evaluating Language Models: Independence assumption

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences

## Evaluating Language Models: Independence assumption

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$

# Evaluating Language Models: Independence assumption

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$  – which can be any  $n$ -gram language model

# Evaluating Language Models: Independence assumption

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$  – which can be any  $n$ -gram language model
- ▶ A language model is better if the value of  $P(T)$  is higher for unseen sentences  $T$ , we want to maximize:

$$P(T) = \prod_{i=0}^m P(s_i)$$



# Evaluating Language Models: Computing the Average

- ▶ However,  $T$  can be any arbitrary size

# Evaluating Language Models: Computing the Average

- ▶ However,  $T$  can be any arbitrary size
- ▶  $P(T)$  will be lower if  $T$  is larger.

# Evaluating Language Models: Computing the Average

- ▶ However,  $T$  can be any arbitrary size
- ▶  $P(T)$  will be lower if  $T$  is larger.
- ▶ Instead of the probability for a given  $T$  we can compute the *average* probability.

# Evaluating Language Models: Computing the Average

- ▶ However,  $T$  can be any arbitrary size
- ▶  $P(T)$  will be lower if  $T$  is larger.
- ▶ Instead of the probability for a given  $T$  we can compute the *average* probability.
- ▶  $M$  is the total number of tokens in the test corpus  $T$ :

$$M = \sum_{i=1}^m \text{length}(s_i)$$

# Evaluating Language Models: Computing the Average

- ▶ However,  $T$  can be any arbitrary size
- ▶  $P(T)$  will be lower if  $T$  is larger.
- ▶ Instead of the probability for a given  $T$  we can compute the *average* probability.
- ▶  $M$  is the total number of tokens in the test corpus  $T$ :

$$M = \sum_{i=1}^m \text{length}(s_i)$$

- ▶ The average *log* probability of the test corpus  $T$  is:

$$\frac{1}{M} \log_2 \prod_{i=1}^m P(s_i) = \frac{1}{M} \sum_{i=1}^m \log_2 P(s_i)$$

# Evaluating Language Models: Perplexity

- ▶ The average *log* probability of the test corpus  $T$  is:

$$\ell = \frac{1}{M} \sum_{i=1}^m \log_2 P(s_i)$$

# Evaluating Language Models: Perplexity

- ▶ The average *log* probability of the test corpus  $T$  is:

$$\ell = \frac{1}{M} \sum_{i=1}^m \log_2 P(s_i)$$

- ▶ Note that  $\ell$  is a negative number

# Evaluating Language Models: Perplexity

- ▶ The average *log* probability of the test corpus  $T$  is:

$$\ell = \frac{1}{M} \sum_{i=1}^m \log_2 P(s_i)$$

- ▶ Note that  $\ell$  is a negative number
- ▶ We evaluate a language model using *Perplexity* which is  $2^{-\ell}$



# Evaluating Language Models

## Question

Show that:

$$2^{-\frac{1}{M} \log_2 \prod_{i=1}^m P(s_i)} = \frac{1}{\sqrt[M]{\prod_{i=1}^m P(s_i)}}$$

# Evaluating Language Models

## Question

What happens to  $2^{-\ell}$  if any  $n$ -gram probability for computing  $P(T)$  is zero?

# Evaluating Language Models: Typical Perplexity Values

From 'A Bit of Progress in Language Modeling' by Chen and Goodman

| Model   | Perplexity |
|---------|------------|
| unigram | 955        |
| bigram  | 137        |
| trigram | 74         |

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

Part 4: Event space in Language Models

# Trigram Models

- ▶ The trigram model:

$$P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1})$$

# Trigram Models

- ▶ The trigram model:

$$P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1})$$

- ▶ Notice that the length of the sentence  $n$  is variable

# Trigram Models

- ▶ The trigram model:

$$P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1})$$

- ▶ Notice that the length of the sentence  $n$  is variable
- ▶ What is the event space?

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$



## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$
- ▶ So strings in this language  $L$  are:

|           |         |
|-----------|---------|
| $a$ stop  | $0.5$   |
| $b$ stop  | $0.5$   |
| $aa$ stop | $0.5^2$ |
| $bb$ stop | $0.5^2$ |
| $\vdots$  |         |

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$
- ▶ So strings in this language  $L$  are:

|           |         |
|-----------|---------|
| $a$ stop  | $0.5$   |
| $b$ stop  | $0.5$   |
| $aa$ stop | $0.5^2$ |
| $bb$ stop | $0.5^2$ |
| $\vdots$  |         |

- ▶ The sum over all strings in  $L$  should be equal to 1:

$$\sum_{w \in L} P(w) = 1$$

# The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$
- ▶ So strings in this language  $L$  are:

|           |         |
|-----------|---------|
| $a$ stop  | $0.5$   |
| $b$ stop  | $0.5$   |
| $aa$ stop | $0.5^2$ |
| $bb$ stop | $0.5^2$ |
| $\vdots$  |         |

- ▶ The sum over all strings in  $L$  should be equal to 1:

$$\sum_{w \in L} P(w) = 1$$

- ▶ But  $P(a) + P(b) + P(aa) + P(bb) = 1.5$  !!

# The stop symbol

- ▶ What went wrong?  
We need to model variable length sequences

# The stop symbol

- ▶ What went wrong?  
We need to model variable length sequences
- ▶ Add an explicit probability for the stopsymbol:

$$P(a) = P(b) = 0.25$$

$$P(\text{stop}) = 0.5$$

# The stop symbol

- ▶ What went wrong?  
We need to model variable length sequences
- ▶ Add an explicit probability for the stopsymbol:

$$P(a) = P(b) = 0.25$$

$$P(\text{stop}) = 0.5$$

- ▶  $P(\text{stop}) = 0.5$ ,  $P(a \text{ stop}) = P(b \text{ stop}) = 0.25 \times 0.5 = 0.125$ ,  
 $P(aa \text{ stop}) = 0.25^2 \times 0.5 = 0.03125$  (now the sum is no longer greater than one)

# The stop symbol

- ▶ With this new stop symbol we can show that  $\sum_w P(w) = 1$   
Notice that the probability of any sequence of length  $n$  is  $0.25^n \times 0.5$   
Also there are  $2^n$  sequences of length  $n$

$$\begin{aligned}\sum_w P(w) &= \\&= \sum_{n=0}^{\infty} 2^n \times 0.25^n \times 0.5 \\&= \sum_{n=0}^{\infty} 0.5^n \times 0.5 = \sum_{n=0}^{\infty} 0.5^{n+1} \\&= \sum_{n=1}^{\infty} 0.5^n = 1\end{aligned}$$



## The stop symbol

- ▶ With this new stop symbol we can show that  $\sum_w P(w) = 1$   
Using  $p_s = P(\text{stop})$  the probability of any sequence of length  $n$  is  $p(n) = p(w_1, \dots, w_{n-1}) \times p_s(w_n)$

$$\begin{aligned}\sum_w P(w) &= \sum_{n=0}^{\infty} p(n) \sum_{w_1, \dots, w_n} p(w_1, \dots, w_n) \\ &= \sum_{n=0}^{\infty} p(n) \sum_{w_1, \dots, w_n} \prod_{i=1}^n p(w_i)\end{aligned}$$

$$\begin{aligned}\sum_{w_1, \dots, w_n} \prod_i p(w_i) &= \\ \sum_{w_1} \sum_{w_2} \dots \sum_{w_n} p(w_1)p(w_2) \dots p(w_n) &= 1\end{aligned}$$

## The stop symbol

$$\sum_{w_1} \sum_{w_2} \dots \sum_{w_n} p(w_1)p(w_2) \dots p(w_n) = 1$$

$$\begin{aligned} \sum_{n=0}^{\infty} p(n) &= \sum_{n=0}^{\infty} p_s(1 - p_s)^n \\ &= p_s \sum_{n=0}^{\infty} (1 - p_s)^n \\ &= p_s \frac{1}{1 - (1 - p_s)} = p_s \frac{1}{p_s} = 1 \end{aligned}$$

## Acknowledgements

Many slides borrowed or inspired from lecture notes by Michael Collins, Chris Dyer, Kevin Knight, Philipp Koehn, Adam Lopez, and Luke Zettlemoyer from their NLP course materials.

All mistakes are my own.