



# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

September 18, 2014

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

Part 1: Probability models of Language

# The Language Modeling problem

## Setup

- ▶ Assume a (finite) vocabulary of words:

$$\mathcal{V} = \{killer, crazy, clown\}$$

# The Language Modeling problem

## Setup

- ▶ Assume a (finite) vocabulary of words:

$$\mathcal{V} = \{killer, crazy, clown\}$$

- ▶ Use  $\mathcal{V}$  to construct an infinite set of *sentences*

$$\mathcal{V}^+ = \{ \\ \text{clown, killer clown, crazy clown,} \\ \text{crazy killer clown, killer crazy clown,} \\ \dots \\ \}$$

# The Language Modeling problem

## Setup

- ▶ Assume a (finite) vocabulary of words:

$$\mathcal{V} = \{killer, crazy, clown\}$$

- ▶ Use  $\mathcal{V}$  to construct an infinite set of *sentences*

$$\mathcal{V}^+ = \left\{ \begin{array}{l} clown, killer clown, crazy clown, \\ crazy killer clown, killer crazy clown, \\ \dots \end{array} \right\}$$

- ▶ A *sentence* is **defined** as each  $s \in \mathcal{V}^+$

# The Language Modeling problem

## Data

Given a training data set of example sentences  $s \in \mathcal{V}^+$

# The Language Modeling problem

## Data

Given a training data set of example sentences  $s \in \mathcal{V}^+$

## Language Modeling problem

Estimate a probability model:

$$\sum_{s \in \mathcal{V}^+} p(s) = 1.0$$

- ▶  $p(\text{clown}) = 1\text{e-}5$
- ▶  $p(\text{killer}) = 1\text{e-}6$
- ▶  $p(\text{killer clown}) = 1\text{e-}12$
- ▶  $p(\text{crazy killer clown}) = 1\text{e-}21$
- ▶  $p(\text{crazy killer clown killer}) = 1\text{e-}110$
- ▶  $p(\text{crazy clown killer killer}) = 1\text{e-}127$

Why do we want to do this?

# Scoring Hypotheses in Speech Recognition

From acoustic signal to candidate transcriptions

Hypothesis	Score
the station signs are in deep in english	-14732
the stations signs are in deep in english	-14735
the station signs are in deep into english	-14739
the station 's signs are in deep in english	-14740
the station signs are in deep in the english	-14741
the station signs are indeed in english	-14757
the station 's signs are indeed in english	-14760
the station signs are indians in english	-14790
the station signs are indian in english	-14799
the stations signs are indians in english	-14807
the stations signs are indians and english	-14815



# Scoring Hypotheses in Machine Translation

From source language to target language candidates

Hypothesis	Score
we must also discuss a vision .	-29.63
we must also discuss on a vision .	-31.58
it is also discuss a vision .	-31.96
we must discuss on greater vision .	-36.09
⋮	⋮

# Scoring Hypotheses in Decryption

Character substitutions on ciphertext to plaintext candidates

Hypothesis	Score
Heopaj, zk ukq swjp pk gjks w oaynap?	-93
Urbcnw, mx hxd fjwc cx twxf j bnlan?	-92
Wtdepy, oz jzf hlye ez vyzh l dpncpe?	-91
Mjtufo, ep zpv xbou up lopx b tfdsfu?	-89
Nkuvgp, fq aqw ycpv vq mpqy c ugetgv?	-87
Gdnozi, yj tjp rvio oj fijr v nzxmzo?	-86
Czjkve, uf pfl nrek kf befn r jvtivk?	-85
Yvfgra, qb lbh jnag gb xabj n frperg?	-84
Zwghsb, rc mci kobh hc ybck o gsqfsh?	-83
Byijud, te oek mqdj je adem q iushuj?	-77
Jgqrcl, bm wms uylr rm ilmu y qcapcr?	-76
Listen, do you want to know a secret?	-25

# Scoring Hypotheses in Spelling Correction

Substitute spelling variants to generate hypotheses

Hypothesis	Score
... stellar and versatile <b>acress</b> whose combination of sass and glamour has defined her ...	-18920
... stellar and versatile <b>acres</b> whose combination of sass and glamour has defined her ...	-10209
... stellar and versatile <b>actress</b> whose combination of sass and glamour has defined her ...	-9801

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.
- ▶ Write down a new model over  $\mathcal{V}^+$  such that  $P(s \mid \ell)$  is in the model

# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.
- ▶ Write down a new model over  $\mathcal{V}^+$  such that  $P(s \mid \ell)$  is in the model
- ▶ **And** the model should be equal to  $\sum_{s \in \mathcal{V}^+} P(s)$ .



# Probability models of language

## Question

- ▶ Given a finite vocabulary set  $\mathcal{V}$
- ▶ We want to build a probability model  $P(s)$  for all  $s \in \mathcal{V}^+$
- ▶ **But** we want to consider sentences  $s$  of each length  $\ell$  separately.
- ▶ Write down a new model over  $\mathcal{V}^+$  such that  $P(s \mid \ell)$  is in the model
- ▶ **And** the model should be equal to  $\sum_{s \in \mathcal{V}^+} P(s)$ .
- ▶ Write down the model

$$\sum_{s \in \mathcal{V}^+} P(s) = \dots$$

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

Part 2:  $n$ -grams for Language Modeling

## Language models

### $n$ -grams for Language Modeling

#### Smoothing $n$ -gram Models

##### Smoothing Counts

- Add-one Smoothing

- Additive Smoothing

- Good-Turing Smoothing

##### Smoothing by Interpolation

- Interpolation: Jelinek-Mercer Smoothing

##### Backoff Smoothing


- Katz Backoff

- Backoff Smoothing with Discounting

## Cross-Entropy and Perplexity

# $n$ -gram Models

## Google $n$ -gram viewer



# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

# Learning Language Models

- ▶ Directly count using a training data set of sentences:

$w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs

# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values

# Learning Language Models

- ▶ Directly count using a training data set of sentences:  
 $w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values
- ▶ Problem: does not generalize to new sentences unseen in the training data.



# Learning Language Models

- ▶ Directly count using a training data set of sentences:

$w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values
- ▶ Problem: does not generalize to new sentences unseen in the training data.
- ▶ What are the chances you will see a sentence: crazy killer clown crazy killer?

# Learning Language Models

- ▶ Directly count using a training data set of sentences:

$w_1, \dots, w_n$ :

$$p(w_1, \dots, w_n) = \frac{n(w_1, \dots, w_n)}{N}$$

- ▶  $n$  is a function that counts how many times each sentence occurs
- ▶  $N$  is the sum over all possible  $n(\cdot)$  values
- ▶ Problem: does not generalize to new sentences unseen in the training data.
- ▶ What are the chances you will see a sentence: crazy killer clown crazy killer?
- ▶ In NLP applications we often need to assign non-zero probability to previously unseen sentences.

# Learning Language Models

Apply the Chain Rule: the unigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2) \dots p(w_n) \\ &= \prod_i p(w_i) \end{aligned}$$

# Learning Language Models

Apply the Chain Rule: the unigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2) \dots p(w_n) \\ &= \prod_i p(w_i) \end{aligned}$$

Big problem with a unigram language model

$p(\text{the the the the the the the}) > p(\text{we must also discuss a vision .})$

# Learning Language Models

Apply the Chain Rule: the bigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2 \mid w_1) \dots p(w_n \mid w_{n-1}) \\ &= p(w_1) \prod_{i=2}^n p(w_i \mid w_{i-1}) \end{aligned}$$

# Learning Language Models

Apply the Chain Rule: the bigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx p(w_1)p(w_2 \mid w_1) \dots p(w_n \mid w_{n-1}) \\ &= p(w_1) \prod_{i=2}^n p(w_i \mid w_{i-1}) \end{aligned}$$

Better than unigram

$p(\text{the the the the the the the}) < p(\text{we must also discuss a vision .})$

# Learning Language Models

Apply the Chain Rule: the trigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx \\ &p(w_1)p(w_2 \mid w_1)p(w_3 \mid w_1, w_2) \dots p(w_n \mid w_{n-2}, w_{n-1}) \\ &p(w_1)p(w_2 \mid w_1) \prod_{i=3}^n p(w_i \mid w_{i-2}, w_{i-1}) \end{aligned}$$

# Learning Language Models

Apply the Chain Rule: the trigram model

$$\begin{aligned} p(w_1, \dots, w_n) &\approx \\ &p(w_1)p(w_2 \mid w_1)p(w_3 \mid w_1, w_2) \dots p(w_n \mid w_{n-2}, w_{n-1}) \\ &p(w_1)p(w_2 \mid w_1) \prod_{i=3}^n p(w_i \mid w_{i-2}, w_{i-1}) \end{aligned}$$

Better than bigram, but ...

p(we must also discuss a vision .) might be zero because we have not seen p(discuss | must also)



# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

## Part 3: Smoothing Probability Models

## Language models

### $n$ -grams for Language Modeling

### Smoothing $n$ -gram Models

#### Smoothing Counts

- Add-one Smoothing

- Additive Smoothing

- Good-Turing Smoothing

#### Smoothing by Interpolation

- Interpolation: Jelinek-Mercer Smoothing

#### Backoff Smoothing

- Katz Backoff

- Backoff Smoothing with Discounting

### Cross-Entropy and Perplexity

# Bigram Models

- In practice:

$$\begin{aligned} P(\text{Mork read a book}) = & \\ & P(\text{Mork} \mid <\text{start}>) \times P(\text{read} \mid \text{Mork}) \times \\ & P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times \\ & P(<\text{stop}> \mid \text{book}) \end{aligned}$$

# Bigram Models

- In practice:

$$P(\text{Mork read a book}) =$$

$$P(\text{Mork} \mid \langle \text{start} \rangle) \times P(\text{read} \mid \text{Mork}) \times$$

$$P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times$$

$$P(\langle \text{stop} \rangle \mid \text{book})$$

- $P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$

On unseen data,  $c(w_{i-1}, w_i)$  or worse  $c(w_{i-1})$  could be zero

$$\sum_{w_i} \frac{c(w_{i-1}, w_i)}{c(w_{i-1})} = ?$$

# Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times

# Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times
- ▶ Smoothing algorithms also tend to improve the accuracy of the model

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

# Smoothing

- ▶ **Smoothing** deals with events that have been observed zero times
- ▶ Smoothing algorithms also tend to improve the accuracy of the model

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Not just unobserved events: what about events observed once?

# Add-one Smoothing

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Add-one Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{1 + c(w_{i-1}, w_i)}{V + c(w_{i-1})}$$



# Add-one Smoothing

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Add-one Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{1 + c(w_{i-1}, w_i)}{V + c(w_{i-1})}$$

- Let  $V$  be the number of words in our vocabulary  
Assign count of 1 to unseen bigrams

## Add-one Smoothing

$$\begin{aligned} P(\text{Mindy read a book}) = & \\ & P(\text{Mindy} \mid \langle \text{start} \rangle) \times P(\text{read} \mid \text{Mindy}) \times \\ & P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times \\ & P(\langle \text{stop} \rangle \mid \text{book}) \end{aligned}$$

- Without smoothing:

$$P(\text{read} \mid \text{Mindy}) = \frac{c(\text{Mindy, read})}{c(\text{Mindy})} = 0$$

# Add-one Smoothing

$$\begin{aligned} P(\text{Mindy read a book}) = & \\ & P(\text{Mindy} \mid \langle \text{start} \rangle) \times P(\text{read} \mid \text{Mindy}) \times \\ & P(\text{a} \mid \text{read}) \times P(\text{book} \mid \text{a}) \times \\ & P(\langle \text{stop} \rangle \mid \text{book}) \end{aligned}$$

- ▶ Without smoothing:

$$P(\text{read} \mid \text{Mindy}) = \frac{c(\text{Mindy, read})}{c(\text{Mindy})} = 0$$

- ▶ With add-one smoothing (assuming  $c(\text{Mindy}) = 1$  but  $c(\text{Mindy, read}) = 0$ ):

$$P(\text{read} \mid \text{Mindy}) = \frac{1}{V + 1}$$

## Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Add-one smoothing works horribly in practice. Seems like 1 is too large a count for unobserved events.

## Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Add-one smoothing works horribly in practice. Seems like 1 is too large a count for unobserved events.
- ▶ Additive Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{\delta + c(w_{i-1}, w_i)}{(\delta \times V) + c(w_{i-1})}$$

## Additive Smoothing: (Lidstone 1920, Jeffreys 1948)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Add-one smoothing works horribly in practice. Seems like 1 is too large a count for unobserved events.
- ▶ Additive Smoothing:

$$P(w_i \mid w_{i-1}) = \frac{\delta + c(w_{i-1}, w_i)}{(\delta \times V) + c(w_{i-1})}$$

- ▶  $0 < \delta \leq 1$   
Still works horribly in practice, but better than add-one smoothing.

## Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- Imagine you're sitting at a sushi bar with a conveyor belt.

## Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Imagine you're sitting at a sushi bar with a conveyor belt.
- ▶ You see going past you 10 plates of tuna, 3 plates of unagi, 2 plates of salmon, 1 plate of shrimp, 1 plate of octopus, and 1 plate of yellowtail



## Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Imagine you're sitting at a sushi bar with a conveyor belt.
- ▶ You see going past you 10 plates of tuna, 3 plates of unagi, 2 plates of salmon, 1 plate of shrimp, 1 plate of octopus, and 1 plate of yellowtail
- ▶ Chance you will observe a new kind of seafood:  $\frac{3}{18}$

## Good-Turing Smoothing: (Good, 1953)

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ Imagine you're sitting at a sushi bar with a conveyor belt.
- ▶ You see going past you 10 plates of tuna, 3 plates of unagi, 2 plates of salmon, 1 plate of shrimp, 1 plate of octopus, and 1 plate of yellowtail
- ▶ Chance you will observe a new kind of seafood:  $\frac{3}{18}$
- ▶ How likely are you to see another plate of salmon: should be  $< \frac{2}{18}$

# Good-Turing Smoothing

- ▶ How many types of seafood (words) were seen once? Use this to predict probabilities for unseen events

Let  $n_1$  be the number of events that occurred once:  $p_0 = \frac{n_1}{N}$

# Good-Turing Smoothing

- ▶ How many types of seafood (words) were seen once? Use this to predict probabilities for unseen events

Let  $n_1$  be the number of events that occurred once:  $p_0 = \frac{n_1}{N}$

- ▶ The Good-Turing estimate states that for any  $n$ -gram that occurs  $r$  times, we should pretend that it occurs  $r^*$  times

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

# Good-Turing Smoothing

- ▶ How many types of seafood (words) were seen once? Use this to predict probabilities for unseen events

Let  $n_1$  be the number of events that occurred once:  $p_0 = \frac{n_1}{N}$

- ▶ The Good-Turing estimate states that for any  $n$ -gram that occurs  $r$  times, we should pretend that it occurs  $r^*$  times

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

- ▶  $n_r$ : number of different objects seen  $r$  times

# Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail

# Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is new data? Let  $n_1$  be the number of items occurring once, which is 3 in this case.  $N$  is the total, which is 18.

$$p_0 = \frac{n_1}{N} = \frac{3}{18} = 0.166$$

# Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail



# Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is *octopus*? Since  $c(\text{octopus}) = 1$  The GT estimate is  $1^*$ .

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

$$p_{GT} = \frac{r^*}{N}$$

# Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is *octopus*? Since  $c(\text{octopus}) = 1$  The GT estimate is  $1^*$ .

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

$$p_{GT} = \frac{r^*}{N}$$

- ▶ To compute  $1^*$ , we need  $n_1 = 3$  and  $n_2 = 1$

$$1^* = 2 \times \frac{1}{3} = \frac{2}{3}$$

$$p_1 = \frac{1^*}{18} = 0.037$$

# Good-Turing Smoothing

- ▶ 10 tuna, 3 unagi, 2 salmon, 1 shrimp, 1 octopus, 1 yellowtail
- ▶ How likely is *octopus*? Since  $c(\text{octopus}) = 1$  The GT estimate is  $1^*$ .

$$r^* = (r + 1) \frac{n_{r+1}}{n_r}$$

$$p_{GT} = \frac{r^*}{N}$$


- ▶ To compute  $1^*$ , we need  $n_1 = 3$  and  $n_2 = 1$

$$1^* = 2 \times \frac{1}{3} = \frac{2}{3}$$

$$p_1 = \frac{1^*}{18} = 0.037$$

- ▶ What happens when  $n_{r+1} = 0$ ? (smoothing before smoothing)

## Simple Good-Turing: linear interpolation for missing $n_{r+1}$



$$f(r) = a + b * r$$

$$a = 2.3$$

$$b = -0.17$$

$r$	$n_r = f(r)$
1	2.14
2	1.97
3	1.80
4	1.63
5	1.46
6	1.29
7	1.12
8	0.95
9	0.78
10	0.61
11	0.44

## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

►  $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$

## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶  $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$
- ▶  $V = 1 + 3 + 2 + 1 + 1 + 1 = 9$

## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶  $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$
- ▶  $V = 1 + 3 + 2 + 1 + 1 + 1 = 9$
- ▶ Important: we added a new word type for unseen words. Let's call it UNK, the unknown word.

## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶  $N = (1 * 3) + (2 * 2) + 3 + 5 + 10 = 25$
- ▶  $V = 1 + 3 + 2 + 1 + 1 + 1 = 9$
- ▶ Important: we added a new word type for unseen words. Let's call it UNK, the unknown word.
- ▶ Check that:  $1.0 == \sum_r n_r \times p_r$   
 $0.12 + (3 * 0.03079) + (2 * 0.06719) + 0.1045 + 0.1797 + 0.3691 = 1.0$



## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ NS = No smoothing:  $p_r = \frac{r}{N}$

## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ NS = No smoothing:  $p_r = \frac{r}{N}$
- ▶ Add1 = Add-one smoothing:  $p_r = \frac{1+r}{V+N}$

## Comparison between Add-one and Good-Turing

freq	num with freq $r$	NS	Add1	SGT
$r$	$n_r$	$p_r$	$p_r$	$p_r$
0	0	0	0.0294	0.12
1	3	0.04	0.0588	0.03079
2	2	0.08	0.0882	0.06719
3	1	0.12	0.1176	0.1045
5	1	0.2	0.1764	0.1797
10	1	0.4	0.3235	0.3691

- ▶ NS = No smoothing:  $p_r = \frac{r}{N}$
- ▶ Add1 = Add-one smoothing:  $p_r = \frac{1+r}{V+N}$
- ▶ SGT = Simple Good-Turing:  $p_0 = \frac{n_1}{N}$ ,  $p_r = \frac{(r+1) \frac{n_{r+1}}{N}}{n_r}$   
with linear interpolation for missing values where  $n_{r+1} = 0$   
(Gale and Sampson, 1995) <http://www.grsampson.net/AGtf1.html>

## Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- In add-one or Good-Turing:

$$P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$$

## Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ In add-one or Good-Turing:  
 $P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$
- ▶ If  $c(w_{i-1}, w_i) = 0$ , then use  $P(w_i)$  (back off)

## Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ In add-one or Good-Turing:  
 $P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$
- ▶ If  $c(w_{i-1}, w_i) = 0$ , then use  $P(w_i)$  (back off)
- ▶ Works for trigrams too: back off to bigrams and then unigrams

## Using unigrams to smooth bigrams: incorrect version

$$P(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶ In add-one or Good-Turing:  
 $P(\text{the} \mid \text{string}) = P(\text{Fonz} \mid \text{string})$
- ▶ If  $c(w_{i-1}, w_i) = 0$ , then use  $P(w_i)$  (back off)
- ▶ Works for trigrams too: back off to bigrams and then unigrams
- ▶ Problem: probabilities get mixed up (unseen bigrams, for example will get higher probabilities than seen bigrams)

# Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$



# Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$
- ▶ Notice that  $P_{JM}(\text{the} \mid \text{string}) > P_{JM}(\text{Fonz} \mid \text{string})$  as we wanted

# Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda)P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$
- ▶ Notice that  $P_{JM}(\text{the} \mid \text{string}) > P_{JM}(\text{Fonz} \mid \text{string})$  as we wanted
- ▶ Jelinek-Mercer (1980) describe an elegant form of this **interpolation**:

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

# Interpolation: Jelinek-Mercer Smoothing

$$P_{ML}(w_i \mid w_{i-1}) = \frac{c(w_{i-1}, w_i)}{c(w_{i-1})}$$

- ▶  $P_{JM}(w_i \mid w_{i-1}) = \lambda P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda) P_{ML}(w_i)$   
where,  $0 \leq \lambda \leq 1$
- ▶ Notice that  $P_{JM}(\text{the} \mid \text{string}) > P_{JM}(\text{Fonz} \mid \text{string})$  as we wanted
- ▶ Jelinek-Mercer (1980) describe an elegant form of this **interpolation**:

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda) P_{JM}(n - 1\text{gram})$$

- ▶ What about  $P_{JM}(w_i)$ ?  
For missing unigrams:  $P_{JM}(w_i) = \lambda P_{ML}(w_i) + (1 - \lambda) \frac{\delta}{V}$

## Interpolation: Finding $\lambda$

$$P_{JM}(n\text{gram}) = \lambda P_{ML}(n\text{gram}) + (1 - \lambda)P_{JM}(n - 1\text{gram})$$

- ▶ Deleted Interpolation (Jelinek, Mercer)  
compute  $\lambda$  values to minimize cross-entropy on **held-out** data  
which is **deleted** from the initial set of training data

# Interpolation: Finding $\lambda$

$$P_{JM}(ngram) = \lambda P_{ML}(ngram) + (1 - \lambda)P_{JM}(n - 1gram)$$

- ▶ Deleted Interpolation (Jelinek, Mercer)  
compute  $\lambda$  values to minimize cross-entropy on **held-out** data  
which is **deleted** from the initial set of training data
- ▶ Improved JM smoothing, a separate  $\lambda$  for each  $w_{i-1}$ :

$$P_{JM}(w_i \mid w_{i-1}) = \lambda(w_{i-1})P_{ML}(w_i \mid w_{i-1}) + (1 - \lambda(w_{i-1}))P_{ML}(w_i)$$

$$\text{where } \sum_i \lambda(w_i) = 1 \text{ because } \sum_{w_i} P(w_i \mid w_{i-1}) = 1$$

# Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.

# Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.
- ▶ Also called discounting since we remove some probability from observed events.

## Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.
- ▶ Also called discounting since we remove some probability from observed events.
- ▶ Katz Backoff (include Good-Turing with Backoff Smoothing)

$$P_{katz}(y \mid x) = \begin{cases} \frac{c^*(xy)}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x)P_{katz}(y) & \text{otherwise} \end{cases}$$



# Backoff Smoothing: Katz Backoff

- ▶ Use smoothing over counts for backoff smoothing.
- ▶ Also called discounting since we remove some probability from observed events.
- ▶ Katz Backoff (include Good-Turing with Backoff Smoothing)

$$P_{katz}(y \mid x) = \begin{cases} \frac{c^*(xy)}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x)P_{katz}(y) & \text{otherwise} \end{cases}$$

- ▶ where  $\alpha(x)$  is chosen to make sure that  $P_{katz}(y \mid x)$  is a proper probability

$$\alpha(x) = 1 - \sum_y \frac{c^*(xy)}{c(x)}$$

## Backoff Smoothing: Katz Backoff

$x$	$c(x)$	$c^*(x)$	$\frac{c^*(x)}{c(the)}$
the	48		
the,dog	15	14.5	14.5/48
the,woman	11	10.5	10.4/48
the,man	10	9.5	9.5/48
the,park	5	4.5	4.5/48
the,job	2	1.5	4.5/48
the,telescope	1	0.5	0.5/48
the>manual	1	0.5	0.5/48
the,afternoon	1	0.5	0.5/48
the,country	1	0.5	0.5/48
the,street	1	0.5	0.5/48
TOTAL			0.9479
the,UNK	0		0.052

# Backoff Smoothing with Discounting

- ▶ Witten-Bell discounting  
use the  $n - 1$  gram model when the  $n$  gram model has too few unique words in the  $n$  gram context

# Backoff Smoothing with Discounting

- ▶ Witten-Bell discounting  
use the  $n - 1$  gram model when the  $n$  gram model has too few unique words **in the  $n$  gram context**
- ▶ Absolute discounting (Ney, Essen, Kneser)

$$P_{abs}(y \mid x) = \begin{cases} \frac{c(xy) - D}{c(x)} & \text{if } c(xy) > 0 \\ \alpha(x)P_{abs}(y) & \text{otherwise} \end{cases}$$

compute  $\alpha(x)$  as was done in Katz smoothing

# Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing  
 $P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$

# Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing
$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$
  - ▶ *Francisco* is common, so interpolation gives  $P(\text{Francisco} \mid \text{eggplant})$  a high value

# Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing

$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$

- ▶ *Francisco* is common, so interpolation gives  $P(\text{Francisco} \mid \text{eggplant})$  a high value
- ▶ But *Francisco* occurs in few contexts (only after *San*)

# Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing

$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$

- ▶ *Francisco* is common, so interpolation gives  $P(\text{Francisco} \mid \text{eggplant})$  a high value
- ▶ But *Francisco* occurs in few contexts (only after *San*)
- ▶ *stew* is common, **and** occurs in many contexts



# Backoff Smoothing with Discounting

- ▶ Kneser-Ney smoothing

$$P(\text{Francisco} \mid \text{eggplant}) > P(\text{stew} \mid \text{eggplant})$$

- ▶ *Francisco* is common, so interpolation gives  $P(\text{Francisco} \mid \text{eggplant})$  a high value
- ▶ But *Francisco* occurs in few contexts (only after *San*)
- ▶ *stew* is common, **and** occurs in many contexts
- ▶ Hence weight the interpolation based on number of contexts for the word using discounting

## Language models

### $n$ -grams for Language Modeling

#### Smoothing $n$ -gram Models

##### Smoothing Counts

- Add-one Smoothing

- Additive Smoothing

- Good-Turing Smoothing

##### Smoothing by Interpolation

- Interpolation: Jelinek-Mercer Smoothing

##### Backoff Smoothing

- Katz Backoff

- Backoff Smoothing with Discounting

## Cross-Entropy and Perplexity

# How good is a model

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$

# How good is a model

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of a corpus

# How good is a model

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of a corpus
- ▶ Let  $T = s_0, \dots, s_m$  be a text corpus with sentences  $s_0$  through  $s_m$

# How good is a model

- ▶ So far we've seen the probability of a sentence:  $P(w_0, \dots, w_n)$
- ▶ What is the probability of a collection of sentences, that is what is the probability of a corpus
- ▶ Let  $T = s_0, \dots, s_m$  be a text corpus with sentences  $s_0$  through  $s_m$
- ▶ What is  $P(T)$ ?  
Let us assume that we trained  $P(\cdot)$  on some *training data*, and  $T$  is the *test data*

## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$

## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences



## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$

## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$

## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let  $W_T$  be the length of the text  $T$  measured in words

## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let  $W_T$  be the length of the text  $T$  measured in words
- ▶ Then for the unigram model,  $P(T) = \prod_{w \in T} P(w)$

# How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let  $W_T$  be the length of the text  $T$  measured in words
- ▶ Then for the unigram model,  $P(T) = \prod_{w \in T} P(w)$
- ▶ A problem: we want to compare two different models  $P_1$  and  $P_2$  on  $T$

## How good is a model

- ▶  $T = s_0, \dots, s_m$  is the text corpus with sentences  $s_0$  through  $s_m$
- ▶  $P(T) = P(s_0, s_1, s_2, \dots, s_m)$  – but each sentence is independent from the other sentences
- ▶  $P(T) = P(s_0) \cdot P(s_1) \cdot P(s_2) \cdot \dots \cdot P(s_m) = \prod_{i=0}^m P(s_i)$
- ▶  $P(s_i) = P(w_0^i, \dots, w_n^i)$
- ▶ Let  $W_T$  be the length of the text  $T$  measured in words
- ▶ Then for the unigram model,  $P(T) = \prod_{w \in T} P(w)$
- ▶ A problem: we want to compare two different models  $P_1$  and  $P_2$  on  $T$
- ▶ To do this we use the *per word* perplexity of the model:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}} = \sqrt[W_T]{\frac{1}{P(T)}}$$

# How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}}$$

# How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{w_T}}$$

- ▶ Recall that  $PP_P(T) = 2^{H_P(T)}$  where  $H_P(T)$  is the cross-entropy of  $P$  for text  $T$ .



# How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}}$$

- ▶ Recall that  $PP_P(T) = 2^{H_P(T)}$  where  $H_P(T)$  is the cross-entropy of  $P$  for text  $T$ .
- ▶ Therefore,  $H_P(T) = \log_2 PP_P(T) = -\frac{1}{W_T} \log_2 P(T)$

# How good is a model

- ▶ The *per word* perplexity of the model is:

$$PP_P(T) = P(T)^{-\frac{1}{W_T}}$$

- ▶ Recall that  $PP_P(T) = 2^{H_P(T)}$  where  $H_P(T)$  is the cross-entropy of  $P$  for text  $T$ .
- ▶ Therefore,  $H_P(T) = \log_2 PP_P(T) = -\frac{1}{W_T} \log_2 P(T)$
- ▶ Above we use a unigram model  $P(w)$ , but the same derivation holds for bigram, trigram, ...

# How good is a model

- ▶ Lower cross entropy values and perplexity values are better  
Lower values mean that the model is *better*  
Correlation with performance of the language model in various applications

# How good is a model

- ▶ Lower cross entropy values and perplexity values are better  
Lower values mean that the model is *better*  
Correlation with performance of the language model in various applications
- ▶ Performance of a language model is its cross-entropy or perplexity on *test data* (unseen data)  
corresponds to the number bits required to encode that data

# How good is a model

- ▶ Lower cross entropy values and perplexity values are better  
Lower values mean that the model is *better*  
Correlation with performance of the language model in various applications
- ▶ Performance of a language model is its cross-entropy or perplexity on *test data* (unseen data)  
corresponds to the number bits required to encode that data
- ▶ On various real life datasets, typical perplexity values yielded by  $n$ -gram models on English text range from about 50 to almost 1000 (corresponding to cross entropies from about 6 to 10 bits/word)

# Natural Language Processing

Anoop Sarkar

[anoopsarkar.github.io/nlp-class](https://anoopsarkar.github.io/nlp-class)

Simon Fraser University

## Part 4: Event space in Language Models

# Trigram Models

- ▶ The trigram model:

$$\begin{aligned} P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1}) \end{aligned}$$

# Trigram Models

- ▶ The trigram model:

$$P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1})$$

- ▶ Notice that the length of the sentence  $n$  is variable



# Trigram Models

- ▶ The trigram model:

$$P(w_1, w_2, \dots, w_n) = \\ P(w_1) \times P(w_2 \mid w_1) \times P(w_3 \mid w_1, w_2) \times P(w_4 \mid w_2, w_3) \times \\ \dots P(w_i \mid w_{i-2}, w_{i-1}) \dots \times P(w_n \mid w_{n-2}, \dots, w_{n-1})$$

- ▶ Notice that the length of the sentence  $n$  is variable
- ▶ What is the event space?

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$
- ▶ So strings in this language  $L$  are:

$a$  stop  $0.5$

$b$  stop  $0.5$

$aa$  stop  $0.5^2$

$bb$  stop  $0.5^2$

$\vdots$

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$
- ▶ So strings in this language  $L$  are:

$a$ stop	$0.5$
$b$ stop	$0.5$
$aa$ stop	$0.5^2$
$bb$ stop	$0.5^2$
$\vdots$	

- ▶ The sum over all strings in  $L$  should be equal to 1:

$$\sum_{w \in L} P(w) = 1$$

## The stop symbol

- ▶ Let  $\mathcal{V} = \{a, b\}$  and the language  $L$  be  $\mathcal{V}^*$
- ▶ Consider a unigram model:  $P(a) = P(b) = 0.5$
- ▶ So strings in this language  $L$  are:

$a$ stop	$0.5$
$b$ stop	$0.5$
$aa$ stop	$0.5^2$
$bb$ stop	$0.5^2$
$\vdots$	

- ▶ The sum over all strings in  $L$  should be equal to 1:

$$\sum_{w \in L} P(w) = 1$$

- ▶ But  $P(a) + P(b) + P(aa) + P(bb) = 1.5$  !!

# The stop symbol

- ▶ What went wrong?  
We need to model variable length sequences

# The stop symbol

- ▶ What went wrong?  
We need to model variable length sequences
- ▶ Add an explicit probability for the stopsymbol:

$$P(a) = P(b) = 0.25$$

$$P(\text{stop}) = 0.5$$



# The stop symbol

- ▶ What went wrong?  
We need to model variable length sequences
- ▶ Add an explicit probability for the stopsymbol:

$$P(a) = P(b) = 0.25$$

$$P(\text{stop}) = 0.5$$

- ▶  $P(\text{stop}) = 0.5$ ,  $P(a \text{ stop}) = P(b \text{ stop}) = 0.25 \times 0.5 = 0.125$ ,  
 $P(aa \text{ stop}) = 0.25^2 \times 0.5 = 0.03125$  (now the sum is no longer greater than one)

# The stop symbol

- ▶ With this new stop symbol we can show that  $\sum_w P(w) = 1$   
Notice that the probability of any sequence of length  $n$  is  $0.25^n \times 0.5$   
Also there are  $2^n$  sequences of length  $n$

$$\begin{aligned}\sum_w P(w) &= \\&= \sum_{n=0}^{\infty} 2^n \times 0.25^n \times 0.5 \\&= \sum_{n=0}^{\infty} 0.5^n \times 0.5 = \sum_{n=0}^{\infty} 0.5^{n+1} \\&= \sum_{n=1}^{\infty} 0.5^n = 1\end{aligned}$$

# The stop symbol

- ▶ With this new stop symbol we can show that  $\sum_w P(w) = 1$   
Using  $p_s = P(\text{stop})$  the probability of any sequence of length  $n$  is  $p(n) = p(w_1, \dots, w_{n-1}) \times p_s(w_n)$

$$\begin{aligned}\sum_w P(w) &= \sum_{n=0}^{\infty} p(n) \sum_{w_1, \dots, w_n} p(w_1, \dots, w_n) \\ &= \sum_{n=0}^{\infty} p(n) \sum_{w_1, \dots, w_n} \prod_{i=1}^n p(w_i)\end{aligned}$$

$$\begin{aligned}\sum_{w_1, \dots, w_n} \prod_i p(w_i) &= \\ \sum_{w_1} \sum_{w_2} \dots \sum_{w_n} p(w_1)p(w_2) \dots p(w_n) &= 1\end{aligned}$$

## The stop symbol

$$\sum_{w_1} \sum_{w_2} \dots \sum_{w_n} p(w_1)p(w_2) \dots p(w_n) = 1$$

$$\begin{aligned} \sum_{n=0}^{\infty} p(n) &= \sum_{n=0}^{\infty} p_s(1 - p_s)^n \\ &= p_s \sum_{n=0}^{\infty} (1 - p_s)^n \\ &= p_s \frac{1}{1 - (1 - p_s)} = p_s \frac{1}{p_s} = 1 \end{aligned}$$

## Acknowledgements

Many slides borrowed or inspired from lecture notes by Michael Collins, Chris Dyer, Adam Lopez, and Luke Zettlemoyer from their NLP course materials. All mistakes are my own.