## 102 RK05 Emulator microSD Adapter v1 ordering instructions

The following instructions serve as a guide to order RK05 Emulator microSD Adapter printed circuit boards directly from JLCPCB.

JLCPCB ordering options that are different from the default options:

- Click "Add gerber file" and upload the Gerber file:
  "Gerber\_PCB\_RK05 microSD board v1\_2024-01-14.zip"
- PCB Qty: select the desired quantity
- PCB Color: Black
- Surface Finish: LeadFree HASL
- Remove Order Number: Specify a location
- PCB Assembly: flip the switch to "on"
- Click "CONFIRM"
- Click "NEXT"
- Click "Add BOM File" and upload the file: "BOM\_PCB\_RK05 microSD board v1\_2024-01-14.csv"
- Click "Add CPL File" and upload the file:
  "PickAndPlace\_PCB\_RK05 microSD board v1\_2024-01-14a.csv"
- Click "Process BOM & CPL"
- Confirm that all 3 part types are available. Click "NEXT".
  If there is not a sufficient quantity of any of the 5 part types, then either decrease the order quantity or choose a substitute part that is compatible with the part footprint.
- View the parts placement diagram. Click "NEXT".
- View the Quote & Order summary form. Click "SAVE TO CART".
- Click "View Cart"
- Click the checkboxs on the left side to select all items.
- Click "**Secure Checkout**" and enter the requested information. Choose the Shipping Method that best suits your delivery time and cost goals.

Note: A future version of the PCB will support the "Specify a location" option. The present v1 version does not have the text string for "Specify a location".

Regarding the "Remove Order Number" option, if "Specify a location" is chosen, then JLCPCB will place the order number in a location that is already specified in the Gerber file. There is no extra charge for selecting this option.