

Introduction to Computer Science, Winter Semester 2016
Practice Assignment 6

Discussion: 03.12.2016 - 08.12.2016

Exercise 6-1 To be discussed

Given the following three algorithms for finding the larger number among three numbers.

- Algorithm 1:

```
a = eval(input())
b = eval(input())
c = eval(input())

if (a >= b) and (a >= c):
    print(a)
if (b >= a) and (b >= c):
    print(b)
if (c >= b) and (c >= a):
    print(c)
```

- Algorithm 2:

```
a = eval(input())
b = eval(input())
c = eval(input())

if (a >= b):
    if (a >= c):
        print(a)
    else:
        print(c)
else:
    if (b >= c):
        print(b)
    else:
        print(c)
```

- Algorithm 3:

```
a = eval(input())
b = eval(input())
c = eval(input())
max = a

if (b > max):
    max = b
if (c > max):
    max = c
print(max)
```

- a) Compare the efficiency of the three algorithms. Please justify your answer.

Solution:

- Algorithm 1 will need 3 checks. The total number of executed instructions in worst case (**a**, **b** and **c** are equal) is 9
- Algorithm 2 will need 2 checks. The total number of executed instructions is 6.
- Algorithm 3 will need 2 checks. The total number of executed instructions in worst case (**a** is smaller than **b** and **b** is smaller than **c**) is 9.

- b) Determine the order of magnitude of the three algorithms.

Solution:

Order of magnitude of the three algorithms: $O(1)$

Exercise 6-2 To be discussed

Given the following algorithms:

- a) Algorithm 1 computes the sum from 1 to n :

```
n = eval(input())
result = 0
i = 1
while (i <= n):
    result = result+i
    i = i+1
print(result)
```

- b) Algorithm 2 finds the smallest value in a list $A_0, \dots, A_{(n-1)}$.

```
list_A = eval(input())
k = len(list_A)
S = list_A[0]
i = 1
while (i < k):
    if (list_A[i] < S):
        S = list_A[i]
    i = i + 1
print(S)
```

- c) Algorithm 3 prints out 64, 32, 16, 8, 4, 2.

```
i = 64
while (i > 1):
    print(i)
    i = int(i/2)
```

Find the total number of executed instructions of the algorithms and determine their order of magnitude (the big-O).

Solution:

- a) Algorithm 1:

<code>n = eval(input())</code>	1 instruction --> executed once
<code>result = 0</code>	1 instruction --> executed once
<code>i = 0</code>	1 instruction --> executed once
<code>while i < n:</code>	1 instruction --> n+1 repetitions
<code>result = result + i</code>	1 instruction --> n repetitions
<code>i = i+1</code>	1 instruction --> n repetitions
<code>print(result)</code>	1 instruction

Total number of executed instructions: $1 + 1 + 1 + (n + 1) + 2n + 1 = 3n + 5$
Order of magnitude: $O(n)$

b) Algorithm 2:

<code>list_A = eval(input())</code>	1 instruction --> executed once
<code>k = len(list_A)</code>	1 instruction --> executed once
<code>S = list_A[0]</code>	1 instruction --> executed once
<code>i = 1</code>	1 instruction --> executed once
<code>while i < k:</code>	1 instruction --> k repetitions
<code>if list_A[i] < S:</code>	1 instruction --> k-1 repetitions
<code>S = list_A[i]</code>	1 instruction --> k-1 repetitions
<code>i = i+1</code>	1 instruction --> k-1 repetitions
<code>print(S)</code>	1 instruction

Total number of executed instructions: $1 + 1 + 1 + 1 + k + 3(k - 1) + 1 = 4 + 4k - 2 = 4k + 2$
Order of magnitude: $O(k)$

c) Algorithm 3

<code>i = 64</code>	1 instruction --> executed once
<code>while (i > 1):</code>	1 instruction --> 7 repetitions
<code>print(i)</code>	1 instruction --> 6 repetitions
<code>i = int(i/2)</code>	1 instruction --> 6 repetitions

Total number of executed instructions: $1 + 7 + 6 + 6 = 20$
Order of magnitude: $O(1)$

Exercise 6-3

Find the total number of instructions and the order of magnitude of the following algorithms

a) `import math`

```

m, n = eval(input()), eval(input())
a = ((m * m) - (n * n))
b = (2 * m * n)
c = (math.sqrt((a * a) + (b * b)))

print(" The Pythagorean Triple consists of the following sides: ")
print(a, b, c)

```

Solution:

<code>import math</code>	
<code>m, n = eval(input()), eval(input())</code>	---> 2 instructions
<code>a = ((m * m) - (n * n))</code>	---> 1 instruction
<code>b = (2 * m * n)</code>	---> 1 instruction
<code>c = (math.sqrt((a * a) + (b * b)))</code>	---> 1 instruction
<code>print(" The Pythagorean Triple consists of")</code>	---> 1 instruction
<code>print(a, b, c)</code>	---> 1 instruction

Total number of executed instructions : 7

Order of Magnitude = $O(1)$

```
b) x, y, z = eval(input()), eval(input()), eval(input())
    if (x > 0):
        average = (x + y + z)/3
        print(average)
    else
        print("Bad data")
    endif
```

Solution:

```
x, y, z = eval(input()), eval(input()), eval(input())    ---> 3 instructions
if (x > 0):                                                ---> 1 instruction
    average = (x + y + z)/3                               ---> 1 instruction
    print(average)                                         ---> 1 instruction
else:
    print("Bad data")
```

Total number of executed instructions : 6

Order of Magnitude = $O(1)$

```
c) n = eval(input())
F = [1, 1]
i = 2
while i < n:
    F = F + F[i-1] + F[i-2]
    print(F[i])
    i = i + 1
```

Solution:

```
n = eval(input())    ---> 1 instruction ---> executed once
F = [1, 1]           ---> 1 instruction ---> executed once
i = 2                ---> 1 instruction ---> executed once
while i < n:         ---> 1 instruction ---> n-1 repetitions
    F = F + F[i-1] + F[i-2]    ---> 1 instruction ---> n-2 repetitions
    print(F[i])               ---> 1 instruction ---> n-2 repetitions
    i = i + 1                ---> 1 instruction ---> n-2 repetitions
```

Total number of executed instructions : $3 + (n - 1) + 3 * (n - 2) = 4n - 4$

Order of Magnitude = $O(n)$

Exercise 6-4 To be discussed

Consider the following algorithm:

```
n = eval(input())
i = 1
sum = 0
while i <= n:
    sum = sum + (1/i - 1/(i+2))
    i = i + 4
print(sum)
```

a) What is the output of the algorithm for $n = 10$? You do not need to calculate the final result.

Solution:

$$\frac{1}{1} - \frac{1}{3} + \frac{1}{5} - \frac{1}{7} + \frac{1}{9} - \frac{1}{11}$$

- b) Calculate the total number of executed instructions of the algorithm and give its order of magnitude.

Solution:

```

n = eval(input())      ----> 1 instruction --> executed once
i = 1                  ----> 1 instruction --> executed once
sum = 0                 ----> 1 instruction --> executed once
while i <= n:           ----> 1 instruction --> ceiling(n/4) + 1 repetitions
    sum = sum + (1/i - 1/(i+2)) ----> 1 instruction --> ceiling(n/4) repetitions
    i = i + 4           ----> 1 instruction --> ceiling(n/4) repetitions
print(sum)              ----> 1 instruction --> executed once

```

Total number of executed operations = $3 \times \text{ceiling}(n/4) + 5$

The order of magnitude of the algorithm: $O(n)$

Exercise 6-5 To be discussed Mystery

Consider the following algorithm:

```

n = eval(input())
m = eval(input())
y = 0

```

```

while(n>0):
    y += 1
    n -= 1

```

```

while(m>0):
    y += 1
    m -= 1
print(y)

```

- a) What is the output of the algorithm for $n = 5$ and $m = 3$?

Solution:

$$1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 + 1 = 8$$

- b) What is the functionality of the algorithm?

Solution:

The algorithm sums up the value of n and m .

- c) Calculate the total number of executed instructions of the algorithm and give its order of magnitude.

Solution:

```

n = eval(input()) ----> 1 instruction --> executed once
m = eval(input()) ----> 1 instruction --> executed once
y = 0               ----> 1 instruction --> executed once

while(n>0):        ----> 1 instruction --> executed n + 1 times
    y += 1          ----> 1 instruction --> executed n times
    n -= 1          ----> 1 instruction --> executed n times

while(m>0):        ----> 1 instruction --> executed m + 1 times
    y += 1          ----> 1 instruction --> executed m times

```

```

    m -= 1          ----> 1 instruction --> executed m times
    print(y)        ----> 1 instruction --> executed 1 times

```

Total number of executed operations = $3 \times n + 3 \times m + 6$

The order of magnitude of the algorithm: $O(n+m)$

Exercise 6-6 To be discussed

Find the total number of instructions and the order of magnitude of the following algorithm:

```

list_A = eval(input())
n = len(list_A)
i = 0
while (i < int(n/2)):
    tmp = list_A[i]
    list_A[i] = list_A[n-(i+1)]
    list_A[n-(i+1)] = tmp
    i = i + 1

print(list_A)

```

Solution:

```

list_A = eval(input())    ----> 1 instruction --> executed once
n = len(list_A)           ----> 1 instruction --> executed once
i = 0                     ----> 1 instruction --> executed once
while (i < int(n/2)):     ----> 1 instruction --> int(n/2)+1 repetitions
    tmp = list_A[i]       ----> 1 instruction --> int(n/2) repetitions
    list_A[i] = list_A[n-(i+1)] ----> 1 instruction --> int(n/2) repetitions
    list_A[n-(i+1)] = tmp ----> 1 instruction --> int(n/2) repetitions
    i = i + 1             ----> 1 instruction --> int(n/2) repetitions

print(list_A)             ----> 1 instruction --> executed once

```

Total number of executed instructions = $4 + 5 \times \text{int}(n/2)$

The order of magnitude of the algorithm: $O(n)$

Exercise 6-7 To be discussed

Find the total number of instructions and the order of magnitude of the following algorithm and determine the best and worst case scenarios:

```

list_A = eval(input("Enter List"))
n = len(list_A)
x = eval(input("Enter Number"))
i = n - 1
c = 0
while(i>=0):
    if(list_A[i] < x):
        list_A[i] = 0
    else:
        list_A[i] = 1
        c +=1
    i-=1
print(list_A, ", ", c)

```

Solution:

<code>list_A = eval(input("Enter List"))</code>	----> 1 instruction --> executed once
<code>n = len(list_A)</code>	----> 1 instruction --> executed once
<code>x = eval(input("Enter Number"))</code>	----> 1 instruction --> executed once
<code>i = n - 1</code>	----> 1 instruction --> executed once
<code>c = 0</code>	----> 1 instruction --> executed once
<code>while(i>=0):</code>	----> 1 instruction ---> n+1 repetitions
<code>if(list_A[i] < x):</code>	----> 1 instruction ---> n repetitions
<code>list_A[i] = 0</code>	
<code>else:</code>	
<code>list_A[i] = 1</code>	----> 1 instruction ---> n repetitions
<code>c +=1</code>	----> 1 instruction ---> n repetitions
<code>i-=1</code>	----> 1 instruction ---> n repetitions
<code>print(list_A, ", ", c)</code>	----> 1 instruction --> executed once

Best case scenario: all the elements in the list are less than x.

Total number of executed instructions = $7 + 4 \times n$

Order of magnitude: $O(n)$

Worst case scenario: all the elements in the list are greater or equal to x.

Total number of executed instructions = $7 + 5 \times n$

Order of magnitude: $O(n)$

Exercise 6-8

Find the total number of instructions and the order of magnitude of the following algorithm and determine the best and worst case scenarios:

```

a = eval(input())
b = eval(input())
m = len(a)
k = len(b)
c = []
i = 0
if(m <= k):
    n = m
else:
    n = k
while(i < n):
    c = c + a[i] + b[i]
    i += 1
if(i < m):
    while(i < m):
        c = c + a[i]
        i += 1
elif(i < k):
    while(i < k):
        c = c + b[i]
        i += 1
print(c)

```

Solution:

<code>a = eval(input())</code>	----> 1 instruction --> executed once
<code>b = eval(input())</code>	----> 1 instruction --> executed once
<code>m = len(a)</code>	----> 1 instruction --> executed once
<code>k = len(b)</code>	----> 1 instruction --> executed once

```

c = []                ----> 1 instruction --> executed once
i = 0                ----> 1 instruction --> executed once
if(m <= k):          ----> 1 instruction --> executed once
    n = m             ----> 1 instruction --> executed once
else:
    n = k
while(i < n):         ----> 1 instruction --> n+1 repetitions
    c = c + a[i]      ----> 1 instruction --> n repetitions
    c = c + b[i]      ----> 1 instruction --> n repetitions
    i += 1            ----> 1 instruction --> n repetitions
if(i < m):            ----> 1 instruction --> executed once
    while(i < m):
        c = c + a[i]
        i += 1
elif(i < k):          ----> 1 instruction --> executed once
    while(i < k):     ----> 1 instruction --> (k-n)+1 repetitions
        c = c + b[i] ----> 1 instruction --> (k-n) repetitions
        i += 1        ----> 1 instruction --> (k-n) repetitions
print(c)              ----> 1 instruction --> executed once

```

Best case scenario: both lists have the same length.

Total number of executed instructions = $12 + 3 \times n$

Order of magnitude: $O(n)$

Worst case scenario: the second list has a larger length.

Total number of executed instructions = $13 + 3 \times k + 1 \times n$

Order of magnitude: $O(x)$, where $x = m + k$