

[echo.0.pl](#)

Perl implementation of /bin/echo always writes a trailing space

```
foreach $arg (@ARGV) {  
    print $arg, " ";  
}  
print "\n";
```

[echo.1.pl](#)

Perl implementation of /bin/echo

```
print "@ARGV\n";
```

[echo.2.pl](#)

Perl implementation of /bin/echo

```
print join(" ", @ARGV), "\n";
```

[sum_arguments.pl](#)

sum integers supplied as command line arguments no check that arguments are numeric

```
$sum = 0;  
foreach $arg (@ARGV) {  
    $sum += $arg;  
}  
print "Sum of the numbers is $sum\n";
```

[array_growth_demo.pl](#)

```
while (1) {  
    print "Enter array index: ";  
    $n = <STDIN>;  
    if (!$n) {  
        last;  
    }  
    chomp $n;  
    $a[$n] = 42;  
    print "Array element $n now contains $a[$n]\n";  
    printf "Array size is now %d\n", $#a+1;  
}
```

[line_count.0.pl](#)

Count the number of lines on standard input.

```
$line_count = 0;  
while (1) {  
    $line = <STDIN>;  
    last if !$line;  
    $line_count++;  
}  
print "$line_count lines\n";
```

[line_count.1.pl](#)

Count the number of lines on standard input - slightly more concise

```
$line_count = 0;
while (<STDIN>) {
    $line_count++;
}
print "$line_count lines\n";
```

[line_count.2.pl](#)

Count the number of lines on standard input - using backwards while to be really concise

```
$line_count = 0;
$line_count++ while <STDIN>;
print "$line_count lines\n";
```

[line_count.3.pl](#)

Count the number of lines on standard input. read the input into an array and use the array size.

```
@lines = <STDIN>;
print $#lines+1, " lines\n";
```

[line_count.4.pl](#)

Count the number of lines on standard input.

Assignment to () forces a list context and hence reading all lines of input.

The special variable \$. contains the current line number

```
() = <STDIN>;
print "$. lines\n";
```

[reverse_lines.0.pl](#)

Print lines read from stdin in reverse order.

In a C-style

```
while ($line = <STDIN>) {
    $line[$line_number++] = $line;
}

for ($line_number = $#line; $line_number >= 0 ; $line_number--) {
    print $line[$line_number];
}
```

[reverse_lines.1.pl](#)

Print lines read from stdin in reverse order.

Using <> in a list context

```
@line = <STDIN>;
for ($line_number = $#line; $line_number >= 0 ; $line_number--) {
    print $line[$line_number];
}
```

[reverse_lines.2.pl](#)

Print lines read from stdin in reverse order.

Using <> in a list context & reverse

```
@lines = <STDIN>;
print reverse @lines;
```

[reverse_lines.3.pl](#)

Print lines read from stdin in reverse order.

Using <> in a list context & reverse

```
print reverse <STDIN>;
```

[reverse_lines.4.pl](#)

Print lines read from stdin in reverse order.

Using push & pop

```
while ($line = <STDIN>) {
    push @lines, $line;
}
while (@lines) {
    my $line = pop @lines;
    print $line;
}
```

[reverse_lines.5.pl](#)

Print lines read from stdin in reverse order.

More succinctly with pop

```
@lines = <STDIN>;
while (@lines) {
    print pop @lines;
}
```

[reverse_lines.6.pl](#)

Print lines read from stdin in reverse order.

Using unshift

```
while ($line = <STDIN>) {
    unshift @lines, $line;
}
print @lines;
```

[cp.0.pl](#)

Simple cp implementation using line by line I/O

```
die "Usage: $0 <infile> <outfile>\n" if @ARGV != 2;

$infile = shift @ARGV;
$outfile = shift @ARGV;

open my $in, '<', $infile or die "Cannot open $infile: $!";
open my $out, '>', $outfile or die "Cannot open $outfile: $!";

while ($line = <$in>) {
    print $out $line;
}

close $in;
close $out;
exit 0;
```

[cp.1.pl](#)

Simple cp implementation using line by line I/O relying on the default variable \$_

```

die "Usage: $0 <infile> <outfile>\n" if @ARGV != 2;

$infile = shift @ARGV;
$outfile = shift @ARGV;

open my $in, '<', $infile or die "Cannot open $infile: $!";
open my $out, '>', $outfile or die "Cannot open $outfile: $!";

# loop could also be written in one line:
# print OUT while <IN>;

while (<$in>) {
    print $out;
}

close $in;
close $out;
exit 0;

```

[cp.2.pl](#)

Simple cp implementation reading entire file into array note that <> returns an array of lines in a list context (in a scalar context it returns a single line)

```

die "Usage: $0 <infile> <outfile>\n" if @ARGV != 2;

$infile = shift @ARGV;
$outfile = shift @ARGV;

open my $in, '<', $infile or die "Cannot open $infile: $!";
@lines = <$in>;
close $in;

open my $out, '>', $outfile or die "Cannot open $outfile: $!";
print $out @lines;
close $out;

exit 0;

```

[cp.3.pl](#)

Simple cp implementation via system!
Will break if filenames contain single quotes

```

die "Usage: $0 <infile> <outfile>\n" if @ARGV != 2;

$infile = shift @ARGV;
$outfile = shift @ARGV;

exit system "/bin/cp '$infile' '$outfile'";

```

[cp.4.pl](#)

Simple cp implementation reading entire file into array \$/ contains the line separator for Perl if it is undefined we can slurp an entire file into a scalar variable with a single read

```

die "Usage: cp <infile> <outfile>\n" if @ARGV != 2;
$infile = shift @ARGV;
$outfile = shift @ARGV;

undef $/;
open my $in, '<', $infile or die "Cannot open $infile: $!";
$content = <$in>;
close $in;

open my $out, '>', $outfile or die "Cannot open $outfile: $!";
print $out $content;
close $out;

exit 0;

```

[snap_memory.0.pl](#)

Reads lines of input until end-of-input

Print snap! if a line has been seen previously

```

while (1) {
    print "Enter line: ";
    $line = <STDIN>;
    if (!defined $line) {
        last;
    }
    if ($seen{$line}) {
        print "Snap!\n";
    }
    $seen{$line}++;
}

```

[snap_memory.1.pl](#)

More concise version of snap_memory.0.pl

```

while (1) {
    print "Enter line: ";
    $line = <STDIN>;
    last if !defined $line;
    print "Snap!\n" if $seen{$line};
    $seen{$line} = 1;
}

```

[expel_student.pl](#)

run as ./expel_student mark_deductions.txt find the student with the largest mark deductions expell them

```

while ($line = <>) {
    chomp $line;
    $line =~ s/^"//;
    $line =~ s/"$//;
    my ($name,$offence,$date,$penalty);
    ($name,$offence,$date,$penalty) = split /\s*,\s*/, $line;
    $penalty =~ s/^[^0-9]//g;
    $deduction{$name} += $penalty;
}

$worst = 0;
foreach $student (keys %deduction) {
    $penalty = $deduction{$student};
    if ($penalty > $worst) {
        $worst_student = $student;
        $worst = $penalty;
    }
}
print "Expel $worst_student who had $worst marks deducted\n";

```

[nth_word.pl](#)

Print the nth word on every line of input files/stdin output is piped through fmt to make reading easy

```
die "Usage: $0 <n> <files>\n" if !@ARGV;
$nth_word = shift @ARGV;
open my $f, '|-', "fmt -w 40" or die "Can not run fmt: $!\n";
while ($line = <>) {
    chomp $line;
    @words = split(/ /, $line);
    print $f "$words[$nth_word]\n" if $words[$nth_word];
}
close $f;
```

COMP(2041|9044) 19T2: Software Construction is brought to you by
the [School of Computer Science and Engineering](#) at the [University of New South Wales](#), Sydney.

For all enquiries, please email the class account at cs2041@cse.unsw.edu.au

CRICOS Provider 00098G