

WiseAI Migration Guide

SUNAPI

2022-03-23
Version: 1.0

Copyright

© 2022 Hanwha Techwin Co., Ltd. All rights reserved.

Restriction

Do not copy, distribute, or reproduce any part of this document without written approval from Hanwha Techwin Co., Ltd.

Disclaimer

Hanwha Techwin Co., Ltd. has made every effort to ensure the completeness and accuracy of this document, but makes no guarantee as to the information contained herein. All responsibility for proper and safe use of the information in this document lies with users. Hanwha Techwin Co., Ltd. may revise or update this document without prior notice.

Contact Information

Hanwha Techwin Co., Ltd.

Hanwha Techwin R&D Center, 701, Sampyeong-dong, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea, 463-400

www.hanwha-security.com

Hanwha Techwin America

100 Challenger Rd. Suite 700 Ridgefield Park, NJ 07660

www.hanwhasecurity.com

Hanwha Techwin Europe

2nd Floor, No. 5 The Heights, Brooklands, Weybridge, Surrey, KT13 0NY, U.K

www.hanwha-security.eu

Hanwha Techwin Shanghai

32F, Blk B, New Caohejing International Business Center, No. 391 Guiping Rd., Shanghai, China, 200233

www.hanwha-security.cn



Table of Contents

1. Scope	3
2. Background	3
3. Introduction	3
3.1. WiseAI	3
4. Basic Integration	3
4.1. Prerequisites	3
4.2. Metadata	4
4.3. SUNAPI Events	4
4.3.1. Getting the supported events and its notification schema	4
4.3.2. Event Status Response	18
4.3.3. ONVIF	26
5. Intermediate Integration	30
5.1. OpenAPI Specification	30
5.2. API Usage	30
5.2.1. STEPS	31
6. Full Integration	43
6.1. Drawback of existing eventaction setup	43
6.2. DynamicEventRule in SUNAPI	43
6.2.1. Dynamic Rules	43
6.2.1.1. Description	43
6.2.1.2. Syntax	43
6.2.1.3. Parameters	44
6.2.1.4. Examples (for Camera)	52
6.2.1.5. Getting the current dynamic rules	52
6.2.1.6. Adding a dynamic rule	54
6.2.1.7. Updating Dynamic Rule	55
6.2.1.8. Removing Dynamic Rule	55
6.2.2. Dynamic Rules Options	55
6.2.2.1. Description	56
6.2.2.2. Syntax	56
6.2.2.3. Parameters	56
6.2.2.4. Examples	57
6.2.2.5. Getting the current dynamic rules options (this submenu supports only JSON response)	57
References	63

1. Scope

Scope of this document is to explain how client can integrate & configure app based analytics module, receive events and setup actions.

2. Background

With the increase in demand to support different detection rules and analytics algorithm, its becoming increasingly difficult to package different analytics module in the camera firmware and this results in frequent firmware changes and constant client (VMS/NVR) integration / changes. To overcome this drawback, going forward WiseNet Cameras will leverage the OpenPlaform and provide analytics modules as installable apps.

3. Introduction

Integration with the new app based cameras, involves three levels of integration,

1. **Basic:** Covers receiving app generated events and metadata in SUNAPI and ONVIF
2. **Intermediate:** Basic + Covers configuring the event source in app using OpenAPI
3. **Full:** Basic + Intermediate + Covers configuring the event actions using SUNAPI

Considering the ease of integration and configuring the app, OpenAPI based REST API is used in APP. This allows client to generate stub code for their language.

3.1. WiseAI

WiseAI is a new OpenSDK-based application from Hanwha Techwin that provides AI analysis and events.

4. Basic Integration

Ability to receive events/metadata generated by installed APP is considered as the first level of integration.

4.1. Prerequisites

To use the WiseAI App features, the WiseAI App must be installed and running on the device. Otherwise the events of the WiseAI app are **not displayed**. To check WiseAI App is installed and running, you can check with the command below. For more details on the OpenSDK configuration, refer to the SUNAPI opensdk document.

NOTE

The WiseAI app starts after a while after the camera boots up, and the app's events may not be displayed during the time the app is not started.

REQUEST

```
http://<Device IP>/stw-cgi/opensdk.cgi?msubmenu=apps&action=view
```

TEXT RESPONSE

```
InstalledApps=1
WiseAI.Status=Running
WiseAI.InstalledDate=Wed Dec 22 16:52:49 2021
WiseAI.Version=1.0
WiseAI.Permission=None
WiseAI.AutoStart=True
WiseAI.Priority=Low
```

JSON RESPONSE

```
{
  "InstalledApps": 1,
  "Apps": [
    {
      "AppID": "WiseAI",
      "Status": "Running",
      "InstalledDate": "Wed Dec 22 16:52:49 2021",
      "Version": "1.0",
      "Permission": [
        "None"
      ],
      "AutoStart": true,
      "Priority": "Low"
    }
  ]
}
```

4.2. Metadata

Metadata notification from the App is delivered through the same Metadata RTP session used in the camera. Client can receive metadata from the App as before. Additionally it follows the ONVIF metadata schema for delivering the metadata.

4.3. SUNAPI Events

After connecting to the camera, the client can use the cgi call below to check all events are supported by the camera, including installed Apps. In the response, event notification schema is provided either in Text or JSON format based on request.

4.3.1. Getting the supported events and its notification schema

REQUEST

```
http://<Device IP>/stw-cgi/eventstatus.cgi?msubmenu=eventstatusschema&action=view
```

TEXT RESPONSE

```
HTTP/1.0 200 OK
Content-type: text/plain
<Body>
```

```
EventStatus.1.Name=AlarmInput
EventStatus.1.Schema.1.Name=AlarmInput.<int>
EventStatus.1.Schema.1.Value=<boolean>
EventStatus.2.Name=AlarmOutput
EventStatus.2.Schema.1.Name=AlarmOutput.<int>
EventStatus.2.Schema.1.Value=<boolean>
EventStatus.3.Name=MotionDetection
EventStatus.3.Schema.1.Name=Channel.<int>.MotionDetection
EventStatus.3.Schema.1.Value=<boolean>
EventStatus.3.Schema.2.Name=Channel.<int>.MotionDetection.RegionID.<int>
EventStatus.3.Schema.2.Value=<boolean>
EventStatus.3.Schema.3.Name=Channel.<int>.MotionDetection.RegionID.<int>.Level
EventStatus.3.Schema.3.Value=<int>
EventStatus.4.Name=Tampering
EventStatus.4.Schema.1.Name=Channel.<int>.Tampering
EventStatus.4.Schema.1.Value=<boolean>
EventStatus.5.Name=AudioDetection
EventStatus.5.Schema.1.Name=Channel.<int>.AudioDetection
EventStatus.5.Schema.1.Value=<boolean>
EventStatus.6.Name=DefocusDetection
EventStatus.6.Schema.1.Name=Channel.<int>.DefocusDetection
EventStatus.6.Schema.1.Value=<boolean>
EventStatus.7.Name=AudioAnalytics
EventStatus.7.Schema.1.Name=Channel.<int>.AudioAnalytics.Scream
EventStatus.7.Schema.1.Value=<boolean>
EventStatus.7.Schema.2.Name=Channel.<int>.AudioAnalytics.Gunshot
EventStatus.7.Schema.2.Value=<boolean>
EventStatus.7.Schema.3.Name=Channel.<int>.AudioAnalytics.Explosion
EventStatus.7.Schema.3.Value=<boolean>
EventStatus.7.Schema.4.Name=Channel.<int>.AudioAnalytics.GlassBreak
EventStatus.7.Schema.4.Value=<boolean>
EventStatus.8.Name=SystemEvent
EventStatus.8.Schema.1.Name=SystemEvent.TimeChange
EventStatus.8.Schema.1.Value=<boolean>
EventStatus.8.Schema.2.Name=SystemEvent.PowerReboot
EventStatus.8.Schema.2.Value=<boolean>
EventStatus.8.Schema.3.Name=SystemEvent.FWUpdate
EventStatus.8.Schema.3.Value=<boolean>
EventStatus.8.Schema.4.Name=SystemEvent.FactoryReset
```

```

EventStatus.8.Schema.4.Value=<boolean>
EventStatus.8.Schema.5.Name=SystemEvent.ConfigurationBackup
EventStatus.8.Schema.5.Value=<boolean>
EventStatus.8.Schema.6.Name=SystemEvent.ConfigurationRestore
EventStatus.8.Schema.6.Value=<boolean>
EventStatus.8.Schema.7.Name=SystemEvent.ConfigChange
EventStatus.8.Schema.7.Value=<boolean>
EventStatus.8.Schema.8.Name=ChangedConfigURI
EventStatus.8.Schema.8.Value=<string>
EventStatus.8.Schema.9.Name=SystemEvent.SDFormat
EventStatus.8.Schema.9.Value=<boolean>
EventStatus.8.Schema.10.Name=SystemEvent.SDFail
EventStatus.8.Schema.10.Value=<boolean>
EventStatus.8.Schema.11.Name=SystemEvent.SDFull
EventStatus.8.Schema.11.Value=<boolean>
EventStatus.8.Schema.12.Name=SystemEvent.SDInsert
EventStatus.8.Schema.12.Value=<boolean>
EventStatus.8.Schema.13.Name=SystemEvent.SDRemove
EventStatus.8.Schema.13.Value=<boolean>
EventStatus.8.Schema.14.Name=SystemEvent.NASConnect
EventStatus.8.Schema.14.Value=<boolean>
EventStatus.8.Schema.15.Name=SystemEvent.NASDisconnect
EventStatus.8.Schema.15.Value=<boolean>
EventStatus.8.Schema.16.Name=SystemEvent.NASFail
EventStatus.8.Schema.16.Value=<boolean>
EventStatus.8.Schema.17.Name=SystemEvent.NASFull
EventStatus.8.Schema.17.Value=<boolean>
EventStatus.8.Schema.18.Name=SystemEvent.NASFormat
EventStatus.8.Schema.18.Value=<boolean>
EventStatus.9.Name=OpenSDK.WiseAI.LineCrossing ①
EventStatus.9.Schema.1.Name=Channel.<int>.OpenSDK.WiseAI.LineCrossing
EventStatus.9.Schema.1.Value=<boolean>
EventStatus.9.Schema.2.Name=Channel.<int>.OpenSDK.WiseAI.LineCrossing.<int>.VideoSourceToken
EventStatus.9.Schema.2.Value=<string>
EventStatus.9.Schema.3.Name=Channel.<int>.OpenSDK.WiseAI.LineCrossing.<int>.RuleName
EventStatus.9.Schema.3.Value=<string>
EventStatus.9.Schema.4.Name=Channel.<int>.OpenSDK.WiseAI.LineCrossing.<int>.State
EventStatus.9.Schema.4.Value=<boolean>
EventStatus.9.Schema.5.Name=Channel.<int>.OpenSDK.WiseAI.LineCrossing.<int>.ObjectId
EventStatus.9.Schema.5.Value=<string>
EventStatus.9.Schema.6.Name=Channel.<int>.OpenSDK.WiseAI.LineCrossing.<int>.Action
EventStatus.9.Schema.6.Value=<string>
EventStatus.10.Name=OpenSDK.WiseAI.IvaArea ②
EventStatus.10.Schema.1.Name=Channel.<int>.OpenSDK.WiseAI.IvaArea
EventStatus.10.Schema.1.Value=<boolean>
EventStatus.10.Schema.2.Name=Channel.<int>.OpenSDK.WiseAI.IvaArea.<int>.VideoSourceToken
EventStatus.10.Schema.2.Value=<string>
EventStatus.10.Schema.3.Name=Channel.<int>.OpenSDK.WiseAI.IvaArea.<int>.RuleName
EventStatus.10.Schema.3.Value=<string>

```

```

EventStatus.10.Schema.4.Name=Channel.<int>.OpenSDK.WiseAI.IvaArea.<int>.State
EventStatus.10.Schema.4.Value=<boolean>
EventStatus.10.Schema.5.Name=Channel.<int>.OpenSDK.WiseAI.IvaArea.<int>.ObjectId
EventStatus.10.Schema.5.Value=<string>
EventStatus.10.Schema.6.Name=Channel.<int>.OpenSDK.WiseAI.IvaArea.<int>.Action
EventStatus.10.Schema.6.Value=<string>
EventStatus.11.Name=OpenSDK.WiseAI.ObjectDetection ③
EventStatus.11.Schema.1.Name=Channel.<int>.OpenSDK.WiseAI.ObjectDetection
EventStatus.11.Schema.1.Value=<boolean>
EventStatus.11.Schema.2.Name=Channel.<int>.OpenSDK.WiseAI.ObjectDetection.<int>.VideoSourceToken
EventStatus.11.Schema.2.Value=<string>
EventStatus.11.Schema.3.Name=Channel.<int>.OpenSDK.WiseAI.ObjectDetection.<int>.RuleName
EventStatus.11.Schema.3.Value=<string>
EventStatus.11.Schema.4.Name=Channel.<int>.OpenSDK.WiseAI.ObjectDetection.<int>.State
EventStatus.11.Schema.4.Value=<boolean>
EventStatus.11.Schema.5.Name=Channel.<int>.OpenSDK.WiseAI.ObjectDetection.<int>.ClassTypes
EventStatus.11.Schema.5.Value=<string>
EventStatus.12.Name=OpenSDK.WiseAI.StoppedVehicleDetection ④
EventStatus.12.Schema.1.Name=Channel.<int>.OpenSDK.WiseAI.StoppedVehicleDetection
EventStatus.12.Schema.1.Value=<boolean>
EventStatus.12.Schema.2.Name=Channel.<int>.OpenSDK.WiseAI.StoppedVehicleDetection.<int>.VideoSourceToken
EventStatus.12.Schema.2.Value=<string>
EventStatus.12.Schema.3.Name=Channel.<int>.OpenSDK.WiseAI.StoppedVehicleDetection.<int>.RuleName
EventStatus.12.Schema.3.Value=<string>
EventStatus.12.Schema.4.Name=Channel.<int>.OpenSDK.WiseAI.StoppedVehicleDetection.<int>.State
EventStatus.12.Schema.4.Value=<boolean>
EventStatus.12.Schema.5.Name=Channel.<int>.OpenSDK.WiseAI.StoppedVehicleDetection.<int>.VehicleTypes
EventStatus.12.Schema.5.Value=<string>
EventStatus.12.Schema.6.Name=Channel.<int>.OpenSDK.WiseAI.StoppedVehicleDetection.<int>.ObjectIDs
EventStatus.12.Schema.6.Value=<string>
EventStatus.13.Name=OpenSDK.WiseAI.TrafficJamDetection ⑤
EventStatus.13.Schema.1.Name=Channel.<int>.OpenSDK.WiseAI.TrafficJamDetection
EventStatus.13.Schema.1.Value=<boolean>
EventStatus.13.Schema.2.Name=Channel.<int>.OpenSDK.WiseAI.TrafficJamDetection.<int>.VideoSourceToken
EventStatus.13.Schema.2.Value=<string>
EventStatus.13.Schema.3.Name=Channel.<int>.OpenSDK.WiseAI.TrafficJamDetection.<int>.RuleName
EventStatus.13.Schema.3.Value=<string>
EventStatus.13.Schema.4.Name=Channel.<int>.OpenSDK.WiseAI.TrafficJamDetection.<int>.State
EventStatus.13.Schema.4.Value=<boolean>

```

- ① : LineCrossing Event Schema in Text Response
- ② : IvaArea Event Schema in Text Response
- ③ : ObjectDetection schema in Text Response
- ④ : StoppedVehicleDetection schema in Text Response
- ⑤ : TrafficJamDetection schema in Text Response

JSON RESPONSE

```
HTTP/1.0 200 OK
Content-type: application/json
<Body>
```

```
{
  "type": "array",
  "items": [
    {
      "type": "object",
      "properties": {
        "Time": {
          "type": "string"
        },
        "EventName": {
          "enum": [
            "AlarmInput",
            "AlarmOutput"
          ]
        },
        "Source": {
          "type": "object",
          "properties": {
            "Channel": {
              "type": "number"
            },
            "SourceID": {
              "type": "number"
            }
          }
        },
        "Data": {
          "type": "object",
          "properties": {
            "State": {
              "type": "boolean"
            }
          }
        }
      }
    }
  ],
}
```



```

{
  "type": "object",
  "properties": {
    "Time": {
      "type": "string"
    },
    "EventName": {
      "enum": [
        "Tampering",
        "AudioDetection",
        "DefocusDetection"
      ]
    },
    "Source": {
      "type": "object",
      "properties": {
        "Channel": {
          "type": "number"
        }
      }
    },
    "Data": {
      "type": "object",
      "properties": {
        "State": {
          "type": "boolean"
        }
      }
    }
  }
},
{
  "type": "object",
  "properties": {
    "Time": {
      "type": "string"
    },
    "EventName": {
      "enum": [
        "AudioAnalytics.Scream",
        "AudioAnalytics.Gunshot",
        "AudioAnalytics.Explosion",
        "AudioAnalytics.GlassBreak"
      ]
    },
    "Source": {
      "type": "object",
      "properties": {
        "Channel": {
          "type": "number"
        }
      }
    }
  }
}

```

```

    }
  },
  "Data": {
    "type": "object",
    "properties": {
      "State": {
        "type": "boolean"
      }
    }
  }
},
{
  "type": "object",
  "properties": {
    "Time": {
      "type": "string"
    },
    "EventName": {
      "enum": [
        "MotionDetection"
      ]
    },
    "Source": {
      "type": "object",
      "properties": {
        "Channel": {
          "type": "number"
        },
        "ROIID": {
          "type": "number"
        }
      }
    },
    "Data": {
      "type": "object",
      "properties": {
        "State": {
          "type": "boolean"
        },
        "Level": {
          "type": "number"
        }
      }
    }
  }
},
{
  "type": "object",
  "properties": {
    "Time": {

```

```

        "type": "string"
    },
    "EventName": {
        "enum": [
            "SystemEvent.TimeChange",
            "SystemEvent.PowerReboot",
            "SystemEvent.FWUpdate",
            "SystemEvent.FactoryReset",
            "SystemEvent.ConfigurationBackup",
            "SystemEvent.ConfigurationRestore",
            "SystemEvent.ConfigChange",
            "SystemEvent.SDFormat",
            "SystemEvent.SDFail",
            "SystemEvent.SDFull",
            "SystemEvent.SDInsert",
            "SystemEvent.SDRemove",
            "SystemEvent.NASConnect",
            "SystemEvent.NASDisconnect",
            "SystemEvent.NASFail",
            "SystemEvent.NASFull",
            "SystemEvent.NASFormat"
        ]
    },
    "Source": {
        "type": "object",
        "properties": {}
    },
    "Data": {
        "type": "object",
        "properties": {
            "State": {
                "type": "boolean"
            }
        }
    }
},
{
    "type": "object",
    "properties": {
        "Time": {
            "type": "string"
        },
        "EventName": {
            "enum": [
                "ConfigChange"
            ]
        },
        "Source": {
            "type": "object",
            "properties": {

```

```

        "Channel": {
            "type": "number"
        },
        "ChangedConfigURI": {
            "type": "string"
        }
    },
    "Data": {
        "type": "object",
        "properties": {
            "State": {
                "type": "boolean"
            }
        }
    }
},
{
    "type": "object",
    "properties": {
        "Time": {
            "type": "string"
        },
        "EventName": {
            "enum": [
                "OpenSDK.WiseAI.LineCrossing" ①
            ]
        },
        "Source": {
            "type": "object",
            "properties": {
                "Channel": {
                    "type": "number"
                },
                "AppName": {
                    "type": "string"
                },
                "AppEvent": {
                    "type": "string"
                },
                "AppID": {
                    "type": "string"
                },
                "Type": {
                    "enum": [
                        "Event"
                    ]
                },
                "VideoSourceToken": {
                    "type": "string"
                }
            }
        }
    }
}

```

```

        },
        "RuleName": {
            "type": "string"
        }
    },
    "Data": {
        "type": "object",
        "properties": {
            "State": {
                "type": "boolean"
            },
            "ObjectId": {
                "type": "string"
            },
            "Action": {
                "type": "string"
            }
        }
    }
},
{
    "type": "object",
    "properties": {
        "Time": {
            "type": "string"
        },
        "EventName": {
            "enum": [
                "OpenSDK.WiseAI.IvaArea" ②
            ]
        },
        "Source": {
            "type": "object",
            "properties": {
                "Channel": {
                    "type": "number"
                },
                "AppName": {
                    "type": "string"
                },
                "AppEvent": {
                    "type": "string"
                },
                "AppID": {
                    "type": "string"
                },
                "Type": {
                    "enum": [
                        "Event"
                    ]
                }
            }
        }
    }
}

```

```

    ],
    "VideoSourceToken": {
      "type": "string"
    },
    "RuleName": {
      "type": "string"
    }
  },
  "Data": {
    "type": "object",
    "properties": {
      "State": {
        "type": "boolean"
      },
      "ObjectId": {
        "type": "string"
      },
      "Action": {
        "type": "string"
      }
    }
  }
},
{
  "type": "object",
  "properties": {
    "Time": {
      "type": "string"
    },
    "EventName": {
      "enum": [
        "OpenSDK.WiseAI.ObjectDetection" ③
      ]
    },
    "Source": {
      "type": "object",
      "properties": {
        "Channel": {
          "type": "number"
        },
        "AppName": {
          "type": "string"
        },
        "AppEvent": {
          "type": "string"
        },
        "AppID": {
          "type": "string"
        }
      }
    }
  }
}

```

```

    },
    "Type": {
      "enum": [
        "Event"
      ]
    },
    "VideoSourceToken": {
      "type": "string"
    },
    "RuleName": {
      "type": "string"
    }
  }
},
"Data": {
  "type": "object",
  "properties": {
    "State": {
      "type": "boolean"
    },
    "ClassTypes": {
      "type": "string"
    }
  }
}
},
{
  "type": "object",
  "properties": {
    "Time": {
      "type": "string"
    },
    "EventName": {
      "enum": [
        "OpenSDK.WiseAI.ObjectCounting" ④
      ]
    },
    "Source": {
      "type": "object",
      "properties": {
        "Channel": {
          "type": "number"
        },
        "AppName": {
          "type": "string"
        },
        "AppEvent": {
          "type": "string"
        },
        "AppID": {

```

```

        "type": "string"
      },
      "Type": {
        "enum": [
          "Event"
        ]
      },
      "VideoSourceToken": {
        "type": "string"
      },
      "RuleName": {
        "type": "string"
      }
    }
  },
  "Data": {
    "type": "object",
    "properties": {
      "ReportType": {
        "type": "string"
      },
      "ObjectType": {
        "type": "string"
      },
      "Direction": {
        "type": "string"
      },
      "Count": {
        "type": "number"
      }
    }
  }
},
{
  "type": "object",
  "properties": {
    "Time": {
      "type": "string"
    },
    "EventName": {
      "enum": [
        "OpenSDK.WiseAI.StoppedVehicleDetection" ⑤
      ]
    },
    "Source": {
      "type": "object",
      "properties": {
        "Channel": {
          "type": "number"
        }
      },

```



```

        "AppName": {
            "type": "string"
        },
        "AppEvent": {
            "type": "string"
        },
        "AppID": {
            "type": "string"
        },
        "Type": {
            "enum": [
                "Event"
            ]
        },
        "VideoSourceToken": {
            "type": "string"
        },
        "RuleName": {
            "type": "string"
        }
    },
    "Data": {
        "type": "object",
        "properties": {
            "State": {
                "type": "boolean"
            },
            "VehicleTypes": {
                "type": "string"
            },
            "ObjectIDs": {
                "type": "string"
            }
        }
    }
},
{
    "type": "object",
    "properties": {
        "Time": {
            "type": "string"
        },
        "EventName": {
            "enum": [
                "OpenSDK.WiseAI.TrafficJamDetection" ⑥
            ]
        },
        "Source": {
            "type": "object",

```

```

    "properties": {
      "Channel": {
        "type": "number"
      },
      "AppName": {
        "type": "string"
      },
      "AppEvent": {
        "type": "string"
      },
      "AppID": {
        "type": "string"
      },
      "Type": {
        "enum": [
          "Event"
        ]
      },
      "VideoSourceToken": {
        "type": "string"
      },
      "RuleName": {
        "type": "string"
      }
    },
    "Data": {
      "type": "object",
      "properties": {
        "State": {
          "type": "boolean"
        }
      }
    }
  }
}

```

- ① : LineCrossing Event Schema in JSON Response
- ② : IvaArea Event Schema in JSON Response
- ③ : ObjectDetection schema in JSON Response
- ④ : ObjectCounting schema in JSON Response
- ⑤ : StoppedVehicleDetection schema in JSON Response
- ⑥ : TrafficJamDetection schema in JSON Response

4.3.2. Event Status Response

Eventstatus response format for the app generated event is shown below depending on whether

SchemaBased request is made or not. When SchemaBased eventstatus request is made, more information regarding the event can be received in addition to the basic event notification (Example like which area or line triggered the event). Therefore, It is recommended to use SchemaBased requests that can receive all information rather than normal data, which is abbreviated information. For more details on getting event status, refer to **5.1. Event Status** of the SUNAPI event document.

Table 1. TEXT RESPONSE FORMAT (NORMAL)

Event Name	EventStatus Response
ObjectDetection	Channel.0.OpenSDK.WiseAI.ObjectDetection=False
IvaArea	Channel.0.OpenSDK.WiseAI.IvaArea=True
LineCrossing	Channel.0.OpenSDK.WiseAI.LineCrossing=True
StoppedVehicleDetection	Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection=True
TrafficJamDetection	Channel.0.OpenSDK.WiseAI.TrafficJamDetection=True

Table 2. JSON RESPONSE FORMAT (NORMAL)

Event Name	EventStatus Response
ObjectDetection	<pre>{ "ChannelEvent": [{ "Channel": 0, "OpenSDK": { "WiseAI": { "ObjectDetection" : true } } }] }</pre>

Event Name	EventStatus Response
IvaArea	<pre> { "ChannelEvent": [{ "Channel": 0, "OpenSDK":{ "WiseAI":{ "IvaArea" : false } } }] } </pre>
LineCrossing	<pre> { "ChannelEvent": [{ "Channel": 0, "OpenSDK":{ "WiseAI":{ "LineCrossing" : true } } }] } </pre>
StoppedVehicleDetection	<pre> { "ChannelEvent": [{ "Channel": 0, "OpenSDK":{ "WiseAI":{ "StoppedVehicleDetection" : false } } }] } </pre>

Event Name	EventStatus Response
TrafficJamDetection	<pre> { "ChannelEvent": [{ "Channel": 0, "OpenSDK":{ "WiseAI":{ "TrafficJamDetection" : false } } }] } </pre>

Table 3. TEXT RESPONSE FORMAT (SCHEMA BASED)

Event Name	EventStatus Response
ObjectDetection	<pre> Channel.0.OpenSDK.WiseAI.ObjectDetection=True Channel.0.OpenSDK.WiseAI.ObjectDetection.1.VideoSourceToken =Token1 Channel.0.OpenSDK.WiseAI.ObjectDetection.1.RuleName=RuleNam e1 Channel.0.OpenSDK.WiseAI.ObjectDetection.1.State=True Channel.0.OpenSDK.WiseAI.ObjectDetection.1.ClassType=Person Vehicle </pre>
IvaArea	<pre> Channel.0.OpenSDK.WiseAI.IvaArea=True Channel.0.OpenSDK.WiseAI.IvaArea.1.VideoSourceToken=VideoSo urceToken-0 Channel.0.OpenSDK.WiseAI.IvaArea.1.RuleName=Rule1 Channel.0.OpenSDK.WiseAI.IvaArea.1.State=True Channel.0.OpenSDK.WiseAI.IvaArea.1.ObjectId=10 Channel.0.OpenSDK.WiseAI.IvaArea.1.Action=Intrusion Channel.0.OpenSDK.WiseAI.IvaArea.2.VideoSourceToken=VideoSo urceToken-0 Channel.0.OpenSDK.WiseAI.IvaArea.2.RuleName=Rule2 Channel.0.OpenSDK.WiseAI.IvaArea.2.State=True Channel.0.OpenSDK.WiseAI.IvaArea.2.ObjectId=12 Channel.0.OpenSDK.WiseAI.IvaArea.2.Action=Enter </pre>

Event Name	EventStatus Response
LineCrossing	<pre> Channel.0.OpenSDK.WiseAI.LineCrossing=True Channel.0.OpenSDK.WiseAI.LineCrossing.1.VideoSourceToken=VideoSourceToken-0 Channel.0.OpenSDK.WiseAI.LineCrossing.1.RuleName=RuleName1 Channel.0.OpenSDK.WiseAI.LineCrossing.1.State=True Channel.0.OpenSDK.WiseAI.LineCrossing.1.ObjectId=13 Channel.0.OpenSDK.WiseAI.LineCrossing.1.Action=Right </pre>
StoppedVehicleDetection	<pre> Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection=True Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection.1.VideoSourceToken=VideoSourceToken-0 Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection.1.RuleName=rulename Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection.1.State=true Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection.1.VehicleTypes=Car Bus Truck Motorcycle Bicycle Channel.0.OpenSDK.WiseAI.StoppedVehicleDetection.1.ObjectIDs=258 260 261 278 280 </pre>
TrafficJamDetection	<pre> Channel.0.OpenSDK.WiseAI.TrafficJamDetection=True Channel.0.OpenSDK.WiseAI.TrafficJamDetection.1.VideoSourceToken=VideoSourceToken-0 Channel.0.OpenSDK.WiseAI.TrafficJamDetection.1.RuleName=rulename Channel.0.OpenSDK.WiseAI.TrafficJamDetection.1.State=True </pre>

Table 4. JSON RESPONSE FORMAT (SCHEMA BASED)

Event Name	EventStatus Response
ObjectDetection	<pre> { "EventName": "OpenSDK.WiseAI.ObjectDetection", "Time": "2021-10-27T07:36:14.509+00:00", "Source": { "Channel": 0, "AppName": "WiseAI", "AppEvent": "ObjectDetection", "AppID": "WiseAI", "Type": "Event", "VideoSourceToken": "VideoSourceToken-0", "RuleName": "Rule1", }, "Data": { "ClassTypes": "Person Vehicle", "State": true, } } </pre>
IvaArea	<pre> { "EventName": "OpenSDK.WiseAI.IvaArea", "Time": "2021-10-27T07:36:14.509+00:00", "Source": { "Channel": 0, "AppName": "WiseAI", "AppEvent": "IvaArea", "AppID": "WiseAI", "Type": "Event", "VideoSourceToken": "VideoSourceToken-0", "RuleName": "Rule1", }, "Data": { "State": true, "ObjectId": "10", "Action": "Enter" } } </pre>

Event Name	EventStatus Response
LineCrossing	<pre> { "EventName": "OpenSDK.WiseAI.LineCrossing", "Time": "2021-10-27T07:36:14.509+00:00", "Source": { "Channel": 0, "AppName": "WiseAI", "AppID": "WiseAI", "AppEvent": "LineCrossing", "Type": "Event", "VideoSourceToken": "VideoSourceToken-0", "RuleName": "RuleName1", }, "Data": { "State": true, "ObjectId": "11", "Action": "Right" } } </pre>
StoppedVehicleDetection	<pre> { "EventName": "OpenSDK.WiseAI.StoppedVehicleDetection", "Time": "2021-10-27T07:36:14.509+00:00", "Source": { "Channel": 0, "AppName": "WiseAI", "AppID": "WiseAI", "AppEvent": "StoppedVehicleDetection", "Type": "Event", "VideoSourceToken": "VideoSourceToken-0", "RuleName": "rulename", }, "Data": { "State": true, "VehicleTypes": "Car Bus Truck Motorcycle Bicycle", "ObjectIDs": "258 260 261 278 280" } } </pre>

Event Name	EventStatus Response
TrafficJamDetection	<pre> { "EventName": "OpenSDK.WiseAI.TrafficJamDetection", "Time": "2021-10-27T07:36:14.509+00:00", "Source": { "Channel": 0, "AppName": "WiseAI", "AppID": "WiseAI", "AppEvent": "TrafficJamDetection", "Type": "Event", "VideoSourceToken": "VideoSourceToken-0", "RuleName": "rulename", }, "Data": { "State": true } } </pre>
ObjectCounting	<div data-bbox="611 1037 697 1068">NOTE</div> <p data-bbox="758 909 1426 1196">The ObjectCounting event is generated only in JSON schema format, this event occurs only when the Count value is changed. "Count" data is counted over 1 second, not cumulative value. Currently only "Punctual" ReportType is supported, but it may be extended to other ReportTypes such as "Summary" in the future.</p> <pre> { "EventName": "OpenSDK.WiseAI.ObjectCounting", "Time": "2021-10-27T07:36:14.509+00:00", "Source": { "Channel": 0, "AppName": "WiseAI", "AppID": "WiseAI", "AppEvent": "ObjectCounting", "Type": "Event", "VideoSourceToken": "VideoSourceToken-0", "RuleName": "rulename" }, "Data": { "ReportType": "Punctual", "ObjectType": "Vehicle", "Direction": "LeftToRightIn", "Count": 1 } } </pre>

4.3.3. ONVIF

When connecting to camera through ONVIF, events supported in Apps are listed as part of ONVIF EventService **GetEventProperties** Command Response. Event topic in ONVIF is structured like below,

App Name
Event Name

{ }
{ }

tns1:OpenApp/WiseAI/ObjectDetection

Table 5. Supported EventTopics and Schema

Event	Topic	Schema
ObjectDetection	tns1:OpenApp/WiseAI/ObjectDetection	<pre> <?xml version="1.0" encoding="UTF-8"?> <ObjectDetection wstop:topic="true" xmlns:tt="http://www.onvif.org/ver10/schema"> <tt:MessageDescription IsProperty="true"> <tt:Source> <tt:SimpleItemDescription Name="VideoSourceToken" Type="tt:ReferenceToken"/> <tt:SimpleItemDescription Name="RuleName" Type="xsd:string"/> </tt:Source> <tt>Data> <tt:SimpleItemDescription Name="ClassTypes" Type="tt:StringList"/> <tt:SimpleItemDescription Name="State" Type="xsd:boolean"/> </tt>Data> </tt:MessageDescription> </ObjectDetection> </pre>

Event	Topic	Schema
IvaArea	tns1:OpenApp/WiseAI/IvaArea	<pre> <?xml version="1.0" encoding="UTF-8"?> <IvaArea wstop:topic="true"> <tt:MessageDescription> <tt:Source> <tt:SimpleItemDescription Name="VideoSourceToken" Type="tt:ReferenceToken"/> <tt:SimpleItemDescription Name="RuleName" Type="xsd:string"/> </tt:Source> <tt>Data> <tt:SimpleItemDescription Name="State" Type="xsd:boolean"/> <tt:SimpleItemDescription Name="ObjectId" Type="tt:StringList"/> <tt:SimpleItemDescription Name="Action" Type="tt:StringList"/> </tt>Data> </tt:MessageDescription> </IvaArea> </pre>

Event	Topic	Schema
LineCrossing	tns1:OpenApp/WiseAI/LineCrossing	<pre> <?xml version="1.0" encoding="UTF-8"?> <LineCrossing wstop:topic="true"> <tt:MessageDescription> <tt:Source> <tt:SimpleItemDescription Name="VideoSourceToken" Type="tt:ReferenceToken"/> <tt:SimpleItemDescription Name="RuleName" Type="xsd:string"/> </tt:Source> <tt>Data> <tt:SimpleItemDescription Name="State" Type="xsd:boolean"/> <tt:SimpleItemDescription Name="ObjectId" Type="tt:StringList"/> <tt:SimpleItemDescription Name="Action" Type="tt:StringList"/> </tt>Data> </tt:MessageDescription> </LineCrossing> </pre>

Event	Topic	Schema
StoppedVehicleDetection	tns1:OpenApp/WiseAI/StoppedVehicleDetection	<pre> <StoppedVehicleDetection wstop:topic="true"> <tt:MessageDescription> <tt:Source> <tt:SimpleItemDescription Name="VideoSourceToken" Type="tt:ReferenceToken"/> <tt:SimpleItemDescription Name="RuleName" Type="xsd:string"/> </tt:Source> <tt:Data> <tt:SimpleItemDescription Name="State" Type="xsd:boolean"/> <tt:SimpleItemDescription Name="VehicleTypes" Type="tt:StringList"/> <tt:SimpleItemDescription Name="ObjectIDs" Type="tt:StringList"/> </tt:Data> </tt:MessageDescription> </StoppedVehicleDetection> </pre>
TrafficJamDetection	tns1:OpenApp/WiseAI/TrafficJamDetection	<pre> <?xml version="1.0" encoding="UTF-8"?> <TrafficJamDetection wstop:topic="true"> <tt:MessageDescription> <tt:Source> <tt:SimpleItemDescription Name="VideoSourceToken" Type="tt:ReferenceToken"/> <tt:SimpleItemDescription Name="RuleName" Type="xsd:string"/> </tt:Source> <tt:Data> <tt:SimpleItemDescription Name="State" Type="xsd:boolean"/> </tt:Data> </tt:MessageDescription> </TrafficJamDetection> </pre>

Event	Topic	Schema
ObjectCounting	tns1:OpenApp/WiseAI/ObjectCounting	<pre> <?xml version="1.0" encoding="UTF-8"?> <ObjectCounting wstop:topic="true"> <tt:MessageDescription> <tt:Source> <tt:SimpleItemDescription Name="VideoSourceToken" Type="tt:ReferenceToken"/> <tt:SimpleItemDescription Name="RuleName" Type="xsd:string"/> </tt:Source> <tt:Data> <tt:SimpleItemDescription Name="ReportType" Type="xsd:string"/> <tt:SimpleItemDescription Name="ObjectType" Type="xsd:string"/> <tt:SimpleItemDescription Name="Direction" Type="xsd:string"/> <tt:SimpleItemDescription Name="Count" Type="xsd:integer"/> </tt:Data> </tt:MessageDescription> </ObjectCounting> </pre>

5. Intermediate Integration

In addition to the [Basic Integration](#), this section covers how the events source can be configured on the WiseAI Application.

5.1. OpenAPI Specification


Unlike SUNAPI, WiseAI App uses OpenAPI Specification to define the service, allowing the client to generate stub code to access the WiseAI app. Please refer to [OpenAPI Documentation](#) for basic understanding of OpenAPI and [OpenAPI Tools](#) for the opensource tools. Could also use swagger hub tools which is free for experimenting and testing [SwaggerHub](#).

5.2. API Usage

For accessing the App's service, below format is followed.

{Scheme}://{Address}/{BasePath}/{APIPath}

Sample getservices api path would look like,


BasePath **API Path**

`http://<IPAddress>/opensdk/WiseAI/configuration/getservices`

Since the capability of the App varies according the camera on which its installed. Its recommended to follow below steps for integration.

For more information on the WiseAI App and its API please refer to [WiseAI API Documentation](#)

NOTE

Please make sure WiseAI App is in **running** state as explained in [Prerequisites Section](#) before accessing the WiseAI API.

5.2.1. STEPS

1. Check the response of "configuration/getservices" api to see what services are supported , how many channels are supported and what methods are supported for which API.

REQUEST

```
http://<Device IP>/opensdk/WiseAI/configuration/getservices?includeDetails=true
```

RESPONSE

```
{
  "appName": "WiseAI",
  "appVersion": "1.0",
  "cgiVersion": "1.0.0",
  "language": "English",
  "manufacturer": "Hanwha Techwin",
  "serviceCapabilities": [
    {
      "channel": 0,
      "serviceDetails": [
        {
          "baseUrl": "/opensdk/WiseAI/configuration",
          "id": "configuration",
          "name": "Configuration Service",
          "urls": [
            {
              "methods": [
                "get"
              ],
              "path": "/getservice"
            }
          ]
        }
      ]
    }
  ]
}
```

```

    },
    {
      "methods": [
        "get"
      ],
      "path": "/capability"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/objectdetection"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/objectdetection/options"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/imagetransfer"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/imagetransfer/options"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/ivaarea"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/ivaarea/options"
    },
    {
      "methods": [
        "delete"
      ],
      "path": "/ivaarea/definedarea"
    }
  ]
}

```



```

    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/linecrossing"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/linecrossing/options"
    },
    {
      "methods": [
        "delete"
      ],
      "path": "/linecrossing/line"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/analyticsexcludesettings"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/analyticsexcludesettings/options"
    },
    {
      "methods": [
        "delete"
      ],
      "path": "/analyticsexcludesettings/excludeareas"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/stoppedvehicledetection"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/stoppedvehicledetection/options"
    }
  ]
}

```

```

    },
    {
      "methods": [
        "delete"
      ],
      "path": "/stoppedvehicledetection/areas"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/trafficjamdetection"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/trafficjamdetection/options"
    },
    {
      "methods": [
        "delete"
      ],
      "path": "/trafficjamdetection/rules"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/objectcounting"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/objectcounting/options"
    },
    {
      "methods": [
        "delete"
      ],
      "path": "/objectcounting/countingrules/excludeareas"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/objectcounting/report"
    }
  ]
}

```

```

    },
    {
      "methods": [
        "get"
      ],
      "path": "/objectcounting/report/options"
    },
    {
      "methods": [
        "delete"
      ],
      "path": "/objectcounting/data"
    },
    {
      "methods": [
        "get",
        "post",
        "delete"
      ],
      "path": "/settings"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/dataserver"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/dataserver/test"
    },
    {
      "methods": [
        "get",
        "put"
      ],
      "path": "/commonanalyticssettings"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/commonanalyticssettings/options"
    },
    {
      "methods": [
        "get"
      ],

```

```

        "path": "/rsa"
    }
]
},
{
    "baseUrl": "/opensdk/WiseAI/search",
    "id": "search",
    "name": "Search Service",
    "urls": [
        {
            "methods": [
                "get"
            ],
            "path": "/capability"
        },
        {
            "methods": [
                "get"
            ],
            "path": "/eventlog"
        },
        {
            "methods": [
                "get"
            ],
            "path": "/systemlog"
        },
        {
            "methods": [
                "get"
            ],
            "path": "/objectcounting"
        },
        {
            "methods": [
                "get"
            ],
            "path": "/objectcounting/{searchToken}"
        },
        {
            "methods": [
                "put"
            ],
            "path": "/objectcounting/{searchToken}/cancel"
        },
        {
            "methods": [
                "get"
            ],
            "path": "/objectcounting/{searchToken}/results"
        },
    ],

```

```

        {
            "methods": [
                "get"
            ],
            "path": "/objectcounting/check"
        }
    ],
    },
    "supportedServices": [
        "configuration",
        "search"
    ]
},
{
    "channel": 1,
    "serviceDetails": [
        {
            "baseUrl": "/opensdk/WiseAI/configuration",
            "id": "configuration",
            "name": "Configuration Service",
            "urls": [
                {
                    "methods": [
                        "get"
                    ],
                    "path": "/getservice"
                },
                {
                    "methods": [
                        "get"
                    ],
                    "path": "/capability"
                },
                {
                    "methods": [
                        "get",
                        "put"
                    ],
                    "path": "/objectdetection"
                },
                {
                    "methods": [
                        "get"
                    ],
                    "path": "/objectdetection/options"
                },
                {
                    "methods": [
                        "get",
                        "put"
                    ],

```

```

    ],
    "path": "/imagetransfer"
  },
  {
    "methods": [
      "get"
    ],
    "path": "/imagetransfer/options"
  },
  {
    "methods": [
      "get",
      "put"
    ],
    "path": "/ivaarea"
  },
  {
    "methods": [
      "get"
    ],
    "path": "/ivaarea/options"
  },
  {
    "methods": [
      "delete"
    ],
    "path": "/ivaarea/definedarea"
  },
  {
    "methods": [
      "get",
      "put"
    ],
    "path": "/linecrossing"
  },
  {
    "methods": [
      "get"
    ],
    "path": "/linecrossing/options"
  },
  {
    "methods": [
      "delete"
    ],
    "path": "/linecrossing/line"
  },
  {
    "methods": [
      "get",
      "put"
    ]
  }

```

```

        ],
        "path": "/analyticsexcludesettings"
    },
    {
        "methods": [
            "get"
        ],
        "path": "/analyticsexcludesettings/options"
    },
    {
        "methods": [
            "delete"
        ],
        "path": "/analyticsexcludesettings/excludeareas"
    },
    {
        "methods": [
            "get",
            "post",
            "delete"
        ],
        "path": "/settings"
    },
    {
        "methods": [
            "get",
            "put"
        ],
        "path": "/commonanalyticssettings"
    },
    {
        "methods": [
            "get"
        ],
        "path": "/commonanalyticssettings/options"
    },
    {
        "methods": [
            "get"
        ],
        "path": "/rsa"
    }
    ]
},
{
    "baseUrl": "/opensdk/WiseAI/search",
    "id": "search",
    "name": "Search Service",
    "urls": [
        {
            "methods": [

```

```

        "get"
      ],
      "path": "/capability"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/eventlog"
    },
    {
      "methods": [
        "get"
      ],
      "path": "/systemlog"
    }
  ]
},
"supportedServices": [
  "configuration",
  "search"
]
}
]
}

```

2. Each service supported has "capability" api to inform feature level capability for each services of channel. (Alternative to Attribute cgi in SUNAPI)

REQUEST

```
http://<Device IP>/opensdk/WiseAI/configuration/capability
```


RESPONSE

```
{
  "capabilities": [
    {
      "channel": 0,
      "frameMetaType": "Classification",
      "imagetransfer": true,
      "imagetransferTypes": [
        "Object"
      ],
      "ivaarea": true,
      "linecrossing": true,
      "maxResolution": {
        "height": 1872,
        "width": 3328
      },
      "objectcounting": true,
      "objectcountingTypes": [
        "Vehicle"
      ],
      "objectdetection": true,
      "rotation": false,
      "stoppedvehicledetection": false,
      "trafficjamdetection": false
    },
    {
      "channel": 1,
      "frameMetaType": "Classification",
      "imagetransfer": true,
      "imagetransferTypes": [
        "Object"
      ],
      "ivaarea": true,
      "linecrossing": true,
      "maxResolution": {
        "height": 1872,
        "width": 3328
      },
      "objectcounting": false,
      "objectdetection": true,
      "rotation": false,
      "stoppedvehicledetection": false,
      "trafficjamdetection": false
    }
  ]
}
```

3. Based on above capability check, a feature can be configured. While configuring a feature the valid range or allowed values, options response can be referred. For example for configuring

"objectdetection" , "objectdetection/options" response can be referred for allowed values.

REQUEST

```
http://<Device IP>/opensdk/WiseAI/configuration/objectdetection/options
```

RESPONSE

```
{
  "objectDetectionOptions": [
    {
      "channel": 0,
      "duration": {
        "max": 5,
        "min": 0
      },
      "objectTypes": [
        "Person",
        "Face",
        "LicensePlate",
        "Vehicle.Bicycle",
        "Vehicle.Car",
        "Vehicle.Motorcycle",
        "Vehicle.Bus",
        "Vehicle.Truck"
      ]
    },
    {
      "channel": 1,
      "duration": {
        "max": 5,
        "min": 0
      },
      "objectTypes": [
        "Person",
        "Face",
        "LicensePlate",
        "Vehicle.Bicycle",
        "Vehicle.Car",
        "Vehicle.Motorcycle",
        "Vehicle.Bus",
        "Vehicle.Truck"
      ]
    }
  ]
}
```

6. Full Integration

In addition to the [Basic Integration](#) and [Intermediate Integration](#), this section covers how the eventactions can be configured in camera using SUNAPI.

6.1. Drawback of existing eventaction setup

In SUNAPI for configuring event actions, two submenus are used depending on the number of channels (Videosources) supported, like eventrules.cgi → rules submenu when only one video source is supported and eventactions.cgi → complexaction submenu when more than one video source is supported. Another drawback of existing "complexaction" and "rules" submenu is, user cannot configure actions based on combination of events. For example, one combination action setup can be, triggering Alarmout only when Motiondetection and AlarmIn is detected.

To overcome above drawback, dynamicrules submenu is newly added in eventrules.cgi.

6.2. DynamicEventRule in SUNAPI

6.2.1. Dynamic Rules

6.2.1.1. Description

The **dynamicrules** submenu is used to configure rules regarding what actions to take on what channels when an event is notified.

NOTE

Attributes to check **dynamicrules** feature support:

"attributes/Eventsource/Support/DynamicRule"

Attribute to check for the maximum number of rules supported:

"attributes/Eventsource/Limit/MaxDynamicRule"

Attribute to check for the maximum number of events supported by the rule:

"attributes/Eventsource/Support/MaxDynamicRule.EventSource" Attribute to check for the maximum number of schedules supported:

"attributes/Eventsource/Limit/MaxScheduleCount"

Access level

Action	Camera	NVR
view	Admin	User
add, update	Admin	User
remove	Admin	User

6.2.1.2. Syntax

```
http://<Device IP>/stw-cgi/eventrules.cgi?msubmenu=dynamicrules&action=<value>[&<parameter>=<value>]
```

6.2.1.3. Parameters

Action	Parameter	Request/ Response	Type/ Value	Description
view	Rule.#.RuleName	RES	<string>	Rule name used for uniquely identifying a rule.
	Rule.#.Duration	RES	<int>	Duration in seconds
	Rule.#.ScheduleName	RES	<string>	Determines which schedule is associated with the rule.
	Rule.#.Enable	RES	<bool> True, False	To enable or disable rule.
	Rule.#.Status	RES	<enum> Unavailable, Available	Indicates the operable state of the rule.
	Rule.#.EventSource. #.Type	RES	<enum> MotionDetection, VideoAnalytics, Tampering, DefocusDetection, FogDetection, AudioDetection, AudioAnalytics, NetworkAlarmInput , PasswordChange, HDDStatus, FANError, PowerOnOff, Recording, AppEvent	In a single rule, there can be several event sources configured.
	Rule.#.EventSource. #.AppName	RES	<string>	<p>The name of installed app</p> <p>Rule.#.EventSource.#.AppName is valid only when Rule.#.EventSource.#.Type is set to AppEvent.</p> <p>CAMERA ONLY</p>

Action	Parameter	Request/ Response	Type/ Value	Description
	Rule.#.EventSource. #.AppEventType	RES	<string>	<p>The event source type of installed app</p> <p>Rule.#.EventSource.#.AppEventType is valid only when Rule.#.EventSource.#.Type is set to AppEvent.</p> <p>CAMERA ONLY</p>
	Rule.#.EventSource. #.RuleIndexType	RES	<enum> Any, Specific	<p>Rule index of the event source type:</p> <ul style="list-style-type: none"> Any – A trigger with one or more of the event’s rule indices Specific - A specific rule index of an event as a trigger <p>Note if RuleIndexType is Specific should specify with Rule.#.EventSource.#.RuleIndex parameter</p> <p>CAMERA ONLY</p>
	Rule.#.EventSource. #.RuleIndex	RES	<int>	<p>A rule index of an event as a trigger.</p> <p>Rule.#.EventSource.#.RuleIndex is valid only when Rule.#.EventSource.#.RuleIndexType is set to Specific.</p> <p>CAMERA ONLY</p>
	Rule.#.EventSource. #.Channel	RES	<int>	<p>Determines from which channel Event source type needs to be handled.</p> <p>CAMERA ONLY</p>

Action	Parameter	Request/ Response	Type/ Value	Description
	Rule.#.EventSource. #.ChannelIDList	RES	<csv>	Determines from which channels Event source type needs to be handled. NVR ONLY
	Rule.#.EventSource. #.DynamicEventName	RES	<string>	Dynamic event name received from Camera NVR ONLY
	Rule.#.EventSource. #.State	RES	<bool> True, False	State of the event source set as the trigger condition CAMERA ONLY
	Rule.#.EventAction.# .Type	RES	<enum> GoToPreset, AlarmOutput.#, SMTP, EventPush, EventSpot, FTP, AudioClip, Record, Handover	Any of the following event actions are possible; multiple event actions can be configured.
	Rule.#.EventAction.# .Channel.#.PresetNumber	RES	<int>	Used when the event action type is GoToPreset
	Rule.#.EventAction.# .AlarmOutput.Mask	RES	<csv>	Used when the event action type is AlarmOutput NVR ONLY
	Rule.#.EventAction.# .AlarmOutput.Duration	RES	<enum> Off, 5s, 10s, 20s, 30s, Always	Duration of alarmout
	Rule.#.EventAction.# .SMTP.GroupIndex	RES	<int>	Used when the event action type is SMTP Recipient group index NVR ONLY

Action	Parameter	Request/ Response	Type/ Value	Description
	Rule.#.EventAction.# .SMTP.UserIndex	RES	<int>	Used when the event action type is SMTP Recipient user index NVR ONLY
	Rule.#.EventAction.# .SMTP.Duration	RES	<enum> Off, 5s, 10s, 20s, 30s, Always	Duration NVR ONLY
	Rule.#.EventAction.# .EventSpot.Enable	RES	<bool> True, False	Used when the event action type is EventSpot Enabled or Disabled NVR ONLY
	Rule.#.EventAction.# .EventSpot.Duration	RES	<int>	Used when the event action type is EventSpot Duration NVR ONLY
	Rule.#.EventAction.# .EventPush.Enable	RES	<bool> True, False	Used when the event action type is EventPush Enable or Disabled NVR ONLY
	Rule.#.EventAction.# .AudioClipIndex	RES	<int>	Used when the event action type is AudioClip Audio clip index CAMERA ONLY
	Rule.#.EventAction.# .HandoverIndex	RES	<int>	Used when the event action type is Handover Handover index CAMERA ONLY

Action	Parameter	Request/ Response	Type/ Value	Description
add/update	RuleName	REQ	<string>	Rulename used for uniquely identifying a rule.
	RuleNewName	REQ	<string>	The Rulename to change. This parameter is used for update action.
	Duration	REQ	<int>	Duration in seconds
	ScheduleName	REQ	<string>	Name of schedule to be associated with this rule.
	Enable	REQ	<bool> True, False	To enable or disable rule.
	Overwrite	REQ	<bool> True, False	Whether to overwrite. This parameter is used for update action. Note If Overwrite is True , all other parameters must be entered.
	EventSource.#.Type	REQ	<enum> MotionDetection, VideoAnalytics, Tampering, DefocusDetection, FogDetection, AudioDetection, AudioAnalytics, NetworkAlarmInput , PasswordChange, HDDStatus, FANError, PowerOnOff, Recording, AppEvent	For a single rule, multiple eventsources can be configured.

Action	Parameter	Request/ Response	Type/ Value	Description
	EventSource.#.AppName	REQ	<string>	<p>The name of installed app</p> <p>EventSource.#.AppName is valid only when EventSource.#.Type is set to AppEvent.</p> <p>CAMERA ONLY</p>
	EventSource.#.AppEventType	REQ	<string>	<p>The event source type of installed app</p> <p>EventSource.#.AppEventType is valid only when EventSource.#.Type is set to AppEvent.</p> <p>CAMERA ONLY</p>
	EventSource.#.RuleIndexType	REQ	<enum> Any, Specific	<p>Rule index of the event source type:</p> <ul style="list-style-type: none"> Any – A trigger with one or more of the event’s rule indices Specific - A specific rule index of an event as a trigger <p>Note if RuleIndexType is Specific should specify with EventSource.#.RuleIndex parameter</p> <p>CAMERA ONLY</p>

Action	Parameter	Request/Response	Type/Value	Description
	EventSource.#.RuleIndex	REQ	<int>	<p>A rule index of an event as a trigger.</p> <p>EventSource.#.RuleIndex is valid only when EventSource.#.RuleIndexType is set to Specific.</p> <p>CAMERA ONLY</p>
	EventSource.#.Channel	REQ	<int>	<p>Determines from which channel Event source type needs to be handled.</p> <p>CAMERA ONLY</p>
	EventSource.#.ChannelIDList	REQ	<csv>	<p>Determines from which channels Event source type needs to be handled.</p> <p>NVR ONLY</p>
	EventSource.#.DynamicEventName	REQ	<string>	<p>Dynamic event name received from Camera</p>
	Rule.#.EventSource.#.State	REQ	<bool> True, False	<p>Set which state of the event source to set as the trigger condition</p> <p>CAMERA ONLY</p>
	EventAction.#.Type	REQ	<enum> GoToPreset, AlarmOutput.#, SMTP, EventPush, EventSpot, FTP, AudioClip, Record, Handover	<p>Any of the following event actions are possible, multiple event actions can be configured.</p>
	EventAction.#.Channel.#.PresetNumber	REQ	<int>	<p>Used when the event action type is GoToPreset</p>
	EventAction.#.AlarmOutput.Mask	REQ	<csv>	<p>Used when the event action type is AlarmOutput</p> <p>NVR ONLY</p>

Action	Parameter	Request/ Response	Type/ Value	Description
	EventAction.#.Alarm Output.Duration	REQ	<enum> Off, 5s, 10s, 20s, 30s, Always	Duration of alarmout
	EventAction.#.SMTP. GroupIndex	REQ	<int>	Used when the event action type is SMTP Recipient group index NVR ONLY
	EventAction.#.SMTP. UserIndex	REQ	<int>	Used when the event action type is SMTP Recipient user index NVR ONLY
	EventAction.#.SMTP. Duration	REQ	<enum> Off, 5s, 10s, 20s, 30s, Always	Duration NVR ONLY
	EventAction.#.Event Spot.Enable	REQ	<bool> True, False	Used when the event action type is EventSpot Enabled or Disabled NVR ONLY
	EventAction.#.Event Spot.Duration	REQ	<int>	Used when the event action type is EventSpot Duration NVR ONLY
	EventAction.#.Event Push.Enable	REQ	<bool> True, False	Used when the event action type is EventPush Enable or Disabled NVR ONLY

Action	Parameter	Request/Response	Type/Value	Description
	EventAction.#.AudioClipIndex	REQ	<int>	Used when the event action type is AudioClip Audio clip index CAMERA ONLY
	EventAction.#.HandoverIndex	REQ	<int>	Used when the event action type is Handover Handover index CAMERA ONLY
remove	RuleName	REQ	<string>	Rule name to be deleted

6.2.1.4. Examples (for Camera)

6.2.1.5. Getting the current dynamic rules

NOTE The camera only supports JSON responses.

REQUEST

```
http://<Device IP>/stw-cgi/eventrules.cgi?submenu=dynamicrules&action=view
```

JSON RESPONSE

```
HTTP/1.0 200 OK
Content-type: application/json
<Body>
```

```
{
  "Rules": [
    {
      "Rule": 0,
      "RuleName": "Test",
      "ScheduleName": "Always",
      "Duration": 5,
      "Enable": true,
      "Status": "Unavailable",
      "EventSources": [
        {
          "EventSource": 0,
          "Type": "MotionDetection",
          "RuleIndexType": "Any",

```

```

        "Channel": 1,
        "State": true
    },
    {
        "EventSource": 1,
        "Type": "AppEvent",
        "AppName": "WiseAI",
        "AppEventType": "ObjectDetection",
        "RuleIndexType": "Any",
        "Channel": 0,
        "State": true
    },
    {
        "EventSource": 2,
        "Type": "AppEvent",
        "AppName": "WiseAI",
        "AppEventType": "IvaArea",
        "RuleIndexType": "Specific",
        "RuleIndex": 1,
        "Channel": 0,
        "State": true
    }
],
"EventActions": [
    {
        "EventAction": 0,
        "Type": "SMTP"
    }
]
},
{
    "Rule": 1,
    "RuleName": "test2",
    "ScheduleName": "Always",
    "Duration": 60,
    "Enable": true,
    "Status": "Unavailable",
    "EventSources": [
        {
            "EventSource": 0,
            "Type": "AlarmInput.1",
            "RuleIndexType": "Any",
            "Channel": 0,
            "State": true
        },
        {
            "EventSource": 1,
            "Type": "TamperingDetection",
            "RuleIndexType": "Any",
            "Channel": 0,
            "State": true
        }
    ]
}

```

```

        },
        {
            "EventSource": 2,
            "Type": "DefocusDetection",
            "RuleIndexType": "Any",
            "Channel": 0,
            "State": true
        }
    ],
    "EventActions": []
}
]
}

```

6.2.1.6. Adding a dynamic rule

Adding a new dynamic rule with Rule name 'Test' and several event sources; MotionDetection, IvaArea and ObjectDetection of WiseAI app's event.

NOTE

The camera should see a list of supported events and actions via the **dynamicrulesoptions** submenu.
The camera only supports JSON responses.

REQUEST

```

http://<Device IP>/stw-
cgi/eventrules.cgi?msubmenu=dynamicrules&action=add&RuleName=Test&ScheduleName=Always&
Enable=True&Duration=5&EventSource.0.Type=MotionDetection&EventSource.0.RuleIndexType=
Specific&EventSource.0.RuleIndex=1&EventSource.0.Channel=1&EventSource.0.State=True&Ev
entSource.1.Type=AppEvent&EventSource.1.AppName=WiseAI&EventSource.1.AppEventType=IvaA
rea&EventSource.1.RuleIndexType=Any&EventSource.1.Channel=0&EventSource.1.State=False&
EventSource.2.Type=AppEvent&EventSource.2.AppName=WiseAI&EventSource.2.AppEventType=Ob
jectDetection&EventSource.2.RuleIndexType=Any&EventSource.2.Channel=0&EventSource.2.St
ate=True&EventAction.0.Type=SMTP&EventAction.1.Type=Handover&EventAction.1.HandoverInd
ex=1

```

JSON RESPONSE

```

HTTP/1.0 200 OK
Content-type: application/json
<Body>

```

```

{
    "Response": "Success"
}

```

6.2.1.7. Updating Dynamic Rule

To update an existing event rule, you must indicate the RuleName.

NOTE | The camera only supports JSON responses.

REQUEST

```
http://<Device IP>/stw-  
cgi/eventrules.cgi?msubmenu=dynamicrules&action=update&RuleName=Test&RuleNewName=Test2  
&Enable=True&EventAction.0.Type=FTP
```

JSON RESPONSE

```
HTTP/1.0 200 OK  
Content-type: application/json  
<Body>
```

```
{  
  "Response": "Success"  
}
```

6.2.1.8. Removing Dynamic Rule

To remove a rule with the **remove** action and by passing the RuleName

NOTE | The camera only supports JSON responses.

REQUEST

```
http://<Device IP>/stw-  
cgi/eventrules.cgi?msubmenu=dynamicrules&action=remove&RuleName=Test
```

JSON RESPONSE

```
HTTP/1.0 200 OK  
Content-type: application/json  
<Body>
```

```
{  
  "Response": "Success"  
}
```

6.2.2. Dynamic Rules Options

6.2.2.1. Description

The **dynamicrulesoptions** submenu provides a list of event sources for devices available in the dynamicrules submenu and information about their action triggers. Event sources and event actions that are not activated do not appear in the list and cannot be added to rules in dynamicrules submenu

NOTE This chapter applies to network cameras only.

Access level

Action	Camera
view	Admin

6.2.2.2. Syntax

```
http://<Device IP>/stw-cgi/eventrules.cgi?msubmenu=dynamicrulesoptions&action=<value>[&<parameter>=<value>]
```

6.2.2.3. Parameters

Action	Parameter	Request/Response	Type/Value	Description
view	Channel	REQ, RES	<csv>	Channel ID
	Language	REQ	<enum>	Language of the interface to the event type
	EventSource.#.Type	RES	<string>	Event types provided by the device
	EventSource.#.Type_<Language>	RES	<string>	Interface language data for the language selected in the Language parameter Displayed only when the Language parameter is specified
	EventSource.#.Status	RES	<enum> Inactive, Active	Indicates whether the event is currently active
	EventSource.#.Policy	RES	<enum> OneShot, Property	Indicates the event policy

Action	Parameter	Request/ Response	Type/ Value	Description
	EventSource.#.ActionTypes	RES	<csv> AlarmOutput.#, SMTP, FTP, Record, HTTP, GoToPreset, AudioClip	Event action types provided by the device
	EventSource.#.Rule.#.Name	RES	<string>	The name of the rule in the event
	AppEventSource.#.AppName	RES	<string>	The name of the app installed through the device's opensdk
	AppEventSource.#.Type	RES	<string>	Event types provided by opensdk app of the device
	AppEventSource.#.Type_<Language>	RES	<string>	Interface language data for the language selected in the Language parameter Displayed only when the Language parameter is specified
	AppEventSource.#.Status	RES	<enum> Inactive, Active	Indicates whether the event of app is currently active
	AppEventSource.#.Policy	RES	<enum> OneShot, Property	Indicates the event policy of app
	AppEventSource.#.ActionTypes	RES	<csv> AlarmOutput.#, SMTP, FTP, Record, HTTP, GoToPreset, AudioClip	Event types provided by the device for the event source of app
	AppEventSource.#.Rule.#.Name	RES	<string>	The name of the rule in the event of app

6.2.2.4. Examples

6.2.2.5. Getting the current dynamic rules options (this submenu supports only JSON response)

REQUEST

```
http://<Device IP>/stw-cgi/eventrules.cgi?msubmenu=dynamicrulesoptions&action=view
```

JSON RESPONSE

```
HTTP/1.0 200 OK  
Content-type: application/json  
<Body>
```

```
{  
  "DynamicRulesOptions": [  
    {  
      "Channel": 0,  
      "EventSources": [  
        {  
          "Type": "AlarmInput.1",  
          "Status": "Active",  
          "ActionTypes": [  
            "AlarmOutput.1",  
            "AlarmOutput.2",  
            "SMTP",  
            "FTP",  
            "Record",  
            "Handover"  
          ]  
        },  
        {  
          "Type": "AlarmInput.2",  
          "Status": "Active",  
          "ActionTypes": [  
            "AlarmOutput.1",  
            "AlarmOutput.2",  
            "SMTP",  
            "FTP",  
            "Record",  
            "Handover"  
          ]  
        },  
        {  
          "Type": "AudioAnalysis",  
          "Status": "Inactive",  
          "ActionTypes": [  
            "AlarmOutput.1",  
            "AlarmOutput.2",  
            "SMTP",  
            "FTP",  
            "Record",  
            "Handover"  
          ]  
        }  
      ]  
    }  
  ]  
}
```

```

    ]
  },
  {
    "Type": "AudioDetection",
    "Status": "Inactive",
    "ActionTypes": [
      "AlarmOutput.1",
      "AlarmOutput.2",
      "SMTP",
      "FTP",
      "Record",
      "Handover"
    ]
  },
  {
    "Type": "DefocusDetection",
    "Status": "Inactive",
    "ActionTypes": [
      "AlarmOutput.1",
      "AlarmOutput.2",
      "SMTP",
      "FTP",
      "Record",
      "Handover"
    ]
  },
  {
    "Type": "MotionDetection",
    "Status": "Active",
    "ActionTypes": [
      "AlarmOutput.1",
      "AlarmOutput.2",
      "SMTP",
      "FTP",
      "Record",
      "Handover"
    ]
  },
  {
    "Type": "NetworkDisconnect",
    "Status": "Active",
    "ActionTypes": [
      "AlarmOutput.1",
      "AlarmOutput.2",
      "Record"
    ]
  },
  {
    "Type": "TamperingDetection",
    "Status": "Active",
    "ActionTypes": [

```

```

        "AlarmOutput.1",
        "AlarmOutput.2",
        "SMTP",
        "FTP",
        "Record",
        "Handover"
    ]
},
{
    "Type": "Timer",
    "Status": "Inactive",
    "ActionTypes": [
        "AlarmOutput.1",
        "AlarmOutput.2",
        "SMTP",
        "FTP",
        "Record",
        "Handover"
    ]
}
],
"AppEventSources": [
{
    "Type": "IvaArea",
    "Status": "Active",
    "AppName": "WiseAI",
    "Rule": [
        {
            "Rule": 1,
            "Name": "name 1"
        },
        {
            "Rule": 2,
            "Name": "name 2"
        }
    ],
    "ActionTypes": [
        "AlarmOutput.1",
        "AlarmOutput.2",
        "SMTP",
        "FTP",
        "Record",
        "Handover"
    ]
},
{
    "Type": "LineCrossing",
    "Status": "Active",
    "AppName": "WiseAI",
    "Rule": [
        {

```

```

        "Rule": 1,
        "Name": "name 1"
    }
],
"ActionTypes": [
    "AlarmOutput.1",
    "AlarmOutput.2",
    "SMTP",
    "FTP",
    "Record",
    "Handover"
]
},
{
    "Type": "ObjectDetection",
    "Status": "Active",
    "AppName": "WiseAI",
    "ActionTypes": [
        "AlarmOutput.1",
        "AlarmOutput.2",
        "SMTP",
        "FTP",
        "Record",
        "Handover"
    ]
}
]
},
{
    "Channel": 1,
    "EventSources": [
        {
            "Type": "DefocusDetection",
            "Status": "Inactive",
            "ActionTypes": [
                "AlarmOutput.1",
                "AlarmOutput.2",
                "SMTP",
                "FTP",
                "Record",
                "Handover"
            ]
        },
        {
            "Type": "MotionDetection",
            "Status": "Active",
            "ActionTypes": [
                "AlarmOutput.1",
                "AlarmOutput.2",
                "SMTP",
                "FTP",

```

```

        "Record",
        "Handover"
    ]
},
{
    "Type": "TamperingDetection",
    "Status": "Inactive",
    "ActionTypes": [
        "AlarmOutput.1",
        "AlarmOutput.2",
        "SMTP",
        "FTP",
        "Record",
        "Handover"
    ]
}
],
"AppEventSources": [
    {
        "Type": "IvaArea",
        "Status": "Active",
        "AppName": "WiseAI",
        "Rule": [
            {
                "Rule": 1,
                "Name": "name 1"
            }
        ],
        "ActionTypes": [
            "AlarmOutput.1",
            "AlarmOutput.2",
            "SMTP",
            "FTP",
            "Record",
            "Handover"
        ]
    },
    {
        "Type": "LineCrossing",
        "Status": "Active",
        "AppName": "WiseAI",
        "Rule": [
            {
                "Rule": 1,
                "Name": "name 1"
            }
        ],
        "ActionTypes": [
            "AlarmOutput.1",
            "AlarmOutput.2",
            "SMTP",

```

```

        "FTP",
        "Record",
        "Handover"
    ]
},
{
    "Type": "ObjectDetection",
    "Status": "Inactive",
    "AppName": "WiseAI",
    "ActionTypes": [
        "AlarmOutput.1",
        "AlarmOutput.2",
        "SMTP",
        "FTP",
        "Record",
        "Handover"
    ]
}
]
}
]
}
}

```

References

- [1] [OpenAPI Documentation](#)
- [2] [OpenAPI Tools](#)
- [3] [SwaggerHub](#)