

Wadzire Village Blood Group Dashboard

DAX Measures & Calculated Columns Reference

Setup required before using these formulas:

1. Table name must be exactly **BloodGroupData** (the Excel sheet is already named this — if Power BI shows a different name after import, rename the table in the Fields pane to match).
2. Source columns already in the file: PersonID, Name, Gender, Age, Village, Taluka, District, State, Pincode, BloodGroup, BloodGroupChartImageURL, BloodTypingTestImageURL.
3. Build order: create calculated columns first (sections 6, 7, 8, 10), then measures (sections 1, 2, 3, 4, 5, 9) — formula 5 depends on the RhFactor column from formula 7.

1. Total People (Measure)

```
Total People = COUNTROWS('BloodGroupData')
```

2. Total Male / Female (Measure)

```
Total Male = CALCULATE([Total People], 'BloodGroupData'[Gender] = "Male")
```

```
Total Female = CALCULATE([Total People], 'BloodGroupData'[Gender] = "Female")
```

3. % Share by Blood Group (Measure)

```
Pct Blood Group =  
DIVIDE(  
    [Total People],  
    CALCULATE([Total People], ALL('BloodGroupData'[BloodGroup]))  
)
```

4. Most Common Blood Group (Measure)

```
Most Common BG =  
CALCULATE(  
    VALUES('BloodGroupData'[BloodGroup]),  
    TOPN(1, VALUES('BloodGroupData'[BloodGroup]), [Total People], DESC)  
)
```

5. Rh Positive vs Negative Count (Measure - uses RhFactor column)

```
Rh Positive Count =  
CALCULATE([Total People], 'BloodGroupData'[RhFactor] = "Positive")
```

```
Rh Negative Count =  
CALCULATE([Total People], 'BloodGroupData'[RhFactor] = "Negative")
```

-- Note: depends on RhFactor calculated column (see #7).

-- Faster than CONTAINSSTRING at 5k+ rows since RhFactor is precomputed at refresh.

6. ABO Type Extract (Calculated Column)

```
ABOType =  
SWITCH(  
    TRUE(),  
    LEFT('BloodGroupData'[BloodGroup], 2) = "AB", "AB",  
    LEFT('BloodGroupData'[BloodGroup], 1) = "A", "A",  
    LEFT('BloodGroupData'[BloodGroup], 1) = "B", "B",  
    LEFT('BloodGroupData'[BloodGroup], 1) = "O", "O",  
    "Unknown"  
)
```

7. Rh Factor Extract (Calculated Column)

```
RhFactor =  
IF(  
    RIGHT('BloodGroupData'[BloodGroup], 1) = "+",  
    "Positive",  
    "Negative"  
)
```

8. Age Group Bucket (Calculated Column)

```
AgeGroup =  
SWITCH(  
    TRUE(),  
    'BloodGroupData'[Age] < 18, "Minor",  
    'BloodGroupData'[Age] <= 30, "18-30",  
    'BloodGroupData'[Age] <= 45, "31-45",  
    'BloodGroupData'[Age] <= 60, "46-60",  
    "60+"  
)
```

9. Gender-wise Blood Group Count (Measure)

```
Male Count by BG =  
CALCULATE([Total People], 'BloodGroupData'[Gender] = "Male")  
  
Female Count by BG =  
CALCULATE([Total People], 'BloodGroupData'[Gender] = "Female")  
  
Gender Ratio (M:F) =  
DIVIDE([Male Count by BG], [Female Count by BG])
```

10. Universal Donor / Recipient Flag (Calculated Column)

```
DonorRecipientFlag =  
SWITCH(  
    TRUE(),  
    'BloodGroupData'[BloodGroup] = "O-", "Universal Donor",  
    'BloodGroupData'[BloodGroup] = "AB+", "Universal Recipient",  
    "Standard"  
)
```