



AutoTech Manufacturing Corp.

2750 Industrial Parkway, Detroit, MI 48201
Tel: +1 (313) 555-4200 | Email: purchasing@autotech-mfg.com | www.autotech-mfg.com
IATF 16949 Certified | Engineering Division

BILL OF MATERIALS (BOM)

DOCUMENT NO.
AT-BOM-3567

REVISION
Rev 2.1

BOM INFORMATION

BOM Revision:	Rev 2.1
BOM Date:	October 10, 2025
Status:	Approved
Effective Date:	October 10, 2025
Supersedes:	Rev 2.0 (Sep 29, 2025)
Document No.:	AT-BOM-3567

REFERENCE INFORMATION

Customer PO:	PO-2025-15903
Customer:	AutoTech Manufacturing Corp.
Project Code:	PRJ-AT-2025-Q4B
Prepared By:	Technical Dept.
PO Line Item:	Line 2 - 50 pcs
Supplier:	Precision Steel & Components Ltd. (SUP-PSC-2024-456)

MATERIAL IDENTIFICATION

ID	TYPE/PART DESIGNATION	DIMENSIONS	MATERIAL GRADE
MAT-3567	Stainless Steel Sheet - Grade 304	1220 x 2440 x 3 mm	304 / 1.4301

Material Overview: Austenitic stainless steel sheet with excellent corrosion resistance and formability. Suitable for food processing equipment, architectural applications, and chemical processing. Material conforms to ASTM A240/A240M specifications.

TECHNICAL SPECIFICATIONS

Material Standard:	ASTM A240/A240M - Stainless Steel 304	Grade:	304 (UNS S30400) / 1.4301
Width:	1220 mm (4 feet)	Length:	2440 mm (8 feet)
Thickness:	3 mm	Surface Finish:	2B finish (cold-rolled, annealed, pickled)
Thickness Tolerance:	±0.15 mm	Width Tolerance:	±3 mm
Length Tolerance:	±5 mm	Weight per Sheet:	71.5 kg (approx.)
Testing Required:	Mill test certificate (MTC) 3.1, dimensional check	Flatness:	Per ASTM A480/A480M, standard
Edge Condition:	Mill edge / slit edge, deburred	Squareness:	Max. 3 mm diagonal difference
Surface Protection:	PVC film, one side (2B face)	Certificate Standard:	EN 10204 Type 3.1

CHEMICAL COMPOSITION (SPEC. LIMITS)

Element	Requirement (wt %)
Carbon (C)	0.07 max
Manganese (Mn)	2.00 max
Phosphorus (P)	0.045 max
Sulfur (S)	0.030 max
Silicon (Si)	0.75 max
Chromium (Cr)	17.5 - 19.5
Nickel (Ni)	8.0 - 10.5
Nitrogen (N)	0.10 max
Iron (Fe)	Balance

MECHANICAL PROPERTIES (MIN.)

Property	Requirement
Tensile Strength	515 MPa (75 ksi)
Yield Strength (0.2%)	205 MPa (30 ksi)
Elongation in 50 mm	40 %
Hardness	92 HRBW max / 201 HBW max
Density (typical)	7.93 g/cm ³

Requirements per ASTM A240/A240M, Table 2, for UNS S30400 plate, sheet and strip.



AutoTech Manufacturing Corp.

2750 Industrial Parkway, Detroit, MI 48201
Tel: +1 (313) 555-4200 | Email: purchasing@autotech-mfg.com | www.autotech-mfg.com
IATF 16949 Certified | Engineering Division

BILL OF MATERIALS (BOM)

DOCUMENT NO.	REVISION
AT-BOM-3567	Rev 2.1

QUALITY & INSPECTION PLAN

#	Characteristic	Method / Reference	Frequency	Record
1	Chemical composition	MTC 3.1 review vs. ASTM A240	Each heat	MTC 3.1
2	Mechanical properties	Tensile & hardness per ASTM A370	Each heat/lot	MTC 3.1
3	Thickness	Micrometer, 4 corners + center	Every sheet	Inspection report
4	Width, length, squareness	Tape & diagonal measurement	10 % of sheets	Inspection report
5	Flatness	Straight edge per ASTM A480	10 % of sheets	Inspection report
6	Surface finish (2B)	Visual, no pits, scratches, staining	100 %	Packing list sign-off

PACKAGING, MARKING & HANDLING

Packaging:	Export-grade wooden crates with moisture barrier, 10 sheets / approx. 715 kg per crate (5 crates); paper interleaving between sheets
Protection:	PVC protective film on finished side; edge protectors; waterproof wrap
Marking:	Stenciled on each sheet: grade 304, heat no., ASTM A240, size, mill ID
Crate Tag:	Material ID MAT-3567, PO-2025-15903, crate no., sheet count, heat no., net/gross weight
Storage / Handling:	Store flat, indoors; avoid contact with carbon steel tools or forks

ADDITIONAL SERVICES & FEES

Fee (per supplier price list)	Applies	Charge basis	Quantity	Notes
Cutting Fee	No	-	-	Full sheets 1220 x 2440 mm; no cutting
Cert Fee (MTC 3.1)	Yes	Per heat/lot	1 certificate	All 50 sheets supplied from a single heat
Testing Fee	No	-	-	Mill tests reported on the MTC; not charged separately
Hydrostatic Testing	No	-	-	Not applicable to this material
Packaging - Export Grade	Yes	Per crate	5 crates	Wooden crate with moisture barrier, 10 sheets per crate
Rush / Same-Day Processing	No	-	-	Standard lead time; no surcharge

Fee names and rates as listed in the Precision Steel & Components Ltd. Master Price List, effective October 01, 2025. Fees marked **Yes** are charged in the quantity shown and are **not** included in the PO unit price or PO total; they are invoiced as separate lines. Fees marked **No** are not charged for this item. No volume discount applies.

REVISION HISTORY

Rev	Date	Description of Change	By	Appr.
Rev 1.0	Jun 16, 2025	Initial release.	S. Patel	M. Alvarez
Rev 2.0	Sep 29, 2025	Updated to MTC 3.1 requirement; finish changed from No. 1 to 2B.	S. Patel	M. Alvarez
Rev 2.1	Oct 10, 2025	Linked to PO-2025-15903; tolerances confirmed with customer.	S. Patel	M. Alvarez

CONTACTS & APPROVALS

Role	Name / Department	Signature	Date
Prepared	Technical Dept. - Sunita Patel	/s/ Sunita Patel	Oct 09, 2025
Checked	Laura Chen, Quality Engineer	/s/ Laura Chen	Oct 10, 2025
Approved By	Quality Control Department - Maria Alvarez, QC Manager	/s/ Maria Alvarez	Oct 10, 2025
Technical Contact	Thomas Richardson, Technical Sales Precision Steel & Components Ltd. (Supplier)	t.richardson@precisionsteel.com	+1 (412) 555-8912

Document Control: This BOM is controlled by AutoTech Manufacturing Corp. Material must meet ASTM A240 Grade 304 specifications with 2B finish.