

```
In [1]: import numpy as np
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [15]: from sklearn import preprocessing
```

```
In [20]: from sklearn.preprocessing import PolynomialFeatures
```

```
In [16]: from sklearn.model_selection import train_test_split
```

```
In [17]: from sklearn.linear_model import LinearRegression, Ridge, Lasso
```

```
In [21]: from sklearn.metrics import r2_score
```

```
In [3]: data = pd.read_csv(r"C:\Users\G BHARANIKA\Desktop\car-mpg.csv")
data.head()
```

```
Out[3]:
```

	mpg	cyl	displacement	hp	wt	acc	yr	origin	car_type	car_name
0	18.0	8	307.0	130	3504	12.0	70	1	0	chevrolet chevelle malibu
1	15.0	8	350.0	165	3693	11.5	70	1	0	buick skylark 320
2	18.0	8	318.0	150	3436	11.0	70	1	0	plymouth satellite
3	16.0	8	304.0	150	3433	12.0	70	1	0	amc rebel sst
4	17.0	8	302.0	140	3449	10.5	70	1	0	ford torino

```
In [4]: data = data.drop(['car_name'], axis = 1)
data['origin'] = data['origin'].replace({1: 'america', 2: 'europe', 3: 'asia'})
data = pd.get_dummies(data, columns = ['origin'], dtype=int)
data = data.replace('?', np.nan)
```

```
In [47]: data = data.apply(pd.to_numeric)

# Fill missing values with median only for numeric columns
numeric_cols = data.select_dtypes(include=[np.number]).columns
data[numeric_cols] = data[numeric_cols].apply(lambda x: x.fillna(x.median()))
```

MODEL BUILDING

```
In [10]: x = data.drop(['mpg'], axis = 1)
y = data[['mpg']]
```

```
In [11]: x_s = preprocessing.scale(x)
x_s = pd.DataFrame(x_s, columns = x.columns)
```

```
y_s = preprocessing.scale(y)
y_s = pd.DataFrame(y_s, columns = y.columns)
```

```
In [18]: #Split into train, test set
x_train, x_test, y_train, y_test = train_test_split(x_s, y_s, test_size = 0.30, random
x_train.shape
```

```
Out[18]: (278, 10)
```

2.SIMPLE LINEAR MODEL

```
In [32]: regression_model = LinearRegression()
regression_model.fit(x_train, y_train)
print(x_train, y_train)
for idx, col_name in enumerate(x_train.columns):
    print('The coefficient for {} is {}'.format(col_name, regression_model.coef_[0]

intercept = regression_model.intercept_[0]
print('The intercept is {}'.format(intercept))
```



```
Lasso model coef: [-0.          -0.          -0.01690287 -0.51890013  0.          0.28
138241
0.1278489 -0.01642647  0.          0.          ]
```

3. SCORE COMPARISON

```
In [38]: print(regression_model.score(x_train, y_train))
print(regression_model.score(x_test, y_test))

print('*****')
#Ridge
print(ridge_model.score(x_train, y_train))
print(ridge_model.score(x_test, y_test))

print('*****')
#Lasso
print(lasso_model.score(x_train, y_train))
print(lasso_model.score(x_test, y_test))
```

```
0.8343770256960538
0.8513421387780066
*****
0.8343617931312616
0.8518882171608507
*****
0.7938010766228453
0.8375229615977083
```

4.MODEL PARAMETER TUNING

```
In [41]: data_train_test = pd.concat([x_train, y_train], axis =1)
data_train_test.head()
```

```
Out[41]:
```

	cyl	dis	hp	wt	acc	yr	car_type	origin_ame
350	-0.856321	-0.849116	-1.081977	-0.893172	-0.242570	1.351199	0.941412	0.773
59	-0.856321	-0.925936	-1.317736	-0.847061	2.879909	-1.085858	0.941412	-1.292
120	-0.856321	-0.695475	0.201600	-0.121101	-0.024722	-0.815074	0.941412	-1.292
12	1.498191	1.983643	1.197027	0.934732	-2.203196	-1.627426	-1.062235	0.773
349	-0.856321	-0.983552	-0.951000	-1.165111	0.156817	1.351199	0.941412	-1.292

```
In [42]: import statsmodels.formula.api as smf
ols1 = smf.ols(formula = 'mpg ~ cyl+dis+hp+wt+acc+yr+car_type+origin_america+origi
ols1.params
```

```
Out[42]: Intercept      0.019284
        cyl             0.321022
        disp            0.324834
        hp              -0.229170
        wt              -0.711210
        acc             0.014714
        yr              0.375581
        car_type         0.381477
        origin_america   -0.074722
        origin_europe    0.048349
        origin_asia      0.044515
        dtype: float64
```

```
In [43]: print(ols1.summary())
```

```

                        OLS Regression Results
=====
Dep. Variable:          mpg      R-squared:                0.834
Model:                  OLS      Adj. R-squared:            0.829
Method:                 Least Squares      F-statistic:        150.0
Date:                   Thu, 21 Aug 2025    Prob (F-statistic):    3.12e-99
Time:                   14:50:35           Log-Likelihood:      -146.89
No. Observations:       278              AIC:                313.8
Df Residuals:           268              BIC:                350.1
Df Model:               9
Covariance Type:        nonrobust
=====
                        coef      std err          t      P>|t|      [0.025      0.975]
-----
Intercept              0.0193      0.025        0.765      0.445      -0.030      0.069
cyl                   0.3210      0.112        2.856      0.005       0.100      0.542
disp                  0.3248      0.128        2.544      0.012       0.073      0.576
hp                    -0.2292      0.079       -2.915      0.004      -0.384     -0.074
wt                    -0.7112      0.088       -8.118      0.000      -0.884     -0.539
acc                   0.0147      0.039        0.373      0.709      -0.063      0.092
yr                    0.3756      0.029       13.088      0.000       0.319      0.432
car_type              0.3815      0.067        5.728      0.000       0.250      0.513
origin_america        -0.0747      0.020       -3.723      0.000      -0.114     -0.035
origin_europe          0.0483      0.021        2.270      0.024       0.006      0.090
origin_asia           0.0445      0.020        2.175      0.031       0.004      0.085
=====
Omnibus:                22.678    Durbin-Watson:          2.105
Prob(Omnibus):           0.000    Jarque-Bera (JB):       36.139
Skew:                    0.513    Prob(JB):               1.42e-08
Kurtosis:                4.438    Cond. No.               1.59e+16
=====
```

Notes:

[1] Standard Errors assume that the covariance matrix of the errors is correctly specified.

[2] The smallest eigenvalue is 6.14e-30. This might indicate that there are strong multicollinearity problems or that the design matrix is singular.

```
In [44]: mse = np.mean((regression_model.predict(x_test)-y_test)**2)

        # root of mean_sq_error is standard deviation i.e. avg variance between predicted a
```


```
import math
rmse = math.sqrt(mse)
print('Root Mean Squared Error: {}'.format(rmse))
```


Root Mean Squared Error: 0.37766934254087847

```
In [45]: fig = plt.figure(figsize=(10,8))
sns.residplot(x= x_test['hp'], y= y_test['mpg'], color='green', lowess=True )

fig = plt.figure(figsize=(10,8))
sns.residplot(x= x_test['acc'], y= y_test['mpg'], color='green', lowess=True )
```

Out[45]: <Axes: xlabel='acc', ylabel='mpg'>






```
In [46]: # predict mileage (mpg) for a set of attributes not in the training or test set
y_pred = regression_model.predict(x_test)

# Since this is regression, plot the predicted y value vs actual y values for the t
# A good model's prediction will be close to actual leading to high R and R2 values
#plt.rcParams['figure.dpi'] = 500
plt.scatter(y_test['mpg'], y_pred)
```

```
Out[46]: <matplotlib.collections.PathCollection at 0x1e0954c5c70>
```

In []: