

REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	LJC 12/20/07		

NOTE:

1. Material:

Housing: Thermoplastics,UL94V-0

Contact: Copper Alloy

Shell: Copper Alloy

2. Specification:

2.1: Rated current: 1.5 A

Insulation Resistance:

1000MΩ Min. at 500V/DC for 1Minute.

Withstanding voltage: 500 VAC/minute

Contact Resistance: 30 mohms Max.

2.2: MECHANICAL

Mating force: 35N(3.57kgf) Max.

Unmating force(Without lock):10N(1.02kgf) Min.

Durability: 1500 cycles Min.

3. PRODUCT NUMBER CODE:

DS1095-06 - X X X X

CONTACT PLATING
0: Selective gold flash
03: Selective gold 3u"
30: Selective gold 30u"

MOUNTING TYPE
R: RIGHT ANGLE



SHELL PLATING:
N: Nickel
6: Tin

COLOR OF HOUSING:
W: White
B: Black

SERIES No.
DS1095-06

RECOMMENDED PCB LAYOUT(TOP VIEW)

GENERAL TOLERANCES:±0.05

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE		USB Female A TYPE		
X.	±0.60	X.	±5°	UNITS	mm			SMT series		
.X	±0.38	.X	±3°	SHEET SIZE	A4	SERIES	DS1095-06 SERIES			
.XX	±0.25	.XX	±2°	<div> 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD</div>						
DRAWING TYPE		CUSTOMER								
SCALE		1:1	SHEET							1 OF 1
DRAWING NO.		C-DS1095-06-XXXX								



晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD