# GASPI: Global Address Space Programming Interface

# Specification of a PGAS API for communication

draft, version 0.92

Daniel Grünewald et al. Fraunhofer ITWM, Fraunhofer Platz 1, 67663 Kaiserslautern

June 7, 2013

# Contents

5 Execution model

1	Intr	oduction to Gaspi	7					
	1.1	Overview and Goals	7					
	1.2	History	7					
	1.3	Design goals	7					
2	GAS	PI terms and conventions	8					
	2.1	Naming Conventions	8					
	2.2	Procedure specification	8					
	2.3	Semantic terms	9					
	2.4	Examples	10					
3	GAS	PI concepts	10					
	3.1	Introduction and overview	10					
	3.2	Gaspi processes	11					
	3.3	Gaspi groups	11					
	3.4	Gaspi segments	11					
	3.5	Gaspi one-sided communication	11					
	3.6	Gaspi queues	11					
	3.7	Gaspi passive communication	12					
	3.8	Gaspi global atomics	12					
	3.9	Gaspi timeouts	13					
	3.10	Gaspi collective communication	13					
	3.11	Gaspi return values	14					
4	Gaspi definitions 14							
	4.1	Types	14					
	4.2	Constants	16					
		4.2.1 Timeout values	16					
		4.2.2 Function return values	17					
		4.2.3 State vector states	17					
		4.2.4 Allocation policies	17					
		4.2.5 Statistics interface	17					

**17** 

	5.1	Introduction and overview					
	5.2	Process configuration					
		5.2.1 Gaspi configuration structure					
		5.2.2 gaspi_config_get					
		5.2.3 gaspi_config_set					
	5.3	Process management calls					
		5.3.1 gaspi_proc_init					
		5.3.2 gaspi_proc_num					
		5.3.3 gaspi_proc_rank					
		5.3.4 gaspi_proc_term					
		5.3.5 gaspi_proc_kill					
		5.3.6 Example					
	5.4	Connection management utilities					
		5.4.1 gaspi_connect					
		5.4.2 gaspi_disconnect					
	5.5	State vector for individual processes					
		5.5.1 Introduction					
		5.5.2 gaspi_state_vec_get					
	5.6	MPI Interoperability					
	5.7	Argument checks and performance					
6	Cro	$_{ m oups}$ 35					
U	6.1	•					
	6.2						
	0.2						
		0 1 11					
	6.3						
	0.5	Group creation					
		0 1 -0 1-					
		0 1 -0 1-					
	C 4	0 1 -0 1 -					
	6.4	Group deletion					
	C =	6.4.1 gaspi_group_delete					
	6.5	Group utilities					
		6.5.1 gaspi_group_num					

		6.5.2	<pre>gaspi_group_size</pre>	10				
		6.5.3	gaspi_group_ranks	11				
7	Gaspi segments 42							
	7.1	Introd	uction and overview	12				
	7.2	Segme	ent creation	13				
		7.2.1	gaspi_segment_alloc	13				
		7.2.2	gaspi_segment_register	14				
		7.2.3	gaspi_segment_create	16				
	7.3	Segme	nt deletion	18				
		7.3.1	gaspi_segment_delete	18				
	7.4	Segme	nt utilities	19				
		7.4.1	gaspi_segment_num 4	19				
		7.4.2	gaspi_segment_list 5	0				
		7.4.3	gaspi_segment_ptr 5	1				
	7.5	Segme	nt memory management	52				
8	One-sided communication 52							
	8.1	Introd	uction and overview	$\tilde{2}$				
	8.2	Basic	communication calls	64				
		8.2.1	gaspi_write	64				
		8.2.2	gaspi_read	66				
		8.2.3	gaspi_wait	69				
		8.2.4	Examples	60				
	8.3	Weak	synchronisation primitives 6	64				
		8.3.1	Introduction	64				
		8.3.2	gaspi_notify6	55				
		8.3.3	gaspi_notify_waitsome6	66				
		8.3.4	gaspi_notify_reset6	69				
	8.4	Extend	ded communication calls	0				
		8.4.1	gaspi_write_notify 7	0				
		8.4.2	gaspi_write_list	2				
		8.4.3	gaspi_write_list_notify	4				
		8.4.4	gaspi_read_list	6				
	8.5	Comm	unication utilities	8				

		8.5.1	gaspi_queue_size	78				
		8.5.2	gaspi_queue_purge	79				
9	Pass	Passive communication 80						
	9.1	Introd	uction and overview	80				
	9.2	Passive	e communication calls	81				
		9.2.1	gaspi_passive_send	81				
		9.2.2	gaspi_passive_receive	83				
	9.3	Passive	e communication utilities	85				
		9.3.1	gaspi_passive_queue_purge	85				
10	Glol	oal ato	omics	86				
	10.1	Introd	uction and Overview	86				
	10.2	Atomic	c operation calls	86				
		10.2.1	gaspi_atomic_fetch_add	86				
		10.2.2	gaspi_atomic_compare_swap	88				
		10.2.3	Examples	90				
11	Collective communication 92							
	11.1	Introd	uction and overview	92				
	11.2	Barrier	r synchronisation	93				
		11.2.1	gaspi_barrier	93				
		11.2.2	Examples	95				
	11.3	Predefi	ined global reduction operations	95				
		11.3.1	gaspi_allreduce	95				
		11.3.2	Predefined reduction operations	97				
		11.3.3	Predefined types	98				
	11.4	User-d	efined global reduction operations	98				
		11.4.1	gaspi_allreduce_user	98				
		11.4.2	User defined reduction operations	100				
		11.4.3	allreduce state	101				
12	GAS	PI <b>gett</b>	er functions	102				
	12.1	Getter	functions for group management	102				
		12.1.1	gaspi group max	102				

	12.2	Getter functions for segment management $\dots \dots \dots$	02
		12.2.1 gaspi_segment_max	02
	12.3	Getter functions for communication management	03
		12.3.1 gaspi_queue_num 10	03
		12.3.2 gaspi_queue_size_max	04
		12.3.3 gaspi_transfer_size_max	04
		$12.3.4 \ \texttt{gaspi\_notification\_num} \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots \ldots 10$	05
	12.4	Getter functions for passive communication	05
		$12.4.1 \hspace{0.1cm} \texttt{gaspi\_passive\_transfer\_size\_max} \hspace{0.1cm} \ldots \hspace{0.1cm} \ldots \hspace{0.1cm} \ldots \hspace{0.1cm} \ldots \hspace{0.1cm} 10$	05
	12.5	Getter functions for collective communication	06
		$12.5.1 \ \texttt{gaspi\_allreduce\_buf\_size} \ \dots \dots \ \dots \ 10$	06
		$12.5.2 \ \texttt{gaspi\_allreduce\_elem\_max} \ \dots \ \dots \ \dots \ 10$	06
	12.6	Getter functions related to infrastructure	07
		12.6.1 gaspi_network_type	07
		$12.6.2$ gaspi_build_infrastructure	07
13	GASI	PI Environmental Management 10	)8
	13.1	Implementation Information	08
		13.1.1 gaspi_version	08
	13.2	Timing information	09
		13.2.1 gaspi_time_get	09
		13.2.2 gaspi_time_ticks	10
	13.3	Error Codes and Classes	10
		13.3.1 Gaspi error codes	10
		13.3.2 gaspi_error_message	10
14	Prof	iling Interface 11	11
		Statistics	
		14.1.1 gaspi_statistic_counter_max	
		14.1.2 gaspi_statistic_counter_info	
		14.1.3 gaspi_statistic_verbosity_level	
		14.1.4 gaspi_statistic_counter_get	
		14.1.5 gaspi_statistic_counter_reset	
	14.2	Event Tracing	17

CONTENTS	6
----------	---

A	Listings	118
	A.1 success_or_die	118
	A.2 wait if queue full	119

# 1 Introduction to GASPI

#### 1.1 Overview and Goals

Gaspi stands for Global Address Space Programming Interface and is a Partitioned Global Address Space (PGAS) API. It aims at extreme scalability, high flexibility and failure tolerance for parallel computing environments. GASPI aims to initiate a paradigm shift from bulk-synchronous two-sided communication patterns towards an asynchronous communication and execution model. To that end Gaspi leverages one-sided RDMA driven communication in a Partitioned Global Address Space. In contrast to other efforts in the PGAS community, Gaspi is neither a new language (like Chapel from Cray), nor an extension to a language (like Co-Array Fortran or UPC). Instead—very much in the spirit of MPI—it complements existing languages like C/C++ or Fortran with a PGAS API which enables the application to leverage the concept of the Partitioned Global Adress Space. In contrast to e.g. OpenShmem or Global Arrays, Gaspi is not limited to a single memory model, but rather provides configurable RDMA PGAS memory segments. GASPI allows application developers to map the memory heterogeneity of a modern supercomputer node to these PGAS segments. As an example GASPI allows users to map the main memory of a GPGPU or Xeon Phi to a specific segment, to configure a GASPI segment per memory controller in a CC-NUMA system or to map non-volatile RAM to a specific segment. All these segments can directly read and write from to each other - within the node and across all nodes. Gaspi is failure tolerant in the sense that it provides timeout mechanisms for all non-local procedures, failure detection and the possibility to adapt to shrinking or growing node sets.

#### 1.2 History

The Gaspi specification originates from the PGAS API of the Fraunhofer ITWM (Fraunhofer Virtual Machine, FVM), which has been developed since 2005. Starting from 2007 this PGAS API has evolved into a robust commercial product (called GPI) which is used in the industry projects of the Fraunhofer ITWM. GPI offers a highly efficient and scalable programming model for Partitioned Global Address Spaces and has replaced MPI completely at Fraunhofer ITWM. In 2011 the partners of Fraunhofer ITWM, Fraunhofer SCAI, TUD, T-Systems SfR, DLR, KIT, FZJ, DWD and Scapos have initiated and launched the Gaspi project to define a novel specification for a PGAS API (Gaspi, based on GPI) and to make this novel Gaspi specification a reliable, scalable and universal tool for the HPC community.

#### 1.3 Design goals

Gaspi has been designed with the following goals in mind:

• Extreme scalability.

- Efficient one sided asynchronous remote read/write operations based on remote completion.
- Multi-segment support to support e. g. heterogeneous systems and NUMApinning.
- Dynamic allocation of segments.
- Timeout mechanisms to allow failure tolerant programming.
- Asynchronous collective operations for groups of processes.
- Flexibility in the number of message queues, the queue sizes, atomic operations etc.
- A maximum freedom to implementors, where details are left to the implementation.
- A strong standard library which takes care of convenience procedures and cosmetics. The specification should be simple and solid.

# 2 Gaspi terms and conventions

This section describes notational terms and conventions used throughout the Gaspi document.

# 2.1 Naming Conventions

All procedures are named in accordance with the following convention. The procedures have gaspi\_ as a prefix. The prefix is followed by the operation name.

#### 2.2 Procedure specification

GASPI has adopted the procedure specification of MPI. Similar to the MPI standard, procedures in GASPI hence are first specified using a language independent notation. Immediately below this, the arguments of the procedure are given and marked as IN or OUT. The meanings of these are:

- the call uses but does not update an argument marked IN. For the C procedures these arguments are const-correct.
- the call may update an argument marked OUT.

Similar to MPI, in GASPI the passing of aliased procedure parameters results in undefined behavior.

Below the procedure arguments the ANSI C version of the function is shown, and below this, a version of the same function is shown for Fortran 2003. For the latter the corresponding definitions and derived types have to be include via

```
use, intrinisic :: ISO_C_BINDING use GASPI_C_BINDING
```

# 2.3 Semantic terms

The following semantic terms are used throughout the document:


**non-blocking** A procedure is non-blocking if the procedure may return before the operation completes.



**blocking** A procedure is blocking if the procedure only returns after the operation has completed.



time-based blocking A procedure is time-based blocking if the procedure may return after the operation completes or after a given timeout has been reached. A corresponding return value is used to distinguish between the two cases.



**local** A procedure is local if completion of the procedure depends only on the local executing GASPI process.

non-local A procedure is non-local if completion of the operation may depend on the existence (and execution) of a remote Gaspi process


**collective** A procedure is collective if all processes in a process group need to invoke the procedure. A collective call may or may not be synchronising.

**predefined** A predefined type is a datatype with a predefined constant name.


timeout A timeout is a mechanism required by procedures that might block (see blocking above). Timeout here is defined as the maximum time (in milliseconds) a called procedure will wait for outstanding communication from other processes. The special value 0 (defined as GASPI\_TEST) indicates that the procedure will complete all local operations. The procedure subsequently returns the current status without waiting for data from other processes (non-blocking). On the other hand the special value -1 (defined as GASPI\_BLOCK) instructs the procedure to wait indefinitely

(blocking). A number greater than 0 indicates the maximum time the procedure will wait for data from other ranks (time-based blocking). The timeouts hence are soft: The timeout value n does not imply that the called procedure will return after n milliseconds. It just means that the procedure should wait for at most n milliseconds for data from other processes

**synchronous** A procedure is called synchronous if progress towards completion only is achieved as long as the application is inside (executing) the procedure.



**asynchronous** A procedure is called asynchronous if progress towards completion may be achieved after the procedure exits.



Please note that some of the semantic terms are not exclusive. Some of them do overlap. According to the definition, a collective procedure may also be a local procedure. Furthermore, a blocking procedure is per definition also a synchronous procedure; the reverse statement is not true.

# 2.4 Examples

The examples in this document are for illustration purposes only. They are not intended to specify the semantics.

# 3 Gaspi concepts

#### 3.1 Introduction and overview

In this section, the basic Gaspi concepts are introduced. A more detailed description with the corresponding procedure specifications can be found in the subsequent topic-specific sections.

Gaspi is a communication API that implements a Partitioned Global Address Space (PGAS) model. Each Gaspi process may host parts (called segments) of the global address space. A local segment can be accessed with standard load/store operations and remote segments can be accessed by every thread of every Gaspi process using the Gaspi read and write operations.

Gaspi was designed with remote direct memory access (RDMA) in mind. A network infrastructure that supports RDMA guarantees asynchronous and one-sided communication operations without involving the CPU. This is one of the

main requirements for high scalability which results from interference free communication, e. g. from overlapping communication with computation.

#### 3.2 Gaspi processes

GASPI has the concept of ranks. Each GASPI process receives a unique rank that identifies it during its runtime.

#### 3.3 Gaspi groups

A group is a subset of all processes. The group members have common collective operations. A collective operation is then restricted to the processes forming the group.

#### 3.4 Gaspi segments

Modern hardware typically involves a hierarchy of memory with respect to the bandwidth and latencies of read and write accesses. Within that hierarchy are non-uniform memory access (NUMA) partitions, solid state devices (SSDs), graphical processing unit (GPU) memory or many integrated cores (MIC) memory. The Gaspi memory segments are supposed to map this variety of hardware layers to the software layer. In the spirit of the PGAS approach, these Gaspi segments may be globally accessible from every thread of every Gaspi process. Gaspi segments can also be used to leverage different memory models within a single application or to even run different applications in a single Partitioned Global Address Space.

#### 3.5 Gaspi one-sided communication

One-sided asynchronous communication is the basic communication mechanism provided by Gaspi. The one-sided communication comes in two flavors. There are read and write operations from and into the Partitioned Global Address Space. These operations are non-blocking and asynchronous, allowing the program to continue its execution along the data transfer. The actual data transfer is managed by the underlying network infrastructure.

#### 3.6 Gaspi queues

Gaspi offers the possibility to use different queues to handle the communication requests. The requests can be submitted to one of the supported queues. These queues allow more scalability and can be used as channels for different types of requests where similar types of requests are queued and then get synchronised together but independently from the other ones (separation of concerns). The specification guarantees fairness of transfers posted to different queues, i. e. no queue should see its communication requests delayed indefinitely.

Listing 1: Allgather with one-sided writes.

```
let nProc be the number of processes;
   let iProc be the unique id of this process;
   let src be the data to be distributed;
   let dst be an array storing the destination addresses;
   foreach process p in [0,nProc):
     write src into dst[p][iProc];
     //
     //
                     remote address if p != iProc
10
   wait for the completion of the writes;
11
12
   barrier;
13
   // the writes of all processes are completed
```

# 3.7 Gaspi passive communication

Passive communication has a two-sided semantic, where there is a matching receive operation to a send request. Passive communication aims at communication patterns where the sender is unknown (i. e. it can be any process from the receiver perspective) but there is potentially the need for synchronisation between different processes.

The receive operation is a blocking call that has as low interference as possible (e.g. consumes no CPU cycles) and is ideally woken up by the network layer. This passive communication allows for fair distributed updates of globally shared parts of data.

# 3.8 Gaspi global atomics

Gaspi provides atomic operations for integral types, i. e. such variables can be manipulated atomically without fear of preemption causing corruption. There are two basic atomic operations: fetch\_and\_add and compare\_and\_swap. The values can be used as global shared variables and to synchronise processes or events.

The specification guarantees fairness, i.e. no process should see its atomic operation delayed indefinitely.

Listing 2: Dynamic work distribution: Clients atomically fetch a packet id and increment the value.

```
do
do
f
packet := fetch_and_add (1);
// increment the value by one, return the old value

if (packet < packet_max): process (packet);</pre>
```

```
7 | }
8 | while (packet < packet_max);</pre>
```

#### 3.9 Gaspi timeouts

Failure tolerant parallel programs necessitate non-blocking communication calls. Hence, Gaspi provides a timeout mechanism for all potentially blocking procedures

Timeouts for procedures are specified in milliseconds. GASPI\_BLOCK is a predefined timeout value which blocks the procedure call until completion. This value should not be used in failure tolerant programs, as it can block for an indefinitely amount of time in case of an error.

GASPI\_TEST is another predefined timeout value which blocks the procedure for the shortest time possible, i. e. the time in which the procedure call processes an atomic portion of its work.

#### Examples:

Listing 3: Blocks until the communication queue is empty and may block indefinitely in case of a failure.

```
WAIT (..., GASPI_BLOCK);
```

Listing 4: Just check if the operation has completed and return as soon as possible.

```
WAIT (..., GASPI_TEST);
```

Listing 5: Blocks until the queue is empty or more than 10 milliseconds have passed since wait has been called.

```
WAIT (..., 10);
```

#### 3.10 Gaspi collective communication

Collective communication is communication which involves a group of GASPI processes. It is collective only for that group.

Collective operations can be either synchronous or asnychronous. Synchronous implies that progress is achieved only as long as the application is inside of the call. The call itself, however, may be interrupted by a timeout. The operation is then continued in the next call of the procedure. This implies that a collective operation may involve several procedure calls until completion.

Collective operations are exclusive per group, i.e. only one collective operation of a specific type can run at a given time for a given group. For example, two allreduce for one group cannot run at the same time; however, an allreduce operation and a barrier can run at the same time.

Implementor advice: Gaspi does not regulate whether individual collective operations should internally be handled synchronously or asynchronously, however: Gaspi aims at an efficient, low-overhead programming model. If asynchronous operation is supported, it should leverage external network-resources, rather than consuming CPU cycles.

Gaspi supports the following collective operations: barriers, reductions with predefined operations, reductions with user defined operations.

Collective operations have their own queue and hence typically will be synchronised independently from the operations on other queues (separation of concerns).

#### 3.11 Gaspi return values

Gaspi procedures have three general return values:

GASPI\_SUCCESS implies that the procedure has completed successfully.

GASPI\_TIMEOUT implies that the procedure could not complete in the given period of time. This does not necessitate an error. The procedure has to be invoked subsequently in order to fully complete the operation.

GASPI\_ERROR implies that the procedure has terminated due to an error. There are no predefined error values specifying the detailed cause of an error. gaspi\_error\_message translates the error code into a human readable format.

Implementor advice: An implementation may provide specific error values. All error codes in the range  $[-1, \ldots, -999]$  are reserved and must not be used. If there are predefined error codes, each of the return codes must have a corresponding error message.

Additionally, each process has a state vector that contains the health state for all processes. The state vector is set after non-local operations and can be used to detect failures on remote processes.

# 4 Gaspi definitions

# 4.1 Types

```
gaspi_rank_t
```

The Gaspi rank type.

```
gaspi_segment_id_t
```

The Gaspi memory segment ID type.

4.1 Types 15

```
gaspi_offset_t
The Gaspi offset type. Offsets are measured relative to the beginning of a mem-
ory segment in units of bytes.
gaspi_size_t
The Gaspi size type. Sizes are measured in units of bytes.
gaspi_queue_id_t
The Gaspi queue ID type.
gaspi_notification_t
The Gaspi notification type.
       Implementor advice: The sum of the sizes of gaspi_notification_
       t and gaspi_tag_t should be at most 8 bytes in order to allow for
       Infiniband specific optimizations.
gaspi_notification_id_t
The Gaspi notification ID type.
gaspi_tag_t
The Gaspi tag type. Tags are used to discriminate different messages in the
passive communication channel.
       Implementor advice: The sum of the sizes of gaspi_notification_
       t and gaspi_tag_t should be at most 8 bytes in order to allow for
       Infiniband specific optimizations.
gaspi_atomic_value_t
The Gaspi global atomic value type.
gaspi_return_t
The Gaspi return value type.
vector<gaspi_return_t>
gaspi_returns_t
```

The vector type with return codes for individual processes. The length of the

vector equals the number of processes in the Gaspi program.

gaspi\_timeout\_t

4.2 Constants

```
The Gaspi timeout type.
gaspi_number_t
A type that is used to count elements. That could be numbers of queues as well
as the size of individual queues.
gaspi_group_t
The Gaspi group type.
gaspi_pointer_t
A type that can point to some (area of) memory.
gaspi_const_pointer_t
A type that can point to some (area of) memory that cannot be modified using
this pointer.
gaspi_alloc_t
The Gaspi allocation policy type.
gaspi_network_t
The Gaspi network infrastructure type.
gaspi_bool_t
The Gaspi boolean type.
gaspi_string_t
The Gaspi string type.
gaspi_statistic_counter_t
The Gaspi statistic counter type.
4.2
      Constants
       Timeout values
4.2.1
GASPI_BLOCK
GASPI_BLOCK is a timeout value which blocks a procedure call until completion. \  \  \, \bot
GASPI_TEST
GASPI_TEST is a timeout value which blocks a procedure call for the shortest time
possible.
```

#### 4.2.2 Function return values

#### GASPI\_SUCCESS

GASPI SUCCESS is returned if a procedure call is completed successfully.

#### GASPI\_TIMEOUT

GASPI TIMEOUT is returned if a procedure call ran into a timeout.

#### GASPI\_ERROR

GASPI ERROR is returned if a procedure call finished with an error.

#### 4.2.3 State vector states

#### GASPI STATE HEALTHY

 $GASPI\_STATE\_HEALTHY \ implies \ that \ a \ remote \ Gaspi \ process \ is \ healthy \ and \ communication \ is \ possible.$ 

# GASPI STATE CORRUPT

 $GASPI\_STATE\_CORRUPT$  implies that the remote Gaspi process is corrupted and communication is impossible.

#### 4.2.4 Allocation policies

#### GASPI\_ALLOC\_DEFAULT

The GASPI\_ALLOC\_DEFAULT policy uses the operating systems default memory allocation policy.  $\ \, \Box$ 

Implementor advice: A GASPI implementation is free to provide additional allocation policies.

#### 4.2.5 Statistics interface

A Gaspi implementation is free to define constants of the type gaspi\_statistic\_counter\_t for specific statistics.

# 5 Execution model

#### 5.1 Introduction and overview

Gaspi allows both SPMD (Single Program, Multiple Data) and MPMD (Multiple Program, Multiple Data) style program execution. Hence, either a single

program or different programs can be started on the computational units. How a Gaspi application is started and initialized is implementation specific.

A rank is attributed to each created process. Ranks are a central aspect as they allow applications to identify processes and therefore allow to distribute work among the processes.

Furthermore, Gaspi provides segments. Segments are globally accessable memory regions. In general, the execution of a Gaspi process can be considered as split into several consecutive phases:

#### • Setup (optional)

Setting up configuration parameters Performing environment checks

#### • Initialization

Initialization of the runtime environment Creation of segments or groups (optional)

# • Working (optional)

Communication calls
Collective operations
Atomic operations

#### • Shutdown

Cleanup of communication infrastructure

In the **setup** phase, the application may retrieve and modify the GASPI configuration structure (see Section 5.2.1) determining the GASPI runtime behavior. Optionally (but advisable), the application can perform environment checks (see Section 13) to make sure the application can be started safely and correctly.

In the **initialization** phase, the Gaspi runtime environment is set up in accordance with the parameters of the configuration structure by invocation of the initialization procedure. The initialization procedure is called before any other functionality, with the exception of pre-initialization routines for environment checking and declaration and retrieval of configuration parameters. After the initialization routine has been called, an optional step to perform is the creation of one or more segments and the creation of one or more groups. Segments are contiguous blocks of memory that may be accessed globally by all processes and where global data should be placed.

After the initialization, the application can proceed with its **working** phase and use the functionalities of Gaspi (communication, collectives, atomic operations, etc.).

The application should call the **shutdown** procedure (see Section 5.3.4) before it is terminated so that all resources and the communication infrastructure is cleaned up.

The entire set of execution phases define the Gaspi life cycle. In principle, several life cycles can be invoked in one Gaspi program.

Calling a routine in an execution phase in which it is not supposed to be executed in results in undefined behavior.

# 5.2 Process configuration

#### 5.2.1 Gaspi configuration structure

The Gaspi configuration structure describes the configuration parameters which influence the Gaspi runtime behavior.

Please note, that for simplicity of notation this is a C-style definition. In bindings to other languages corresponding definitions will be used.

Listing 6: GASPI configuration structure.

```
typedef struct {
     // maximum number of groups
     gaspi_number_t
                         group_max;
     // maximum number of segments
     gaspi_number_t
                         segment_max
     // one-sided comm parameter
     gaspi_number_t queue_num;
10
     gaspi_number_t
                         queue_size_max;
     gaspi_size_t
                         transfer_size_max;
11
     // notification parameter
13
     gaspi_number_t
                         notification_num;
14
15
     // passive comm parameter
16
     gaspi_number_t
                         passive_queue_size_max;
17
     gaspi_size_t
                         passive_transfer_size_max;
18
     // collective comm parameter
     gaspi_size_t
                         allreduce_buf_size;
21
     gaspi_number_t
                         allreduce_elem_max;
22
23
     // network selection parameter
     gaspi_network_t
                         network;
25
26
     // communication infrastructure build up notification
27
                         build_infrastructure
     gaspi_bool_t
28
29
                         user_defined;
     void *
30
   } gaspi_configuration_t;
```

The definition of each of the configuration structure fields is as follows:

- **group\_max** the desired maximum number of permissible groups per process. There is a hardware/implementation dependent maximum.
- **segment\_max** the desired number of maximally permissible segments per Gaspi process. There is a hardware/implementation dependent maximum.
- **queue\_num** the desired number of one-sided communication queues to be created. There is a hardware/implementation dependent maximum.
- **queue\_size\_max** the desired number of simultaneously allowed on-going requests on a one-sided communication queue. There is a hardware/implementation dependent maximum.
- transfer\_size\_max the desired maximum size of a single data transfer in the one-sided communication channel. There is a hardware/implementation dependent maximum.
- **notification**\_num the desired number of internal notification buffers for weak synchronisation to be created. There is a hardware/implementation dependent maximum.
- passive\_queue\_size\_max the desired number of simultaneously allowed on-going requests on the passive communication queue. There is a hardware/implementation dependent maximum.
- passive transfer size max the desired maximum size of a single data transfer in the passive communication channel. There is a hardware/implementation dependent maximum.
- allreduce\_elem\_max the maximum number of elements in gaspi\_allreduce. There is a hardware/implementation dependent maximum.
- allreduce\_buf\_size the size of the internal buffer of gaspi\_allreduce\_user.

  There is a hardware/implementation dependent maximum.
- **network** the network type to be used.
- build <u>infrastructure</u> boolean to set whether the communication infrastructure should be built up at startup time. The default value is true.

The default configuration structure can be retrieved by gaspi\_config\_get. Its default values are implementation dependent. If some of the parameters are externally set by the program and assigned with gaspi\_config\_set, the requested values are just proposals. Depending on the underlying hardware capabilities, the implementation is allowed to overrule these proposals. gaspi\_config\_set has to be used in order to commit modifications of the configuration structure before the initialization routine is invoked. The actual values of the parameters can be retrieved by the corresponding Gaspi getter routines (see section 12) after the successful program initialization. The values of the configuration structure parameters need to be the same on all Gaspi processes.

The user has the possibility to set the values on her own or leave the default values. Each field (where applicable) also has a maximum value to avoid user errors that might lead to too much instability or scalability problems (for example, the number of queues).

#### 5.2.2 gaspi\_config\_get

The gaspi\_config\_get procedure is a *synchronous local blocking* procedure which retrieves the default configuration structure.

```
GASPI_CONFIG_GET ( config )
```

Parameter:

(out) config: the default configuration

```
gaspi_return_t
gaspi_config_get ( gaspi_configuration_t *config )
```

```
gaspi_config_get ( config ) BIND(C)
  TYPE(gaspi_configuration_t), INTENT(OUT) :: config
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Setup

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value GASPI\_SUCCESS, config represents the default configuration.

In case of error, the return value is GASPI\_ERROR.

#### 5.2.3 gaspi\_config\_set

The gaspi\_config\_set procedure is a *synchronous local blocking* procedure which sets the configuration structure for process initialization.

```
GASPI_CONFIG_SET ( config )
```

Parameter:

(in) config: the configuration structure to be set

```
gaspi_return_t
gaspi_config_set ( gaspi_configuration_t const *config )

gaspi_config_set ( config ) BIND(C)
   TYPE(gaspi_configuration_t), INTENT(IN) :: config
   TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Setup

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the runtime parameters for the GASPI process initialization are set in accordance with parameters of *config*.

In case of error, the return value is GASPI\_ERROR.

# 5.3 Process management calls

#### 5.3.1 gaspi\_proc\_init

gaspi\_proc\_init implements the Gaspi initialization of the application. It is a non-local synchronous time-based blocking procedure.

Parameter:

- (in) config: the configuration to be used
- (in) timeout: the timeout

```
gaspi_config_set ( config ) BIND(C)
  TYPE(gaspi_configuration_t), INTENT(IN) :: config
  TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

#### Initialization

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

The explicit start of a Gaspi process or launch from command line is not specified. This is implementation dependent.

However, it is anticipated that gaspi\_proc\_init has information about the list of hosts on which the entire Gaspi application is running either by environment variables, a command line argument, a daemon or some other mechanism. The actual transfer of knowledge is implementation dependent.

gaspi\_proc\_init registers a given process at the other remote Gaspi processes and sets the corresponding entries in the state vector to a healthy state. If the parameter <code>build\_infrastructure</code> in the configuration structure is set, also the communication infrastructure for passive and one-sided communication to all of the other processes is setup. Otherwise, there is no set up of communication infrastructure during the initialization. A rank is assigned to the given Gaspi process in accordance with the position of the host in the list. The Gaspi process running on the first host in the list has rank zero. The Gaspi process running on the second host in the list has rank one and so on.

In case of a node failure, a Gaspi process can be started on a new host, freshly allocated or selected from a set of pre-allocated spare hosts, by providing the list of machines in which the failed node is substituted by the new host. The new Gaspi process then has the rank of the Gaspi process which has been running on the failed node.

In case of the subsequent start of additional Gaspi processes, the newly started Gaspi process registers with the other remote Gaspi processes. Note, that a subsequent change of the number of running Gaspi processes invalidates Gaspi\_GROUP\_ALL for the old running processes. Also the return value of gaspi\_proc\_num is changed.

The configuration structure should be created by the application before passing it to the gaspi\_proc\_init procedure.

After successful procedure completion, gaspi\_proc\_init returns GASPI\_SUCCESS and it guarantees that the application has been started on all hosts. In case that the *build\_infrastructure* is set, return value GASPI\_SUCCESS also implies that the communication infrastructure is up and ready to be used.

In case the application could not be initialized in line with the timeout parameter, the return value is GASPI\_TIMEOUT. The application has not been initialized yet. A subsequent invocation is required to completely initialize the application.

In case of error, the return value is GASPI\_ERROR. The application is not initialized.

In case of the return value GASPI\_TIMEOUT or GASPI\_ERROR, a check of the state vector by invocation of gaspi\_state\_vec\_get gives information about whether the involved remote GASPI processes are healthy or whether they are corrupted.

Implementor advice: Calling gaspi\_proc\_init with an enabled parameter build\_infrastructure is semantically equivalent to calling gaspi\_proc\_init with a disabled parameter build\_infrastructure and subsequent calls to gaspi\_connect in which an all-to-all connection is established.

User advice: For resource critical applications, it is recommended to disable the parameter  $build\_infrastructure$  in the configuration structure.

User advice: Adjusting the passed list of hosts yields the possibility to take into account the topology of the network.

User advice: A successful procedure completion does not mean that any communication or collective operation can already be used. Connections might need to be established. A segment has to be allocated for passive communication capabilities. If one-sided communication is supposed to be used, than the segment has to registered in addition. If collective operations are needed, a group has to be created and committed. Only global atomic operations are feasible right from the beginning.

#### 5.3.2 gaspi\_proc\_num

The total number of GASPI processes started, can be retrieved by gaspi\_proc\_num. This is a *local synchronous blocking* procedure.

```
GASPI_PROC_NUM ( proc_num )
```

Parameter:

(out) proc num: the total number of Gaspi processes

```
gaspi_return_t
gaspi_proc_num ( gaspi_rank_t *proc_num )
```

```
gaspi_proc_num ( proc_num ) BIND(C)
  TYPE(gaspi_rank_t), INTENT(OUT) :: proc_num
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

If successful, the return value is GASPI\_SUCCESS and gaspi\_proc\_num retrieves the total number of processes that have been initialized and places this number in the  $proc\ num$ .

In case of error, the return value is  $GASPI\_ERROR$  and the value of  $proc\_num$  is undefined.

#### 5.3.3 gaspi\_proc\_rank

A rank identifies a Gaspi process. The rank of a process lies in the interval [0, P) where P can be retrieved through  $\texttt{gaspi\_proc\_num}$ . Each process has a unique rank associated with it. The rank of the invoking Gaspi process can be retrieved by  $\texttt{gaspi\_proc\_rank}$ . It is a  $local\ synchronous\ blocking\ procedure$ .

```
GASPI_PROC_RANK ( rank )
```

Parameter:

(out) rank: the rank of the calling GASPI process.

```
gaspi_return_t
gaspi_proc_rank ( gaspi_rank_t *rank )
```

```
gaspi_proc_rank ( rank ) BIND(C)
  TYPE(gaspi_rank_t), INTENT(OUT) :: rank
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

 ${\tt gaspi\_proc\_rank}$  retrieves, if successful, the rank of the calling process, placing it in the parameter rank and returning GASPI\_SUCCESS.

In case of error, the return value is  ${\tt GASPI\_ERROR}$  and the value of the rank is undefined.

# 5.3.4 gaspi\_proc\_term

The shutdown procedure gaspi\_proc\_term is a synchronous non-local time-based blocking operation that releases resources and performs the required clean-

up. There is no definition in the specification of a verification of a healthy global state (i. e. all processes terminated correctly).

After a shutdown call on a given Gaspi process, it is undefined behavior if another Gaspi process tries to use any non-local Gaspi functionality involving that process.

```
GASPI_PROC_TERM ( timeout )

Parameter:
(in) timeout: the timeout

gaspi_return_t
gaspi_proc_term ( gaspi_timeout_t timeout )

gaspi_proc_term ( timeout ) BIND(C)
```

Execution phase:

Shutdown

Return values:

GASPI\_SUCCESS: operation has returned successfully

TYPE(gaspi\_timeout\_t), INTENT(IN) :: timeout
TYPE(gaspi\_return\_t), INTENT(OUT) :: ireturn

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

In case of successful procedure completion, i.e. return value GASPI\_SUCCESS, the allocated GASPI specific resources of the invoking GASPI process have been released. That means in particular that the communication infrastructure is shut down, all committed groups are released and all allocated segments are freed.

In case of timeout, i. e. return value GASPI\_TIMEOUT, the local resources of the invoking GASPI process could not be completely released in the given period of time. A subsequent invocation is required to completely release all of the resources.

In case of error, i. e. return value GASPI\_ERROR, the resources of the local GASPI process could not be released. The process is in an undefined state.

#### 5.3.5 gaspi\_proc\_kill

gaspi\_proc\_kill sends an interrupt signal to a given GASPI process. It is a synchronous non-local time-based blocking procedure.

Parameter:

- (in) rank: the rank of the process to be killed
- (in) timeout: the timeout

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_proc\_kill sends an interrupt signal to the Gaspi process incorporating the rank given by parameter rank. This can be used, for example, to realise the registration of a user defined signal handler function which ensures the controlled shut down of an entire Gaspi application at the global level if the application receives an interrupt signal (STRG + C) in the interactive master process. Every Gaspi application should register such or a similar signal handler (c. f. listing 8).

In case of successful procedure completion, i. e. return value GASPI\_SUCCESS, the remote GASPI process has been terminated.

In case of timeout, i.e. return value GASPI\_TIMEOUT, the remote GASPI process could not be terminated in the given time. A subsequent invocation of the procedure is needed in order to complete the operation.

In case of error, i. e. return value GASPI\_ERROR, the state of the remote GASPI process is undefined.

User advice: The kill signal terminates a Gaspi process in an uncontrolled way. In this case, in order to provide a clean shutdown, it is advisable to register a user defined signal callback function which guarantees a clean shutdown.

#### 5.3.6 Example

The listing 7 shows a Gaspi "Hello world" example. Please note that this example does not deal with failures.

Listing 7: Gaspi hello world example.

```
#include <stdio.h>
   #include <stdlib.h>
   #include <GASPI.h>
   int
   main (int argc, char *argv[])
6
   {
7
     gaspi_proc_init (GASPI_BLOCK);
     gaspi_rank_t iProc = GASPI_NORANK;
10
     gaspi_rank_t nProc = GASPI_NORANK;
11
12
     gaspi_proc_rank (&iProc);
     gaspi_proc_num (&nProc);
14
1.5
     printf ("Hello world from rank %i of %i!\n", iProc, nProc);
16
17
     gaspi_proc_term (GASPI_BLOCK);
18
19
     return EXIT_SUCCESS;
20
   }
21
```

The listing 8 shows the registration of a user defined signal handler function which ensures the controlled shut down of an entire Gaspi application at the global level if the application receives an interrupt signal (STRG + C) in the interactive master process. Every Gaspi application should register such or a similar signal handler.

Listing 8: Signal handling.

```
#include <signal.h>
   #include <stdlib.h>
   #include <GASPI.h>
   void
   signalHandler (int sigint)
6
   {
7
     gaspi_rank_t iProc = GASPI_NORANK;
     gaspi_rank_t nProc = GASPI_NORANK;
10
     gaspi_proc_rank (&iProc);
11
     gaspi_proc_num (&nProc);
12
13
     if (0 == iProc)
14
       {
1.5
```

```
for (iProc = 1; iProc < nProc; ++iProc)</pre>
16
               gaspi_proc_kill (iProc, GASPI_BLOCK);
18
19
        }
20
21
      gaspi_proc_term (GASPI_BLOCK);
22
23
      exit (EXIT_FAILURE);
^{24}
   }
25
26
27
28
   int
   main (int argc, char *argv[])
29
30
      gaspi_proc_init (GASPI_BLOCK);
31
32
      signal (SIGINT, &signalHandler);
33
34
      /* working phase */
35
36
      gaspi_proc_term (GASPI_BLOCK);
37
38
      return EXIT_SUCCESS;
39
   }
40
```

# 5.4 Connection management utilities

#### 5.4.1 gaspi\_connect

In order to be able to communicate between two GASPI processes, the communication infrastructure has to be established. This is achieved with the *synchronous non-local time-based blocking* procedure gaspi\_connect. It is bound to the working phase of the GASPI life cycle.

```
GASPI_CONNECT ( rank
           , timeout )
```

Parameter:

(in) rank: the remote rank with which the communication infrastructure is established

(in) timeout: The timeout for the operation

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_connect builds up the communication infrastructure, passive as well as one-sided, between the local and the remote Gaspi process representing rank rank. The connection is bi-directional, i.e. it is sufficient that gaspi\_connect is invoked by only one of the connection partners.

In case of successful procedure completion, i. e. return value GASPI\_SUCCESS, the communication infrastructure is established. If there is an allocated segment, the segment can be used as a destination for passive communication between the two nodes. In case the connection has already been established, e.g. by the connection partner, the return value is GASPI\_SUCCESS.

In case of return value GASPI\_TIMEOUT, the communication infrastructure could not be established between the local Gaspi process and the remote Gaspi process in the given period of time.

In case of return value GASPI\_ERROR, the communication infrastructure could not be established between the local GASPI process and the remote GASPI process.

In case of the latter two return values, a check of the state vector by invocation of gaspi\_state\_vec\_get gives information on whether the remote Gaspi process is still healthy.

User advice: Under the assumption that the GASPI process is initialized with parameter build\_infrastructure set to true, all the connections are set up at initialization time. Hence, a subsequent call to gaspi\_connect is superfluous in this case.

# 5.4.2 gaspi\_disconnect

The gaspi\_disconnect procedure is a *synchronous local blocking* procedure which disconnects a given process, identified by its rank, and frees all associated ressources.

It is bound to the working phase of the Gaspi life cycle.

#### Parameter:

(in) rank: the remote rank from which the communication infrastructure is disconnected

(in) timeout: The timeout for the operation

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_disconnect disconnects the communication infrastructure, passive as well as one-sided, between the local and the remote GASPI process representing rank rank. The connection is bi-directional, i.e. it is sufficient if gaspi\_disconnect is invoked by only one of the connection partners.

In case of successful procedure completion, i. e. return value GASPI\_SUCCESS, the communication infrastructure is disconnected. Associated resources are freed on the local as well as on the remote side. In case the connection has already been disconnected, e. g. by the connection partner, the return value is GASPI\_SUCCESS.

In case of error the return value is GASPI\_ERROR.

In case of return value GASPI\_TIMEOUT, the connection between the local GASPI process and the remote GASPI process could not be disconnected in the given period of time.

In case of the latter two return values local resources are freed and a check of the state vector by invocation of <code>gaspi\_state\_vec\_get</code> gives information whether the remote Gaspi process is still healthy.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the connection is disconnected and can no longer be used.

# 5.5 State vector for individual processes

#### 5.5.1 Introduction

A necessary pre-condition for realising a failure tolerant code is a detailed knowledge about the state of the communication partners of each local GASPI process.

Gaspi provides a predefined type to describe the state of a remote Gaspi process, which is the gaspi\_state\_t type. gaspi\_state\_t can have one of two values:

GASPI\_STATE\_HEALTHY implies that the remote Gaspi process is healthy, i. e. communication is possible.

GASPI\_STATE\_CORRUPT means that the remote Gaspi process is corrupted, i. e. there is no communication possible.

```
typedef vector<gaspi_state_t> gaspi_state_vector_t
```

gaspi\_state\_vector\_t is a vector with state information for individual processes. The length of the vector equals the number of processes in the GASPI program and the entries are ordered based on the process ranks, i.e. entry 0 of the vector represents the state of process with the rank 0.

There are procedures to query the state of the communication partners after a given communication request and also to reset the state after successful recovery. These are described in the following subsections.

The state vector does not provide a global view, instead each process has its own state vector that may be different to the state vector of another process.

```
5.5.2 gaspi_state_vec_get
```

The state vector is obtained by the *local synchronous blocking* function gaspi\_state\_vec\_get.

The state vector represents the states of all Gaspi processes.

```
GASPI_STATE_VEC_GET ( state_vector )
```

Parameter:

(out) returns: the vector with individual return codes

```
gaspi_return_t
gaspi_state_vec_get ( gaspi_state_vector_t *state_vector )
```

```
gaspi_state_vec_get ( state_vector ) BIND(C)
  TYPE(gaspi_state_vector_t), INTENT(OUT) :: state_vector
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

The state vector has one entry for each rank. It is initialized during gaspi\_proc\_init. It is updated after each of the following operations

- process management
  - gaspi\_proc\_init
- group commitment
  - gaspi\_group\_commit
- segment registration
  - gaspi\_segment\_register
- one-sided communication
  - gaspi\_wait
- collective operations
  - gaspi\_barrier
  - gaspi\_allreduce
  - gaspi\_allreduce\_user
- ullet global atomic operations
  - gaspi\_atomic\_fetch\_and\_add
  - gaspi\_atomic\_compare\_swap

An update is not guaranteed to update all entries in the state vector, but may only update the entries of the direct communication partners. <code>gaspi\_state\_vec\_get</code> retrieves in case of successful completion, i. e. return value <code>GASPI\_SUCCESS</code>, the state vector. It contains the states of the <code>GASPI</code> processes with which the local process has been communicating. All other entries are unmodified.

In case of error, the return value is GASPI\_ERROR and the value of the state vector is undefined.

User advice: For failure tolerant code, the state vector should be checked after each of the above procedure calls in case they return with either return value GASPI\_ERROR or GASPI\_TIMEOUT.

# 5.6 MPI Interoperability

Gaspi aims at providing interoperability with MPI in order to allow for incremental porting of such applications.

The startup of mixed MPI and Gaspi code is achieved by invoking gaspi\_proc\_init in an existing MPI program. This way, MPI takes care of distributing and starting the binary and Gaspi just takes care of setting up its internal infrastructure.

Gaspi and MPI communication should not occur at the same time, i. e. only the program layout given in Listing 9 is supported

Listing 9: Embedded Gaspi program

```
mpi_startup;
2
   /* MPI part, no ongoing GASPI communication... */
   /* ...finish all ongoing MPI communication */
5
   mpi_barrier;
   /* no ongoing MPI communication */
9
10
   gaspi_proc_init;
11
12
   while (!done) {
13
14
     /* GASPI part, no ongoing MPI communication... */
15
16
     /* ...finish all ongoing GASPI communication */
17
18
     gaspi_barrier;
20
     /* MPI part, no ongoing GASPI communication... */
21
22
     /* ...finish all ongoing MPI communication */
23
^{24}
     mpi_barrier;
25
   }
26
27
   gaspi_proc_term;
28
29
   /* MPI part, no ongoing GASPI communication */
30
31
   mpi_shutdown;
32
```

# 5.7 Argument checks and performance

GASPI aims at high performance and does not provide any argument checks at procedure invocation per default.

Implementor advice: The implementation should provide a specific library which includes argument checks. The Gaspi procedures should include out of bounds checks, there.

# 6 Groups

#### 6.1 Introduction

Groups are subsets of the total number of Gaspi processes. The group members have common collective operations. Each Gaspi process may participate in more than one group.

The use-cases are the collective operations provided in section 11 that make sense to be performed only for a subset of GASPI processes in order to avoid a complete (all processes) collective synchronisation point.

A group has to be defined and declared in each of the participating Gaspi processes. Defining a group is a two step procedure. An empty group has to be created first. Then the participating Gaspi processes, represented by their ranks, have to be attached. The group definition is a local operation. In order to activate the group, the group has to be committed by each of the participating Gaspi processes. This is a collective operation for the group. Only after successful group commitment the group can be used for collective operations.

The maximum number of groups allowed per GASPI process is restricted by the implementation. A desired value can be passed to gaspi\_proc\_init by the configuration structure.

In case one group disappears due to some failure, the group has to be reestablished. If there is a new process replacing the failed one, the group has to be defined and declared on the newly started Gaspi process(es). Reestablishment of the group is then achieved by recommitment of the group by the Gaspi processes which were still 'alive' (functioning) and by the commitment of the group by the newly started Gaspi process.

# 6.2 Gaspi group generics

# 6.2.1 Gaspi group type

Groups are specified with a special group type gaspi\_group\_t.

#### 6.2.2 GASPI\_GROUP\_ALL

GASPI\_GROUP\_ALL is a predefined default group that corresponds to the whole set of Gaspi processes. This is to be used for collective operations that work for the whole system.

```
gaspi_group_t GASPI_GROUP_ALL;
```

User advice: Note that GASPI\_GROUP\_ALL is a group definition like any other sub group. In order to be used, GASPI\_GROUP\_ALL also has to be committed by gaspi\_group\_commit.

# 6.3 Group creation

## 6.3.1 gaspi\_group\_create

The gaspi\_group\_create procedure is a *synchronous local blocking* procedure which creates an empty group.

```
GASPI_GROUP_CREATE ( group )
```

Parameter:

(out) group: the created empty group

```
gaspi_return_t
gaspi_group_create ( gaspi_group_t *group )
```

```
gaspi_group_create ( group ) BIND(C)
  TYPE(gaspi_group_t), INTENT(OUT) :: group
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value <code>GASPI\_SUCCESS</code>, group represents an empty group without any members.

In case of error, the return value is GASPI\_ERROR.

## 6.3.2 gaspi\_group\_add

The gaspi\_group\_add procedure is a *synchronous local blocking* procedure which adds a given rank to an existing group.

```
GASPI_GROUP_ADD ( group )
```

Parameter:

(inout) group: the group to which the rank is added

(in) rank: the rank to add to the group

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the GASPI process with rank is added to group.

In case of error, the return value is GASPI\_ERROR.

## 6.3.3 gaspi\_group\_commit

The gaspi\_group\_commit procedure is a synchronous collective time-based blocking procedure which establishes a group.

- (in) group: the group to commit
- (in) timeout: the timeout

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the group given by the parameter *group* is established. Collective operations invoked by the members of the group are allowed from this moment on.

In case of timeout, i.e. return value GASPI\_TIMEOUT, the group could not be established on all ranks forming the group in the given period of time. The group is in an undefined state and collective operations on the group yield undefined behavior. A subsequent invocation is required in order to completely establish the group.

In case of error, i.e. return value GASPI\_ERROR, the group could not be established. The group is in an undefined state and collective operations defined on the given group yield undefined behavior.

In both cases, GASPI\_TIMEOUT and GASPI\_ERROR, the GASPI state vector should be checked in order to eliminate the possibility of a failure.

User advice: Any group commit should be performed only by a single thread of a process. If two Gaspi processes are members of two groups, then the order of the group commits should be the same on both processes in order to avoid deadlocks.

Implementor advice: If the parameter build\_infrastructure is not set, the procedure gaspi\_group\_commit must set up the infrastructure for all possible operations of the group.

## 6.4 Group deletion

#### 6.4.1 gaspi\_group\_delete

The gaspi\_group\_delete procedure is a *synchronous local blocking* procedure which deletes a given group.

```
GASPI_GROUP_DELETE ( group )
```

Parameter:

(in) group: the group to be deleted

```
gaspi_return_t
gaspi_group_delete ( gaspi_group_t group )
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value  $GASPI\_SUCCESS$ , group is deleted and cannot be used further.

In case of error, the return value is GASPI\_ERROR.

Implementor advice: If the parameter build\_infrastructure is not set to true, the procedure gaspi\_group\_delete must disconnect all connections which have been set up in the call to gaspi\_group\_commit and free all associated resources.

## 6.5 Group utilities

## 6.5.1 gaspi\_group\_num

The gaspi\_group\_num procedure is a *synchronous local blocking* procedure which returns the current number of allocated groups.

```
GASPI_GROUP_NUM ( group_num )
```

Parameter:

(out) group num: the current number of groups

```
gaspi_return_t
gaspi_group_num ( gaspi_number_t *group_num )
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS,  $group\_num$  contains the current number of allocated groups. The value of  $group\_num$  is related to the parameter  $group\_max$  in the configuration structure and cannot exceed that value. The value can be implementation specific.

#### 6.5.2 gaspi\_group\_size

The gaspi\_group\_size procedure is a *synchronous local blocking* procedure which returns the number of ranks of a given group.

Parameter:

(in) group: the group to be examined

(out) group size: the number of ranks in a given group

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, group size contains the number of GASPI processes forming the group.

In case of error, the return value is GASPI\_ERROR. The parameter  $group\_size$  has an undefined value.

#### 6.5.3 gaspi\_group\_ranks

The gaspi\_group\_ranks procedure is a *synchronous local blocking* procedure which returns a list of ranks of Gaspi processes forming the group.

Parameter:

(in) group: the group to be examined

(out) group\_ranks: the list of ranks forming the group

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value GASPI\_SUCCESS, the list  $group\_ranks$  contains the ranks of the processes that belong to the group. The list is not allocated by the procedure. The list allocation is supposed to be done outside of the procedure. The size of the list can be inquired by gaspi\_group\_size.

In case of error, the return value is GASPI\_ERROR. The list  $group\_ranks$  has an undefined value.

# 7 Gaspi segments

#### 7.1 Introduction and overview

Modern hardware has an entire memory hierarchy concerning the bandwidth and latencies of read and write accesses. Among them are non-uniform memory access (NUMA) partitions, solid state devices (SSDs), graphical processing unit (GPU) memory or many integrated cores (MIC) memory.

The Gaspi memory segments are thus an abstraction representing any kind of memory level, mapping the variety of hardware layers to the software layer. A segment is a contiguous block of virtual memory. In the spirit of the PGAS approach, these Gaspi segments may be globally accessible from every thread of every Gaspi process and represent the partitions of the global address space.

By means of the Gaspi memory segments it is also possible for multiple memory models or indeed multiple applications to share a single Partitioned Global Address Space.

Since segment allocation is expensive and the total number of supported segments is limited due to hardware constraints, the Gaspi memory management paradigm is the following. Gaspi provides only a few relatively large segments. Allocations inside of the pre-allocated segment memory are managed by the application.

Every Gaspi process may possess a certain number of segments (not necessarily equal to the number possessed by the other ranks) that may be accessed as common memory, whether is local—with normal memory operations—or remote—with the communication routines of Gaspi.

In order to use a segment for communication between two processes, some setup steps are required in general.

A memory segment has to be allocated in each of the processes by the local

procedure gaspi\_segment\_alloc. In order to also use the segments for one-sided communication, the memory segment has to be registered on the remote process which will access the memory segment at some point. This is achieved by the *non-local* procedure gaspi\_segment\_register.

User advice: If the parameter build\_infrastructure is not set, a connection has to be established between the processes before the segment can be registered at the remote process. This is accomplished by calling the procedure gaspi\_connect.

gaspi\_segment\_create unites these steps into a single *collective* procedure for an entire group. After successful procedure completion, a common segment is created on each Gaspi process forming the group which can be immediately used for communication among the group members.

During the lifetime of an application there is no segment available unless it is explicitly created with gaspi\_segment\_alloc or gaspi\_segment\_create after the GASPI startup.

## 7.2 Segment creation

## 7.2.1 gaspi\_segment\_alloc

The *synchronous local blocking* procedure gaspi\_segment\_alloc allocates a memory segment and optionally maps it in accordance with a given allocation policy.

- (in) segment\_id: The segment ID to be created. The segment IDs need to be unique on each Gaspi process
- (in) size: The size of the segment in bytes
- (in) alloc\_policy: allocation policy

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

gaspi\_segment\_alloc allocates a segment of size size that will be referenced by the segment\_id identifier. This identifier parameter has to be unique in the local GASPI process. Creating a new segment with an existing segment ID results in undefined behavior. Note that the total number of segments is restricted by the underlying hardware capabilities. The maximum number of supported segments can be retrieved by invoking gaspi\_segment\_max. The alloc\_policy is used to pass an allocation policy. The default allocation policy behavior is left to the implementation.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the segment can be accessed locally. In case that there is a connection established to a remote GASPI process, it can also be used for passive communication between the two GASPI processes. (Note that this is always the case if the process has been initialized with the parameter <code>build\_infrastructure</code> set to <code>true</code>), it can also be used for passive communication between the two GASPI processes; either as a source segment for <code>gaspi\_passive\_send</code> or as a destination segment for <code>gaspi\_passive\_receive</code>.

A return value GASPI\_ERROR indicates that the segment allocation failed. The segment cannot be used locally or for passive communication.

Implementor advice: In case of non-uniform memory access architectures, the memory should be allocated close to the calling process. The allocation policy of the calling process should not be modified.

## 7.2.2 gaspi\_segment\_register

In order to be used in a one-sided communication request on an existing connection, a segment allocated by gaspi\_segment\_alloc needs to be made visible and accessible for the other Gaspi processes. This is accomplished by the procedure gaspi\_segment\_register. It is a synchronous non-local time-based blocking procedure.

#### Parameter:

- (in) segment\_id: The segment ID to be registered. The segment ID's need to be unique for each GASPI process
- (in) rank: The rank of the GASPI process which should register the new segment
- (in) timeout: The timeout for the operation

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_segment\_register makes the segment referenced by the segment\_id identifier visible and accessible to the Gaspi process with the associated rank.

User advice: If the parameter build\_infrastructure is not set, a connection has to be established between the processes before the segment can be registered at the remote process. This is accomplished calling the procedure gaspi\_connect.

In case of successful procedure completion, i.e. return value GASPI\_SUCCESS, the local segment can be used for one-sided communication requests which are invoked by the given remote process.

In case of return value GASPI\_TIMEOUT, the segment could not be registered in the given period of time. The segment cannot be used for one-sided communication requests which are invoked by the given remote process. A subsequent call of gaspi\_segment\_register has to be invoked in order to complete the registration request.

In case of return value GASPI\_ERROR, the segment could not be registered on the remote side. The segment cannot be used for one-sided communication requests which are invoked by the given remote process.

In case of the latter two return values, a check of the state vector by invocation of gaspi\_state\_vec\_get gives information as to whether or not the remote GASPI process is still healthy.

*User advice:* Note that a local return value GASPI\_SUCCESS does not imply that the remote process is informed explicitly that the segment is accessible. This can be achieved through an explicit synchronisation, either by one of the collective operations or by an explicit notification.  $\Box$ 

#### 7.2.3 gaspi\_segment\_create

gaspi\_segment\_create is a synchronous collective time-based blocking procedure. It is semantically equivalent to a collective aggregation of gaspi\_segment\_alloc, gaspi\_segment\_register and gaspi\_barrier involving all of the members of a given group. If the communication infrastructure was not established for all group members beforehand, gaspi\_segment\_create will accomplish this as well.

- (in) segment\_id: The ID for the segment to be created. The segment ID's need to be unique for each GASPI process
- (in) size: The size of the segment in bytes
- (in) group: The group which should create the segment
- (in) timeout: The timeout for the operation
- (in) alloc policy: allocation policy

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully GASPI\_TIMEOUT: operation has run into a timeout GASPI\_ERROR: operation has finished with an error

gaspi\_segment\_create allocates a segment of size size that will be referenced by the segment\_id identifier. This identifier parameter has to be unique on the local Gaspi process. Creating a new segment with an existing segment ID results in undefined behavior. gaspi\_segment\_create makes the segment referenced by the segment\_id identifier visible and accessible to all of the Gaspi processes forming the group group. The maximum number of supported segments can be retrieved by invoking gaspi\_segment\_max. The alloc\_policy is used to pass an allocation policy. The default allocation policy behavior is left to the implementation.

After successful procedure completion, i.e. GASPI\_SUCCESS, the segment can be accessed locally and it can be used as a destination for the passive communication channel. Either as a source segment for gaspi\_passive\_send or as a destination segment for gaspi\_passive\_receive. Furthermore, it can be used for one-sided communication requests, which are invoked by the remote processes forming the group group. The segment segment\_id is ready to be used.

For consistency and programs with hard failure tolerance requirements, the operation must be performed within *timeout* milliseconds. In case of return value GASPI\_TIMEOUT, progress has been achieved, however the operation could not be completed in the given timeout. The segment cannot be used locally or for passive communication. Furthermore, the segment cannot be used for one-sided communication requests which are invoked by the other remote processes forming the group. A subsequent call of gaspi\_segment\_create has to be invoked in order to complete the segment creation.

In case of return value GASPI\_ERROR, the segment creation failed in one of the above progress steps on at least one of the involved GASPI processes. The segment cannot be used locally or for passive communication. Furthermore, the segment cannot be used for one-sided communication requests which are invoked by the other remote processes forming the group.

In case of the latter two return values, a check of the state vector by invocation of gaspi\_state\_vec\_get gives information whether the involved remote GASPI processes are still healthy.

Implementor advice: In case of non-uniform memory access architectures, the memory should be allocated close to the calling process. The allocation policy of the calling process should not be modified.

## 7.3 Segment deletion

#### 7.3.1 gaspi\_segment\_delete

The *synchronous local blocking* procedure gaspi\_segment\_delete releases the resources of a previously allocated memory segment.

```
GASPI_SEGMENT_DELETE ( segment_id )
```

Parameter:

(in) segment id: The segment ID to be deleted.

```
gaspi_return_t
gaspi_segment_delete ( gaspi_segment_id_t segment_id )
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

gaspi\_segment\_delete releases the resources of the segment which is referenced by the segment id identifier.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the segment is deleted and the resources are released. It would be an application error to use the segment for communication between two GASPI processes after gaspi\_delete has been called.

In case of return value GASPI\_ERROR, the segment deletion failed. The segment is in an undefined state. It cannot be used locally or for passive communication. Furthermore, the segment cannot be used for one-sided communication requests which are invoked by other remote processes.

## 7.4 Segment utilities

#### 7.4.1 gaspi\_segment\_num

The gaspi\_segment\_num procedure is a *synchronous local blocking* procedure which returns the current number of allocated segments.

```
GASPI_SEGMENT_NUM ( segment_num )
```

Parameter:

(out) segment num: the current number of allocated segments

```
gaspi_return_t
gaspi_segment_num ( gaspi_number_t *segment_num )
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value GASPI\_SUCCESS, segment\_num contains the current number of locally allocated segments provided

by GASPI. The value of  $segment\_num$  is related to the parameter  $segment\_max$  in the configuration structure which is retrieved by  $gaspi\_proc\_init$  at startup and cannot exceed that value. The maximum number of allocatable segments per process might be implementation specific.

In case of error, the return value is GASPI\_ERROR. The parameter  $segment\_num$  has an undefined value.

## 7.4.2 gaspi\_segment\_list

The gaspi\_segment\_list procedure is a *synchronous local blocking* procedure which returns a list of locally allocated segment IDs.

Parameter:

(in) num: number of segment IDs to collect

(out) segment list/num/: list of locally allocated segment IDs

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS,  $segment\ id\ list[num]$  contains the IDs of num locally allocated segments.

The size of segment id list[num] needs to be at least num elements long.

In case of error, the return value is GASPI\_ERROR. The parameter  $segment\_list[num]$  has an undefined value.

## 7.4.3 gaspi\_segment\_ptr

Segments are identified by a unique ID. This ID can be used to obtain the virtual address of that local segment of memory. The procedure gaspi\_segment\_ptr returns the pointer to the segment represented by a given segment ID. It is a synchronous local blocking procedure.

Parameter:

(in) segment id: The segment ID.

(out) pointer: The pointer to the memory segment.

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. GASPI\_SUCCESS, the output parameter *pointer* contains the virtual address pointer of the memory identified by  $segment\_id$ . This <code>gaspi\_pointer\_t</code> can then be used to reference the segment and perform memory operations.

In case of return value GASPI\_ERROR, the translation of the segment ID to a pointer to a virtual memory address failed. The pointer contains an undefined value and cannot be used to reference the segment.

## 7.5 Segment memory management

Each thread of a process may have global read or write access to all of the segments provided by remote Gaspi processes if there is a connection established between the processes and if the respective segments have been registered on the local process.

Since a segment is an entire contiguous block of virtual memory, allocations inside of the pre-allocated segment memory need to be managed.

Gaspi does not provide dedicated memory management functionality for the local segments. This is left to the application. High performance is the guiding principle of Gaspi. A good problem-related implementation of a memory management is always better than any predefined implementation. A default implementation cannot include knowledge about the specific problem.

Local and non-local Gaspi procedures specify in general memory addresses within the Partitioned Global Address Space by the triple consisting of a rank, a segment identifier and an offset. This prevents a global all-to-all distribution of memory addresses, since memory addresses of memory segments could be and normally are different on different Gaspi processes.

A local buffer is specified by the pair  $segment\_id$ , offset. The rank parameter is superfluous since it can be derived from the rank of the local Gaspi process. The buffer is located at address

```
buffer address = base addr (segment id) + offset
```

where base\_addr(segment\_id) is the base address of the segment with identifier  $segment_id$ . It can be obtained by applying gaspi\_segment\_ptr on the local process.

A remote buffer is specified by the triple <code>remote\_rank</code>, <code>remote\_segment\_id</code>, <code>remote\_offset</code>. The address of the remote buffer can be calculated analogously to the local buffer. The only difference is the determination of the base address. Here, it is the address which would be obtained by invoking <code>gaspi\_segment\_ptr</code> on the remote <code>Gaspi</code> process with <code>remote\_segment\_id</code> as input parameter.

## 8 One-sided communication

#### 8.1 Introduction and overview

One-sided asynchronous communication is the basic communication mechanism provided by Gaspi. Hereby, one Gaspi process specifies all communication parameters, both for the local and the remote side. Due to the asynchronicity, a complete communication involves two procedure calls. First, one call to initiate the communication. This call posts a communication request to the underlying network infrastructure. The second call waits for the completion of the communication request.

For one-sided communication, Gaspi provides the concept of communication queues. All operations placed on a certain queue q by one or several threads

are finished after a single wait call on the queue q has returned successfully. Separation of concerns is possible by using different queues for different tasks, e. g. one queue for operations on data and another queue for operations on meta-data.

The different communication queues guarantee fair communication, i.e. no queue should see its communication requests delayed indefinitely.

One-sided communication calls can basically be divided into two operation types: read and write. The read operations transfer data from a remote segment to a local segment. For the write operation, it is vice versa.

The number of communication queues and their size can be configured at initialization time, otherwise default values will be used. The default values are implementation dependent. Maximum values are also defined.

Due to the direct memory access of one-sided communication calls, some notes regarding the memory addresses should be made: Memory addresses within the Partitioned Global Address Space are specified uniquely by the triple consisting of the rank, segment identifier and the offset. This prevents a global all-to-all distribution of memory addresses, since the memory addresses of memory segments could be and normally are different on different GASPI processes.

For the write operation there are four different variants that allow different communication patterns:

- gaspi\_write
- gaspi\_write\_notify
- gaspi\_write\_list
- gaspi\_write\_list\_notify

The read operations have two different variants that allow different communication patterns:

- gaspi\_read
- gaspi\_read\_list

The read operations do not support notification calls. This is due to the fact that a notification can only be transferred after ensuring that the communication request has been processed. This would imply that a subsequent wait call has to be invoked directly after invoking read. However, this can be managed more effectively by the application.

A valid one-sided communication request requires that the local and the remote segment are allocated, that there is a connection between the local and the remote Gaspi process and that the remote segment has been registered on the local Gaspi process.

#### 8.2 Basic communication calls

#### 8.2.1 gaspi\_write

The simplest form of a write operation is gaspi\_write which is a single communication call to write data to a remote location. It is an asynchronous non-local time-based blocking procedure.

```
GASPI_WRITE ( segment_id_local
    , offset_local
    , rank
    , segment_id_remote
    , offset_remote
    , size
    , queue
    , timeout
)
```

- (in) segment id local: the local segment ID to read from
- (in) offset local: the local offset in bytes to read from
- (in) rank: the remote rank to write to
- (in) segment id remote: the remote segment to write to
- (in) offset remote: the remote offset to write to
- (in) size: the size of the data to write
- (in) queue: the queue to use
- (in) timeout: the timeout

```
gaspi_write ( segment_id_local
            , offset_local
             rank
            , segment_id_remote
            , offset_remote
            , size
            , queue
            , timeout
            , ireturn
            ) BIND(C)
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_local
  TYPE(gaspi_offset_t), INTENT(IN) :: offset_local
  TYPE(gaspi_rank_t), INTENT(IN) :: rank
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_remote
  TYPE(gaspi_offset_t), INTENT(IN) :: offset_remote
 TYPE(gaspi_size_t), INTENT(IN) :: size
 TYPE(gaspi_queue_id_t), INTENT(IN) :: queue
  TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_write posts a communication request which asynchronously transfers a contiguous block of *size* bytes from a source location of the local Gaspi process to a target location of a remote Gaspi process. This communication request is posted to the communication queue queue. The source location is specified by the pair <code>segment\_id\_local</code>, <code>offset\_local</code>. The target location is specified by the triple <code>rank</code>, <code>segment\_id\_remote</code>, <code>offset\_remote</code>.

A valid <code>gaspi\_write</code> communication request requires that the local and the remote segment are allocated, that there is a connection between the local and the remote <code>Gaspi</code> process and that the remote segment has been registered on the local <code>Gaspi</code> process. Otherwise, the communication request is invalid and the procedure returns with <code>GASPI\_ERROR</code>.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the communication request has been posted to the underlying network infrastructure. One new entry is inserted into the given queue.

Successive gaspi\_write calls posted to the same queue and the same destination rank are not guaranteed to be non-overtaking. However, a subsequent gaspi\_notify, which is posted to the same queue is guaranteed to be non-overtaking. In particular, one can hence assume, that if the corresponding notification has

arrived on the remote process, the data from the earlier posted request to the same process has also arrived on the remote side.

gaspi\_write calls may be posted from every thread of the GASPI process.

If the procedure returns with GASPI\_TIMEOUT, the communication request could not be posted to the hardware during the given timeout. This can happen, if another thread is in a gaspi\_wait for the same queue. A subsequent call of gaspi\_write has to be invoked in order to complete the write call.

A communication request posted to a given queue can be considered as completed, if the correspondent gaspi\_wait returns with GASPI\_SUCCESS.

If the queue to which the communication request is posted is full, i.e. if the number of posted communication requests has already reached the queue size of a given queue, the communication request fails and the procedure returns with return value GASPI\_ERROR. If a saturated queue is detected, there are the following two options: Either one invokes a gaspi\_wait on the given queue in order to wait for all the posted requests to be finished. Or one tries to use another queue.

User advice: Return value GASPI\_SUCCESS does not mean, that the data has been transferred or buffered or that the data has arrived at the remote side.

It is allowed to write data to the source location while the communication is ongoing. However, the result on the remote side would be some undefined interleaving of the data that was present when the call was issued and the data that was written later.

It is also allowed to read from the source location while the communcation is ongoing and such a read would retrieve the data written by the application.

Use gaspi\_notify to synchronise the communication.

## 8.2.2 gaspi\_read

The simplest form of a read operation is gaspi\_read which is a single communication call to read data from a remote location. It is an asynchronous non-local time-based blocking procedure.

```
(in) segment_id_local: the local segment ID to write to
(in) offset_local: the local offset in bytes to write to
(in) rank: the remote rank to read from
(in) segment_id_remote: the remote segment to read from
(in) offset_remote: the remote offset to read from
(in) size: the size of the data to read
(in) queue: the queue to use
(in) timeout: the timeout
gaspi_return_t
```

```
gaspi_read ( segment_id_local
           , offset_local
           , rank
           , segment_id_remote
           , offset_remote
           , size
           , queue
           , timeout
           , ireturn
           ) BIND(C)
 TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_local
 TYPE(gaspi_offset_t), INTENT(IN) :: offset_local
 TYPE(gaspi_rank_t), INTENT(IN) :: rank
 TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_remote
 TYPE(gaspi_offset_t), INTENT(IN) :: offset_remote
 TYPE(gaspi_size_t), INTENT(IN) :: size
 TYPE(gaspi_queue_id_t), INTENT(IN) :: queue
  TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
 TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_read posts a communication request which asynchronously transfers a contiguous block of *size* bytes from a source location of a remote GASPI process to a target location of the local GASPI process. This communication request is posted to the communication queue queue. The target location is specified by the pair segment\_id\_local, offset\_local. The source location is specified by the triple rank, segment\_id\_remote, offset\_remote.

A valid gaspi\_read communication request requires that the local and the remote segment are allocated, that there is a connection between the local and the remote Gaspi process and that the remote segment has been registered on the local Gaspi process. Otherwise, the communication request is invalid and the procedure returns with GASPI\_ERROR.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the communication request has been posted to the underlying network infrastructure. One new entry is inserted into the given queue.

gaspi\_read calls may be posted from every thread of the GASPI process.

If the procedure returns with GASPI\_TIMEOUT, the communication request could not be posted to the hardware during the given timeout. This can happen, if another thread is in a gaspi\_wait for the same queue. A subsequent call of gaspi\_read has to be invoked in order to complete the read call.

A communication request posted to a given queue can be considered as completed, if the the correspondent gaspi\_wait returns with GASPI\_SUCCESS. For completed gaspi\_read requests, the data is guaranteed to be locally available.

If the queue to which the communication request is posted is full, i.e. that the number of posted communication requests has already reached the queue size of a given queue, the communication request fails and the procedure returns with return value GASPI\_ERROR. If a saturated queue is detected, there are the following two options: Either one invokes a gaspi\_wait on the given queue in order to wait for all the posted requests to be finished. Or one tries to use another queue.

User advice: Return value GASPI\_SUCCESS does not mean, that the data transfer has started or that the data has been received at the local side. It is allowed to write data to the local target location while the communication is ongoing. However, the content of the memory would be some undefined interleaving of the data transferred from remote side and the data written locally.

Also, it is allowed to read from the local target location while the communication is ongoing. Such a read would retrieve some undefined interleaving of the data that was present when the call was issued and the data that was transferred from the remote side.

Use gaspi\_notify to synchronise the communication.

## 8.2.3 gaspi\_wait

The gaspi\_wait procedure is a time-based blocking local procedure which waits until all one-sided communication requests posted to a given queue are processed by the network infrastructure. It is an asynchronous non-local time-based blocking procedure.

```
GASPI_WAIT ( queue
    , timeout
    )
```

Parameter:

- (in) queue: the queue ID to wait for
- (in) timeout: the timeout

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the hitherto posted communication requests have been processed by the network infrastructure and the queue is cleaned up. After that, any communication request which has been posted to the given queue can be considered as completed on the local and remote sides.

gaspi\_wait procedure calls may be posted from every thread of the local GASPI process. However, the wait operation is a thread exclusive operation and therefore needs privileged access to the queue which means that if a write/read is

done while a wait is in operation, the write/read operation blocks to ensure correctness. Enforcing this provides correctness and safety to the user while being easier for the implementor and still allows for a high performance implementation. As a consequence, successive <code>gaspi\_wait</code> calls invoked for the same queue by different threads are processed in some sequence one after another.

If the procedure returns with GASPI\_TIMEOUT, the wait request could not be completed during the given timeout. This can happen, if there is another thread in a gaspi\_wait for the same queue. A subsequent call of gaspi\_wait has to be invoked in order to complete the call.

If the procedure returns with GASPI\_ERROR, the wait request aborted abnormally.

In both cases, GASPI\_TIMEOUT and GASPI\_ERROR, the GASPI state vector should be checked in order to eliminate the possibility of a failure. If a failure is detected, all of the communication requests which have been posted to the given queue since the last gaspi\_wait are in an undefined state. Here, undefined state means that the local GASPI process does not know which requests have been processed and which requests are still outstanding. A call to gaspi\_queue\_purge has to be invoked in order to reset the queue.

User advice: Return value GASPI\_SUCCESS means, that the data of all posted write requests has been transferred to the remote side. It does not mean, that the data has arrived at the remote side. However, write accesses to the local source location will not affect the data that is placed in the remote target location.

User advice: Return value GASPI\_SUCCESS means, that the data of all posted read requests have arrived at the local side.

#### 8.2.4 Examples

Listing 10 shows a matrix transpose of a distributed square matrix implemented with the function gaspi\_write.

Listing 10: Gaspi all-to-all communication (matrix transpose) implemented with gaspi\_write

```
#include <stdlib.h>
#include <GASPI.h>
#include <success_or_die.h>
#include <wait_if_queue_full.h>

extern void dump (int *arr, int nProc);

int
main (int argc, char *argv[])
{
    ASSERT (gaspi_proc_init (GASPI_BLOCK));

gaspi_rank_t iProc = GASPI_NORANK;
```

```
gaspi_rank_t nProc = GASPI_NORANK;
14
15
     ASSERT (gaspi_proc_rank (&iProc));
16
     ASSERT (gaspi_proc_num (&nProc));
17
18
     gaspi_notification_id_t notification_max;
     ASSERT (gaspi_notification_num(&notification_max));
20
21
     if (notification_max < (gaspi_notification_id_t)nProc)</pre>
22
23
         exit (EXIT_FAILURE);
24
25
26
     ASSERT (gaspi_group_commit (GASPI_GROUP_ALL, GASPI_BLOCK));
27
28
     const gaspi_segment_id_t segment_id_src = 0;
29
     const gaspi_segment_id_t segment_id_dst = 1;
30
     const gaspi_size_t segment_size = nProc * sizeof(int);
32
33
     ASSERT (gaspi_segment_create ( segment_id_src, segment_size
                                      GASPI_GROUP_ALL, GASPI_BLOCK
35
36
            );
37
     ASSERT (gaspi_segment_create ( segment_id_dst, segment_size
38
                                      GASPI_GROUP_ALL, GASPI_BLOCK
39
40
            );
41
     int *src = NULL;
43
     int *dst = NULL;
44
     ASSERT (gaspi_segment_ptr (segment_id_src, &src));
46
     ASSERT (gaspi_segment_ptr (segment_id_dst, &dst));
47
48
     const gaspi_queue_id_t queue_id = 0;
49
     for (gaspi_rank_t rank = 0; rank < nProc; ++rank)</pre>
51
       {
52
         src[rank] = iProc * nProc + rank;
53
54
          const gaspi_offset_t offset_src = rank * sizeof (int);
55
          const gaspi_offset_t offset_dst = iProc * sizeof (int);
56
          const gaspi_notification_id_t notify_ID = rank;
57
58
         wait_if_queue_full (queue_id, 2);
59
          const gaspi_notification_t notify_val = 1;
62
          ASSERT
63
```

```
(gaspi_write_notify ( segment_id_src, offset_src
64
                                   , rank, segment_id_dst, offset_dst
                                   , sizeof (int), notify_ID, notify_val
66
                                    queue_id, GASPI_BLOCK
67
                                   )
68
            );
        }
70
7.1
      gaspi_notification_id_t notify_cnt = nProc;
72
      const gaspi_notification_id_t notify_ID_max = nProc;
73
74
      while (notify_cnt > 0)
7.5
76
      {
        ASSERT (gaspi_notify_waitsome (0, nProc, GASPI_BLOCK));
77
78
        for ( gaspi_notification_id_t notify_ID = 0
             ; notify_ID < notify_ID_max</pre>
              ++notify_ID
82
          {
83
             gaspi_notification_id_t notify_val = 0;
85
             ASSERT (gaspi_notify_reset (notify_ID, &notify_val));
86
             if (notify_val != 0)
               {
89
                 --notify_cnt;
90
91
          }
      }
93
94
      dump (dst, nProc);
      ASSERT (gaspi_wait (queue_id, GASPI_BLOCK));
97
98
      ASSERT (gaspi_barrier (GASPI_GROUP_ALL, GASPI_BLOCK));
99
      ASSERT (gaspi_proc_term (GASPI_BLOCK));
101
102
      return EXIT_SUCCESS;
103
    }
104
```

Listing 11 shows a matrix transpose of a distributed square matrix implemented with the function <code>gaspi\_read</code>. Please note the differences between the transpose implemented with write and the transpose implemented with read: The implementation using write can initialize the matrix on-the-fly, right before the data is transferred, while the implementation using read has to synchronise all processes after the local initialization in order to be sure to read valid data. On the other hand, in the implementation using write one has to synchronise after

the local wait whereas in the implementation using read one can directly use the data after the local wait returns.

Listing 11: Gaspi all-to-all communication (matrix transpose) implemented with gaspi\_read

```
#include <stdlib.h>
   #include <GASPI.h>
   #include <success_or_die.h>
   #include <wait_if_queue_full.h>
   extern void dump (int *arr, int nProc);
   int
   main (int argc, char *argv[])
10
     ASSERT (gaspi_proc_init (GASPI_BLOCK));
11
12
     gaspi_rank_t iProc = GASPI_NORANK;
13
     gaspi_rank_t nProc = GASPI_NORANK;
14
1.5
     ASSERT (gaspi_proc_rank (&iProc));
     ASSERT (gaspi_proc_num (&nProc));
17
18
     ASSERT (gaspi_group_commit (GASPI_GROUP_ALL, GASPI_BLOCK));
19
     const gaspi_segment_id_t segment_id_src = 0;
21
     const gaspi_segment_id_t segment_id_dst = 1;
22
23
     const gaspi_size_t segment_size = nProc * sizeof(int);
25
     ASSERT (gaspi_segment_create ( segment_id_src, segment_size
26
                                      GASPI_GROUP_ALL, GASPI_BLOCK
27
            );
29
     ASSERT (gaspi_segment_create ( segment_id_dst, segment_size
30
                                    , GASPI_GROUP_ALL, GASPI_BLOCK
31
            );
33
34
     int *src = NULL;
35
     int *dst = NULL;
36
37
     ASSERT (gaspi_segment_ptr (segment_id_src, &src));
38
     ASSERT (gaspi_segment_ptr (segment_id_dst, &dst));
39
40
     const gaspi_queue_id_t queue_id = 0;
41
42
     for (gaspi_rank_t rank = 0; rank < nProc; ++rank)</pre>
43
44
         src[rank] = iProc * nProc + rank;
45
```

```
}
46
47
     ASSERT (gaspi_barrier (GASPI_GROUP_ALL, GASPI_BLOCK));
48
49
     for (gaspi_rank_t rank = 0; rank < nProc; ++rank)</pre>
50
51
          const gaspi_offset_t offset_src = iProc * sizeof (int);
52
          const gaspi_offset_t offset_dst = rank * sizeof (int);
53
          wait_if_queue_full (queue_id, 1);
55
56
          ASSERT (gaspi_read ( segment_id_dst, offset_dst
57
                               , rank, segment_id_src, offset_src
58
                                 sizeof (int), queue_id, GASPI_BLOCK
59
60
                 );
61
       }
62
     ASSERT (gaspi_wait (queue_id, GASPI_BLOCK));
64
65
     dump (dst, nProc);
66
67
     ASSERT (gaspi_barrier (GASPI_GROUP_ALL, GASPI_BLOCK));
68
69
     ASSERT (gaspi_proc_term (GASPI_BLOCK));
70
71
     return EXIT_SUCCESS;
72
   }
73
```

The definition of the macro ASSERT is given in the listings 14 and 15. The definition of the function wait\_if\_queue\_full is given in the listings 16 and 17 starting on page 119.

## 8.3 Weak synchronisation primitives

## 8.3.1 Introduction

The one-sided communication procedures have the characteristics that the entire communication is managed by the local process only. The remote process is not involved. This has the advantage that there is no inherent synchronisation between the local and the remote process in every communication request. However, at some point, the remote process needs the information as to whether the data which has been sent to that process has arrived and is valid.

Therefore, Gaspi provides so-called weak synchronisation primitives which allows the application to inform the remote side that the data has been transferred by updating a notification on the remote side. These notifications must be attached to the same queue to which the data payload has been attached. Otherwise, causality is not guaranteed.

As counterpart, there are routines which wait for an update of a single or even an entire set of notifications. This is not thread save. There is a thread safe atomic function to reset the local notification with a given ID which returns the value of the notification before it is reset.

These notification procedures are also one-sided and involve only the local process.

#### 8.3.2 gaspi\_notify

gaspi\_notify is an asynchronous non-local time-based blocking procedure.

- (in) rank: the remote rank to notify
- (in) notification id: the remote notification ID
- (in) notification value: the notification value (> 0) to write
- (in) queue: the queue to use
- (in) timeout: the timeout

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_notify posts a notification request which asynchronously transfers the notification notification\_value of the local Gaspi process to an internal notification buffer of a remote Gaspi process. This notification request is posted to the communication queue queue. The remote notification buffer is specified by the pair rank, notification id.

A valid gaspi\_notify communication request requires that there is a connection between the local and the remote Gaspi process. Otherwise, the communication request is invalid and the procedure returns with Gaspi\_Error.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the notification request has been posted to the underlying network infrastructure.

A gaspi\_notify call which is posted subsequent to an arbitrary number of gaspi\_write requests and which is posted to the same queue and the same destination rank is guaranteed to be non-overtaking. Non-overtaking means that the order of communication requests is preserved on the remote side. In particular, one can assume, that if the data from the gaspi\_notify request has arrived on the remote process, also the data from the earlier posted write request(s) to the same process have arrived on the remote side.

gaspi\_notify calls may be posted from every thread of the Gaspi process.

If the procedure returns with GASPI\_TIMEOUT, the notification request could not be posted to the hardware during the given timeout. This can happen if another thread is in a gaspi\_wait for the same queue. A subsequent call of gaspi\_notify has to be invoked in order to complete the call.

A notification request posted to a given queue can be considered as completed, if the the correspondent gaspi\_wait returns with GASPI\_SUCCESS.

If the queue to which the communication request is posted is full, i. e. that the number of posted communication requests has already reached the queue size of a given queue, the communication request fails.

*User advice:* Return value GASPI\_SUCCESS does not mean, that the notification has been transferred or that the notification has arrived at the remote side.

## 8.3.3 gaspi\_notify\_waitsome

For the procedures with notification, gaspi\_notify and the extendend function gaspi\_write\_notify, gaspi\_notify\_waitsome is the correspondent wait

procedure for the receiver (notified) side. gaspi\_notify\_waitsome is a synchronous, non-local time-based blocking procedure.

### Parameter:

- (in) notification\_begin: the local notification ID for the first notification to wait for
- (in) notification num: the number of notification ID's to wait for
- (in) timeout: the timeout

## Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_notify\_waitsome waits that at least one of a number of consecutive notifications residing in the local internal buffer has a value that is not zero.

The notification buffer is specified by the pair notification\_begin, notification\_num. It contains notification\_num many consecutive notifications beginning at the notification with ID notification\_begin.

If  $notification\_num == 0$  then gaspi\_notify\_waitsome returns immediately with GASPI\_SUCCESS.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the value of at least one of the notifications in the notification buffer has changed to a value that is not zero. All threads that are waiting for the notifications are notified.

If the procedure returns with GASPI\_TIMEOUT, no notification has changed during the given period of time.

In case of an error, i. e. GASPI\_ERROR, the values of the notifications are undefined.

User advice: One scenario for the usage of gaspi\_notify\_waitsome inspecting only one notification is the following: The remote side uses a gaspi\_write call followed by a subsequent call of gaspi\_notify posted to the same queue and the same destination rank. Gaspi guarantees, that if the notification has arrived on the remote process, the previously posted request carrying the work load has arrived as well.

User advice: If in a multi-threaded application more than one thread calls gaspi\_notify\_waitsome for the range of notifications, then all waiting threads are notified about the change of at least one of the notifications. By inspecting the actual values of each of the notifications with gaspi\_notify\_reset, only one thread per changed notification receives a value different from zero.

User advice: In a multi-threaded application the code in listing 12 selects one thread to act on the change of a single notification. The code waits in a blocking manner and thus cannot be used in failure tolerant applications.

Listing 12: Blocking waitsome in a multi-threaded application

```
#include <GASPI.h>
   #include <success_or_die.h>
2
3
   extern void process ( const gaspi_notification_id_t id
                         , const gaspi_notification_t val
5
                        );
6
   void blocking_waitsome ( const gaspi_notification_id_t id_begin
                              const gaspi_notification_id_t id_end
9
10
11
     ASSERT ( gaspi_notify_waitsome ( id_begin
12
                                       , id_end - id_begin
13
                                         GASPI_BLOCK
14
15
            );
16
17
```

```
for (gaspi_notification_id_t i = id_begin; i < id_end; ++i)</pre>
18
          gaspi_notification_t val = 0;
20
21
          // atomic reset
22
          ASSERT (gaspi_notify_reset (i, &val));
24
          // re-check, other threads are notified too!
25
          if (val != 0)
              process (i, val);
28
29
30
        }
31
   }
32
```

#### 8.3.4 gaspi\_notify\_reset

For the gaspi\_notify\_waitsome procedure, there is a notification initialization procedure which resets the given notification to zero. It is a *synchronous local blocking* procedure.

Parameter:

(in) notification\_id: the local notification ID to reset(out) old\_notification\_val: notification value before reset

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

gaspi\_notify\_reset resets the notification with ID notification\_id to zero. The function gaspi\_notify\_reset is an atomic operation: Threads can use gaspi\_notify\_reset to safely extract the value of a specific notification.

The notification buffer on the local side is specified by the notification ID notification id.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the value of the notification buffer was set to zero and old\_notification\_val contains the content of the notification buffer before it was set to zero. To read the old value and to set the value to zero is a single atomic operation.

gaspi\_notify\_reset calls may be posted from every thread of the GASPI process.

In case of error, i. e. return value  $\texttt{GASPI\_ERROR}$ , the value of  $old\_notification\_val$  is undefined.

## 8.4 Extended communication calls

All restrictions applying to gaspi\_write and gaspi\_notify also apply here. In case of timeout or error, no assumptions may be made regarding either the written data or the notification.

#### 8.4.1 gaspi\_write\_notify

The gaspi\_write\_notify variant extends the simple gaspi\_write with a notification on the remote side. This applies to communication patterns that require tighter synchronisation on data movement. The remote receiver of the data is notified when the write is finished and can verify this through the respective wait procedure. It is an asynchronous non-local time-based blocking procedure.

```
(in) segment_id_local: the local segment ID to read from
```

- (in) offset local: the local offset in bytes to read from
- (in) rank: the remote rank to write to
- (in) segment id remote: the remote segment to write to
- (in) offset remote: the remote offset to write to
- (in) size: the size of the data to write
- (in) notification id: the remote notification ID
- (in) notification\_value: the value of the notification to write
- (in) queue: the queue to use
- (in) timeout: the timeout

```
gaspi_write_notify ( segment_id_local
                   , offset_local
                   , rank
                   , segment_id_remote
                   , offset_remote
                   , size
                   , notification_id
                   , notification_value
                   , queue
                    timeout
                   , ireturn
                   ) BIND(C)
 TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_local
 TYPE(gaspi_offset_t_t), INTENT(IN) :: offset_local
  TYPE(gaspi_rank_t), INTENT(IN) :: rank
 TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_remote
 TYPE(gaspi_offset_t_t), INTENT(IN) :: offset_remote
 TYPE(gaspi_size_t), INTENT(IN) :: size
 TYPE(gaspi_notification_id_t), INTENT(IN) :: notification_id
 TYPE(gaspi_notification_t), INTENT(IN) :: notification_value
 TYPE(gaspi_queue_id_t), INTENT(IN) :: queue
 TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
 TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

Implementor advice: The procedure is semantically equivalent to a call to gaspi\_write and a subsequent call of gaspi\_notify. However, it should be implemented more efficiently, if supported by the network infrastructure.

# 8.4.2 gaspi\_write\_list

The gaspi\_write\_list variant allows strided communication where a list of different data locations are processed at once. Semantically, it is equivalent to a sequence of calls to gaspi\_write but it should (if possible) be more efficient. It is an asynchronous non-local time-based blocking procedure.

- (in) num: the number of elements to write
- (in) segment id local[num]: list of local segment ID's to read from
- (in) offset local[num]: list of local offsets in bytes to read from
- (in) rank: the remote rank to write to
- (in) segment id remote/num/: list of remote segments to write to
- (in) offset remote/num/: list of remote offsets to write to
- (in) size[num]: list of sizes of the data to write
- (in) queue: the queue to use
- (in) timeout: the timeout

```
gaspi_write_list ( num
                 , segment_id_local
                 , offset_local
                 , rank
                 , segment_id_remote
                 , offset_remote
                 , queue
                 , timeout
                 , ireturn
                 ) BIND(C)
  TYPE(gaspi_number_t), INTENT(IN) :: num
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_local(num)
 TYPE(gaspi_offset_t), INTENT(IN) :: offset_local(num)
  TYPE(gaspi_rank_t), INTENT(IN) :: rank
 TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_remote(num)
 TYPE(gaspi_offset_t), INTENT(IN) :: offset_remote(num)
 TYPE(gaspi_size_t), INTENT(IN) :: size(num)
  TYPE(gaspi_queue_id_t), INTENT(IN) :: queue
  TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
 TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

Implementor advice: The procedure is semantically equivalent to num subsequent calls of gaspi\_write with the given local and remote location specification, provided that the destination rank and the used queue are invariant. However, it should be implemented more efficiently, if supported by the network infrastructure.

# 8.4.3 gaspi\_write\_list\_notify

The gaspi\_write\_list\_notify operation performs strided communication as gaspi\_write\_list but also includes a notification that the remote receiver can use to ensure that the communication step is completed. It is an asynchronous non-local time-based blocking procedure.

- (in) num: the number of elements to write
- (in) segment id local[num]: list of local segment ID's to read from
- (in) offset\_local[num]: list of local offsets in bytes to read from
- (in) rank: the remote rank to be write to
- (in) segment id remote/num/: list of remote segments to write to
- (in) offset remote/num/: list of remote offsets to write to
- (in) size/num/: list of sizes of the data to write
- (in) notification id: the remote notification ID
- (in) notification value: the value of the notification to write
- (in) queue: the queue to use
- (in) timeout: the timeout

```
gaspi_write_list_notify
                ( num
                , segment_id_local
                , offset_local
                , rank
                , segment_id_remote
                , offset_remote
                , notification_id
                , notification_value
                , queue
                 timeout
                 ireturn
                ) BIND(C)
  TYPE(gaspi_number_t), INTENT(IN) :: num
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_local(num)
  TYPE(gaspi_offset__t), INTENT(IN) :: offset_local(num)
  TYPE(gaspi_rank_t), INTENT(IN) :: rank
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_remote(num)
  TYPE(gaspi_offset_t), INTENT(IN) :: offset_remote(num)
  TYPE(gaspi_size_t), INTENT(IN) :: size(num)
  TYPE(gaspi_notification_id_t), INTENT(IN) :: notification_id
  TYPE(gaspi_notification_t), INTENT(IN) :: notification_value
  TYPE(gaspi_queue_id_t), INTENT(IN) :: queue
  TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully GASPI\_TIMEOUT: operation has run into a timeout GASPI\_ERROR: operation has finished with an error

Implementor advice: The procedure is semantically equivalent to a call to gaspi\_write\_list and a subsequent call of gaspi\_notify. However, it should be implemented more efficiently, if supported by the network infrastructure.

#### 8.4.4 gaspi\_read\_list

The gaspi\_read\_list variant allows strided communication where a list of different data locations are processed at once. Semantically, it is equivalent to a sequence of calls to gaspi\_read but it should (if possible) be more efficient. It is an asynchronous non-local time-based blocking procedure.

- (in) num: the number of elements to read
- (in) segment id local[num]: list of local segment ID's to write to
- (in) offset local[num]: list of local offsets in bytes to write to
- (in) rank: the remote rank to read from
- (in) segment id remote[num]: list of remote segments to read from
- (in) offset remote/num/: list of remote offsets to read from
- (in) size[num]: list of sizes of the data to read
- (in) queue: the queue to use
- (in) timeout: the timeout

```
gaspi_read_list ( num
                , segment_id_local
                , offset_local
                , rank
                , segment_id_remote
                , offset_remote
                , queue
                , timeout
                , ireturn
                ) BIND(C)
  TYPE(gaspi_number_t), INTENT(IN) :: num
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_local(num)
  TYPE(gaspi_offset__t), INTENT(IN) :: offset_local(num)
  TYPE(gaspi_rank_t), INTENT(IN) :: rank
  TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id_remote(num)
  TYPE(gaspi_offset_t), INTENT(IN) :: offset_remote(num)
  TYPE(gaspi_size_t), INTENT(IN) :: size(num)
  TYPE(gaspi_queue_id_t), INTENT(IN) :: queue
  TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
  TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

# 8.5 Communication utilities

#### 8.5.1 gaspi\_queue\_size

The gaspi\_queue\_size procedure is a *synchronous local blocking* procedure which determines the number of open communication requests posted to a given queue.

Parameter:

(in) queue: the queue to probe

(out) queue size: the number of open requests posted to the queue

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the parameter  $queue\_size$  contains the number of open requests posted to the queue queue. In a threaded program this result is uncertain, since another thread may have posted an additional request in the meantime or issued a wait call.

The queue size is set to zero by a successful call to gaspi\_wait.

In case of error, the return value is GASPI\_ERROR. The parameter queue\_size has an undefined value.

### 8.5.2 gaspi\_queue\_purge

The gaspi\_queue\_purge procedure is a synchronous local time-based blocking procedure which purges a given queue.

```
GASPI_QUEUE_PURGE ( queue , timeout )
```

Parameter:

(in) queue: the queue to purge

(in) timeout: the timeout

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

This procedure should only be invoked in the situation in which a node failure is detected by inspecting the global health state with gaspi\_state\_vec\_get.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the communication queue is purged. All communication requests posted to the queue queue are eliminated from the queue. The local GASPI process has no information about the completion of communication requests posted to the given queue since the last invocation of gaspi\_wait.

If the procedure returns with GASPI\_TIMEOUT, the purge request could not be completed during the given timeout. This might happen if there is another thread in a gaspi\_wait for the same queue. A subsequent call of gaspi\_queue\_purge has to be invoked in order to complete the call.

If the procedure returns with GASPI\_ERROR, the purge request aborted abnormally.

# 9 Passive communication

#### 9.1 Introduction and overview

Passive communication has a two-sided semantic, where there is a matching receiver to a send request. Passive communication aims at communication patterns where the sender is unknown (i. e. it can be any process from the receiver perspective) but there is potentially the need for synchronisation between processes. Typical example uses cases are:

- Distributed update where many processes contribute to the data of one process.
- Pass arguments and results.
- Global error handling.

The implementation should try to enforce fairness in communication that is, no sender should see its communication request delayed indefinitely.

The passive keyword means that the communication calls should avoid busy-waiting and consume no CPU cycles, freeing the system for computation.

The send request is synchronous, whereas the matching receive is *time-based blocking*. A valid passive communication request requires that the local and the remote segment are allocated and that there is a connection between the local and the remote Gaspi process. Otherwise, the communication request is invalid and the procedure returns with GASPI\_ERROR.

#### 9.2 Passive communication calls

#### 9.2.1 gaspi\_passive\_send

The blocking gaspi\_passive\_send is the routine called by the sender side to engage in passive communication. It is an *synchronous non-local time-based blocking* procedure.

- (in) segment id local: the local segment ID from which the data is sent
- (in) offset local: the local offset from which the data is sent
- (in) rank: the remote rank to which the data is sent
- (in) size: the size of the data to be sent
- (in) timeout: the timeout

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully GASPI\_TIMEOUT: operation has run into a timeout GASPI\_ERROR: operation has finished with an error

gaspi\_passive\_send posts a passive communication request which transfers a contiguous block of *size* bytes from a source location of the local GASPI process to the remote GASPI process with the indicated rank *rank*. On the remote side, a corresponding gaspi\_passive\_receive has to be posted. The source location is specified by the pair *segment id local*, *offset local*.

There is a size limit for the data sent with gaspi\_passive\_send. The maximum size is returned by the function gaspi\_passive\_transfer\_size\_max.

A valid gaspi\_passive\_send communication request requires that the local and the remote segment are allocated and that there is a connection between the local and the remote Gaspi process. Otherwise, the communication request is invalid and the procedure returns with GASPI\_ERROR.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the passive communication request has been posted to the underlying network infrastructure and was completed.

gaspi\_passive\_send calls may be posted from every thread of the GASPI process.

If the procedure returns with GASPI\_TIMEOUT, the communication request could not be posted to the hardware during the given timeout.

If the passive communication queue is full at the time when a new passive communication request is posted, i.e. the number of posted communication requests has already reached the queue size, the communication request fails and the procedure returns with return value GASPI\_ERROR.

User advice: [see also the advice in 8.2.1 on page 56] It is allowed to write data to the source location while the communication is ongoing. However, the result on the remote side would be some undefined interleaving of the data that was present when the call was issued and the data that was written later.

It is also allowed to read from the source location while the communcation is ongoing and such a read would retrieve the data written by the application.

User advice: If the parameter build\_infrastructure is not set, a connection has to be established between the processes before the gaspi\_passive\_send can be be used. This is accomplished calling the procedure gaspi\_connect.

# 9.2.2 gaspi\_passive\_receive

The synchronous non-local time-based blocking gaspi\_passive\_receive is one of the routines called by the receiver side to engage in passive communication.

- (in) segment\_id\_local: the local segment ID where to write the data
- (in) offset local: the local offset where to write the data
- (out) rank: the remote rank from which the data is transferred
- (in) size: the size of the data to be received
- (in) timeout: the timeout

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully GASPI\_TIMEOUT: operation has run into a timeout GASPI\_ERROR: operation has finished with an error

gaspi\_passive\_receive receives a contiguous block of data into a target location from some unspecified remote GASPI process. The target location is specified by the pair segment id local, offset local.

There is no need for the gaspi\_passive\_receive procedure to be active before a corresponding gaspi\_passive\_send procedure is invoked. However, as long as there is no matching receive, the gaspi\_passive\_send cannot achieve any progress and thus cannot return GASPI\_SUCCESS.

The target location needs to have enough space to hold the maximum passive transfer size that could be sent be any other process. Otherwise, the received data might overwrite memory regions outside of the allocated memory and the application will be in an undefined state.

A valid gaspi\_passive\_receive communication request requires that the local destination segment is allocated and that there is a connection between the local and the remote Gaspi process from which a data transfer originates. Otherwise, the communication request is invalid and the procedure returns with GASPI\_ERROR.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the data has been received and is available at the target location. Further rank contains the rank of the sending process and associated to the communication request.

Successive gaspi\_passive\_receive calls posted by two different threads using two different target locations are allowed. However, either the first incoming

data is received by the first thread or the by the second. That means that the gaspi\_passive\_receive should be posted only from a single thread of a GASPI process.

If the procedure returns with GASPI\_TIMEOUT, there was no pending communication request in the queue. The output parameter rank has no defined value.

*User advice:* It is allowed to write data to the local target location while the passive communication is ongoing. However, the content of the memory would be some undefined interleaving of the data transferred from remote side and the data written locally.

Also, it is allowed to read from the local target location while the passive communication is ongoing. Such a read would retrieve some undefined interleaving of the data that was present when the call was issued and the data that was transferred from the remote side.

Implementor advice: A quality implementation enforces fairness in communication that is, no sender should see its communication request delayed indefinitely. The passive keyword means the communication calls shall avoid busy-waiting and consume no CPU cycles, freeing the system for computation.

# 9.3 Passive communication utilities

#### 9.3.1 gaspi\_passive\_queue\_purge

The gaspi\_passive\_queue\_purge procedure is a synchronous local time-based blocking procedure which purges the passive queue.

TYPE(gaspi\_return\_t), INTENT(OUT) :: ireturn

Execution phase:

Working

Return values:

10 Global atomics 86

```
GASPI_SUCCESS: operation has returned successfully
```

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

This procedure should only be invoked in the situation in which a node failure is detected by inspecting the global health state with gaspi\_state\_vec\_get.

┙

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the passive communication queue is purged.

If the procedure returns with GASPI\_TIMEOUT, the purge request could not be completed during the given timeout. A subsequent call of gaspi\_passive\_queue\_purge has to be invoked in order to complete the call.

If the procedure returns with GASPI\_ERROR, the purge request was not satisfied and returned abnormally.

# 10 Global atomics

# 10.1 Introduction and Overview

An atomic operation is an operation which is guaranteed to be executed without fear of interference from other processes during the procedure call. Only one GASPI process at a time has access to the global variable and can modify it.

Atomic operations are also guaranteed to be fair. That means no GASPI process should see its atomic operation request delayed indefinitely.

# 10.2 Atomic operation calls

#### 10.2.1 gaspi\_atomic\_fetch\_add

The gaspi\_atomic\_fetch\_add procedure is a synchronous non-local time-based blocking procedure which atomically adds a given value to a globally accessible value.

```
GASPI_ATOMIC_FETCH_ADD ( segment_id , offset , rank , value_add , value_old , timeout )
```

- (in) segment id: the segment ID where the value is located
- (in) offset: the offset where the value is located

```
(in) rank: the rank where the value is located
```

- (in) value add: the value which is to be added
- (out) value old: the old value before the operation
- (in) timeout: the timeout

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_atomic\_fetch\_add atomically adds the value of value\_add to the value on rank rank, segment\_id\_remote and offset\_offset\_remote.

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the parameter value old contains the value before the operation has been applied.

If the procedure returns with GASPI\_TIMEOUT, the fetch and add request could not be completed during the given timeout. The parameter value\_old has an

undefined value. A subsequent call of gaspi\_atomic\_fetch\_add needs to be invoked in order to complete the operation.

If the procedure returns with GASPI\_ERROR, the fetch and add request aborted abnormally. The parameter *value\_old* as well as the global value (segment\_id, offset, rank) have undefined values.

In both cases, GASPI\_TIMEOUT and GASPI\_ERROR, the GASPI state vector should be checked in order to deal with possible failures.

Implementor advice: The implementation might require some alignment restrictions that is, the triple(segment\_id, offset, rank) might be required to respect some alignment restrictions.

User advice: Concurrent accesses to the location represented by the triple(segment\_id, offset, rank) are possible but consistency must be handled by the application.

# 10.2.2 gaspi\_atomic\_compare\_swap

The gaspi\_atomic\_compare\_swap procedure is a *synchronous non-local time-based blocking* procedure which atomically compares the value of a global value against some user given value and in case these are equal the old value is replaced by a new value.

```
GASPI_ATOMIC_COMPARE_SWAP ( segment_id , offset , rank , comparator , value_new , value_old , timeout )
```

- (in) segment id local: the segment ID where the value is located
- (in) offset: the offset where the value is located
- (in) rank: the rank where the value is located
- (in) comparator: the value which is compared to the remote value
- (in) value\_new: the new value to which the remote location is set if the result of the comparison is true
- (out) value old: the value before the operation
- (in) timeout: the timeout

```
gaspi_atomic_compare_swap ( segment_id
                           , offset
                           , rank
                          , comparator
                           , value_new
                           , value_old
                           , timeout
                           , ireturn
                          ) BIND(C)
    TYPE(gaspi_segment_id_t), INTENT(IN) :: segment_id
    TYPE(gaspi_offset_t), INTENT(IN) :: offset
    TYPE(gaspi_rank_t), INTENT(OUT) :: rank
    TYPE(gaspi_atomic_value_t), INTENT(IN) :: comparator
    TYPE(gaspi_atomic_value_t), INTENT(IN) :: value_new
    TYPE(gaspi_atomic_value_t), INTENT(OUT) :: value_old
    TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
    TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

 ${\tt GASPI\_TIMEOUT:\ operation\ has\ run\ into\ a\ timeout}$ 

GASPI\_ERROR: operation has finished with an error

gaspi\_atomic\_compare\_swap atomically compares the global value of the the value on rank rank, segment segment\_id\_remote and offset offset\_remote to the value of comparator. If the comparison is true, this global value is set to value new. If the comparison is false, it keeps its value.

After successful procedure completion, i.e. return value <code>GASPI\_SUCCESS</code>, the parameter  $value\_old$  contains the previous value before the comparison was done.

If the procedure returns with <code>GASPI\_TIMEOUT</code>, the compare and swap request could not be completed during the given timeout. The parameter  $value\_old$  has

an undefined value. A subsequent call of gaspi\_atomic\_compare\_swap needs to be invoked in order to complete the operation.

If the procedure returns with GASPI\_ERROR, the compare and swap request aborted abnormally. The parameter  $value\_old$  as well as well as the global value (segment id, offset, rank) have undefined values.

In both cases, GASPI\_TIMEOUT and GASPI\_ERROR, the GASPI state vector should be checked in order to deal with possible failures.

Implementor advice: The implementation might require some alignment restrictions that is, the triple(segment\_id, offset, rank) might be required to respect some alignment restrictions.

User advice: Concurrent accesses to the location represented by the triple(segment\_id, offset, rank) are possible but consistency must be handled by the application.

## 10.2.3 Examples

The example in listing 13 illustrates the usage of global atomic operations for implementing a global resource lock. The example is implemented with timeout.

Listing 13: Gaspi global resource lock implemented with atomic counters

```
#include <GASPI.h>
   #include <assert.h>
2
   #define SUCCESS_OR_RETURN(f)
5
       const int ec = (f);
       if (ec != GASPI_SUCCESS)
            return ec;
11
12
13
   #define VAL_UNLOCKED 9999999
14
15
   gaspi_return_t
16
   global_lock_init ( const gaspi_segment_id_t seg,
17
                        const gaspi_offset_t off,
18
                        const gaspi_rank_t rank_loc,
19
                        const gaspi_timeout_t timeout
20
21
22
     gaspi_rank_t iProc = GASPI_NORANK;
23
24
     SUCCESS_OR_RETURN (gaspi_proc_rank (&iProc));
26
```

```
if( iProc == rank_loc)
27
28
          gaspi_pointer_t vptr;
29
          gaspi_atomic_value_t *lock_ptr;
30
31
          SUCCESS_OR_RETURN(gaspi_segment_ptr, &vptr);
          lock_ptr = (gaspi_atomic_value_t *) vptr;
33
34
          *lock_ptr = VAL_UNLOCKED;
35
       }
36
37
     SUCCESS_OR_RETURN (gaspi_barrier ( GASPI_GROUP_ALL
38
39
                                             timeout
40
                          );
41
42
     return GASPI_SUCCESS;
43
   }
44
45
   gaspi_return_t
46
   global_try_lock ( const gaspi_segment_id_t seg,
47
                       const gaspi_offset_t off,
48
                       const gaspi_rank_t rank_loc,
49
                      const gaspi_timeout_t timeout
50
51
52
     gaspi_rank_t iProc = GASPI_NORANK;
53
54
     SUCCESS_OR_RETURN (gaspi_proc_rank (&iProc));
55
56
     gaspi_atomic_value_t old_value;
57
     SUCCESS_OR_RETURN (gaspi_atomic_compare_swap ( seg
                                                         , off
60
                                                         , rank_loc
61
                                                         , VAL_UNLOCKED
62
                                                         , iProc
                                                         , &old_value
64
                                                           timeout
65
66
                          );
67
68
     return (old_value == VALUE_UNLOCKED) ? GASPI_SUCCESS
69
                                                  : GASPI_ERROR
70
71
                                                  ;
72
73
   gaspi_return_t
   global_unlock ( const gaspi_segment_id_t seg,
75
                     const gaspi_offset_t off,
76
```

```
77
                     const gaspi_rank_t rank_loc,
                     const gaspi_timeout_t timeout
79
80
     gaspi_rank_t iProc = GASPI_NORANK;
81
82
     SUCCESS_OR_RETURN (gaspi_proc_rank (&iProc));
83
84
     gaspi_atomic_value_t current_value;
85
86
     SUCCESS_OR_RETURN (gaspi_atomic_compare_swap ( seg
87
                                                          , off
88
                                                          , rank_loc
89
                                                            iProc
90
                                                            VAL_UNLOCKED
91
                                                            &current_value
92
                                                            timeout
93
                          );
95
96
     return GASPI_SUCCESS;
97
   }
98
```

# 11 Collective communication

#### 11.1 Introduction and overview

Collective operations are collective with respect to a given group. A necessary condition for successful collective procedure completion is that all GASPI processes forming the given group have invoked the operation.

Collective operations support both synchronous and asynchronous implementations as well as time-based blocking. That means, progress towards successful procedure completion can be achieved either inside the call (for a synchronous implementation) or outside of the call (for an asynchronous implementation) before the procedure exits. In the case of a timeout (which is indicated by return value GASPI\_TIMEOUT) the operation is then continued in the next call of the procedure. This implies that a collective operation may involve several procedure calls until completion. Completion is indicated by return value GASPI\_SUCCESS.

Collective operations are exclusive per group, i.e. only one collective operation of a specific type on a given group can run at a given time. Starting a specific collective operation before another one of the same kind is not finished on all processes of the group (and marked as such) is not allowed and yields undefined behavior. For example, two allreduce operations for one group can not run at the same time; however, an allreduce and a barrier operation can run at the same time.

The timeout is a necessary condition in order to be able to write failure tolerant code. Timeout = 0 makes an atomic portion of progress in the operation if possible. If progress is possible, the procedure returns as soon as the atomic portion of progress is achieved. Otherwise, the procedure returns immediately. Here, an atomic portion of progress is defined as the smallest set of non-dividable instructions in the current state of the collective operation.

Reduction operations can be defined by the application via callback functions.

User advice: Not every collective operation will be implementable in an asynchronous fashion – for example if a user-defined callback function is used within a global reduction. Progress in this case can only be achieved inside of the call. Especially for large systems this implies that a collective potentially has to be called a substantial number of times in order to complete – especially if used in combination with GASPI\_TEST. In this combination the called collective immediately returns (after completing local work) and never waits for data from remote processes. A corresponding code fragment in this case would assume the form:

```
1
     while (GASPI_allreduce_user ( buffer_send
 2
                                    , buffer_receive
 3
                                    , char num
 4
                                      size_element
 5
                                      reduce_operation
 6
                                      reduce_state
7
                                    , group
8
                                      GASPI_TEST
9
                                    ) != GASPI_SUCCESS
10
          )
     {
11
          work();
12
     }
13
```

# 11.2 Barrier synchronisation

# 11.2.1 gaspi\_barrier

The gaspi\_barrier procedure is a *collective time-based blocking* procedure. An implementation is free to provide it as a synchronous or an asynchronous procedure.

Parameter:

(in) group: the group of ranks which should participate in the barrier

┙

(in) timeout: the timeout

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_TIMEOUT: operation has run into a timeout

GASPI\_ERROR: operation has finished with an error

gaspi\_barrier blocks the caller until all group members of group have invoked the procedure or if timeout milliseconds have been reached since procedure invocation. After successful procedure completion, i. e. return value GASPI\_SUCCESS, all group members have invoked the procedure. In case of GASPI\_TIMEOUT it is unknown whether or not all GASPI processes forming the given group have invoked the call.

Progress towards successful gaspi\_barrier completion is achieved even if the procedure exits due to timeout. The barrier is then continued in the next call of the procedure. This implies that a barrier operation may involve several gaspi\_barrier calls until completion.

Barrier operations are exclusive per group, i. e. only one barrier operation on a given group can run at a time. Starting a barrier operation in another thread before a previously invoked barrier is finished on all processes of the group is not allowed and yields undefined behavior.

In case of error, the return value is GASPI\_ERROR. The error vector should be investigated.

User advice: The barrier is supposed to synchronise processes and not threads.

#### 11.2.2 Examples

In the following example a gaspi\_barrier is interrupted after 100 ms in order to check for errors.

```
1
     gaspi_return_t err;
2
3
4
         err = gaspi_barrier (g, 100);
5
6
         if (err == GASPI_TIMEOUT && error vector indicates error)
7
           {
8
9
             goto ERROR_HANDLING;
10
       }
11
12
     while (err != GASPI_SUCCESS);
```

The following example shows a non-blocking barrier. Some local work (in this case: cleanup) is performed, overlapping it with the barrier and only then a full synchronisation is achieved by calling the barrier again with a blocking semantics (if needed).

```
const gaspi_return_t err = GASPI_barrier (g, GASPI_TEST);

do_local_cleanup();

if (err != GASPI_ERROR)

err = GASPI_barrier (g, GASPI_BLOCK);

}
```

# 11.3 Predefined global reduction operations

#### 11.3.1 gaspi\_allreduce

The gaspi\_allreduce procedure is a *collective time-based blocking* procedure. An implementation is free to provide it as a synchronous or an asynchronous procedure.

#### Parameter:

- (in) buffer send: pointer to the buffer where the input is placed
- (in) buffer receive: pointer to the buffer where the result is placed
- (in) num: the number of elements to be reduced on each process
- (in) operation: the Gaspi reduction operation type
- (in) datatype: the Gaspi element type
- (in) group: the group of ranks which participate in the reduction operation
- (in) timeout: the timeout

```
gaspi_allreduce ( buffer_send
                , buffer_receive
                , num
                , operation
                , datatype
                , group
                , timeout
                ) BIND(C)
    TYPE(gaspi_pointer_t), INTENT(IN) :: buffer_send
    TYPE(gaspi_pointer_t), INTENT(IN) :: buffer_receive
    TYPE(gaspi_number_t), INTENT(IN) :: num
    TYPE(gaspi_operation_t), INTENT(IN) :: operation
    TYPE(gaspi_datatype_t), INTENT(IN) :: datatype
    TYPE(gaspi_group_t), INTENT(IN) :: group
    TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
    TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

#### Execution phase:

Working

#### Return values:

```
GASPI_SUCCESS: operation has returned successfully GASPI_TIMEOUT: operation has run into a timeout GASPI_ERROR: operation has finished with an error
```

gaspi\_allreduce combines the *num* elements of type *datatype* residing in *buffer\_send* on each process in accordance with the given *operation*. The reduction operation is on a per element basis, i. e. the operation is applied to each of the elements. gaspi\_allreduce blocks the caller until all data is available that is needed to calculate the result or if *timeout* milliseconds have been reached since procedure invocation. After successful procedure completion, i. e. return value GASPI\_SUCCESS, all group members have invoked the procedure and *buffer\_receive* contains the result of the reduction operation on every GASPI process of *group*. In case of GASPI\_TIMEOUT not all data is available that is needed to calculate the result.

Progress towards successful gaspi\_allreduce completion is achieved even if the procedure exits due to timeout. The reduction operation is then continued in the next call of the procedure. This implies that a reduction operation may involve several gaspi\_allreduce calls until completion.

Reduction operations are exclusive per group, i. e. only one reduction operation on a given group can run at a time. Starting a reduction operation for the same group in a separate thread before previously innvoked operation is finished on all processes of the group is not allowed and yields undefined behavior.

The buffer\_send as well as the buffer\_receive do not need to reside in the global address space. gaspi\_allreduce copies the send buffer into an internal buffer at the first invocation. The result is copied from an internal buffer into the receive buffer immediatley before the procedure returns successfully. The buffers need to have the appropriate size to host all of the num elements. Otherwise the reduction operation yields undefined behavior. The maximum permissible number of elements is implementation dependent and can be retrieved by gaspi\_allreduce\_elem\_max.

In case of error, the return value is GASPI\_ERROR. The error vector should be examined. buffer\_receive has an undefined value.

In case of GASPI\_TIMEOUT, the reduction operation is not finished yet, i.e. not all data is available that is needed to calculate the result. The <code>buffer\_receive</code> has an undefined value.

### 11.3.2 Predefined reduction operations

There are three predefined reduction operations:

- GASPI\_OP\_MIN determines the minimum of the elements of each column of the input vector.
- GASPI\_OP\_MAX determines the maximum of the elements of each column of the input vector.
- GASPI\_OP\_SUM sums up all elements of each column of the input vector.

#### 11.3.3 Predefined types

And the types are:

```
typedef enum { GASPI_TYPE_INT
, GASPI_TYPE_UINT
, GASPI_TYPE_LONG
, GASPI_TYPE_ULONG
, GASPI_TYPE_FLOAT
, GASPI_TYPE_DOUBLE
} gaspi_datatype_t;

GASPI_TYPE_INT integer

GASPI_TYPE_UINT unsigned integer

GASPI_TYPE_LONG long

GASPI_TYPE_LONG unsigned long

GASPI_TYPE_ULONG unsigned long

GASPI_TYPE_FLOAT float

GASPI_TYPE_DOUBLE double
```

# 11.4 User-defined global reduction operations

#### 11.4.1 gaspi\_allreduce\_user

The procedure gaspi\_allreduce\_user allows the user to specify its own reduction operation. Only operations are supported which are commutative and associative. It is a *collective time-based blocking* procedure. An implementation is free to provide it as a synchronous or an asynchronous procedure.

```
GASPI_ALLREDUCE_USER ( buffer_send , buffer_receive , num , size_element , reduce_operation , reduce_state , group , timeout )
```

- (in) buffer\_send: pointer to the buffer where the input is placed
- (in) buffer receive: pointer to the buffer where the result is placed
- (in) num: the number of elements to be reduced on each process
- (in) size element: Size in bytes of one element to be reduced

(in) reduce\_operation: pointer to the user defined reduction operation procedure

(inout) reduce state: reduction state vector

- (in) group: the group of ranks which participate in the reduction operation
- (in) timeout: the timeout

```
gaspi_allreduce_user ( buffer_send
                     , buffer_receive
                     , num
                     , size_element
                     , reduce_operation
                     , reduce_state
                     , group
                     , timeout
                     , ireturn
                     ) BIND(C)
    TYPE(gaspi_pointer_t), INTENT(IN) :: buffer_send
    TYPE(gaspi_pointer_t), INTENT(IN) :: buffer_receive
    TYPE(gaspi_number_t), INTENT(IN) :: num
    TYPE(gaspi_size_t), INTENT(IN) :: size_element
    TYPE(gaspi_reduce_operation_t), INTENT(IN) :: reduce_operation
    TYPE(gaspi_reduce_state_t), INTENT(IN) :: reduce_state
    TYPE(gaspi_group_t), INTENT(IN) :: group
    TYPE(gaspi_timeout_t), INTENT(IN) :: timeout
    TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully GASPI\_TIMEOUT: operation has run into a timeout GASPI\_ERROR: operation has finished with an error

gaspi\_allreduce\_user has the same semantics as the predefined reduction operation gaspi\_allreduce described in the last section.

A user defined reduction operation  $reduce\_operation$  and a user defined state  $reduce\_state$  are passed.

The elements on which the user defined reduction operation is applied are described by their byte size  $size\_element$ . The entire size of the data to be reduced, i. e. num times  $size\_element$ , must not be larger than the internal buffer size of gaspi\_allreduce\_user. The internal buffer size can be queried through gaspi\_allreduce\_buf\_size.

#### 11.4.2 User defined reduction operations

The prototype for the user defined reduction operations is the following:

- (in) operand one: pointer to the first operand
- (in) operand\_two: pointer to the second operand
- (in) result: pointer to the result
- (in) state: pointer to the state
- (in) timeout: the timeout

Return values:

```
GASPI_SUCCESS: operation has returned successfully
GASPI_TIMEOUT: operation has run into a timeout
GASPI_ERROR: operation has finished with an error
```

A pointer to the first operand and a pointer to the second operand are passed. The result is stored in the memory represented by the pointer result. In addition to the actual data, also a state can be passed to the operator which might be required in order to compute the result. In order to meet real time system specifications, a timeout can be passed to the user defined reduction operator. The reduction operator should return a gaspi\_return\_t with the same semantics, i. e. GASPI\_SUCCESS for successful procedure completion. GASPI\_TIMEOUT in case of timeout and GASPI\_ERROR in case of error.

The user defined reduction operator needs to be commutative and associative.

The reduce operator type passed to gaspi\_allreduce\_user is a pointer to a function with the prototype described above.

```
typedef gaspi_reduce_operation* gaspi_reduce_operation_t
```

# 11.4.3 allreduce state

The Gaspi reduction operation type

The allreduce state type

```
typedef void* gaspi_reduce_state_t
```

The Gaspi reduction operation state type

is a pointer to a state which may be passed to the user defined reduction operation. A state may contain additional information beside the actual data to be reduced needed to perform the reduction operation.

# 12 Gaspi getter functions

The Gaspi specification provides getter functions for all entries in the Gaspi configuration. These getter functions are *synchronous local blocking* procedures which, after successful procedure completion (i. e. return value GASPI\_SUCCESS), read out the corresponding value of the current configuration setting.

The values of the parameters in the Gaspi configuration are determined in gaspi\_proc\_init at startup. If the value of one of these parameters is compliant with the system capabilities, the parameter is set to the requested/preferred value. Otherwise, the parameter is set to the maximum value compliant with the system capabilities. The values of the parameters realised in the Gaspi configuration are implementation specific.

In case of error, the return value is GASPI\_ERROR and the corresponding parameter in the getter function has an undefined value.

# 12.1 Getter functions for group management

```
12.1.1 gaspi_group_max
```

```
GASPI_GROUP_MAX (group_max)
```

Parameter:

(out) group max: the total number of groups

```
gaspi_return_t
gaspi_group_max (gaspi_number_t *group_max)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

# 12.2 Getter functions for segment management

```
12.2.1 gaspi_segment_max
```

```
GASPI_SEGMENT_MAX (segment_max)
```

```
Parameter:
```

```
(out) segment max: the total number of permissible segments
```

```
gaspi_return_t
gaspi_segment_max (gaspi_number_t *segment_max)
```

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

# 12.3 Getter functions for communication management

# 12.3.1 gaspi\_queue\_num

```
GASPI_QUEUE_NUM (queue_num)
```

Parameter:

(out) queue num: the number of available queues

```
gaspi_return_t
gaspi_queue_num (gaspi_number_t *queue_num)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

```
12.3.2 \quad {\tt gaspi\_queue\_size\_max}
```

```
GASPI_QUEUE_SIZE_MAX ( queue_size_max )
```

Parameter:

(out) queue size max: the maximum number of simultaneous requests allowed

```
gaspi_return_t
gaspi_queue_size_max ( gaspi_number_t* queue_size_max )
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

# 12.3.3 gaspi\_transfer\_size\_max

```
GASPI_TRANSFER_SIZE_MAX (transfer_size_max)
```

Parameter:

(out) transfer\_size\_max: the maximum transfer size allowed for a single request

```
gaspi_return_t
gaspi_transfer_size_max (gaspi_size_t *transfer_size_max)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

# 12.3.4 gaspi\_notification\_num

```
GASPI_NOTIFICATION_NUM (notification_num)
```

Parameter:

(out) notification num: the number of available notifications

```
gaspi_return_t
gaspi_notification_num (gaspi_number_t *notification_num)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

# 12.4 Getter functions for passive communication

# 12.4.1 gaspi\_passive\_transfer\_size\_max

```
GASPI_PASSIVE_TRANSFER_SIZE_MAX (transfer_size_max)
```

Parameter:

 $(out)\ transfer\_size\_max:$  maximal transfer size per single passive communication request

```
gaspi_return_t
gaspi_passive_transfer_size_max (gaspi_size_t *transfer_size_max)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

#### 12.5 Getter functions for collective communication

# 12.5.1 gaspi\_allreduce\_buf\_size

```
GASPI_ALLREDUCE_BUF_SIZE (buf_size)
```

Parameter:

(out) buf size: the size of the internal buffer in gaspi\_allreduce\_user

```
gaspi_return_t
gaspi_allreduce_buf_size (gaspi_size_t *buf_size)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

## 12.5.2 gaspi\_allreduce\_elem\_max

```
GASPI_ALLREDUCE_ELEM_MAX (elem_max)
```

Parameter:

 $(out)\ elem\_max:$  the maximum number of elements allowed in <code>gaspi\_allreduce</code>

```
gaspi_return_t
gaspi_allreduce_elem_max (gaspi_number_t *elem_max)
```

```
gaspi_allreduce_elem_max ( elem_max
                           , ireturn
                          ) BIND(C)
    TYPE(gaspi_number_t), INTENT(OUT) :: elem_max
    TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
Execution phase:
Working
Return values:
GASPI_SUCCESS: operation has returned successfully
GASPI_ERROR: operation has finished with an error
12.6
       Getter functions related to infrastructure
12.6.1
       gaspi_network_type
GASPI_NETWORK_TYPE (network_type)
Parameter:
(out) network type: the chosen network type
gaspi_return_t
gaspi_network_type (gaspi_network_t *network_type)
gaspi_network_type ( network_type
                    , ireturn
                    ) BIND(C)
    TYPE(gaspi_network_t), INTENT(OUT) :: network_type
    TYPE(gaspi_return_t), INTENT(OUT) :: ireturn
Execution phase:
Working
Return values:
GASPI_SUCCESS: operation has returned successfully
GASPI_ERROR: operation has finished with an error
12.6.2 gaspi_build_infrastructure
GASPI_BUILD_INFRASTRUCTURE (build_infrastructure)
```

```
(out) build infrastructure: the current value of build infrastructure
```

```
gaspi_return_t
gaspi_build_infrastructure (gaspi_bool_t *build_infrastructure)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

# 13 Gaspi Environmental Management

# 13.1 Implementation Information

# 13.1.1 gaspi\_version

The gaspi\_version procedure is a *synchronous local blocking* procedure which determines the version of the running Gaspi installation.

```
GASPI_VERSION (version)
```

Parameter:

(out) version: The version of the running Gaspi installation

```
gaspi_return_t
gaspi_version (float *version)
```

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value GASPI\_SUCCESS version contains the version of the running GASPI installation.

In case of error, the return value is GASPI\_ERROR. The output parameter *version* has an undefined value.

# 13.2 Timing information

#### 13.2.1 gaspi\_time\_get

The gaspi\_time\_get procedure is a *synchronous local blocking* procedure which determines the time elapsed since an arbitrary point of time in the past.

```
GASPI_TIME_GET (wtime)
```

Parameter:

(out) wtime: time elapsed in milliseconds

```
gaspi_return_t
gaspi_time_get (gaspi_time_t *wtime)
```

Execution phase:

Working

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the parameter *wtime* contains elapsed time in milliseconds since an arbitrary point in the past. The parameter *wtime* is not synchronised among the different GASPI processes.

In case of error, the return value is  $\texttt{GASPI\_ERROR}$ . The value of the output parameter wtime is undefined.

# 13.2.2 gaspi\_time\_ticks

The gaspi\_time\_ticks procedure is a *synchronous local blocking* procedure which returns the resolution of the internal timer in terms of milliseconds.

```
GASPI_TIME_TICKS (resolution)
```

Parameter:

(out) resolution: the resolution of the internal timer in milliseconds

```
gaspi_return_t
gaspi_time_ticks (gaspi_time_t *resolution)
```

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS, the parameter *resolution* contains the resolution of the internal timer in units of milliseconds.

In case of error, the return value is GASPI\_ERROR. The value of the output parameter resolution is undefined.

# 13.3 Error Codes and Classes

#### 13.3.1 Gaspi error codes

In principle all return values less than zero represent an error. Every implementation is free to define specific error codes.

### 13.3.2 gaspi\_error\_message

The gaspi\_error\_message procedure is a *synchronous local blocking* procedure which translates an error code to a text message.

```
GASPI_ERROR_MESSAGE ( error_code
    , error_message
    )
```

Parameter:

(in) error code: the error code to be translated

(out) error message: the error message

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i.e. return value GASPI\_SUCCESS  $er-ror\_message$  contains the error message corresponding to the error code  $er-ror\_code$ .

In case of error, the return value is GASPI\_ERROR.

The procedure can be invoked in any of the Gaspi execution phases.

# 14 Profiling Interface

The profiling interface of GASPI consists of two parts. The statistics part provides the means to allow the user to collect basic profiling data about a program run. The event tracing part describes the requirements for an GASPI implementation in order to support the transparent interception and inspection of function calls.

#### 14.1 Statistics

#### 14.1.1 gaspi\_statistic\_counter\_max

The gaspi\_statistic\_counter\_max procedure is a synchronous local blocking procedure, which provides a way to inform the Gaspi user dynamically about the number of avialable counters. An implementation should not provide a compile-time constant maximum for gaspi\_statistic\_counter\_t. Instead the user can call gaspi\_statistic\_counter\_max in order to determine the maximum value for gaspi\_statistic\_counter\_t.

```
GASPI_STATISTIC_COUNTER_MAX ( counter_max )
```

Parameter:

(out) counter\_max: the maximum value for gaspi\_statistic\_counter\_t. The allowed value range is  $0 \le counter < counter = max$ 

```
gaspi_return_t
gaspi_statistic_counter_max ( gaspi_number_t *counter_max )
```

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

If a GASPI implementation defines symbolic constants for gaspi\_statistic\_counter\_t a priori, then gaspi\_statistic\_counter\_max should set counter\_max to the corresponding maximum value. A high-speed implementation will likely set counter\_max to 0 and does not provide any statistics by default. A dynamically linked wrapper library can provide extra counters by adjusting the return value of gaspi\_statistic\_counter\_max.

Library implementor advice: A sensible wrapper library will respect the value returned by the native gaspi\_statistic\_counter\_max and append their own counters accordingly. Thus accesses to statistic counters provided by the GASPI implementation itself are not harmed.

### 14.1.2 gaspi\_statistic\_counter\_info

The gaspi\_statistic\_counter\_info procedure is a synchronous local blocking procedure which provides an implementation independent way to retrieve information for a particular statistic counter. Beside the name and a description this function also yields the meaning of the argument value for this counter, if any. The meaning is defined in terms of the gaspi\_statistic\_argument\_t enumeration.

A Gaspi implementation is free to extend the above enumeration.

#### Parameter:

1)

```
(in) counter: the counter, for which detailed information is requested
(out) counter_argument: the meaning of the argument value
(out) counter_name: a short name of this counter
(out) counter_description: a more verbose description of this counter
(out) verbosity level: minimum verbosity level to activate this counter (at least
```

```
GASPI_STATISTIC_COUNTER_INFO ( counter
                             , counter_argument
                             , counter_name
                             , counter_description
                             , verbosity_level
                               ireturn
                             ) BIND(C)
    TYPE(gaspi_statistic_counter_t), INTENT(IN) :: counter
    TYPE(gaspi_statistic_argument_t), INTENT(OUT) :: counter_argument
    TYPE(gaspi_string_t), INTENT(OUT) ::
                                          counter_name
    TYPE(gaspi_string_t), INTENT(OUT) ::
                                          counter_description
    TYPE(gaspi_number_t), INTENT(OUT) ::
                                          verbosity_level
    TYPE(gaspi_return_t), INTENT(OUT) ::
                                          ireturn
```

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

After successful procedure completion, i. e. return value GASPI\_SUCCESS, the out variables contain the desired information. A dynamically linked wrapper library should provide information for added counters by wrapping gaspi\_statistic\_counter\_info. The verbosity level for all counters should be at least 1 (see gaspi\_statistic\_verbosity\_level below).

If the return value is GASPI\_ERROR, the particular *counter* issued to gaspi\_statistic\_counter\_info does not exist.

#### 14.1.3 gaspi\_statistic\_verbosity\_level

The gaspi\_statistic\_verbosity\_level procedure is a synchronous local blocking procedure which sets the process-wide verbosity level of the statistic interface. A counter is only active (that is, it is updated), if the process-wide verbosity level is higher or equal to the minimum verbosity level of that counter. If a call to gaspi\_statistic\_verbosity\_level activates or deactivates counters and there are asynchronous operations in progress, it is unspecified, whether and how these counters are affected by the operations. It is furthermore unspecified whether and how counters of higher verbositiy levels are updated.

A verbosity level of 0 deactivates all counting. It is not guaranteed, that counters with a minimum verbosity level of 0 are counted properly, if the verbosity level is set to 0.

```
GASPI_STATISTIC_VERBOSITY_LEVEL ( verbosity_level )
```

Parameter:

(in) verbosity\_level: the level of desired verbosity

Execution phase:

Any

Return values:

 ${\tt GASPI\_SUCCESS:}\ operation\ has\ returned\ successfully$ 

GASPI\_ERROR: operation has finished with an error

### 14.1.4 gaspi\_statistic\_counter\_get

The gaspi\_statistic\_counter\_get procedure is a *synchronous local blocking* procedure which retrieves a statistical counter from the local Gaspi process.

Parameter:

- (in) counter: the counter to be retrieved
- (in) argument: the argument for the counter
- (out) value: the current value of the counter

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

The meaning of parameter argument depends on the retrieved counter. For instance, if a counter retrieves the bytes sent per target rank, then argument contains the target rank number. If the retrieved counter has no argument, the value of argument is ignored. After successful procedure completion, i. e. return value GASPI\_SUCCESS value contains the current value of the corresponding counter

The return value is GASPI\_ERROR, if *counter* does not exist, i.e. exceeds gaspi\_statistic\_counter\_max.

It is allowed to access a counter even, if the process-wide verbosity level is lower than the minimum verbosity level of that counter. Thus it is possible to profile certain regions of an application by changing the verbosity level and read the counter values at a later point in time independently of the current verbosity level.

# 14.1.5 gaspi\_statistic\_counter\_reset

The gaspi\_statistic\_counter\_reset procedure is a synchronous local blocking procedure which sets a statistical counter to 0.

```
GASPI_STATISTIC_COUNTER_RESET (counter)
```

Parameter:

(in) counter: the counter to be reset

```
gaspi_return_t
gaspi_statistic_counter_reset (gaspi_statistic_counter_t counter)
```

Execution phase:

Any

Return values:

GASPI\_SUCCESS: operation has returned successfully

GASPI\_ERROR: operation has finished with an error

The return value is GASPI\_ERROR, if *counter* does not exist, i.e. exceeds gaspi\_statistic\_counter\_max.

# 14.2 Event Tracing

The Gaspi event tracing interface defines the requirements for an implementation to support the transparent interception and inspection of Gaspi calls. A Gaspi implementation must provide a mechanism, through which all Gaspi functions may be accessed with a name shift. The alternate entry point names have the prefix pgaspi\_ instead of gaspi\_. In addition the function gaspi\_pcontrol is provided.

# 14.2.1 gaspi\_pcontrol

The function gaspi\_pcontrol is a no-op. A GASPI implementation itself ignores the value of *argument* and returns immediately.

This routine is provided in order to enable users to communicate with an event trace interface from inside the application. The meaning of *argument* is specified by the used event tracer.

A Listings 118

```
Execution phase:
```

Any

Return values:

 ${\tt GASPI\_SUCCESS:}\ operation\ has\ returned\ successfully$ 

GASPI\_ERROR: operation has finished with an error

# A Listings

# A.1 success or die

Listing 14: success\_or\_die.h

Listing 15: success or die.c

```
#include <success_or_die.h>
   #include <stdlib.h>
   #include <stdio.h>
   #include <GASPI.h>
   void success_or_die ( const char* file, const int line
                        , const int ec
9
     if (ec != GASPI_SUCCESS)
10
11
         gaspi_string_t str = GASPI_NOSTRING;
12
         gaspi_error_message (ec, &str);
14
15
         fprintf (stderr, "error in %s[%i]: %s\n", file, line, str);
16
```

# A.2 wait if queue full

Listing 16: wait if queue full.h

```
#ifndef _WAIT_IF_QUEUE_FULL_H

#define _WAIT_IF_QUEUE_FULL_H 1

#include <GASPI.h>

void wait_if_queue_full ( const gaspi_queue_id_t queue_id

const gaspi_number_t request_size
);

#endif
#endif
```

Listing 17: wait if queue full.c

```
#include <wait_if_queue_full.h>
   #include <success_or_die.h>
   void wait_if_queue_full ( const gaspi_queue_id_t queue_id
                            , const gaspi_number_t request_size
     gaspi_number_t queue_size_max = GASPI_NOQUEUESIZE;
     gaspi_number_t queue_size = GASPI_NOQUEUESIZE;
10
     ASSERT (gaspi_queue_size_max (queue_id, &queue_size_max));
11
     ASSERT (gaspi_queue_size (queue_id, &queue_size));
12
     if (queue_size + request_size >= queue_size_max)
14
       {
15
         ASSERT (gaspi_wait (queue_id, GASPI_BLOCK));
16
       }
17
18
```