



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Experiment 3

Student Name: Gaurav Singh

Branch: BE CSE

Semester: 5

Subject Name: ADBMS

UID: 23BCS12992

Section/Group: KRG-1-A

Date of Performance: 14-8-25

Subject Code: 23CSP-333

1. Aim:

Q.1. Generate an employee relation with only one attribute i.e., EMP_ID. Then, find the max EMP_ID, but excluding the duplicates.

Q.2. Create two tables, Department(ID, name) and Employees(ID, name, salary, deptID). Then output the highest earners from each department.

Q.3. Create two tables A and B with the attributes (EmpID, EmpName, Salary) and output the lowest salary of each employee across the two tables.

2. Requirements (Hardware/Software):

Microsoft SQL server

3. Procedure:

Q.1. Code:

```
CREATE TABLE TBL_EMPLOYEE(  
    EMP_ID INT
```

```
);
```

```
INSERT INTO TBL_EMPLOYEE VALUES (2),(4),(4),(6),(6),(7),(8),(8);
```

```
SELECT MAX(EMP_ID) as [Greatest Unique ID] FROM TBL_EMPLOYEE WHERE  
EMP_ID IN
```

```
(SELECT EMP_ID FROM TBL_EMPLOYEE GROUP BY EMP_ID HAVING  
COUNT(EMP_ID)=1);
```

Q.2. Code:

```
CREATE TABLE department (  
  id INT PRIMARY KEY,  
  dept_name VARCHAR(50)  
);
```

```
-- Create Employee Table  
CREATE TABLE employee (  
  id INT,  
  name VARCHAR(50),  
  salary INT,  
  department_id INT,  
  FOREIGN KEY (department_id) REFERENCES department(id)  
);
```

```
-- Insert into Department Table  
INSERT INTO department (id, dept_name) VALUES  
(1, 'IT'),  
(2, 'SALES');
```

```
-- Insert into Employee Table  
INSERT INTO employee (id, name, salary, department_id) VALUES  
(1, 'JOE', 70000, 1),  
(2, 'JIM', 90000, 1),  
(3, 'HENRY', 80000, 2),  
(4, 'SAM', 60000, 2),  
(5, 'MAX', 90000, 1);
```

```
select d.dept_name, e.name, e.salary, d.id from employee as e inner join  
department as D on e.department_id=d.id where e.salary in (Select  
max(salary) from employee group by department_id);
```

Q.3. Code:

```
create table tbl_A ( empid  
int PRIMARY key,  
empname varchar(20),  
salary int  
)
```

```
insert into tbl_A values (1,'AA',1000), (2, 'BB',300);  
create table tbl_B ( empid int PRIMARY key,  
empname varchar(20), salary int  
)
```

```
insert into tbl_B values (2, 'BB',400), (3,'CC',100);
```

```
select empid, min(empname) as empname, min(salary) as min_salary from
(select * FROM tbl_A
UNION
select * from tbl_b)
as UNI group by
empid;
```

4. Output:

Q.1.

Output:

Greatest Unique ID

7

Q.2.

Output:

dept_name	name
IT	JIM
IT	MAX
SALES	HENRY

Q.3.

Output:

empid	empname	min_salary
1	AA	1000
2	BB	300
3	CC	100

5. Learning Outcome:

- Understand the role of sub-queries in simplifying complex SQL operations.
- Apply sub-queries in SELECT, WHERE, and FROM clauses to retrieve specific data.

- **Utilize sub-queries for filtering, aggregation, and conditional logic.**
- **Analyze query performance implications when using sub-queries versus joins.**