

Rules, Tasks and the API

Fundamentals of IdentityIQ
Implementation

IdentityIQ 7.0

Overview

Rules, Tasks and the API

- Rules
 - Defining and using
 - Best Practices
- Tasks
 - Defining and using
 - Common tasks
 - Writing a custom task
- The SailPoint API
 - Resources
 - Common areas of usage
 - Best Practices

Rules

Beanshell Rules

- Small snippets of code that can control many aspects of IdentityIQ's behavior
- Defined and stored as objects of type Rule
 - Loaded from XML
 - Exported from another IdentityIQ environment
 - Created in developers favorite IDE*
 - Created in the UI

Responsible rule development is an important skill
for the IdentityIQ Implementer!

Rule Usage


Why Rules?

- Control the loading of account and group data during aggregation
- Define policy violations and how to display them
- Define values, lists of allowed values and validation logic for provisioning policies and forms
- Control the behavior of certifications
- Control provisioning
- ...and implement many other business goals

Anatomy of a Rule

- All rules include a type
 - Type defines where in the UI the rule can be used
- All rules are passed two objects
 - context – `sailpoint.api.SailPointContext`
 - log – `org.apache.log4j.Logger`
- All rules have inputs and most expect return values
 - Inputs/returns are defined in Rule Registry
 - Return type specifies the actual Java Object being returned
 - Object, Identity, Map, etc.
 - Returns
 - List of values being returned
 - For Maps, this can be multiple entries
 - For Object, this can be one of many types of object
- Rules can set values directly or perform other actions
- RuleRegistry documents each type of rule and its signature
 - Console: get RuleRegistry “Rule Registry”
 - Debug Page: select RuleRegistry object; open Rule Registry

Rule Registry Drives Rule Creation



Example Creation Rule - XML

```
<?xml version='1.0' encoding='UTF-8'?>
<!DOCTYPE Rule PUBLIC "sailpoint.dtd" "sailpoint.dtd">
<Rule created="1359045226692" id="ff8080813c6382d0013c6d6870c40226" language="beanshell" modified="1359045226692"
name="Creation Rule - Set Password Default" type="IdentityCreation">
  <Description>Identity creation rules are used to set attributes on new Identity objects when they are created.
  <Signature returnType="void">
    <Inputs>
      <Argument name="log">
        <Description>
          The log object associated with the SailPointContext.
        </Description>
      </Argument>
      <Argument name="context">
        <Description>
          A sailpoint.api.SailPointContext object that can be used to query the database if necessary.
        </Description>
      </Argument>
      <Argument name="environment" type="Map">
        <Description>
          Arguments passed to the aggregation task.
        </Description>
        ...
      </Argument>
    </Inputs>
    </Signature>
    <Source>
      import sailpoint.object.Identity;
      System.out.println("In Creation Rule");
      identity.setPassword("xyzzzy");
    </Source>
  </Rule>
```

Rule Name

Rule Type

Inputs standard to
all rules

Inputs specific to
this rule

Rule Script
(BeanShell)

Rule Development

```
<?xml version='1.0' encoding='UTF-8'?>
<!DOCTYPE Rule PUBLIC "sailpoint.dtd" "sailpoint.dtd">
<Rule created="1359045226692" id="ff8080813c6382d0013c6d6870c40226" modified="1359068664579" language="beanshell"
name="Creation Rule - Set Password Default" type="IdentityCreation">
  <Description>Identity creation rules are used to set attributes on new Identity objects when they are created ... </Description>
  <Signature returnType="void">
    <Inputs>
      <Argument name="log">
        <Description>
          The log object associated with the SailPointContext.
        </Description>
      </Argument>
      <Argument name="context">
        <Description>
          A sailpoint.api.SailPointContext object that can be used to query the database if necessary.
        </Description>
      </Argument>
      <Argument name="environment" type="Map">
        <Description>
          Arguments passed to the aggregation task.
        </Description>
      </Argument>
      ...
    </Inputs>
  </Signature>
  <Source>
import sailpoint.object.Identity;
System.out.println("In Creation Rule");
identity.setPassword("xyzz");
  </Source>
</Rule>
```

Provided by IdentityIQ

Provided by developer

Remainder – Auto populated by Rule Editor or Provided by developer

Implementing Rules

- Check the signature
 - Learn the inputs
 - Learn the expected return values
 - Read the description of the rule
- Look at examples
 - Compass
 - Documentation
 - Rule Example file (/WEB-INF/config/examplerules.xml)
- General strategy
 - Figure out what you have to work with (input variables) - A
 - Can use println statements to see values being passed in
 - Figure out what you need to return (from signature) - B
 - Use API calls to get from A to B

Creating Rules

IdentityIQ Deployment Accelerator (optional)

- Eclipse IDE Plug-in
- Features
 - Create Rule – generates boilerplate Rule structure
 - Syntax checking for BeanShell in rules/script sections
 - Code-completion
 - Import/Export of IdentityIQ artifacts to/from multiple deployments
 - Compare local copy with deployed copy
 - Remote debug viewer
- Process
 - Download plugin from Compass (.jar file and workflow XML)
 - Place .jar file in Eclipse directory: /dropins
 - Import Workflow into each IdentityIQ system

Rules – Logging

- Use built in log object (log4j) for logging
 - Control logging via config file
 - No need to comment/uncomment System.out.println() messages.
- Perform custom logging per rule
 - Code

```
Logger mylogger =  
Logger.getLogger("com.xxxx.yyyy.FinanceCorrelationRule ");  
mylogger.debug("This is a debug message.");
```

- Log4j.properties file (turn it on or off)

```
log4j.logger.com.xxxx.yyyy.FinanceCorrelationRule =<loglevel>
```

- Include log4j Trace statement every 5 lines (best practice)
 - Code

```
mylogger.trace("Entering com.xxxx.yyyy.FinanceCorrelationRule.");
```

Rules – Performance

- Be aware of Iterative Rules

- Rules that run many times
 - Data Loading and Correlation
 - BuildMap, MergeMaps, Transformation, ResourceObjectCustomization, Correlation
 - Certification Generation
 - Exclusion, Pre-Delegation
- Performance of these rules can have serious impacts
 - BuildMap rule runs for every row in a 30,000 line file
 - .02 seconds * 30,000 rows = 600 seconds or 10 minutes
 - Small improvements in performance have major impact
- Pull non-iterative functions out of iterative rules
 - Connections
 - Lookups for correlations
 - Use state object or CustomGlobal to store pre-calculated information for use during iterative rules

Rules – Rule Libraries

- Create a rule containing convenience functions, etc.

```
<Rule name='My Library'>  
  <Source>  
    public void doSomething() { // do stuff }  
  </Source>  
</Rule>
```


- Include this rule library in other rules, using:

```
<Rule...>  
  <ReferencedRules>  
    <Reference class='Rule' name='My Library' />  
  </ReferencedRules>  
  <Source>  
    doSomething();  
  </Source>  
</Rule>
```

Rules – Executing in Debug or Console

- Debug Page

- SailPoint context and logging objects auto-provided
- Additional arguments must be hard coded
- System.out sent to App Server Standard Out



- Console

- SailPoint context and logging objects auto-provided
- Arguments can be hard coded or provided in an XML file attributes map
- System.out will go to Console

```
> list rule Allowed
Name
----
AllowedValues-Location-UsingCustom
> rule AllowedValues-Location-UsingCustom
[Austin, Brazil, Brussels, London, Munich, San Jose, Singapore, Taipei, Tokyo]
```

Rules – Executing through Task

Run Rule Task (6.2)

New Task

Standard Properties

*Indicates a required field.

Name* **Previous Result Action**

Description

Allow Concurrency ☐

Require Signoff ☐

Email Task Alerts

Email Notification

Run Rule Options

Rule	<input type="button" value="Clear CustomGlobal"/>
Rule Config	<input type="text"/>

Note: Rule must include code to return status

```
return "Success";  
return "Failure";
```


Rules – Reference

Compass Whitepapers

- **BeanShell Developers Guide for IdentityIQ (BSDG)**
 - Contains examples, illustration and explanations for creating excellent code
- **Rules in IdentityIQ**
 - Includes descriptions, usage, and examples of all IdentityIQ rule types

Tasks

Tasks

- Tasks perform periodic operations such as
 - Aggregation
 - Identity Refresh
 - Running Rules
 - System Maintenance
 - Moving Certifications along and finishing them
 - Checking for remediations
 - Pruning or archiving old objects
 - Running ordered set of tasks (Sequential Task Launcher)
- Tasks are represented in the UI under Setup → Tasks
- Tasks can be scheduled or run from the UI
- Tasks can email upon warning/failure/always

Tasks – Anatomy of a Task

- Singleton tasks

- Specialized purpose
- One instance of the task can be defined per installation

Example: Check Expired Work Items

- Template tasks

- Support parameterization and creation of multiple instances of the same type of Task

Example: Account Aggregation

The screenshot displays the 'Tasks' management interface in SailPoint. The main panel shows a list of tasks under the 'Account Aggregation' category. Two tasks are highlighted with red boxes: 'Aggregate Employees and Contractors' and 'Aggregate Financial Application'. The sidebar on the right contains a 'New Task' button and a list of task types, including 'Account Aggregation', 'Account Group Aggregation', 'Activity Aggregation', 'BMC ESS Application Creator', 'Continuous Certification Refresh', 'Data Export', and 'Encrypted Data Synchronization Task'.


Name	Description
Aggregate Employees and Contractors	Aggregate Employees from HR Data and Contractors from Contract...
Aggregate Financial Application	Task to aggregate accounts from the Financials application.

- Account Aggregation
- Account Group Aggregation
- Activity Aggregation
- BMC ESS Application Creator
- Continuous Certification Refresh
- Data Export
- Encrypted Data Synchronization Task

Tasks – Anatomy of a Task (Continued)

- Task object (XML) defines
 - Name of the task
 - Is it a template?
 - Task Signature
 - Inputs to the task
 - Applications Name
 - Checkbox reflecting task options
 - Returns from the task
 - What items will the task return once done
 - Which Java class to use to execute the task

Tasks – Process and Objects



Tasks – Creating your own

- Method creation

- Extend a Java class off of sailpoint.task.AbstractTaskExecutor
- Create a TaskDefinition XML file that sets your Java class as the executor of the task.
- Implement the following methods:

```
public void execute(SailPointContext ctx,  
TaskSchedule sched, TaskResult result,  
Attributes<String, Object> args) throws  
GeneralException
```

```
public boolean terminate()
```

Tasks – Creating your own (continued)

- Compile your java class and put in the classpath of your Application Server
- Load the TaskDefinition XML file
- Your task will be available to execute
 - When it runs, the execute() method of your TaskExecutor is called
 - When the task completes,
 - Results are copied into a result variable and returned
 - Results are available in the UI
- There is an example task and build/deploy environment in the training VM
 - Search Task
 - Searches through objects of a given class for a specified string

The SailPoint API

The SailPoint API


- Basic Object Model

- Identities, Accounts and Entitlements
- Roles
- Certifications
- For more, see the JavaDoc
 - in SailPoint deployment directory: `/doc/javadoc/index.html`
 - in training VM, click shortcut link for IdentityIQ Javadoc


- The SailPoint Context

- Searching for objects
- QueryOptions and Filters
- Modifying objects
- Saving objects


Identity/Accounts/Entitlements



Roles



Certifications



Object Model

Java Doc lays out most common areas of SailPoint object model

Packages

[openconnector](#)

[sailpoint](#)

[sailpoint.api](#)

[sailpoint.connector](#)

[sailpoint.integration](#)

[sailpoint.object](#)

[sailpoint.policy](#)

[sailpoint.reporting.datasource](#)

[sailpoint.server](#)

[sailpoint.task](#)

[sailpoint.tools](#)

[sailpoint.tools.ldap](#)

[sailpoint.tools.xml](#)

[sailpoint.web](#)

[sailpoint.web.certification](#)

[sailpoint.workflow](#)

The SailPoint API Package
SailPoint Context, Emailer

Connectors
DelimitedFile, JDBC Connector, Abstract class for creating
Custom Connectors

SailPoint Objects
Identity, Link, Bundle, Application, ManagedAttribute,
Provisioning Plan, Provisioning Project, Filter, etc.

SailPoint Tasks
Abstract Task for creating Custom Tasks

SailPoint Tools
Util object (lots of utility methods for SailPoint development)

SailPoint *Context*

- Starting point for using the SailPoint API
- Passed into Rules, Tasks and Workflow steps
- Provides mechanisms for:
 - Determining the current logged in user
 - Getting System Configuration
 - Getting DB Connection information
 - Send an email
 - Counting items
 - Searching for items
 - Saving changes to items
 - Running rules

Finding a Single Object

- Find single object by name or Id
 - getObjectByName(<Class>, name)
 - getObjectById(<Class>,id)
- Example (given an identity name, get their manager)

```
Identity user =  
(Identity)context.getObjectByName(Identity.class,"Bob.Doe");  
return user.getManager();
```

- Example (given an application id, get the name of the application)

```
Application app =  
(Application)context.getObjectById(Application.class,"402881823a  
afe88a013aafe8dbfe0029")  
return app.getName();
```


Finding Objects with `getObjects()`

- To find multiple objects:
 - `getObjects(<Class>)`
 - `getObjects(<Class>, queryoptions)`
- Example (get all Rules)

```
List rules = context.getObjects(Rule.class);
```

`getObjects()`
returns a java List

- Example (get all Rules of type BuildMap)

```
QueryOptions qo = new QueryOptions();  
qo.addFilter(Filter.eq("type", "BuildMap"));  
List rules = getObjects(Rule.class, qo);
```

QueryOptions
allow for the
filtering of the
results

Finding Objects with search()

- To find multiple objects:

- search(<Class>,queryoptions)
- search(<Class>,queryoptions,properties)

This type of query is a projection query

- Example (get all Identities that are uncorrelated)

```
QueryOptions go = new QueryOptions();
go.addFilter(Filter.eq("correlated", (Boolean) false));
Iterator identIter = context.search(Identity.class, go);
while (identIter.hasNext()) {
    Identity identity = (Identity) identIter.next();
}
```

search() returns a Java Iterator

- Example (get the name only for each uncorrelated identity)

```
QueryOptions go = new QueryOptions();
go.addFilter(Filter.eq("correlated", (Boolean) false));
Iterator identIter = context.search(Identity.class, go, "name");
while (identIter.hasNext()) {
    String identity = (String) identIter.next()[0];
    System.out.println("Identity = " + identity);
}
```

projection search returns an array of objects (Strings)

Processing Cursors

- Ensure cursors are not left open
 - sailpoint.tools.Util class
 - Util.flushIterator()
- Example (look for specific account, break the loop when found)

```
QueryOptions qo = new QueryOptions();  
qo.addFilter(Filter.eq("application.name", "Active_Directory");  
Iterator iter = context.search(Link.class, qo, "id");
```

```
while (iter.hasNext()){  
    Object[] row = (Object[]) iter.next();  
    String id = row[0];  
    // use id of the object to fetch it and process it  
    // drop out of loop  
}
```

```
Util.flushIterator(iter);
```

Saving Objects

- Save objects after modifications:
 - saveObject(object)
- Example: set password on an identity

```
// assume that user is an Identity objects  
user.setPassword(newPassword);  
context.saveObject(user);  
context.commitTransaction();
```

- Note: Many rules do not require the saving of objects that are returned from the rule.

Best Practices

- Use `search()` with properties wherever possible versus `getObjects()`
 - `search()` returns a database cursor whereas `getObjects` returns a list of objects
- Perform filtering using `QueryOptions` instead of querying for all objects
- When iterating over a large volume of objects
 - use a projection query to pull in the Ids only
 - use `getObjectById` to get each individual object
 - occasionally (perhaps every 100 objects) call `context.decache()`

API by Example

- Problem: Find all uncorrelated identities in the system.
- Solution: Search for all identities, walk one by one and check the `isCorrelated()` method to see if they are correlated or not

```
QueryOptions qo = new QueryOptions();

Iterator result = context.search(Identity.class, qo);
while (result.hasNext()) {
    Identity user = (Identity)result.next();
    if (!user.isCorrelated()) {
        // do stuff here
    }
}
```

- Problems with this approach?

API by Example

- Problem: Find all uncorrelated identities in the system.
- Solution: Use the API to search for only the correlated Identities

```
QueryOptions qo = new QueryOptions();

// Either take a static string representation of a filter or build one
// using the Filter api
//qo.addFilter(Filter.compile("correlated == false"));

qo.addFilter(Filter.eq("correlated", (Boolean>false));

Iterator result = context.search(Identity.class, qo);
while (result.hasNext()) {
    Identity user = (Identity)result.next();
    // do stuff here
}
```

- Is this better? Why?

API by Example

- Problem: Find all uncorrelated identities in the system.
- Solution: Use the API to search for only the correlated Identities' id values, then get the objects one at a time

```
QueryOptions qo = new QueryOptions();

qo.addFilter(Filter.eq("correlated", (Boolean)false));

Iterator result = context.search(Identity.class, qo, "id");
while (result.hasNext()) {
    String userId = (String)result.next()[0];
    Identity user = (Identity)context.getObjectById(Identity.class, userId);
    // Do Stuff
}
```

- Positives? Why is this better?

Questions?

Exercise Preview

Section 3, Exercises 4, 5

- Exercise 4: Using Rules to Learn the API
- Exercise 5: Running Tasks Sequentially and Running Rules on a Schedule
- Exercise 6: Compiling and Deploying a Custom Task