M.Gayathri
192472074

1. A csv file is imported into pandas, but the first row of actual data is wrongly treated as column names, what is the best correction?

A. Use header=None while reading the wiles

2. A Dataset has 25 columns, but only Age, salary, and Department are required for analysis. Why should only these columns be selected?

A. To reduce unnecessary data processing

3. A manager wants employees from the IT department with salary above ₹ 60,000. which command is correct?

A. df[df['Department']=='IT') & (df['salary']>60000)]

4. A student dataset is filtered using:

df[df['Marks']>=50]

what does this operation Return?

A. Students who scored 50 or above

5. A dataset has 40% missing values in one column. what is the most Analytical concern before filling missing value

A. whether missingness may affect the reliability of analysis

6. Mean imputation is most suitable when:

A. The numerical data is approxematately symetric.

7. A symmetric column contains a few very high exclusive-ly salaries. which method is more suitable?

A. Median.

8. A city column contains missing values. which method is usually suitable?

A. Replace the missing values with most frequent city.

9. A dataset has 10,000 rows, and only 12 rows contain missing values. what is a reasonable approach?

A. Drop all the 12 incomplete rows.

10. A company wants to identify the top 5 highest-paid employees which sequence is most appropriate?

A. sort salary in descending order and select first 5 rows.

11. A school wants to sort students first by class and then by Marks in descending order within each class.

A. df.sort_values['class', 'Marks'].ascending = [True, False])

12. A sales dataset cointains Region, Prodeut and sales. To Find the Total sales for each region and product combination. which operation is best?

A df.groupby(['Region', 'product'])['sales'].sum()

13. A college wants to compare average Marks department-wise. which result best support this Analysis?

A. Mean Marks grouped by department

14. A company wants partment-wise average salary and Maximum salary. which command is suitable?

A. df.groupby('Department')['salary'].agg(['mean','max'])

15. Two students have the same mark. what does ranking help identify?

A. It assigns relative positions while handling ties based on rank method.

16. A company wants to rank employees by salary within each department. which command is correct?

A. df['Rank'] = df.groupby('Department')['salary'].rank(ascending=False)

17. A Researcher wants to compare average Marks of five Department. which visualization is most suitable?

A. Bar chart.

18. A company Records monthly profit for 24months. which chart gives the best analytical understanding of growth.

A. Line chart

19. A Dataset contains Advertising Budget and Sales Revenue

A. Scatter plot.

20. A Dataset contains employee salaries, and the analyst suspects some extremely high salaries. which visualisation is most useful?

A. Box plot.