MYRRHA Handover — HTML Slide Design Guide

1. Slide structure

Every slide is one `<section class="slide">` with:
- `<h1>` title (project blue `#0b3d91`)
- optional `.sub` subtitle (muted)
- `.content` body — markdown-rendered
- optional `.caption` (italic, muted)
- optional `.notes` (dashed top border, accent-highlighted TODO/REVIEW/ACTION)

2. Color scheme (from `master/config.yaml`)

Token	Hex	Use
primary	`#0b3d91`	titles, labels, links
accent	`#ff8a00`	review markers, CTAs
bg	`#f7f8fa`	page background
fg	`#1b1f24`	body text
rule	`#d8dde3`	borders, dividers

3. Typography

- **Body / headings:** Aptos (fallbacks: Segoe UI, system-ui)
- **Code / ASCII / mono:** Consolas (fallbacks: JetBrains Mono, Courier New)
- ASCII trees, code blocks, table IDs, and operating-point values are **always** in mono.

4. Layout templates

Layout	Grid	When to use
`text-only`	`1fr`	hierarchy, exec summary, roadmap
`text-table`	`1.618fr 1fr` (golden)	argument + supporting table
`text-graph`	`1.618fr 1fr`	argument + chart
`4-quadrants`	`1fr 1fr / 1fr 1fr`	comparative analysis

5. Smart labeling system

Prefix	Domain	Examples
`B`	Design arguments	B1 baseline, B2 ALaT, B3 LKT
`G`	Graphs	G1, G2, G3
`T`	Tables	T1, T2
`E`	Equations	E1, E2
`F`	Figures (incl. ASCII)	F1

Cross-reference syntax in markdown: `See **G1** in graphs.html`.
The renderer auto-numbers within each artifact page; IDs declared in `master/slides.md` front-matter (`caption: F1 — …`) are preserved verbatim.

6. Outline numbering

Slides are ordered by `slides_order` in `master/config.yaml`. Each slide carries a sequential pill `n/N` plus its layout name. Argument labels (B1..B5) link directly back to `truth.html`.