Python For Data Science *Cheat Sheet*

PvSpark - SQL Basics

Learn Python for data science Interactively at www.DataCamp.com



PvSpark & Spark SQL

Spark SQL is Apache Spark's module for working with structured data.



Initializing SparkSession

A SparkSession can be used create DataFrame, register DataFrame as tables, execute SQL over tables, cache tables, and read parquet files.

```
>>> from pyspark.sql import SparkSession
>>> spark = SparkSession \
       .builder \
       .appName("Python Spark SQL basic example") \
       .config("spark.some.config.option", "some-value") \
```

Creating DataFrames

From RDDs

```
>>> from pyspark.sql.types import *
 Infer Schema
>>> sc = spark.sparkContext
>>> lines = sc.textFile("people.txt")
>>> parts = lines.map(lambda l: l.split(","))
>>> people = parts.map(lambda p: Row(name=p[0],age=int(p[1])))
>>> peopledf = spark.createDataFrame(people)
Specify Schema
>>> people = parts.map(lambda p: Row(name=p[0],
                                      age=int(p[1].strip())))
>>> schemaString = "name age"
>>> fields = [StructField(field name, StringType(), True) for
field name in schemaString.split()]
>>> schema = StructType(fields)
>>> spark.createDataFrame(people, schema).show()
      name|age
      Mine| 28
  Filip 29
Jonathan 30
```

From Spark Data Sources

```
>>> df = spark.read.json("customer.json")
>>> df.show()
                address|age|firstName |lastName|
                                                            phoneNumber|
 [New York, 10021, N... | 25 | New York, 10021, N... | 21 |
                                          Smith [[212 555-1234,ho...]
Doe [[322 888-1234,ho...]
                                  Jane
>>> df2 = spark.read.load("people.json", format="json")
Parquet files
>>> df3 = spark.read.load("users.parguet")
>>> df4 = spark.read.text("people.txt")
```

Duplicate Values

>>> df = df.dropDuplicates()

Queries

```
>> from pyspark.sql import functions as F
Select
>>> df.select("firstName").show()
                                                  Show all entries in firstName column
>>> df.select("firstName","lastName") \
      .show()
                                                  Show all entries in firstName, age
>>> df.select("firstName",
                "age",
                                                   and type
                explode("phoneNumber") \
               .alias("contactInfo")) \
       .select("contactInfo.type",
                "firstName",
                "age") \
       .show()
>>> df.select(df["firstName"],df["age"]+ 1) Show all entries in firstName and age,
       .show()
                                                  add 1 to the entries of age
>>> df.select(df['age'] > 24).show()
                                                  Show all entries where age >24
When
>>> df.select("firstName",
                                                  Show firstName and o or 1 depending
                 F.when(df.age > 30, 1) \
                                                  on age >30
                .otherwise(0)) \
       show()
```

Show firstName if in the given options

Return substrings of firstName

Show age: values are TRUE if between

Like

```
>>> df.select("firstName",
                                                   Show firstName, and lastName is
                df.lastName.like("Smith")) \ TRUE if lastName is like Smith
       .show()
 Startswith - Endswith
>>> df.select("firstName",
                                                   Show firstName, and TRUE if
                df.lastName \
                                                   lastName starts with Sm
                   .startswith("Sm")) \
       .show()
>>> df.select(df.lastName.endswith("th")) \ Show last names ending in th
       .show()
```

>>> df[df.firstName.isin("Jane", "Boris")]

.collect()

>>> df.select(df.firstName.substr(1, 3) \ .collect()

Between >>> df.select(df.age.between(22, 24)) \

Add, Update & Remove Columns

Adding Columns

```
>>> df = df.withColumn('city',df.address.city)
           .withColumn('postalCode', df.address.postalCode) \
           .withColumn('state', df.address.state) \
           .withColumn('streetAddress',df.address.streetAddress) \
           .withColumn('telePhoneNumber',
                       explode(df.phoneNumber.number)) \
           .withColumn('telePhoneType',
                       explode(df.phoneNumber.type))
```

.alias("name"))

Updating Columns

>>> df = df.withColumnRenamed('telePhoneNumber', 'phoneNumber')

Removing Columns

```
>>> df = df.drop("address", "phoneNumber")
>>> df = df.drop(df.address).drop(df.phoneNumber)
```

Inspect Data

```
>>> df.dtypes
                                       Return df column names and data types
>>> df.show()
                                      Display the content of df
>>> df.head()
                                       Return first n rows
>>> df.first()
                                       Return first row
>>> df.take(2)
                                      Return the first n rows
>>> df.schema
                                      Return the schema of df
```

```
>>> df.describe().show()
                                   Compute summary statistics
>>> df.columns
                                   Return the columns of df
>>> df.count()
                                   Count the number of rows in df
                                   Count the number of distinct rows in df
>>> df.distinct().count()
>>> df.printSchema()
                                   Print the schema of df
>>> df.explain()
                                   Print the (logical and physical) plans
```

GroupBy

```
>>> df.groupBy("age")\
      .count() \
      .show()
```

Group by age, count the members in the groups

Filter

```
>>> df.filter(df["age"]>24).show() Filter entries of age, only keep those
                                             records of which the values are >24
```

Sort

```
>>> peopledf.sort(peopledf.age.desc()).collect()
>>> df.sort("age", ascending=False).collect()
>>> df.orderBy(["age","city"],ascending=[0,1])\
     .collect()
```

Missing & Replacing Values

```
>>> df.na.fill(50).show() Replace null values
                            Return new df omitting rows with null values
>>> df.na.drop().show()
                             Return new df replacing one value with
>>> df.na \
       .replace(10, 20) \
       .show()
```

Repartitioning

```
>>> df.repartition(10)\
                                                df with 10 partitions
      .rdd \
      .getNumPartitions()
>>> df.coalesce(1).rdd.getNumPartitions() df with1partition
```

Running SQL Queries Programmatically

Registering DataFrames as Views

```
>>> peopledf.createGlobalTempView("people")
>>> df.createTempView("customer")
>>> df.createOrReplaceTempView("customer")
```

Query Views

```
>>> df5 = spark.sql("SELECT * FROM customer").show()
>>> peopledf2 = spark.sql("SELECT * FROM global temp.people") \
```

Output

Data Structures

```
>>> rdd1 = df.rdd
                                    Convert df into an RDD
>>> df.toJSON().first()
                                    Convert df into a RDD of string
>>> df.toPandas()
                                    Return the contents of df as Pandas
                                    DataFrame
```

Write & Save to Files

```
>>> df.select("firstName", "city")\
     .write \
      .save("nameAndCity.parquet")
>>> df.select("firstName", "age") \
      .save("namesAndAges.json",format="json")
```

Stopping SparkSession

```
>>> spark.stop()
```



