


Parallel Algorithms for Monte Carlo Linear Solvers

Stuart Slattery
Steven Hamilton
Tom Evans (PI)

Oak Ridge National Laboratory

March 17, 2015



Acknowledgments

This material is based upon work supported by the U.S. Department of Energy, Office of Science, Advanced Scientific Computing Research program.

This research used resources of the Oak Ridge Leadership Computing Facility at the Oak Ridge National Laboratory, which is supported by the Office of Science of the U.S. Department of Energy under Contract No. DE-AC05-00OR22725.

Motivation

- As we move towards exascale computing, the rate of errors is expected to increase dramatically
 - The probability that a compute node will fail during the course of a large scale calculation may be near 1
- Algorithms need to not only have increased concurrency/scalability but have the ability to recover from hardware faults
 - Lightweight machines
 - Heterogeneous machines
 - Both characterized by low power and high concurrency

Towards Exascale Concurrency and Resiliency

- Two basic strategies:
 - 1 Start with current “state of the art” methods and make incremental modifications to improve scalability and fault tolerance
 - Many efforts are heading in this direction, attempting to find additional concurrency to exploit
 - 2 Start with methods having natural scalability and resiliency aspects and work at improving performance (e.g. Monte Carlo)
 - Soft failures introduce an additional stochastic error component
 - Hard failures potentially mitigated by replication
 - Concurrency enabled by several levels of parallelism

Outline

- Monte Carlo Linear Solvers
- Domain Decomposition and Replication
- Scaling Studies
- Algorithm Variations
- Conclusions and Future Work

Monte Carlo Methods

Monte Carlo for Linear Systems

- Suppose we want to solve $\mathbf{Ax} = \mathbf{b}$
- If $\rho(\mathbf{I} - \mathbf{A}) < 1$, we can write the solution using the Neumann series

$$\mathbf{x} = \sum_{n=0}^{\infty} (\mathbf{I} - \mathbf{A})^n \mathbf{b} = \sum_{n=0}^{\infty} \mathbf{H}^n \mathbf{b}$$

where $\mathbf{H} \equiv (\mathbf{I} - \mathbf{A})$ is the Richardson iteration matrix

- Build the Neumann series stochastically

$$x_i = \sum_{k=0}^{\infty} \sum_{i_1}^N \sum_{i_2}^N \cdots \sum_{i_k}^N h_{i,i_1} h_{i_1,i_2} \cdots h_{i_{k-1},i_k} b_{i_k}$$

- Define a sequence of state transitions

$$\nu = i \rightarrow i_1 \rightarrow \cdots \rightarrow i_{k-1} \rightarrow i_k$$

Forward Monte Carlo

- Choose a row-stochastic matrix \mathbf{P} and weight matrix \mathbf{W} such that $\mathbf{H} = \mathbf{P} \circ \mathbf{W}$
- Typical choice (Monte Carlo Almost-Optimal):

$$\mathbf{P}_{ij} = \frac{|\mathbf{H}_{ij}|}{\sum_{j=1}^N |\mathbf{H}_{ij}|}$$

- To compute solution component \mathbf{x}_i :
 - Start a history in state i (with initial weight of 1)
 - Transition to new state j based probabilities determined by \mathbf{P}_i
 - Modify history weight based on corresponding entry in \mathbf{W}_{ij}
 - Add contribution to \mathbf{x}_i based on current history weight and value of \mathbf{b}_j
- A given random walk can only contribute to a single component of the solution vector with $\mathbf{x} \approx \mathbf{M}_{\text{MC}} \mathbf{b}$

Sampling Example (Forward Monte Carlo)

- Suppose

$$\mathbf{A} = \begin{bmatrix} 1.0 & -0.2 & -0.6 \\ -0.4 & 1.0 & -0.4 \\ -0.1 & -0.4 & 1.0 \end{bmatrix} \rightarrow \mathbf{H} \equiv (\mathbf{I} - \mathbf{A}) = \begin{bmatrix} 0.0 & 0.2 & 0.6 \\ 0.4 & 0.0 & 0.4 \\ 0.1 & 0.4 & 0.0 \end{bmatrix}$$

then

$$\mathbf{P} = \begin{bmatrix} 0.0 & 0.25 & 0.75 \\ 0.5 & 0.0 & 0.5 \\ 0.2 & 0.8 & 0.0 \end{bmatrix}, \quad \mathbf{W} = \begin{bmatrix} 0.0 & 0.8 & 0.8 \\ 0.8 & 0.0 & 0.8 \\ 0.5 & 0.5 & 0.0 \end{bmatrix}$$

- If a history is started in state 3, there is a 20% chance of it transitioning to state 1 and an 80% chance of moving to state 2

Solving the Heat Equation: Forward Method




Figure : **Forward solution.** 2.5×10^3 *total histories.*

Solving the Heat Equation: Forward Method




Figure : **Forward solution.** 2.5×10^4 *total histories.*

Solving the Heat Equation: Forward Method




Figure : **Forward solution.** 2.5×10^5 *total histories.*

Solving the Heat Equation: Forward Method




Figure : **Forward solution.** 2.5×10^6 *total histories.*

Domain Decomposition and Replication

Domain Decomposed Monte Carlo

- Each parallel process owns a piece of the domain (linear system)
- Random walks must be transported between adjacent domains through parallel communication
- Domain decomposition determined by the input system
- Load balancing not yet addressed






Figure : Domain decomposition example illustrating how domain-to-domain transport creates communication costs.

Asynchronous Monte Carlo Transport Kernel

- General extension of the Milagro algorithm (LANL)
- Asynchronous nearest neighbor communication of histories
- System-tunable communication parameters of buffer size and check frequency (performance impact)
- Need an asynchronous strategy for exiting the transport loop without a collective (running sum)



Exiting the Transport Loop without Collectives




Figure : Master/Slave




Figure : Binary Tree




Figure : Weak scaling absolute efficiency


Replication

Different batches of Monte Carlo samples can be combined in summation via superposition if they have different random number streams. For two different batches:

$$\mathbf{M}_{\text{MC}}\mathbf{x} = \frac{1}{2}(\mathbf{M}_1 + \mathbf{M}_2)\mathbf{x}$$

Consider each of these batches independent *subsets* of a Monte Carlo operator where now the operator can be formed as a general additive decomposition of N_S subsets:

$$\mathbf{M}_{\text{MC}} = \frac{1}{N_S} \sum_{n=1}^{N_S} \mathbf{M}_n$$

We replicate the linear problem and form each subset on a different group of parallel processes. Applying the subsets to a vector requires an AllReduce to form the sum. Each subset is domain decomposed. 

Scaling Studies

Parallel Test - Simplified P_N (SP_N) Assembly Problem




Figure : SP_N solution example

The (SP_N) equations are an approximation to the Boltzmann neutron transport equation used to simulate nuclear reactors

$$-\nabla \cdot \mathbb{D}_n \nabla \mathbf{U}_n + \sum_{m=1}^4 \mathbb{A}_{nm} \mathbf{U}_m = \frac{1}{k} \sum_{m=1}^4 \mathbb{F}_{nm} \mathbf{U}_m$$

Scaling problem – 1×1 to 17×17 array of fuel assemblies with 289 pins each resolved by a 2×2 spatial mesh and 200 axial zones

- 7 energy groups, 1 angular moment, 1.6M to 273.5M degrees of freedom
- 64 to 10,800 computational cores via domain decomposition
- We are usually interested in solving generalized eigenvalue problem - we use the operator from these problems to test the kernel scaling

Monte Carlo Communication Parameters

		Message Check Frequency			
		128	256	512	1 024
Message Buffer Size	256	1.054	1.061	1.076	1.076
	512	1.103	1.146	1.211	1.270
	1 024	1.062	1.088	1.133	1.176
	2 048	1.030	1.042	1.072	1.107
	4 096	1.010	1.012	1.025	1.050
	8 192	1.001	1.000	1.008	1.018
	16 384	1.017	1.003	1.010	1.009

- OLCF Eos: 736-node Cray XC30, Intel Xeon E5-2670, 11,776 cores, 47 TB memory, Cray Aries interconnect
- 64 cores, 1.6M DOFs, history length of 15, 3 histories per DOF
- 27% decrease in runtime observed for bad parameter choices
- Worth the time to do this parameter study when running on new hardware

Monte Carlo Scaling

Cores	DOFs	DOFs/Core	Time Min (s)	Time Max (s)	Time Ave (s)	Efficiency
256	273 509 600	1 068 397	260.53	260.54	260.54	1.00
1 024	273 509 600	267 099	61.92	61.92	61.92	1.05
4 096	273 509 600	66 775				
7 744	273 509 600	35 319				
10 816	273 509 600	25 288				

Table : Strong Scaling

Cores	DOFs	DOFs/Core	Time Min (s)	Time Max (s)	Time Ave (s)	Efficiency
64	1 618 400	25 288	6.432	6.432	6.432	1.00
256	6 473 600	25 288	6.493	6.493	6.493	0.99
1 024		25 288				
4 096		25 288				
7 744		25 288				
10 816		25 288				

Table : Weak Scaling

Subsets	Cores	DOFs	Time Min (s)	Time Max (s)	Time Ave (s)	Efficiency
1	256	6 473 600	6.493	6.493	6.493	1.00
2	512	6 473 600				
3	768	6 473 600				
4	1 024	6 473 600				

Table : Replication Scaling. 256 cores per subset.

Algorithm Variations

Monte Carlo Synthetic Acceleration (MCSA)

- Devised by Evans and Mosher in the 2000's as an acceleration scheme for radiation diffusion problems (LANL)
- Can be abstracted as a general linear solver with Monte Carlo as a preconditioner
- First Richardson step hits the high frequency error modes and second Monte Carlo step hits the low frequency error modes

$$\begin{aligned}\mathbf{r}^k &= \mathbf{b} - \mathbf{A}\mathbf{x}^k \\ \mathbf{x}^{k+1/2} &= \mathbf{x}^k + \mathbf{r}^k \\ \mathbf{r}^{k+1/2} &= \mathbf{b} - \mathbf{A}\mathbf{x}^{k+1/2} \\ \mathbf{x}^{k+1} &= \mathbf{x}^{k+1/2} + \mathbf{M}_{\text{MCR}}\mathbf{r}^{k+1/2}\end{aligned}$$

Matrix-Free Algorithm

- At each application of \mathbf{M}_{MC} , execute the Monte Carlo process
- Must perform Monte Carlo every time you want to apply with a better approximation requiring more time and more operations
- Variations in random number streams are amortized over iterations
- Vast majority of solve time spent doing Monte Carlo

L	N_S	MC Time (s)	MC Fraction	MCSA Iters
3	1	30.885	0.96	266
3	2	60.869	0.98	261
5	1	27.422	0.97	180
5	2	54.319	0.98	175
10	1	23.871	0.98	102
10	2	45.551	0.99	97
15	1	50.395	0.98	164
15	2	42.951	0.99	69
15	3	65.292	0.99	68
25	1	-	-	-
25	2	70.505	0.99	78
25	3	63.677	1.00	47

Table : MCSA performance. A had 115 600 rows and 1 186 464 non-zero entries.

Stochastic Approximate Inverse Algorithm

- Construct \mathbf{M}_{MC} as a sparse matrix by executing the Monte Carlo process once and tallying the row entries
- Use this operator as a stochastic approximation to the inverse
- A better approximation to the inverse requires more setup time and more storage
- We will investigate a drop tolerance strategy to control sparsity

L	N_S	NNZ	NNZ Ratio	MC Time (s)	Setup Time (s)	MCSA Iters
3	2	484 714	0.41	0.104	0.671	255
3	3	622 123	0.52	0.145	0.705	255
5	2	783 153	0.66	0.158	0.737	185
5	3	1 032 573	0.87	0.237	0.831	171
5	4	1 241 442	1.05	0.302	0.906	171
10	3	1 969 540	1.66	0.433	1.061	95
10	4	2 416 572	2.04	0.570	1.214	95
15	3	2 867 005	2.42	0.645	1.317	132
15	4	3 544 181	2.99	0.833	1.534	67
15	5	4 157 269	3.50	1.029	1.765	66

Table : MCSA Performance. A had 115 600 rows and 1 186 464 non-zero entries.

Unpreconditioned Algorithm Comparison

- No preconditioning, serial computation, fastest MCSA times reported
- GMRES easier to preconditioner - performance here only indicates Monte Carlo potential
- These results indicate good stochastic approximate inverse performance for traditional CPU architectures
- Matrix-free approach may be more effective when vectorized for new architectures by favoring operations over storage - 95%+ of the runtime spent in Monte Carlo

Solver	Setup Time (s)	Solve Time (s)	Total Time (s)	Iters
MCSA Matrix-Free	2.104	24.389	26.493	102
MCSA Approximate Inverse	2.953	0.779	3.731	95
Belos GMRES	1.791	1.021	2.812	81

Table : A had 115 600 rows and 1 186 464 non-zero entries.

Conclusions and Future Work

Conclusions

- Monte Carlo methods offer great potential for both resilient and highly parallel solvers
- A fully asynchronous algorithm provides a scheme without collectives
- Good scaling demonstrated so far on reasonably load balanced problems
- Replication a potential resiliency strategy with some overhead
- Matrix-free and stochastic approximate inverse algorithms are complementary - trade operations for storage

Current and Future Work

- Vectorization an area of active research with a focus on heterogeneous architectures (Titan and Summit)
- Multiple threading models are being explored (Kokkos, HPX, etc.)
- Extending methods to broader problem areas is significant algorithmic challenge and an attractive area for continued research
- Performance modeling and resiliency simulations this FY