



The Path of Leaping Stones

author : Charef Amine

Difficulty: medium

Description

You are an adventurer traversing the legendary Path of Leaping Stones, a mystical trail made of floating stones suspended over a bottomless abyss. Each stone "stones[i]" holds a number—the maximum number of stones you can leap forward from there so if "stones[i]=3, u can leap by 1 or 2 or 3 stones.

You begin your journey on the first stone (index 0), and your goal is to safely reach the final stone (last index). But beware—some stones may not allow you to leap far enough to continue your journey.

Write a function to determine whether it is possible to reach the final stone using only forward leaps based on each stone's power.

Example 1

Input : stones = 4 2 0 0 2 0 1

Output: True

Explanation:

- Start at index 0 (value = 4), you can jump to any of index 1 through 4.
- Let's jump to index 4 (value = 2).



- From index 4, jump to index 6 (value = 1).
- From index 6, you're already at the final stone — mission accomplished!

Example 2

Input: stones = 2 0 1 0 0 0 1

Output: False

Explanation:

- Start at index 0 (value = 2), you can jump to index 1 or 2.
- Index 1 has value 0 — dead end.
- Index 2 has value 1, lets you jump to index 3.
- Index 3 = 0 → stuck again.
- You cannot reach past index 3, so you'll never get to the last stone.

Example 3

Input: stones = 3 2 1 0 4

Output: False

Explanation:

- You will always arrive at index 3 (val==0) no matter what. Its maximum jump length is 0, which makes it impossible to reach the last index.

Example 4

Input: stones = 0

Output: True

Explanation:

- You are already at the last stone.

Constraints:



- $1 \leq \text{stones.length} \leq 10^4$
- $0 \leq \text{stones}[i] \leq 10^5$