

CONTENTS INCLUDE:

- Core Spring Annotations
- Spring MVC Annotations
- AspectJ Annotations
- JSR-250 Annotations
- Testing Annotations
- Hot Tips and more...

Spring Annotations

By Craig Walls

SPRING ANNOTATIONS

From its beginning, Spring's most common means of configuration has been XML-based. But as developers grow weary of navigating through a seemingly endless maze of angle-brackets, some have started looking for other ways to wire the beans in their Spring-enabled applications. Spring has responded with several annotation-driven configuration options. In this reference card, you'll find a guide to all of the annotations supported in Spring 2.5.

CORE SPRING ANNOTATIONS

Context Configuration Annotations

These annotations are used by Spring to guide creation and injection of beans.

Annotation	Use	Description
@Autowired	Constructor, Field, Method	Declares a constructor, field, setter method, or configuration method to be autowired by type. Items annotated with @Autowired do not have to be public.
@Configurable	Type	Used with <context:spring-configured> to declare types whose properties should be injected, even if they are not instantiated by Spring. Typically used to inject the properties of domain objects.
@Order	Type, Method, Field	Defines ordering, as an alternative to implementing the org.springframework.core.Ordered interface.
@Qualifier	Field, Parameter, Type, Annotation Type	Guides autowiring to be performed by means other than by type.
@Required	Method (setters)	Specifies that a particular property must be injected or else the configuration will fail.
@Scope	Type	Specifies the scope of a bean, either singleton, prototype, request, session, or some custom scope.

Autowiring Bean Properties

A typical Spring bean might have its properties wired something like this:

```
<bean id="pirate" class="Pirate">
  <constructor-arg value="Long John Silver" />
  <property name="treasureMap" ref="treasureMap" />
</bean>
```

But it's also possible to have Spring automatically inject a bean's properties from other beans in the context. For example, if the Pirate class were annotated with @Autowired like this...

```
public class Pirate {
  private String name;
  private TreasureMap treasureMap;
  public Pirate(String name) { this.name = name; }
```

Autowiring Bean Properties, continued

```
@Autowired
public void setTreasureMap(TreasureMap treasureMap) {
  this.treasureMap = treasureMap;
}
```

...and if you were to configure annotation configuration in Spring using the <context:annotation-configuration> element like this...

```
<beans ... >
  <bean id="pirate" class="Pirate">
    <constructor-arg value="Long John Silver" />
  </bean>
  <bean id="treasureMap" class="TreasureMap" />
  <context:annotation-config />
</beans>
```

...then the "treasureMap" property will be automatically injected with a reference to a bean whose type is assignable to TreasureMap (in this case, the bean whose ID is "treasureMap").

Autowiring Without Setter Methods

@Autowired can be used on any method (not just setter methods). The wiring can be done through any method, as illustrated here:

```
@Autowired
public void directionsToTreasure(TreasureMap
treasureMap) {
  this.treasureMap = treasureMap;
}
```

And even on member variables:

```
@Autowired
private TreasureMap treasureMap;
```

To resolve any autowiring ambiguity, use the @Qualifier attribute with @Autowired.

```
@Autowired
@Qualifier("mapToTortuga")
private TreasureMap treasureMap;
```



Get More Refcardz (They're free!)

- Authoritative content
- Designed for developers
- Written by top experts
- Latest tools & technologies
- Hot tips & examples
- Bonus content online
- New issue every 1-2 weeks

Subscribe Now for FREE!
Refcardz.com

Ensuring That Required Properties are Set

To ensure that a property is injected with a value, use the `@Required` annotation:

```
@Required
public void setTreasureMap(TreasureMap treasureMap) {
    this.treasureMap = treasureMap;
}
```

In this case, the “treasureMap” property must be injected or else Spring will throw a `BeanInitializationException` and context creation will fail.

Stereotyping Annotations

These annotations are used to stereotype classes with regard to the application tier that they belong to. Classes that are annotated with one of these annotations will automatically be registered in the Spring application context if `<context:component-scan>` is in the Spring XML configuration.

In addition, if a `PersistenceExceptionTranslationPostProcessor` is configured in Spring, any bean annotated with `@Repository` will have `SQLExceptions` thrown from its methods translated into one of Spring’s unchecked `DataAccessExceptions`.

Annotation	Use	Description
<code>@Component</code>	Type	Generic stereotype annotation for any Spring-managed component.
<code>@Controller</code>	Type	Stereotypes a component as a Spring MVC controller.
<code>@Repository</code>	Type	Stereotypes a component as a repository. Also indicates that <code>SQLExceptions</code> thrown from the component’s methods should be translated into Spring <code>DataAccessExceptions</code> .
<code>@Service</code>	Type	Stereotypes a component as a service.

Automatically Configuring Beans

In the previous section, you saw how to automatically wire a bean’s properties using the `@Autowired` annotation. But it is possible to take autowiring to a new level by automatically registering beans in Spring. To get started with automatic registration of beans, first annotate the bean with one of the stereotype annotations, such as `@Component`:

```
@Component
public class Pirate {
    private String name;
    private TreasureMap treasureMap;

    public Pirate(String name) { this.name = name; }

    @Autowired
    public void setTreasureMap(TreasureMap treasureMap) {
        this.treasureMap = treasureMap;
    }
}
```

Then add `<context:component-scan>` to your Spring XML configuration:

```
<context:component-scan
    base-package="com.habuma.pirates" />
```

The `base-package` annotation tells Spring to scan `com.habuma.pirates` and all of its subpackages for beans to automatically register.

You can specify a name for the bean by passing it as the value of `@Component`.

```
@Component("jackSparrow")
public class Pirate { ... }
```



Specifying Scope For Auto-Configured Beans

By default, all beans in Spring, including auto-configured beans, are scoped as singleton. But you can specify the scope using the `@Scope` annotation. For example:

```
@Component
@Scope("prototype")
public class Pirate { ... }
```

This specifies that the pirate bean be scoped as a prototype bean.

Creating Custom Stereotypes

Autoregistering beans is a great way to cut back on the amount of XML required to configure Spring. But it may bother you that your autoregistered classes are annotated with Spring-specific annotations. If you’re looking for a more non-intrusive way to autoregister beans, you have two options:

1. Create your own custom stereotype annotation. Doing so is as simple as creating a custom annotation that is itself annotated with `@Component`:

```
@Component
public @interface MyComponent {
    String value() default "";
}
```

2. Or add a filter to `<context:component-scan>` to scan for annotations that it normally would not:

```
<context:component-scan
    base-package="com.habuma.pirates">
    <context:include-filter type="annotation"
        expression="com.habuma.MyComponent" />
    <context:exclude-filter type="annotation"
        expression="
            "org.springframework.stereotype.Component" />
</context:component-scan>
```

In this case, the `@MyComponent` custom annotation has been added to the list of annotations that are scanned for, but `@Component` has been excluded (that is, `@Component`-annotated classes will no longer be autoregistered).

Regardless of which option you choose, you should be able to autoregister beans by annotating their classes with the custom annotation:

```
@MyComponent
public class Pirate { ...}
```

Spring MVC Annotations

These annotations were introduced in Spring 2.5 to make it easier to create Spring MVC applications with minimal XML configuration and without extending one of the many implementations of the Controller interface.

Annotation	Use	Description
<code>@Controller</code>	Type	Stereotypes a component as a Spring MVC controller.
<code>@InitBinder</code>	Method	Annotates a method that customizes data binding.
<code>@ModelAttribute</code>	Parameter, Method	When applied to a method, used to preload the model with the value returned from the method. When applied to a parameter, binds a model attribute to the parameter.

table continues on next page

Spring MVC Annotations, continued

Annotation	Use	Description
@RequestMapping	Method, Type	Maps a URL pattern and/or HTTP method to a method or controller type.
@RequestParam	Parameter	Binds a request parameter to a method parameter.
@SessionAttributes	Type	Specifies that a model attribute should be stored in the session.

Setting up Spring for Annotated Controllers

Before we can use annotations on Spring MVC controllers, we'll need to add a few lines of XML to tell Spring that our controllers will be annotation-driven. First, so that we won't have to register each of our controllers individually as `<bean>`s, we'll need a `<context:component-scan>`:

```
<context:component-scan
base-package="com.habuma.pirates.mvc"/>
```

In addition to autoregistering `@Component`-annotated beans, `<context:component-scan>` also autoregisters beans that are annotated with `@Controller`. We'll see a few examples of `@Controller`-annotated classes in a moment.

But first, we'll also need to tell Spring to honor the other Spring MVC annotations. For that we'll need `<context:annotation-config>`:

```
<context:annotation-config/>
```



Use a conventions-based view resolver.

If you use a conventions-based view resolver, such as Spring's `UrlBasedViewResolver` or `InternalResourceViewResolver`, along with `<context:component-scan>` and `<context:annotation-config>`, you can grow your application indefinitely without ever touching the Spring XML again.

Creating a Simple MVC Controller

The following `HomePage` class is annotated to function as a Spring MVC controller:

```
@Controller
@RequestMapping("/home.htm")
public class HomePage {
    @RequestMapping(method = RequestMethod.GET)
    public String showHomePage(Map model) {
        List<Pirate> pirates = pirateService.
            getPirateList();
        model.add("pirateList", pirates);
        return "home";
    }
    @Autowired
    PirateService pirateService;
}
```

There are several important things to point out here. First, the `HomePage` class is annotated with `@Controller` so that it will be autoregistered as a bean by `<context:component-scan>`. It is also annotated with `@RequestMapping`, indicating that this controller will respond to requests for `"/home.htm"`.

Within the class, the `showHomePage()` method is also annotated with `@RequestMapping`. In this case, `@RequestMapping` indicates that HTTP GET requests to `"/home.htm"` will be handled by the `showHomePage()` method.

Creating a Form-Handling Controller

In a pre-2.5 Spring MVC application, form-processing controllers would typically extend `SimpleFormController` (or some similar base class). But with Spring 2.5, a form-processing controller just has a method that is annotated to handle the HTTP POST request:

Creating a Form-Handling Controller, continued

```
@Controller
@RequestMapping("/addPirate.htm")
public class AddPirateFormController {
    @RequestMapping(method = RequestMethod.GET)
    public String setupForm(ModelMap model) {
        return "addPirate";
    }
    @ModelAttribute("pirate")
    public Pirate setupPirate() {
        Pirate pirate = new Pirate();
        return pirate;
    }
    @RequestMapping(method = RequestMethod.POST)
    protected String addPirate(@ModelAttribute("pirate")
        Pirate pirate) {
        pirateService.addPirate(pirate);
        return "pirateAdded";
    }
    @Autowired
    PirateService pirateService;
}
```

Here the `@RequestMapping` annotation is applied to two different methods. The `setupForm()` method is annotated to handle HTTP GET requests while the `addPirate()` method will handle HTTP POST requests. Meanwhile, the `@ModelAttribute` is also pulling double duty by populating the model with a new instance of `Pirate` before the form is displayed and then pulling the `Pirate` from the model so that it can be given to `addPirate()` for processing.

Transaction Annotations

The `@Transactional` annotation is used along with the `<tx:annotation-driven>` element to declare transactional boundaries and rules as class and method metadata in Java.

Annotation	Use	Description
@Transactional	Method, Type	Declares transactional boundaries and rules on a bean and/or its methods.

Annotating Transactional Boundaries

To use Spring's support for annotation-declared transactions, you'll first need to add a small amount of XML to the Spring configuration:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/
beans"
    xmlns:tx="http://www.springframework.org/schema/tx"
    xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
    xsi:schemaLocation="http://www.springframework.org/
schema/beans
http://www.springframework.org/schema/beans/
springbeans-2.5.xsd
http://www.springframework.org/schema/tx
http://www.springframework.org/schema/tx/spring-tx-
2.5.xsd">
    <tx:annotation-driven />
    ...
</beans>
```

The `<tx:annotation-driven>` element tells Spring to keep an eye out for beans that are annotated with `@Transactional`. In addition, you'll also need a platform transaction manager bean declared in the Spring context. For example, if your application uses Hibernate, you'll want to include the `HibernateTransactionManager`:

```
<bean id="transactionManager"
    class="org.springframework.orm.hibernate3.
    HibernateTransactionManager">
    <property name="sessionFactory" ref="sessionFactory"
/>
</bean>
```

Annotating Transactional Boundaries, continued

With the basic plumbing in place, you're ready to start annotating the transactional boundaries:

```
@Transactional(propagation=Propagation.SUPPORTS,
readOnly=true)
public class TreasureRepositoryImpl implements
TreasureRepository {
...
    @Transactional(propagation=Propagation.REQUIRED,
readOnly=false)
    public void storeTreasure(Treasure treasure) { ...}
...
}
```

At the class level, `@Transactional` is declaring that all methods should support transactions and be read-only. But, at the method-level, `@Transactional` declares that the `storeTreasure()` method requires a transaction and is not read-only.

Note that for transactions to be applied to `@Transactional`-annotated classes, those classes must be wired as beans in Spring.

JMX Annotations

These annotations, used with the `<context:mbean-export>` element, declare bean methods and properties as MBean operations and attributes.

Annotations	Use	Description
<code>@ManagedAttribute</code>	Method	Used on a setter or getter method to indicate that the bean's property should be exposed as a MBean attribute.
<code>@ManagedNotification</code>	Type	Indicates a JMX notification emitted by a bean.
<code>@ManagedNotifications</code>	Type	Indicates the JMX notifications emitted by a bean.
<code>@ManagedOperation</code>	Method	Specifies that a method should be exposed as a MBean operation.
<code>@ManagedOperationParameter</code>	Method	Used to provide a description for an operation parameter.
<code>@ManagedOperationParameters</code>	Method	Provides descriptions for one or more operation parameters.
<code>@ManagedResource</code>	Type	Specifies that all instances of a class should be exposed as MBeans.

Exposing a Spring Bean as a MBean

To get started with Spring-annotated MBeans, you'll need to include `<context:mbean-export>` in the Spring XML configuration: `<context:mbean-export/>`

Then, you can annotate any of your Spring-managed beans to be exported as MBeans:

```
@ManagedResource(objectName="pirates:name=PirateService")
public interface PirateService {
    @ManagedOperation(
        description="Get the pirate list")
    public List<Pirate> getPirateList();
}
```

Here, the `PirateService` has been annotated to be exported as a MBean and its `getPirateList()` method is a managed operation.

ASPECTJ ANNOTATIONS

For defining aspects, Spring leverages the set of annotations provided by AspectJ.

Annotation	Use	Description
<code>@Aspect</code>	Type	Declares a class to be an aspect.
<code>@After</code>	Method	Declares a method to be called after a pointcut completes.

Aspect J Annotations, continued

Annotation	Use	Description
<code>@AfterReturning</code>	Method	Declares a method to be called after a pointcut returns successfully.
<code>@AfterThrowing</code>	Method	Declares a method to be called after a pointcut throws an exception.
<code>@Around</code>	Method	Declares a method that will wrap the pointcut.
<code>@Before</code>	Method	Declares a method to be called before proceeding to the pointcut.
<code>@DeclareParents</code>	Static Field	Declares that matching types should be given new parents—that is, it introduces new functionality into matching types.
<code>@Pointcut</code>	Method	Declares an empty method as a pointcut placeholder method.

What's important to note, however, is that while you can use AspectJ annotations to define Spring aspects, those aspects will be defined in the context of Spring AOP and will not be handled by the AspectJ runtime. This is significant because Spring AOP is limited to proxying method invocations and does not provide for the more exotic pointcuts (constructor interception, field interception, etc.) offered by AspectJ.

Annotating Aspects

To use AspectJ annotations to create Spring aspects, you'll first need to provide a bit of Spring XML plumbing:

```
<beans xmlns="http://www.springframework.org/schema/
beans"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:aop="http://www.springframework.org/schema/aop"
xsi:schemaLocation="http://www.springframework.org/
schema/beans
http://www.springframework.org/schema/beans/
spring-beans-2.5.xsd
http://www.springframework.org/schema/aop
http://www.springframework.org/schema/aop/spring-
aop-2.5.xsd">
...
<aop:aspectj-autoproxy/>
...
</beans>
```

The `<aop:aspectj-autoproxy>` element tells Spring to watch for beans annotated with AspectJ annotations and, if it finds any, to use them to create aspects. Then you can annotate bean classes to be aspects:

```
@Aspect
public class ChantySinger {
    @Pointcut("execution(* Pirate.plunder(..))")
    public void plunderPC() {}

    @Before("plunderPC()")
    public void singYoHo() {
        ...
    }

    @AfterReturning("plunderPC()")
    public void singAPiratesLifeForMe() {
        ...
    }
}
```

This simple annotation-based aspect has a pointcut that is triggered by the execution of a `plunder()` method on the `Pirate` class. Before the `Pirate.plunder()` method is executed, the `singYoHo()` method is called. Then, after the `Pirate.plunder()` method returns successfully, the `singAPiratesLifeForMe()`

Annotating Aspects, continued

method is invoked. (For more advanced examples of AspectJ annotations, see the AspectJ documentation at <http://www.eclipse.org/aspectj/docs.php>.)

Note the rather odd looking `plunderPC()` method. It is annotated with `@Pointcut` to indicate that this method is a pointcut placeholder. The key thing here is that the most interesting stuff happens in the annotation itself and not in the method. In fact, pointcut placeholder methods must be empty methods and return void.

JSR-250 ANNOTATIONS

In addition to Spring's own set of annotations, Spring also supports a few of the annotations defined by JSR-250, which is the basis for the annotations used in EJB 3.

Annotation	Use	Description
<code>@PostConstruct</code>	Method	Indicates a method to be invoked after a bean has been created and dependency injection is complete. Used to perform any initialization work necessary.
<code>@PreDestroy</code>	Method	Indicates a method to be invoked just before a bean is removed from the Spring context. Used to perform any cleanup work necessary.
<code>@Resource</code>	Method, Field	Indicates that a method or field should be injected with a named resource (by default, another bean).

Wiring Bean Properties with `@Resource`

Using `@Resource`, you can wire a bean property by name:

```
public class Pirate {
    @Resource
    private TreasureMap treasureMap;
}
```

In this case, Spring will attempt to wire the "treasureMap" property with a reference to a bean whose ID is "treasureMap". If you'd rather explicitly choose another bean to wire into the property, specify it to the name attribute:

```
public class Pirate {
    @Resource(name="mapToSkullIsland")
    private TreasureMap treasureMap;
}
```

Initialization and Destruction Methods

Using JSR-250's `@PostConstruct` and `@PreDestroy` methods, you can declare methods that hook into a bean's lifecycle. For example, consider the following methods added to the Pirate class:

```
public class Pirate {
    ...
    @PostConstruct
    public void wakeUp() {
        System.out.println("Yo ho!");
    }
    @PreDestroy
    public void goAway() {
        System.out.println("Yar!");
    }
}
```

As annotated, the `wakeUp()` method will be invoked just after Spring instantiates the bean and `goAway()` will be invoked just before the bean is removed from the Spring container.

TESTING ANNOTATIONS

These annotations are useful for creating unit tests in the JUnit 4 style that depend on Spring beans and/or require a transactional context.

Annotation	Use	Description
<code>@AfterTransaction</code>	Method	Used to identify a method to be invoked after a transaction has completed.
<code>@BeforeTransaction</code>	Method	Used to identify a method to be invoked before a transaction starts.
<code>@ContextConfiguration</code>	Type	Configures a Spring application context for a test.
<code>@DirtiesContext</code>	Method	Indicates that a method dirties the Spring container and thus it must be rebuilt after the test completes.
<code>@ExpectedException</code>	Method	Indicates that the test method is expected to throw a specific exception. The test will fail if the exception is not thrown.
<code>@IfProfileValue</code>	Type, Method	Indicates that the test class or method is enabled for a specific profile configuration.
<code>@NotTransactional</code>	Method	Indicates that a test method must not execute in a transactional context.
<code>@ProfileValueSourceConfiguration</code>	Type	Identifies an implementation of a profile value source. The absence of this annotation will cause profile values to be loaded from system properties.
<code>@Repeat</code>	Method	Indicates that the test method must be repeated a specific number of times.
<code>@Rollback</code>	Method	Specifies whether or not the transaction for the annotated method should be rolled back or not.
<code>@TestExecutionListeners</code>	Type	Identifies zero or more test execution listeners for a test class.
<code>@Timed</code>	Method	Specifies a time limit for the test method. If the test does not complete before the time has expired, the test will fail.
<code>@TransactionConfiguration</code>	Type	Configures test classes for transactions, specifying the transaction manager and/or the default rollback rule for all test methods in a test class.

Writing a Spring-Aware Test

The key to writing a Spring-aware test is to annotate the test class with `@RunWith`, specifying `SpringJUnit4ClassRunner` as the class runner behind the test:

```
@RunWith(SpringJUnit4ClassRunner.class)
public class PirateTest {
    ...
}
```

In this case, the Spring test runner will try to load a Spring application context from a file named `PirateTest-context.xml`. If you'd rather specify one or more XML files to load the application context from, you can do that with `@ContextConfiguration`:

```
@RunWith(SpringJUnit4ClassRunner.class)
@ContextConfiguration(locations = { "pirates.xml" })
public class PirateTest {
    ...
}
```

With test configured to load a Spring application context, you now may request that Spring autowire properties of the test class with beans from the Spring context:

Writing a Spring-Aware Test, continued

```
@RunWith(SpringJUnit4ClassRunner.class)
@ContextConfiguration(locations = { "pirates.xml" })
public class PirateTest {
    @Autowired
    private Pirate pirate;
    @Autowired
    private TreasureMap treasureMap;
    @Test
    public void annotatedPropertyShouldBeAutowired() {
        assertNotNull(pirate.getTreasureMap());
        assertEquals(treasureMap, pirate.getTreasureMap());
    }
}
```


In this case, the pirate and treasureMap properties will be wired with the beans whose ID are "pirate" and "treasureMap", respectively.

Accessing the Spring Context in a Test

If you need the Spring application context itself in a test, you can autowire it into the test the same as if it were a bean in the context:

```
@RunWith(SpringJUnit4ClassRunner.class)
@ContextConfiguration(locations = { "pirates.xml" })
public class PirateTest {
    @Autowired
    private Pirate pirate;
    @Autowired
    private ApplicationContext applicationContext;
    @Test
    public void annotatedPropertyShouldBeAutowired() {
        assertNotNull(pirate.getTreasureMap());
        assertEquals(applicationContext.
            getBean("treasureMap"), pirate
                .getTreasureMap());
    }
}
```

ABOUT THE AUTHOR



Craig Walls

Craig Walls is a Texas-based software developer with more than 13 years experience working in the telecommunication, financial, retail, educational, and software industries. He's a zealous promoter of the Spring Framework, speaking frequently at local user groups and conferences and writing about Spring on his blog. When he's not slinging code, Craig spends as much time as he can with his wife, two daughters, six birds, three dogs, and an ever-fluctuating number of tropical fish.

Publications

- *Spring in Action, 2nd Edition*, 2007
- *XDoclet in Action*, 2003

Blog

- <http://www.springinaction.com>

Projects

- Committer to XDoclet project;
- Originator of Portlet and Spring modules for XDoclet

RECOMMENDED BOOK



Spring in Action, 2nd Edition is a practical and comprehensive guide to the Spring Framework, the framework that forever changed enterprise Java development. What's more, it's also the first book to cover the new features and capabilities in Spring 2.

BUY NOW

books.dzone.com/books/spring-in-action

Want More? **Download Now.** Subscribe at refcardz.com

Upcoming Refcardz:

- Core CSS: Part II
- Core CSS: Part III
- SOA Patterns
- Scalability and High
- Agile Methodologies
- Getting Started with PHP
- Core Java
- JUnit
- MySQL
- Seam

Available:

Published September 2008

- Getting Started with JPA
- Core CSS: Part I
- Struts 2

Published August 2008

- Very First Steps in Flex
- C#
- Groovy
- Core .NET

Published July 2008

- NetBeans IDE 6.1 Java Editor
- RSS and Atom
- GlassFish Application Server
- Silverlight 2
- IntelliJ IDEA


Published June 2008

- jQuerySelectors
- Flexible Rails: Flex 3 on Rails 2

Published May 2008

- Windows PowerShell
- Dependency Injection in EJB 3

Visit <http://refcardz.dzone.com> for a complete listing of available Refcardz.



Design Patterns
Published June 2008



DZone communities deliver over 3.5 million pages per month to more than 1.5 million software developers, architects and designers. DZone offers something for every developer, including news, tutorials, blogs, cheatsheets, feature articles, source code and more. "DZone is a developer's dream," says PC Magazine.

DZone, Inc.
1251 NW Maynard
Cary, NC 27513

888.678.0399
919.678.0300

Refcardz Feedback Welcome
refcardz@dzone.com

Sponsorship Opportunities
sales@dzone.com

ISBN-13: 978-1-934238-29-5
ISBN-10: 1-934238-29-5



\$7.95