
```
mysqlコード
//department のテーブル作成
CREATE TABLE department(
departmentID int,
departmentName varchar(255)
);
```

INSERT INTO department VALUES(1,"開発部"); INSERT INTO department VALUES(2,"営業部"); INSERT INTO department VALUES(3,"総務部");

SELECT * FROM department;

XAMPP for Windows - mysql -h localhost -u root



```
//stationのテーブル作成
CREATE TABLE station(
stationID int,
stationName varchar(255)
);
INSERT INTO station
VALUES(1,"九段下");
INSERT INTO station
VALUES(2,"永田町");
INSERT INTO station
VALUES(3,"渋谷");
INSERT INTO station
VALUES(4,"神保町");
INSERT INTO station
VALUES(5,"上井草");
SELECT *
FROM station;
```

XAMPP for Windows - mysql -h localhost -u root

```
//userのテーブル作成
CREATE TABLE user(
userID int PRIMARY KEY,
name varchar(255),
tell varchar(255),
age int,
birthday date,
departmentID int REFFERENCES department(departmentID),
stationID int REFFERENCES station(stationID)
);
INSERT INTO user
VALUES(1,"田中実","012-345-6789",30,"1994-02-01",3,1);
INSERT INTO user
VALUES(2,"鈴木茂","090-1122-3344",37,"1987-08-12",3,4);
INSERT INTO user
VALUES(3,"鈴木実","080-5566-7788",24,"2000-12-24",2,5);
INSERT INTO user
VALUES(4,"佐藤清","012-0987-6543",19,"2005-08-01",1,5);
INSERT INTO user
VALUES(5,"高橋清","090-9900-1234",24,"2000-12-24",3,5);
SELECT*
```

SELECT * FROM user;

XAMPP for Windows - mysql -h localhost -u root

