

Quantifying the accuracy of OpenStreetMap for longitudinal cycling-infrastructure change: A reproducible validation framework using Google Street View

Abstract

Cities are rapidly expanding their cycling networks to promote sustainable mobility, yet robust longitudinal data needed to evaluate change are scarce. OpenStreetMap (OSM) provides a global, time-stamped record of urban infrastructure, but its reliability for detecting change remains uncertain. This study quantified the temporal accuracy of OSM for identifying cycling-infrastructure additions and removals, using Barcelona (2015–2023) as a case study within a reproducible open-source workflow **with manual validation using street-level imagery**.

We reconstructed baseline and follow-up cycling-infrastructure networks from dated OSM snapshots and applied geometric differencing to detect change. A stratified sampling design based on population density and centrality was used to validate detected changes against historical Google Street View (GSV) imagery, allowing estimation of precision, recall, and F1 scores. OSM-derived estimates indicate an 80.3% increase in cycling-infrastructure length, from 130.7 km to 235.7 km. For additions, validation shows high recall (0.96) and strong precision (0.82), indicating that OSM captures most network expansions. For removals, recall is high (1.00) but precision is low (0.20; $n = 5$), **with wide uncertainty given the small sample. Apparent losses may reflect mapping edits rather than real infrastructure change.**

By quantifying detection accuracy, this study provides a framework for calibrating OSM-based measures of infrastructure change. OSM snapshot differencing can serve as a scalable screening approach for identifying infrastructure additions, while apparent removals require cautious interpretation and verification to avoid mapping artefacts being mistaken for physical infrastructure loss. This calibration strengthens longitudinal research by reducing exposure misclassification in public health, transport safety, and urban equity.

1 Introduction

In recent years, many cities worldwide have expanded their cycling-infrastructure network in pursuit of cleaner, healthier and more equitable mobility (Szell et al. 2022; Buehler and Pucher 2021). Reliable data on how these networks evolve are essential for evidence-based planning and robust longitudinal research (Hirsch et al. 2016). Such data enable researchers and policymakers to examine how infrastructure change relates to mode choice, safety and equity (Houde et al. 2018; Prince et al. 2025).

Yet longitudinal infrastructure data are often incomplete or inconsistent. Official inventories are rarely maintained systematically across years, and field audits, although precise, are resource-intensive and difficult to replicate at scale (Winters et al. 2025; Dai et al. 2024). In the absence of consistent data, researchers and policymakers must rely on fragmented sources, increasing the risk of exposure misclassification and biased impact estimates (Batomen et al. 2026). As a result, comparable evidence on cycling-infrastructure change remains limited, constraining both robust research and informed policy development (Houde et al. 2018).

The growing availability of Volunteered Geographic Information (VGI) offers new opportunities to address these data gaps (Goodchild 2007). Among such sources, OpenStreetMap (OSM) stands out for providing open, editable, and time-stamped spatial data on a wide range of urban features, making it a valuable

resource for reconstructing historical infrastructure networks and studying urban infrastructure change over time (Minghini and Frassinelli 2019; Zhang and Pfoser 2019).

Early comparisons with **official datasets** suggest that OSM can achieve good positional accuracy and substantial agreement in mapped features (Haklay 2010; Girres and Touya 2010). However, its use for longitudinal change analysis remains more uncertain. OSM data quality varies across space and time, and edits may reflect not only real-world changes but also evolving mapping practices, including delayed or retrospective updates (Barron et al. 2014; Senaratne et al. 2017; Minghini and Frassinelli 2019). In addition, tagging practices and compliance can vary across local contexts, introducing further heterogeneity in how features are represented (Almendros-Jiménez and Becerra-Terón 2018). This uncertainty in timing can influence analytical results when historical OSM snapshots are used as proxies for real-world change (Schmidl et al. 2021; Juhász 2021).

Cycling infrastructure poses additional challenges because some facilities, particularly on-street cycle lanes, are represented as attributes of road segments rather than as independent geometries. This makes them less visually distinct, harder to map consistently, and more prone to omission or incorrect tagging (Hochmair et al. 2015; Ferster et al. 2023). Despite these challenges, empirical comparisons with reference datasets suggest that OSM can provide useful cycling-infrastructure inventories in many contexts, although agreement varies across cities and infrastructure types and depends on consistent tagging practices (Ferster et al. 2020). Evidence also suggests that OSM bicycle-infrastructure data quality varies spatially, particularly outside dense urban cores (Vierø et al. 2025).

Importantly, recent work has shown the value of OSM histories for measuring cycling-infrastructure network growth at scale, providing a scalable alternative when consistent historical **official datasets** are unavailable (Bres et al. 2023; Winters et al. 2025). At the same time, these studies highlight that observed changes can reflect both real-world infrastructure change and improvements in mapping and tagging.

For this reason, OSM-derived changes require independent validation. To assess whether changes detected from historical OSM snapshots reflect real on-street changes, an external source of evidence is needed. Street-level imagery, including Google Street View (GSV), has increasingly been used to audit and validate built-environment features remotely (Rundle et al. 2011; Askari et al. 2025; Hanibuchi et al. 2019). However, to our knowledge, no study has yet provided a **transparent**, reproducible end-to-end workflow that combines OSM snapshot differencing, probability-based stratified sampling, and GSV-based verification to quantify precision and recall of cycling-infrastructure change.

Building on this gap, this study aims to quantify the temporal accuracy of OSM-derived cycling-infrastructure change. Using Barcelona over the 2015–2023 period as a case study, we implement a reproducible open-source workflow that combines longitudinal snapshot differencing with probability-based stratified validation against historical GSV imagery. The selected time window aligns with a broader research project examining infrastructure change across policy-relevant governance periods, although the present paper focuses exclusively on methodological validation. Detection performance is evaluated using precision, recall, and F1 scores. By integrating change detection and external validation within a transparent **workflow with fully reproducible computational components and structured manual validation**, the study provides a framework for calibrating OSM-based measures of infrastructure change.

2 Data and methods

2.1 Study setting

Barcelona is a large, dense Mediterranean city in northeastern Spain (around 1.7 million inhabitants within the municipal boundary) with an extensive and evolving cycling network. Between 2015 and 2023, the city experienced substantial cycling-infrastructure expansion, generating measurable network change over time. These dynamics make Barcelona a suitable case for evaluating OSM-based network reconstruction, change detection, and validation procedures.

2.2 Data sources

We used three data sources. OpenStreetMap (OSM) extracts for Barcelona were retrieved for 1 January 2016 and 1 January 2024 using the `osmextract` R package (Gilardi and Lovelace 2025); these Geofabrik snapshots were used as proxies for baseline and follow-up network conditions, representing infrastructure as mapped at the end of 2015 and 2023, respectively. Historical Google Street View (GSV) panoramas were used to manually validate a sample of OSM-detected cycling-infrastructure additions and removals, selecting imagery closest to the baseline and follow-up reference periods. Census-tract boundaries (2015) and resident population counts (2022) were obtained from official statistical sources and used to design a stratified validation sample based on population density and centrality.

2.3 Analytical workflow

The analysis follows a five-step workflow (Figure 1), implemented as a single pipeline with reproducible computational steps and structured manual validation. Steps 1–2 detect cycling-infrastructure change, while Steps 3–5 evaluate these detections using stratified GSV validation.

Step 1. Build OSM cycling-infrastructure networks

We constructed baseline and follow-up cycling-infrastructure networks from the dated OSM extracts described above, representing 2015 and 2023 conditions. From each extract, we derived a core cycling-infrastructure network intended to represent bicycle-specific, physically visible infrastructure encoded by the segment geometry. A segment was classified as cycling infrastructure if either (i) it was mapped as a dedicated cycleway (`highway = cycleway`), or (ii) it was a street segment carrying explicit cycleway tags indicating a lane or track. In the second case, we searched cycleway-related keys (e.g., `cycleway`, `cycleway:left`, `cycleway:right`, `cycleway:both`, and other `cycleway:*` variants) and retained segments where any value matched `{lane, track, opposite_lane, opposite_track}` (OpenStreetMap contributors, n.d.). Values were matched case-insensitively and, where multiple values were present, a segment was retained if any value matched the set above.

To reduce duplication from parallel OSM representations of the same facility (e.g., a dedicated cycle track mapped as a separate geometry while a cycle lane is also tagged on the adjacent carriageway), we applied a no-double-counting (NDC) rule. Specifically, on-road cycle-lane segments were excluded when they overlapped with nearby dedicated cycling infrastructure, defined as cases where at least 20 m of the lane segment and at least 50% of its length fell within a 15 m buffer around dedicated cycling geometries. The 15 m proximity threshold reflects typical spatial offsets between carriageway-centreline representations and adjacent segregated cycle tracks in dense urban settings, while remaining conservative enough to avoid conflating distinct facilities on opposite sides of wide corridors. The additional requirements of a minimum 20 m overlap and at least 50% segment inclusion ensure that exclusions reflect substantive parallel representation rather than incidental geometric proximity.

Step 2. Detect OSM network change

Cycling-infrastructure change between the baseline and follow-up networks was detected using geometric differencing in a projected CRS. First, each network was dissolved and buffered by 10 m to accommodate minor geometric misalignments and small positional edits. This tolerance absorbs small positional shifts introduced by re-digitisation or geometry refinement, while remaining conservative relative to typical urban carriageway widths. Additions were defined as segments present in the 2023 proxy network but absent from the buffered 2015 proxy network; removals were defined analogously as segments present in the 2015 proxy network but absent from the buffered 2023 proxy network. Resulting fragments shorter than 10 m were discarded to remove small artefacts arising from geometric differencing.

To avoid counting positional edits in OSM as real infrastructure change, we flagged likely realignments as cases where an added segment lay within 15 m of a corresponding removed segment, reflecting small shifts in mapped geometry rather than substantive infrastructure modification. These cases were excluded from the validation evaluation pool. The 15 m proximity threshold served a distinct purpose from the differencing buffer: it was intended to capture cases where added and removed fragments likely represent the




Figure 1: Five-step workflow for OSM-based change detection and GSV-based validation. Steps 1–2 reconstruct cycling-infrastructure networks and detect change from historical OSM snapshots, while Steps 3–5 evaluate these detections using stratified manual validation with GSV imagery.

same infrastructure feature that has been re-drawn, split, or slightly shifted in OSM rather than physically removed and rebuilt.

To define control locations and support the identification of false negatives, we constructed a non-cycling comparison pool (NONCYC) consisting of general street segments that did not meet the cycling-infrastructure tagging criteria. NONCYC candidates were restricted to standard road classes (`highway` $\in$ {`primary`, `secondary`, `tertiary`, `unclassified`, `residential` and corresponding link classes, `living_street`, `pedestrian`}). To ensure a clear separation between cycling and non-cycling locations, we excluded any NONCYC candidate geometries located within 10 m of cycling infrastructure in either reference year (2015 proxy or 2023 proxy). Resulting fragments shorter than 10 m were discarded to remove small geometric artefacts.

The robustness of results to key geometric parameter choices (buffer distance, realignment threshold, and minimum segment length) was assessed through dedicated sensitivity analyses (see Section 3.1 and Supplement S1).

Step 3. Design stratified GSV sample

To evaluate the accuracy of OSM-detected cycling-infrastructure changes, we designed a stratified GSV validation across Barcelona’s 1,063 census tracts by population density and centrality (2015; Figure 2 a). Population density was calculated as the 2022 resident population per square kilometre for each tract, using official census counts and tract area. Centrality was operationalised as a simple, reproducible proxy for inner vs outer areas, measured via Euclidean distance to Plaça Catalunya. Each variable was divided into terciles, and their combination produced nine density–centrality strata (D1_C1 to D3_C3). From each stratum, six tracts were randomly selected (total $n = 54$).

Within each sampled tract, we attempted to sample up to two OSM-detected additions, two removals, and one NONCYC control segment. Segments were sampled with probability proportional to their length, so longer segments were more likely to be selected than shorter fragments. Candidate segments were split at census-tract boundaries before sampling so that segment length (and therefore sampling probability) was calculated only within each tract.

Each sampled segment was converted to a single validation point located at its mid-length position (Figure 2 b). Points were linked to the nearest available GSV panorama and exported to a structured coding workbook (Supplement S2). The same points were also provided in an interactive map with direct Street View links (Supplement S3).

Step 4. Inspect and code GSV

Each validation site was independently coded by two trained coders following a standardised protocol (Supplement S4). Coders assessed whether cycling infrastructure was present in a baseline and follow-up period corresponding to the OSM reference snapshots. When the nearest panorama did not provide a clear view of the sampled location, coders were permitted to adjust the Street View position slightly along the same street segment, provided that the original sampled point remained visible and spatially identifiable. For each site and period, coders recorded infrastructure presence/absence and the month of the imagery used.

Because GSV imagery availability varies across locations and years, coders prioritised imagery as close as possible to the reference dates. For the baseline period, coders attempted 2016 and 2015 first (using 2014 only as a fallback when required); for the follow-up period, coders attempted 2024 and 2023 first (using 2022 only as a fallback when required). When multiple candidate years were available, the observation closest in time to the reference date was selected to define the baseline and follow-up values.

Sites were coded as missing when available imagery did not allow a clear determination of cycling-infrastructure presence for the reference period (e.g., obscured views, roadworks, or ambiguous visual evidence). Missing observations were excluded from analyses of change, as these require clear identification of both baseline and follow-up conditions to determine whether a change occurred. Intercoder agreement was assessed on usable sites, and any discrepancies were resolved through reconciliation to produce the reconciled validation dataset (Supplement S5).




Figure 2: Outputs used in the validation design: (a) Bivariate tract stratification; (b) Validation points by type.

Step 5. Evaluate OSM performance

Using the reconciled baseline and follow-up GSV observations, we evaluated whether OSM snapshot differencing correctly identified additions and removals of cycling infrastructure. For segments flagged as additions, a true positive (TP) corresponded to a 0→1 transition between baseline and follow-up, whereas a false positive (FP) corresponded to no change (0→0) or persistence of cycling infrastructure (1→1). For segments flagged as removals, a TP corresponded to a 1→0 transition, whereas an FP corresponded to no change (1→1) or no cycling infrastructure in either period (0→0). NONCYC control locations were used to identify false negatives (FN), defined as cycling-infrastructure changes visible in GSV but not detected by OSM differencing. Examples of TP additions and removals are shown in Figure 3.

Validation performance was summarised using standard classification metrics. Precision, recall and the F1 score were computed as:

$$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}, \quad F_1 = \frac{2 \cdot \text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}.$$

Pooled metrics were computed by first aggregating TP, FP and FN across addition and removal events, and then calculating precision, recall and the F1 score from these pooled counts. For precision and recall, 95% confidence intervals were computed using Wilson score intervals for the corresponding numerators and denominators, which provide stable coverage for proportions, particularly with small sample sizes or extreme values.

All data processing, change detection, sampling, and validation procedures were implemented in an open-source R workflow. Code availability is detailed in the Data and code availability section.



(a)



(b)



(c)



(d)

Figure 3: Examples of true positive changes identified during GSV validation: (a–b) addition ($0 \rightarrow 1$), from no cycling infrastructure in 2015 to a newly implemented segregated cycle track in 2023; (c–d) removal ($1 \rightarrow 0$), from a cycle track in 2015 to its absence in 2023 following street redesign.

3 Results

3.1 Network change detected from OSM (2015–2023)

Between 2015 and 2023, the OSM-derived cycling-infrastructure network in Barcelona increased from 130.7 to 235.7 km, corresponding to a net growth of 105.0 km, an 80.3 % increase (Figure 4). Network lengths were calculated as the summed length of cycling-infrastructure line geometries in OSM, without collapsing parallel or spatially separated facilities into a single corridor-level measure (e.g., cycle tracks on both sides of a street). Geometric differencing identified 127.1 km of added and 24.9 km of removed cycling infrastructure, yielding a net change of 102.2 km. The small discrepancy (−2.8 km) reflects minor geometric artefacts introduced by the buffering, dissolving, and fragment-filtering steps used in the differencing procedure, and indicates good internal consistency between aggregate network totals and change estimates (Table 1).

Table 1: Consistency between yearly totals and differencing estimates (2015–2023, Barcelona)

Metric	Value (km)
Total network length (2015)	130.7
Total network length (2023)	235.7
Net growth (2023 − 2015)	105.0
Additions	127.1
Removals	24.9
Additions − removals	102.2
Gap: (Additions − removals) − Net	-2.8

As an external consistency check, we compared OSM-derived network length over time with official municipal data for Barcelona. OSM estimates indicate an increase from 130.7 km to 235.7 km between 2015 and 2023, while the official data show a comparable increase from 133.0 km to 234.0 km over the same period. This close agreement suggests that the OSM-derived estimates capture the overall growth pattern observed in the official record. The comparison is used as an aggregate consistency check, while the GSV-based validation remains the basis for assessing whether detected additions and removals correspond to visible on-street changes. Official municipal data were obtained from the Àrea Metropolitana de Barcelona for 2015 and from the Barcelona Open Data portal for 2023 (Àrea Metropolitana de Barcelona 2015; Ajuntament de Barcelona 2023).

Given the reliance on geometric parameters in Step 2, we assessed robustness to geometric parameter choices, we conducted sensitivity checks varying the differencing buffer (5 m, 10 m, 15 m), minimum segment length (5 m, 10 m, 20 m), and realignment threshold (10 m, 15 m, 20 m). Net change estimates remained broadly stable across configurations, varying within approximately 8% of the baseline. Detected additions showed limited variation across parameter settings, whereas estimated removals were more sensitive, particularly to the realignment threshold. Across all configurations, additions consistently exceeded removals. Full results are provided in Supplement S5.

OSM-detected additions were unevenly distributed across the city. Low-density strata (D1_C1, D1_C2 and D1_C3) accounted for 60.0 % of all added length, with particularly large gains in low-density peripheral (D1_C1) and low-density central (D1_C3) areas (Table 2). Additions were also substantial in medium-density central tracts (D2_C3) and high-density central tracts (D3_C3), indicating that expansion was not confined to the urban periphery. In contrast, removals were limited in total length and were more unevenly distributed, with the largest shares observed in low-density central areas (D1_C3; 37.7 %) and low-density peripheral areas (D1_C1; 28.8 %), while all other strata each accounted for less than 12 % of removed length.

Table 2: OSM-estimated additions and removals (2015–2023) by density $\times$ centrality stratum. Totals may differ slightly from the aggregate city-level estimates because change segments are split at census-tract boundaries before aggregation.

Stratum	Definition	Added (km)	Removed (km)	Added (%)	Removed (%)
D1_C1	Low density, peripheral	31.0	7.0	24	29
D1_C2	Low density, intermediate	16.0	1.0	13	4
D1_C3	Low density, central	29.0	9.0	23	38
D2_C1	Medium density, peripheral	2.0	0.0	2	2
D2_C2	Medium density, intermediate	11.0	1.0	9	6
D2_C3	Medium density, central	15.0	3.0	12	11
D3_C1	High density, peripheral	1.0	0.0	1	0
D3_C2	High density, intermediate	10.0	1.0	8	5
D3_C3	High density, central	12.0	1.0	9	5
TOTAL	All strata combined	126.8	24.8	100	100

3.2 Validation of OSM-detected changes using GSV

Of the 105 sampled sites (39 additions, 6 removals and 50 non-cycling control sites), 86 (82%) provided usable GSV panoramas for both the baseline and follow-up periods, yielding 33 additions, 5 removals and 48 non-cycling control sites for analysis (Table 3). **These validation points correspond to a sample drawn from a total of 946 OSM-detected change segments (850 additions and 96 removals) in the filtered evaluation dataset (after excluding short fragments and likely realignments). From this pool, 45 change segments (39 additions and 6 removals) were sampled for validation, corresponding to approximately 4.8% of all eligible change candidates. The final number of usable validation observations is lower due to the requirement for valid GSV imagery in both reference periods.** These validation points were distributed across all density–centrality strata, reflecting the stratified sampling design and the spatial availability of candidate change segments within the sampled tracts.

Table 3: Validation points by class and stratum (usable points only)

Stratum	Definition	Add	Remove	NONCYC	Total
D1_C1	Low density, peripheral	5	1	6	12
D1_C2	Low density, intermediate	5	0	4	9
D1_C3	Low density, central	6	0	5	11
D2_C1	Medium density, peripheral	2	2	6	10
D2_C2	Medium density, intermediate	4	0	6	10
D2_C3	Medium density, central	3	1	5	9
D3_C1	High density, peripheral	1	0	6	7
D3_C2	High density, intermediate	3	1	5	9
D3_C3	High density, central	4	0	5	9
TOTAL	All strata combined	33	5	48	86

Initial intercoder agreement on the binary presence/absence coding was 92% (79/86). The remaining 7 cases were resolved by consensus, and the **final** baseline and follow-up values were used in the accuracy analysis.

Table 4 summarises the validation outcomes. CI reflect sampling uncertainty in the GSV validation and are wider for classes with fewer usable sites. For additions, OSM shows high recall (0.96, 95 % CI [0.82–0.99]) and good precision (0.82, 95 % CI [0.66–0.91]), indicating that most real additions were detected, although some false positives remain. For removals, recall is 1.00 but with a very wide confidence interval due to the




Figure 4: OSM-detected cycling-infrastructure changes in Barcelona, 2015–2023.

small sample size ($n = 5$), while precision is very poor (0.20, 95 % CI [0.04–0.62]), suggesting that most OSM-detected removals do not correspond to true infrastructure loss. When pooling additions and removals, overall precision is 0.74, recall is 0.97, and the F1 score is 0.84, reflecting strong sensitivity to change but more limited specificity, particularly for removals.

Table 4: Validation metrics for OSM-inferred cycling-infrastructure changes (Barcelona, 2015–2023)

Class	n (usable)	TP	FP	FN	Precision (95% CI)	Recall (95% CI)	F1
ADD	33	27	6	1	0.82 [0.66-0.91]	0.96 [0.82-0.99]	0.89
REMOVE	5	1	4	0	0.20 [0.04-0.62]	1.00 [0.21-1.00]	0.33
Pooled	38	28	10	1	0.74 [0.58-0.85]	0.97 [0.83-0.99]	0.84

Note: ADD and REMOVE refer to segments present only in 2023 or 2015, respectively; Pooled combines both change types. Only change events are included ($n = 33 + 5 = 38$); NONCYC sites are used to identify false negatives and are not counted as observations. Confidence intervals are Wilson score intervals.

4 Discussion

This study quantified the temporal accuracy of OSM-derived cycling-infrastructure change in Barcelona (2015–2023) by combining longitudinal snapshot differencing with stratified GSV validation. To date, the available literature has either validated OSM cycling infrastructure cross-sectionally against reference datasets (Ferster et al. 2020; Hochmair et al. 2015), used OSM snapshots to measure cycling-network growth at scale without externally validating whether detected changes reflect on-street infrastructure change (Winters et al. 2025), or applied street-level imagery to audit built-environment features independently of OSM (Rundle et al. 2011). By designing and implementing a transparent end-to-end workflow combining historical network reconstruction, geometric differencing, stratified spatial sampling, and independent visual verification, we produce reproducible **computational outputs and transferable validation-based accuracy estimates** (precision, recall, and F1 score) for cycling-infrastructure change detection. Our workflow therefore provides a practical calibration strategy for longitudinal research using OSM when authoritative year-on-year inventories are unavailable.

As an additional external consistency check, we compared the temporal evolution of OSM-derived network length with official municipal data for Barcelona, one of the relatively few cities where consistent historical infrastructure data are available. The two sources show a broadly similar pattern of network growth over the study period, providing aggregate-level support for the plausibility of the OSM-derived estimates. This comparison is specific to the Barcelona case, while the proposed workflow is designed for application in contexts where such longitudinal official data are not available.

Overall, OSM performed well in detecting cycling-infrastructure additions, but performance was substantially weaker for removals. Although recall remained high for both change types, precision for removals was very low, **although estimates are based on a small number of validated cases. This suggests that many** apparent removals detected through snapshot differencing do not correspond to actual on-street cycling-infrastructure loss. These results highlight that OSM-derived removals must be carefully verified before estimating net changes in the cycling-infrastructure network.

To understand this asymmetry, it is important to consider how OSM records change over time. Because OSM objects can be split, merged, re-tagged, deleted, or recreated (Minghini and Frassinelli 2019), structural edits between snapshots may produce apparent removals without corresponding physical change on the street. This is especially likely for removals, as segments may disappear from a snapshot when they are re-drawn with new geometries, reclassified under different tags, or merged into adjacent features, even though the underlying infrastructure remains in place. Additions, in contrast, require the introduction of new geometries or tags and may therefore more often correspond to genuinely new on-street features. OSM-based differencing can

therefore over-detect removals when edits reflect changes in representation rather than physical interventions. This is consistent with the nature of OSM as a continuously edited VGI resource, in which objects are routinely revised rather than fixed as in a static dataset (Goodchild 2007).

From a practical perspective, for cities that lack consistently maintained inventories, OSM snapshot differencing can function as a screening tool for identifying likely infrastructure additions at scale, with targeted imagery checks providing an efficient quality-control layer. This matters because practitioners often need to monitor delivery (corridor completion, network coverage growth) and to allocate limited auditing resources; virtual audits have repeatedly been shown to reduce the burden of in-person observation while remaining usable for built-environment measurement (Rundle et al. 2011). Our results suggest that OSM-derived additions can be treated as generally informative, but apparent removals should not be interpreted as “rollback” without independent verification.

Beyond planning practice, these measurement characteristics also have implications for longitudinal research designs. Studies evaluating cycling interventions often rely on the timing and location of network changes to define exposure, treatment, and control conditions at the street or neighborhood level. When removals are over-detected, analyses can be substantially distorted, and even net growth can be biased in settings where apparent removals are more frequent than in Barcelona. More importantly, misclassifying segments as removed could bias estimates in longitudinal designs that depend on staggered implementation and upgrades. In this context, the observed precision values can be used to inform calibration of snapshot-differenced estimates. For example, scaling raw OSM change counts by change-specific precision (approximately 0.8 for additions and 0.2 for removals in the Barcelona case) provides an approximate adjustment for false positives when estimating net growth from OSM alone. However, calibration of removals remains uncertain due to the small number of validated removal cases and should be interpreted as indicative rather than definitive.

At a broader conceptual level, this study contributes to efforts to assess the temporal validity of OSM and other forms of VGI. Longitudinal applications of OSM require attention to how edits, reclassification, and representation changes may be expressed as apparent cycling-infrastructure change. The approach presented here provides a practical way to distinguish true interventions from mapping artefacts, supporting more robust use of OSM histories in transport, health, and urban studies.

5 Generalisability and limitations

The workflow developed in this study is designed to be transferable to other cities where historical OSM extracts are available and street-level imagery coverage is sufficient for validation. **Reproducibility is full for the computational components, while the validation stage relies on structured manual interpretation of imagery following a standardised protocol.** The main requirements are (i) consistent OSM snapshots for two reference years, (ii) a spatial sampling frame (e.g., census tracts or equivalent small areas), and (iii) imagery that allows adjudication of infrastructure presence at both time points.

Several limitations should be acknowledged. First, the **overall validation sample was relatively small (n = 86 usable sites), particularly for removals**, resulting in wide confidence intervals for removal-specific metrics. This reflects the scarcity of eligible removal candidates in the OSM-detected change pool under our cycling infrastructure definition and differencing rules, and the removal pool was further reduced by realignment filtering and incomplete GSV coverage for both reference periods. Sensitivity checks increasing the number of sampled tracts and candidate segments yielded only marginal gains in removal sites, indicating that removal sample size was constrained by event availability rather than by the sampling strategy. **In addition, while the sampling design follows a stratified approach across tracts with target quotas per tract (up to two additions, two removals, and one NONCYC segment), the final allocation is constrained by the availability of eligible change segments and usable GSV imagery. As a result, the validation sample reflects a structured but feasibility-constrained allocation rather than a strictly proportional or representative subset of all detected changes. This leads to imbalances across classes, particularly for removals, and implies that the reported metrics should be interpreted as conditional on the sampled validation set rather than as population-**

level estimates.

Second, GSV imagery dates vary within each anchor year and across locations, occasionally creating minor temporal mismatches with the OSM reference snapshots. This variability can blur the exact timing of change and may lead to a small number of misclassifications when cycling infrastructure was built, modified, or removed close to the snapshot dates. **Third, the validation relies on GSV as an observational reference rather than a direct measure of ground truth, which introduces additional sources of uncertainty.** Coverage is not uniform across space, and the requirement for imagery at both time points restricts the set of usable validation locations, potentially introducing selection bias towards better-covered areas. In addition, the visibility and interpretability of cycling infrastructure vary by type (e.g., segregated lanes versus painted or shared facilities), which may affect coding consistency. As such, the reported precision and recall should be interpreted as agreement conditional on observable locations rather than as a direct measure of absolute ground truth accuracy.

Fourth, the construction of the NONCYC control pool may influence the interpretation of recall. NONCYC candidates were generated from general street segments after excluding or cutting portions located within the tolerance buffer around cycling infrastructure in either reference year. This design provides a clearer and more interpretable non-cycling comparison pool, but it may reduce the likelihood of identifying false negatives near already mapped cycling facilities, potentially leading to an overestimation of recall. As a result, recall estimates should be interpreted as conditional on the sampling framework rather than as a comprehensive measure of missed cycling-infrastructure changes across the full street network.

Fifth, although inter-rater agreement was high, subtle interpretive differences, such as deciding whether a facility meets the definition of cycling infrastructure, remain possible, especially for borderline or mixed designs.

Sixth, the definition of cycling infrastructure used in this study is based on a specific set of OSM tags intended to provide a consistent representation of clearly defined, physically visible infrastructure. However, the way these tags are applied in practice may vary across cities. For example, facilities that would fall within our definition (e.g. painted lanes) may in some cases be represented using tags such as `cycleway=shared_lane`, which are excluded from our filter. This leads to context-dependent under-detection of cycling infrastructure. As a result, while the framework itself is transferable, the magnitude of underestimation may vary across contexts, with implications for completeness and cross-city comparability.

Seventh, Barcelona likely represents a relatively well-mapped OSM context, given the concentration of OSM contributors and higher mapped completeness in many European and high-income urban areas; future research should assess how this workflow performs in lower-activity contexts and where mapping practices and tag usage may evolve differently (Herfort et al. 2023).

Finally, while the proposed workflow is conceptually scalable, its application to much larger validation samples (e.g., thousands of sites) would face practical limitations. The validation relies on manual inspection of historical GSV imagery, which is time-intensive to scale. Importantly, currently available programmatic access options (e.g., the Google Street View API) do not provide systematic access to historical imagery across time points, which limits the feasibility of fully automated large-scale validation. These limitations should be considered when extending the approach to larger study areas or higher-resolution validation designs.

6 Conclusions

This study quantified the accuracy of OSM for detecting longitudinal cycling-infrastructure change by implementing and validating a reproducible snapshot-differencing framework in Barcelona (2015–2023). Using probability-based stratified GSV validation, we estimated precision, recall, and F1 scores for OSM-detected

additions and removals.

The results indicate that OSM-detected additions are generally reliable, whereas apparent removals identified through snapshot differencing often do not correspond to on-street cycling-infrastructure loss. This asymmetry suggests that OSM histories can be informative for tracking network expansion, but inferred removals should not be interpreted without independent verification or calibration.

By producing quantitative accuracy estimates within a transparent, transferable workflow, this study provides a practical basis for calibrating OSM-derived measures of cycling-infrastructure change and for accounting for measurement error in longitudinal evaluations. More broadly, the findings support the responsible use of OSM and other VGI sources for urban change analysis, while underscoring the need to validate temporal change signals before drawing substantive policy or behavioural inferences.

Data and code availability

The full reproducible workflow (R scripts and documentation) used in this study will be made publicly available in an online repository upon acceptance.

Supplements

The supplementary materials (S1–S5) are provided as separate files and are included with the peer-review submission.

S1. Sensitivity analysis of change-detection parameters (XLSX)

Provides the results of sensitivity checks for key geometric parameters used in the OSM change-detection workflow, including the differencing buffer, minimum segment length, and realignment threshold.

The table reports the total length of detected additions, removals, and net change under alternative parameter settings, along with deviations from the baseline configuration.

The baseline scenario corresponds to the default parameter configuration used in the analysis (10 m differencing buffer, 10 m minimum segment length, and 15 m realignment threshold). Values are computed on the filtered evaluation dataset (after excluding short fragments and likely realignments) and therefore differ from the raw network-level change estimates reported in `tbl-consistency`.

S2. Raw validation workbook (XLSX)

Contains the sampled segments and coding sheets completed independently by the two coders prior to reconciliation.

S3. Interactive maps (HTML)

Two standalone interactive HTML visualisations:

- validation points with direct Google Street View links;
- OSM change-detection map showing additions and removals.

The maps support zooming, panning, layer toggling, and inspection of individual validation points and network segments. They can be opened locally in any modern web browser (an internet connection is required to load basemap tiles).

S4. Google Street View validation protocol (PDF)

Details the standardised coding procedure, imagery selection rules, and reconciliation process.

S5. Reconciled validation results (XLSX)

Provides the reconciled validation dataset used to compute precision, recall, and F1 scores.

Declaration of Generative AI and AI-assisted technologies in the writing process

During the preparation of this manuscript the authors used ChatGPT (version 5.2) to support language editing and improve readability. All content was subsequently reviewed and edited by the authors, who take full responsibility for the final manuscript.

References

- Ajuntament de Barcelona. 2023. *Carril Bici Dataset (2023 T4)*. <https://opendata-ajuntament.barcelona.cat/data/es/dataset/carril-bici>.
- Almendros-Jiménez, Jesús M., and Antonio Becerra-Terón. 2018. “Analyzing the Tagging Quality of the Spanish OpenStreetMap.” *ISPRS International Journal of Geo-Information* 7 (8): 323. <https://doi.org/10.3390/ijgi7080323>.
- Àrea Metropolitana de Barcelona. 2015. *Carril Bici Dataset (December 2015)*.
- Askari, Sajad, Devon Snyder, Chu Li, Michael Saugstad, Jon E. Froehlich, and Yochai Eisenberg. 2025. “Validating Pedestrian Infrastructure Data: How Well Do Street-View Imagery Audits Compare to Government Field Data?” *Urban Science* 9 (4): 130. <https://doi.org/10.3390/urbansci9040130>.
- Barron, Christopher, Pascal Neis, and Alexander Zipf. 2014. “A Comprehensive Framework for Intrinsic OpenStreetMap Quality Analysis.” *Transactions in GIS* 18 (6): 877–95. <https://doi.org/10.1111/tgis.12073>.
- Batomen, Brice, Richard Wen, Joonsoo Lyeo, et al. 2026. “Pedaling Towards Safer Streets: Evaluating the Impact of Cycling Infrastructure on Road Safety.” *Accident Analysis & Prevention* 225 (February): 108308. <https://doi.org/10.1016/j.aap.2025.108308>.
- Bres, Raphaël, Veronika Peralta, Arnaud Le-Guilcher, Thomas Devogele, Ana-Maria Olteanu Raimond, and Cyril De Runz. 2023. “Analysis of Cycling Network Evolution in OpenStreetMap Through a Data Quality Prism.” *AGILE: GIScience Series* 4 (June): 1–9. <https://doi.org/10.5194/agile-giss-4-3-2023>.
- Buehler, Ralph, and John Pucher, eds. 2021. *Cycling for Sustainable Cities*. Urban and Industrial Environments. MIT Press.
- Dai, Shaoqing, Yuchen Li, Alfred Stein, Shujuan Yang, and Peng Jia. 2024. “Street View Imagery-Based Built Environment Auditing Tools: A Systematic Review.” *International Journal of Geographical Information Science* 38 (6): 1136–57. <https://doi.org/10.1080/13658816.2024.2336034>.
- Ferster, Colin, Jaimy Fischer, Kevin Manaugh, Trisalyn Nelson, and Meghan Winters. 2020. “Using OpenStreetMap to Inventory Bicycle Infrastructure: A Comparison with Open Data from Cities.” *International Journal of Sustainable Transportation* 14 (1): 64–73. <https://doi.org/10.1080/15568318.2018.1519746>.

- Ferster, Colin, Trisalyn Nelson, Kevin Manaugh, Jeneva Beirsto, Karen Laberee, and Meghan Winters. 2023. "Developing a National Dataset of Bicycle Infrastructure for Canada Using Open Data Sources." *Environment and Planning B: Urban Analytics and City Science* 50 (9): 2543–59. <https://doi.org/10.1177/23998083231159905>.
- Gilardi, Andrea, and Robin Lovelace. 2025. *Osmextract: Download and Import OpenStreetMap Data Extracts*. <https://docs.ropensci.org/osmextract/>.
- Girres, Jean-François, and Guillaume Touya. 2010. "Quality Assessment of the French OpenStreetMap Dataset." *Transactions in GIS* 14 (4): 435–59. <https://doi.org/10.1111/j.1467-9671.2010.01203.x>.
- Goodchild, Michael F. 2007. "Citizens as Sensors: The World of Volunteered Geography." *GeoJournal* 69 (4): 211–21. <https://doi.org/10.1007/s10708-007-9111-y>.
- Haklay, Mordechai. 2010. "How Good Is Volunteered Geographical Information? A Comparative Study of OpenStreetMap and Ordnance Survey Datasets." *Environment and Planning B: Planning and Design* 37 (4): 682–703. <https://doi.org/10.1068/b35097>.
- Hanibuchi, Tomoya, Tomoki Nakaya, and Shigeru Inoue. 2019. "Virtual Audits of Streetscapes by Crowdworkers." *Health & Place* 59 (September): 102203. <https://doi.org/10.1016/j.healthplace.2019.102203>.
- Herfort, Benjamin, Sven Lautenbach, João Porto de Albuquerque, Jennings Anderson, and Alexander Zipf. 2023. "A Spatio-Temporal Analysis Investigating Completeness and Inequalities of Global Urban Building Data in OpenStreetMap." *Nature Communications* 14 (1): 3985. <https://doi.org/10.1038/s41467-023-39698-6>.
- Hirsch, Jana A., Katie A. Meyer, Marc Peterson, et al. 2016. "Obtaining Longitudinal Built Environment Data Retrospectively Across 25 Years in Four US Cities." *Frontiers in Public Health* 4 (April). <https://doi.org/10.3389/fpubh.2016.00065>.
- Hochmair, Hartwig H., Dennis Zielstra, and Pascal Neis. 2015. "Assessing the Completeness of Bicycle Trail and Lane Features in OpenStreetMap for the United States." *Transactions in GIS* 19 (1): 63–81. <https://doi.org/10.1111/tgis.12081>.
- Houde, Maxime, Philippe Apparicio, and Anne-Marie Séguin. 2018. "A Ride for Whom: Has Cycling Network Expansion Reduced Inequities in Accessibility in Montreal, Canada?" *Journal of Transport Geography* 68 (April): 9–21. <https://doi.org/10.1016/j.jtrangeo.2018.02.005>.
- Juhász, Levente. 2021. *Towards Understanding the Temporal Accuracy of OpenStreetMap: A Quantitative Experiment*. July. <https://doi.org/10.5281/ZENODO.5112236>.
- Minghini, Marco, and Francesco Frassinelli. 2019. "OpenStreetMap History for Intrinsic Quality Assessment: Is OSM up-to-Date?" *Open Geospatial Data, Software and Standards* 4 (1): 9. <https://doi.org/10.1186/s40965-019-0067-x>.
- OpenStreetMap contributors. n.d. "Bicycle - OpenStreetMap Wiki." In *Bicycle*. Accessed January 30, 2026. <https://wiki.openstreetmap.org/wiki/Bicycle>.
- Prince, Stephanie A., Tyler Thomas, Philippe Apparicio, et al. 2025. "Cycling Infrastructure as a Determinant of Cycling for Recreation and Transportation in Montréal, Canada: A Natural Experiment Using the Longitudinal National Population Health Survey." *The International Journal of Behavioral Nutrition and Physical Activity* 22 (June): 71. <https://doi.org/10.1186/s12966-025-01767-y>.

- Rundle, Andrew G., Michael D. M. Bader, Catherine A. Richards, Kathryn M. Neckerman, and Julien O. Teitler. 2011. "Using Google Street View to Audit Neighborhood Environments." *American Journal of Preventive Medicine* 40 (1): 94–100. <https://doi.org/10.1016/j.amepre.2010.09.034>.
- Schmidl, Martin, Gerhard Navratil, and Ioannis Giannopoulos. 2021. "An Approach to Assess the Effect of Currentness of Spatial Data on Routing Quality." *AGILE: GIScience Series* 2 (June): 1–12. <https://doi.org/10.5194/agile-giss-2-13-2021>.
- Senaratne, Hansi, Amin Mobasheri, Ahmed Loai Ali, Cristina Capineri, and Mordechai (Muki) Haklay. 2017. "A Review of Volunteered Geographic Information Quality Assessment Methods." *International Journal of Geographical Information Science* 31 (1): 139–67. <https://doi.org/10.1080/13658816.2016.1189556>.
- Szell, Michael, Sayat Mimar, Tyler Perlman, Gourab Ghoshal, and Roberta Sinatra. 2022. "Growing Urban Bicycle Networks." *Scientific Reports* 12 (1): 6765. <https://doi.org/10.1038/s41598-022-10783-y>.
- Vierø, Ane Rahbek, Anastassia Vybornova, and Michael Szell. 2025. "How Good Is Open Bicycle Network Data? A Countrywide Case Study of Denmark." *Geographical Analysis* 57 (1): 52–87. <https://doi.org/10.1111/gean.12400>.
- Winters, Meghan, Colin Ferster, and Karen Laberee. 2025. "Mapping Change in Cycling Infrastructure Across Canada: What, Where, and for Whom?" *Canadian Journal of Public Health*, ahead of print, December. <https://doi.org/10.17269/s41997-025-01139-w>.
- Zhang, Liming, and Dieter Pfoser. 2019. "Using OpenStreetMap Point-of-Interest Data to Model Urban Change—A Feasibility Study." *PLoS ONE* 14 (2): e0212606. <https://doi.org/10.1371/journal.pone.0212606>.