

UTRECHT UNIVERSITY

DOCTORAL THESIS

Human Activity Recognition Using Accelerometer Data

Author:

R.Q. VLASVELD

Supervisor:

Dr. James SMITH

*A thesis submitted in fulfilment of the requirements
for the degree of Master of Science*

in the

Research Group Name

Department or School Name

May 2013

Declaration of Authorship

I, R.Q. VLASVELD, declare that this thesis titled, 'Human Activity Recognition Using Accelerometer Data' and the work presented in it are my own. I confirm that:

- This work was done wholly or mainly while in candidature for a research degree at this University.
- Where any part of this thesis has previously been submitted for a degree or any other qualification at this University or any other institution, this has been clearly stated.
- Where I have consulted the published work of others, this is always clearly attributed.
- Where I have quoted from the work of others, the source is always given. With the exception of such quotations, this thesis is entirely my own work.
- I have acknowledged all main sources of help.
- Where the thesis is based on work done by myself jointly with others, I have made clear exactly what was done by others and what I have contributed myself.

Signed:

Date:

“Thanks to my solid academic training, today I can write hundreds of words on virtually any topic without possessing a shred of information, which is how I got a good job in journalism.”

Dave Barry

UNIVERSITY NAME (IN BLOCK CAPITALS)

Abstract

Faculty Name

Department or School Name

Master of Science

Human Activity Recognition Using Accelerometer Data

by R.Q. VLASVELD

The Thesis Abstract is written here (and usually kept to just this page). The page is kept centered vertically so can expand into the blank space above the title too...

Acknowledgements

The acknowledgements and the people to thank go here, don't forget to include your project advisor...

Contents

| | |
|---|-------------|
| Declaration of Authorship | i |
| Abstract | iii |
| Acknowledgements | iv |
| List of Figures | vii |
| List of Tables | viii |
| Abbreviations | ix |
| Physical Constants | x |
| Symbols | xi |
| | |
| 1 Introduction | 1 |
| 1.1 Outline | 1 |
| 2 Literature review | 2 |
| 2.1 Outline | 2 |
| 2.2 Statistical framework | 2 |
| 2.3 CUSUM and GLR | 3 |
| 2.3.1 CUSUM | 3 |
| 2.3.2 GLR | 3 |
| 2.4 Change-detection by Density-Ratio Estimation | 4 |
| 2.5 Change-detection by Support Vector Machines | 4 |
| 2.5.1 One-class Support Vector Machine | 4 |
| 2.6 Change-detection by Dimensionality Reduction / Covariance structure . . | 5 |
| 3 Change detection by Density-Estimation | 6 |
| 3.1 Outline | 6 |
| 4 Proposed method | 7 |
| 4.1 Outline | 7 |

| | |
|----------------------------------|-----------|
| 5 Result | 8 |
| 5.1 Outline | 8 |
| 6 Real-world applications | 9 |
| 6.1 Outline | 9 |
| | |
| A Appendix Title Here | 10 |
| | |
| Bibliography | 11 |

List of Figures

List of Tables

Abbreviations

LAH List Abbreviations **H**ere

PCA Principle Component **A**nalysis

Physical Constants

Speed of Light $c = 2.997\,924\,58 \times 10^8 \text{ ms}^{-\text{s}}$ (exact)

Symbols

| | | |
|----------|-------------------|------------------------|
| a | distance | m |
| P | power | W (Js^{-1}) |
| ω | angular frequency | rads^{-1} |

For/Dedicated to/To my...

Chapter 1

Introduction

1.1 Outline

- Context of research (human activity recognition), real-world applications
- Current methods, wrapper vs. filter methods
- Problem statement with current filter methods (which follows from Chapter [3](#) which goes in-depth with methods).
- Purpose of this research. E.g. "Find a better algorithm for short-activity segmentation"
- Relate to real-world applications

Chapter 2

Literature review

2.1 Outline

- Literature review about Temporal Segmentation (previous draft was more about classification)
- Consider methods for the context of filter-methods for classification
- Take a look at 3-4 different kind of methods for change detection:
 - Dimensionality reduction
 - Density-ratio estimation
 - Support Vector Machines (?) - if there are more sources about this
 - CUSUM - or other more traditional methods
- With each method, shortly look at characteristics, strengths and weaknesses and consider applicability to accelerometer sensor data

2.2 Statistical framework

Many applications require the detection of time points at which the underlying properties of a system change. This problem thus has received a lot of attention in the fields of data mining, etc... *** list and refs ***. Often this problem is formulated in a statistical framework, by inspecting the data generating PDF (Probability Density Function) of the time series data. A change point is then defined as a significant change in the properties of the PDF, such as the mean and variance.

The widely used CUSUM (cumulative sum) method by Basseville *et al.* [1], and the GLR (Generalized Likelihood Ratio) by Gustafsson [2, 3] take this approach. The former originates from control methods for detection from bench marks. The latter compares the logarithm of the likelihood ratio over two consecutive intervals. These two methods is discussed and analyzed in section 2.3.

The GLR method, as with others, relies on pre-specified parametric model assumptions and considers the data be independent over time, which makes it less flexible to real-world applications. The proposed methods by Kawahara *et al.* [4] and Lui *et al.* [5] try to overcome these problems by estimating the *ratio* between the PDF, instead of estimating each PDF. This approach is discussed and analyzed in section 2.4.

The density-estimation methods, as with the GLR, rely on the log-likelihood ratio between PDFs. The method of Camci [6] takes an other approach within the statistical framework, by using a SVM (Support Vector Machine). One problem it tries to overcome is the (claimed) weakness of many methods to detect a decrease in variance. The method represents the distribution over the data points as a hyper-sphere in a higher dimension using kernel trick. A change in the PDF is represented by a change in the radius of this sphere. Section 2.5 discusses the SVM-method.

The final method under consideration, change detection via (intrinsic) dimensionality reduction, takes a different point of view. Opposed to the other discussed methods, dimensionality reduction is framed in the MDL (Minimum Description Length) framework. It uses the estimated underlying number of parameters of the time series as a model for change detection. Section 2.6 discusses this method.

2.3 CUSUM and GLR

2.3.1 CUSUM

Non-Bayesian change detection algorithm (thus: no prior distribution believe available for the change time).

The CUSUM (cumulative sum) method is developed by Page [7] for the application of statistical quality control (it is also known as a control chart).

2.3.2 GLR

Also: maximum-likelihood estimation. "When applied to a dataset and a given statistical model, it provides estimates for the model's parameters."

2.4 Change-detection by Density-Ratio Estimation

Formulate the problem of detecting change in the statistical framework. Consider the probability distributions from which two consecutive segments of time series around a target time point are generated. When the distributions differ significantly the target time point is regarded as a change point.

CUSUM (cumulative sum) [1] and GLR (generalized likelihood ratio)

The distribution over the values of time series data can be represented with a probability density function (pdf). Two sections of a time series data can be generated with the same underlying pdf or each with a different.

2.5 Change-detection by Support Vector Machines

Introduced by Vapnik [8, 9], Support Vector Machines offer a way to segment, and classify, linear separable data. When combined with a mapping function, which maps the data from the input space I to a higher dimension feature space F , the input data can be non-linear separable. The linear hyperplane, which segments the data in the feature space F , yields to a non-linear segmentation in the lower-dimensional input space I . Instead of explicitly mapping the input data to the higher dimensional space, a kernel function can be used. This kernel function can calculate values of the feature space directly, without the need to first map the input values to this space. This process is referred to as the kernel trick.

*** Let sigma be a mapping from I to F such that the dot product in F can be computed using some simple kernel ***

2.5.1 One-class Support Vector Machine

The proposed method of Camci [6] uses a one-class support vector machine to segment time series data. One-class SVMs are used to describe the current data under consideration, by assuming all data points are from the same class [10]. The class is described by a spherical boundary around the data with center c and radius r , such that the volume is minimized. Following the definition of Camci [6], the class description is obtained by minimizing r^2 :

$$\text{Min } r^2 \tag{2.1}$$

$$\text{Subject to : } \|\mathbf{x}_i - \mathbf{c}\|^2 \leq r^2 \quad \forall i, \quad \mathbf{x}_i : i\text{th data point} \tag{2.2}$$

To be able to handle outliers in the input data, a penalty cost function ε_i for each outlier can be added.

*** Add new function and constraints? ***

Using this one-class SVM formulation, differences between two (consecutive) windows of data points with size w can be obtained. The first window is used as the input set, h_1 and the second as the test set h_t . For the first window a one-class SVM is constructed, yielding in a representation by c_1 and r_1 . When the data points of the second window belong to the same class, the representation of that one-class SVM would equal the first:

$$c_1 = c_2, r_1 = r_2 \quad (2.3)$$

*** First tell more about (underlying) probability density functions, to relate to other methods ***

In case the second window of data points does not belong to the same class, i.e. the probability density function that describes the data differs from the first, the describing values of the second window will differ from the first. The amount of difference can be expressed by a dissimilarity measure over the representations. When the dissimilarity between the two windows exceeds some predefined threshold th , there exists a change point between the windows.

This process can be visualized as done in *** insert figure of four circles ***. The second window, h_2 can be constructed from the first by e.g. a shift of one data point. *** explain data point positions by circle ***.

Note that a difference in the SVM center c or radius r represent a change in the mean and variance, respectively.

2.6 Change-detection by Dimensionality Reduction / Covariance structure

Chapter 3

Change detection by Density-Estimation

3.1 Outline

- In-depth analysis on one of the methods of Chapter 2
- This method (e.g. Density-Ratio estimation) will be the basis for the real research
- Explain why this methods seems worthy and interesting
- Look at problems when applied to accelerometer sensor data
- *The problems discovered here will give rise to the problem statement at the Introduction / beginning of research*
- Opens the possibility for own method

Chapter 4

Proposed method

4.1 Outline

- Based on the problem statement with current research as stated in [Chapter 3](#)
- Adjust method to needs
- Explain using graphs, pseudo-algorithms. Make clear distinction in origin of ideas and why to apply

Chapter 5

Result

5.1 Outline

- Compare proposed method with methods of Chapter [2](#)
- Provide plots, tables, graphs, error rates, precision, etc.
- Apply to a multiple of data, to compare to previous research - use that data
- Give theoretical analysis about performance. Big-O, memory, run-time, precision.
- This sections needs programmed implementations of own method and the ones compared

Chapter 6

Real-world applications

6.1 Outline

- Apply proposed method to real-world applications, such as
 - Daily life activity recognition (as the original context of this thesis is)
 - PowerHouse sensor data
 - Stock data?
- Relate back to filter vs. wrapper methods - give results with different methods?

Appendix A

Appendix Title Here

Write your Appendix content here.

Bibliography

- [1] M. Basseville, I.V. Nikiforov, et al. *Detection of abrupt changes: theory and application*, volume 104. Prentice Hall Englewood Cliffs, NJ, 1993.
- [2] Fredrik Gustafsson. The marginalized likelihood ratio test for detecting abrupt changes. *Automatic Control, IEEE Transactions on*, 41(1):66–78, 1996.
- [3] Fredrik Gustafsson. *Adaptive filtering and change detection*, volume 1. Wiley Londres, 2000.
- [4] Y. Kawahara and M. Sugiyama. Change-point detection in time-series data by direct density-ratio estimation. In *Proceedings of 2009 SIAM International Conference on Data Mining (SDM2009)*, pages 389–400, 2009.
- [5] Song Liu, Makoto Yamada, Nigel Collier, and Masashi Sugiyama. Change-point detection in time-series data by relative density-ratio estimation. *Neural Networks*, 2013.
- [6] Fatih Camci. Change point detection in time series data using support vectors. *International Journal of Pattern Recognition and Artificial Intelligence*, 24(01):73–95, 2010.
- [7] ES Page. Continuous inspection schemes. *Biometrika*, 41(1/2):100–115, 1954.
- [8] Vladimir Vapnik. Statistical learning theory. 1998, 1998.
- [9] Vladimir Vapnik. *The nature of statistical learning theory*. springer, 1999.
- [10] David MJ Tax. One-class classification. 2001.