

Surface Data Logging
5" MD Formation Evaluation Log

1 : 240

Country	: USA	Company	: Great Bear Petroleum, LLC
Field	: Exploration	Rig	: Nabors 105E
Location	: Lat: 69° 59' 26.11" North Long: 148° 40' 40.99" West	Well	: Alcor 1
Well	: Alcor 1	Field	: Exploration
Company	: Great Bear Petroleum, LLC	Country	: USA
Rig	: Nabors 105E	API Number	: 50-223-20026-00-00
LOCATION	Latitude : 69° 59' 26.11" North Longitude : 148° 40' 40.99" West UTM Easting = 665,672.48 ft UTM Northing = 5,847,838.30 ft	Other Services	
Permanent Datum	: Mean Sea Level	Elevation	: 0.00 ft
Log Measured From	: Drill Floor	Plot Type	: Final
Drilling Measured From	: Drill Floor	Plot Date	: 28-Aug-12
Depth Logged	: 102.00 ft	To	10,812.00 ft
Date Logged	: 16-Jun-12	To	09-Aug-12
Total Depth MD	: 10,812.00 ft	TVD:	10,802.05 ft
Spud Date	: 16-Jun-12	Unit No.	: 117
		Job No.	: AK-AM-0009285348

LEGEND

Abbreviations and Symbols

Lithology Symbols

Drilling Data

Mud Data

BG	Background Gas	Ci	Chloride Ion Conc	Rm	Mud Resistivity
BHT	Bottomhole Temp	FC	Filter Cake	Rmf	Filtrate Resistivity
C	Carbide Test	FL	Filtrate Loss	S	Solids Content
CB	Core Bit	G	Gels	Vis	Funnel Viscosity
CG	Connection Gas	pH	Hydrogen Ion Content	MW	Mud Weight
CKF	Check For Flow	PV	Plastic Viscosity	YP	Yield Point
CO	Circulate Out				
DB	Diamond Bit				
DC	Depth Correction				
DS	Direction Survey				
DST	Drillstem Test				
FLT	Flowline Temp.				
LAT	Logged After Trip				
NB	New Bit				
NR	No Returns				
PDC	Polycrystalline Diamond				
PR	Compound Bit				
RPM	Partial Returns				
RRB	Revs Per Minute				
STG	Rerun Bit				
TB	Short Trip Gas				
TG	Turbo Drill				
U	Trip Gas				
WOB	Gas Units				
	Weight On Bit				

Engineering Data

Core No.	Water	Sand
DST No.	Salt Water	Sandstone
Casing Seat	Fresh Water	Silt
Side Wall Core	Hydrocarbons Smell	Siltstone
Gas Traces	H2S Smell	Clay
Gas	Interval Tester	Claystone
Oil Traces	Wireline Log Run	Shale
Oil	Leakoff Test	Lignite
Bitumen	Pressure Integrity Test	Anhydrite



Sand



Dolomite



Sandstone



Marl



Silt



Mudstone



Gumbo



Chalk



Clay



Chert



Claystone



Halite



Shale



Anhydrite



Lignite



Coal





Gypsum



Gravel

ROP ft/hr		0	Gas Max units		2K	Chromatograph Gas Analysis (ppm)		MW In ppg	12	Deviation Surveys	Lithologic Descriptions
Gamma api	0	150	Gas Avg units		2K	Methane	Ethane	Propane	Total Butane	Total Pentane	
WOB lbs	0	40	Resistivity ohms		50	ECD	9	ppg	12		Remarks
RPM rpm	0	200	Density 1 g/cc	3	10 100 1K 10K 100KM						





Gubik
448' MD, 448' TVD

Conn


Conn


231.15' MD
231.15' TVD
INC 0.19°
AZI 271.35°

322.39' MD
322.39' TVD
INC 0.46°
AZI 261.45°


GRAV: dkgy - med gy, occ blk, vc - c gr, plysrt, tr clyst.

416.62' MD
416.61' TVD
INC 0.80°
AZI 219.77°






GRAV: dkgy, trnsl - trnsr, vc gr, ply
srt, tr sst.



SST : trnsr - trnsr, med g/y, med gr,
sb-ang - sb-rnd, mo srt - ply srt, n
calc, uncons.



1355.56' MD
1355.45' TVD
INC 0.78°
AZI 205.42°

MW 10.1, Vis 280, PV 53, YP
72, Fil 6.4, FC 3/0, pH 9.6,
Cl 300

1451.70' MD
1451.58' TVD
INC 0.70°
AZI 209.13°

CLYST : dkgy - lt gy, rhy, n calc.

1547.61' MD
1547.48' TVD
INC 0.87°
AZI 214.97°


Conn

140

150

Conn

Conn
21 June 2012 (1598' MD)





1642.98' MD
1642.84' TVD
INC 0.86°
AZI 205.66°


CLYST : dkgy - med gy, rhy - sm, n
calc, tr sst.

1739.38' MD
1739.23' TVD
INC 0.64°
AZI 193.71°

SST : trsp - trnsl, dkgy - med gy,
occ tan, f - med gr, sb sph - sb elg,
sb ang - sb rnd, mo - wsrt, n calc,
glauc, tr cyst.








TD Surface Hole Section
2510' MD, 2510' TVD
Off Bot 17:20 21 June 2012

Bit #2 HDBS FX56
Jts: 5x16, TFA: 0.9817
In: 2510' MD / 2510' TVD
Out: 6365' MD / 6365' TVD
Grade: 24-CT-A-X-2-WT-HP

Commenced 8.5" Intermediate Hole
Section
On Bot: 14:40 27 June 2012

Perform FIT to 14.0 ppg

Upper Canning
2596' MD, 2596' TVD



2600

2700

MW 10.2, Vis 150, PV 51, YP
57, Fil 6.0, FC 3/0, pH 9.4,
Cl 400

Callibrate 8800 THA
C1=10.000%
10,000 Units = 100% Gas in
Air

Calibrate 8900 GC
Cl = 1.03 %
C2 = 0.500 %
C3 = 0.251 %
C4 = 0.250 % nC4 = 0.250 %
C5 = 0.102 % nC5 = 0.102 %

Displaced well to 10.2
MOB M

MW 10.2, Vis 50, PV 26, YP
18, Fil 3.3, FC 1/0, AgNO3
2.2

2606.45' MD
2606.26' TVD
INC 1.05°
AZI 112.70°


CLYST : It gybrn, lt - med gy, sft -
frm, mo comp, amor - blk, n calc, tr
sst, tr cmnt, scat mud add.


CLYST : It- med gy, lt brngy, frm -
hd, mo - w comp, 1 - 3 in cttings, ln -
blk, n calc, scat mud add.


CLYST : It- med gy, frm, 0.5 - 1 in
cttings, elg, pdc bit imprint, scat mud
add.


2700.00' MD
2699.80' TVD
INC 0.12°
AZI 96.30°


CLYST : It- med gy, sft, fn - 1 in
cttings, elg - sb-sph, pdc bit imprint,
scat mud add.











SST : lt gy, gy, brwn, blk, transl -
opaque, f - vf, sph, sb-md, wsrt, dy
cement, poorly cemented.

3984.95' MD
3948.65' TVD
INC 0.63°
AZI 109.99°

SST : trnspr - trnsl, lt gy, lt brn gy, tr
wh, frm - hd, m - f gr, ang - sb ang,
mo - wsrt, silic cment, tr coal.


COAL: blk brn blk, hd - brit, blky -
peaty, shny - slky, abun ssst.


4043.92' MD
4043.62' TVD
INC 0.19°
AZI 103.09°


SST : lt gy - med gy, lt blu gy, frm -
sft, m - vf gr, sb rnd - rnd, mo - wsrt,
r coal.


Staines Tongue
4059 MD, 4059 TVD


Conn











5286.20' MD
5285.86' TVD
INC 0.26°
AZI 183.07°

nd - trm, 0.1 - 0.2 in ctngs, bit grvs,
tr sst.

SST : trnsl - trnspl, lt gy, vf - f gr, sb
rnd - rnd, w - mod srt, r tufaceous sst, r
intrbddd coal, tr coal.

5382.80' MD
5382.46' TVD
INC 0.32°
AZI 212.82°

SST : lt gy - med gy, occ tan, f - m
gr, sb rnd - rnd, occ sb ang, sb sph -
sph, silic cmnt, mod - w srt, r coal, r
cyst.

CLYST : dkgy, frm, 0.1 - 0.2 in
ctngs, scat bit grvs, scat arg sst
with mod cm.

5476.87' MD
5476.53' TVD
INC 0.51°
AZI 208.96°

CLYST : Itgy- dkgy, frm, 0.1 - 0.5 in
cttngs, scat bit grvs, scat arg sst
with mod cem.

5573.78' MD
5573.43' TVD
INC 0.60°
AZI 174.46°

CLYST : Itgy- dkgy, frm, 0.1 - 0.5 in
cttngs, scat bit grvs, scat arg sst
with mod cem, scat cttngs wth slstn
banding.


Prince Creek
5644 MD, 5644' TVD

MW 9.9, Vis 77, PV 26, YP
12, Fil -, FC 0/1, AgNO3 1.4

5669.61' MD
5669.26' TVD
INC 0.39°
AZI 169.03°

CLYST : Itgy- gy, frm, 0.1 - 0.5 in
cttngs, scat bit grvs, scat arg sst
with mod cem.

CLYST : Itgy- gy, frm, 0.1 - 0.2 in
cttngs, scat bit grvs, scat arg sst
with gd cem.



Short Wiper Tripto 4926' MD

Conn

6000

MW 10.0, Vis 78, PV 29, YP
12, Fil -, FC 0/1, AgNO3 1.3

SLTST : dk - med gy, dk brn gy, occ
blk, frm - hd, sb rnd - rnd, w - mod srt,
arg cem, mod cem, occ lmntrs, bit cut
grns, scat v gr sst, r clyst.

Conn

6100

MW 10.0, Vis 75, PV 26, YP
13, Fil -, FC 0/1, AgNO3 1.3

SLTST : dk - med gy, occ blk, frm -
hd, sb rnd - rnd, w - mod srt, arg cem,
mod cem, n calc, occ bit cut grns,
scat v gr sst, scat mud add.


Conn

6200

6149.17' MD
6148.80' TVD
INC 0.43°
AZI 229.35°

SLTST : dk - med gy, occ blk, frm -
hd, sb rnd - rnd, w - mod srt, mod
cem, n calc, tr bit cut grns, tr v gr
sst, tr mud add, tr pyr.

SST : trnsl - trnspl, lt gy, tr tan, vf - f,
sb rnd - rnd, sb sph - sph, mo - wsrt,
tr pyr, scat gy - tan slst.



6436.95' TVD
INC 0.65°
AZI 159.50°

SLTST : med - dk gy, lt tan gy, med
brn gy, frm - hd, mod - wsrt, mod
cmnt, sl calc, tr cyst, tr sst, scat
LCM.

6534.86' MD
6534.48' TVD
INC 0.49°
AZI 172.94°


SLTST : med - dk gy, frm - hd, mod -
wsrt, mod cmnt, sl calc, silstn
banding, tr cyst, tr sst, scat LCM,
scat barafibre.

Lower Canning
6601' MD, 6601' TVD

CLYST : ltgy - gy, frm, 0.1 - 0.5 in
cttngs, sb-ang cttngs, mod cem,
PDC bit cut grooves .

6630.89' MD
6630.50' TVD
INC 0.45°
AZI 184.45°

SST : gy, brn, org, f - vf, sb-sph,
sb-rnd, wsrt, uncons, pr samp
quality, hy mud add.



mod cmnt, sl calc, silstn banding, tr
clyst, tr sst, scat LCM, scat steelseal,
scat mud add.

6918.13' MD
6917.73' TVD
INC 0.56°
AZI 174.04°

TF : It gy, sft, glassy, amorph, seen
as sharp boundary from silstn on bit
cut grooved ctng.

MW 9.4, Vis 78, PV 34, YP
10, Fil 1, FC 0/1, AgNO3 1.2

7011.46' MD
7011.06' TVD
INC 0.32°
AZI 185.63°

SLTST : med gy - drkgy, frm - hd,
well srt, mod cmnt, sl calc, silstn
banding.

SLTST : med gy - drkgy, med brn gy,
frm - hd, w - mod srt, mod cmnt, sl
calc, silstn banding, tr sst, tr qtz, r mud
add.

7109.41' MD
7109.01' TVD
INC 0.54°
AZI 204.95°

SLTST : med gy - drkgy, frm - hd,
mod srt, mod cmnt, sl calc, slst
bndng, tr lt blugysh, r mud add.

7200

MW 9.4, Vis 80, PV 29, YP
12, Fil r, FC 0/1, AgNO₃ 1.3

7205.30' MD
7204.89' TVD
INC 0.45°
AZI 211.55°

SLTST : dk - med gy, dkblu gy, frm-
hd, mod srt, mod cmnt, vsl calc, tr lt
blugysh, r f gr sst.

7300

GP 386 U

7301.43' MD
7301.02' TVD
INC 0.57°
AZI 216.27°

SST : lt - med gy, lt tan gy, brn gy, vf
gr, sb sph to sph, sb md - rnd, mod
srt, sl calc, tr slst, SHOW: dull pitchy
yel flour, slow strng dull yel cut.

Middle Schrader Bluff
7248' MD, 7248' TVD


Lower Canning
7335' MD, 7335' TVD

Corn

Corn

Corn

SLTST : med - dk gy, dkbrn gy, hd-
frm, w - mod srt, mod cmnt, vsl calc,
sh lmnns, tr intrbd lt gy - tan, vf gr
sst.



SST : It - med gy, It tan gy, brn gy, vf gr, sb sph to sph, sb rnd - rnd, mod srt, sl calc, tr srt, SHOW: dull pitchy yel w/ pnt brt fluor, slow strng pnt yel cut.

SST : brn, It - med gy, It tan gy, pred vf - scat mgr, sb ang to sph, sb rnd - rnd, mod srt, sl calc, tr srt, SHOW: dull pitchyel w/ pnt brt fluor, imm dull yell cut.

SST : brn, org, It - med gy, It tan gy, vf gr, sb ang to sph, sb rnd - rnd, mod srt, sl calc, tr tuff, SHOW: scat dull yll fluor, no cut fluor, no cut residue.

SST : It - med gy, It tangy, opaque, vf gr, sb ang - sph, sb rnd - rnd, mod srt, sl calc, mod cem SHOW: scat dull yll fluor, no cut fluor, no cut residue.

AZI 283.13°

SST : lt - med gy, lt tangy, opaque, vf gr, sb ang - sph, sb rnd - rnd, mod srt, sl calc, mod cem SHOW: no fluor, no cut fluor, no cut residue.

MW 9.4, Vis 80, PV 37, YP
13, Fil⁻, FC 0/l, AgNO₃ 1.2

7684.78' MD
7684.33' TVD
INC 0.72°
AZI 280.36°

SST : lt - med gy, lt tangy, opaque, vf gr, sb ang - sph, sb rnd - rnd, mod srt, sl calc, mod cem SHOW: no fluor, no cut fluor, no cut residue.

Conn

7600

7700

7800

Conn

08 July 2012 (7760' MD)

TF : lt gy, sft, glassy, amorph, vsl calc, mtrxforsst.

7779.85' MD
7779.40' TVD
INC 0.64°
AZI 297.13°

SST : lt - med gy, lt tangy, opaque, hd, vf gr, sb ang - sph, sb rnd - rnd, mod srt, sl calc, mod cem SHOW: dull yell fluor, imm wht fluor cut, ambr cut residue.

Conn

SLTST : med - dk gy, dk brn gy, frm - hd, w srt, mod - w cmnt, v sl calc, occ intrbd lt gy - tan vf gr sst.

7877.15' MD
7876.69' TVD
INC 0.79°
AZI 282.23°


SST : lt - med gy, lt tangy, opaque, frm - hd, vf gr, sbang - sph, sb rnd - rnd, mod srt, sl calc, mod cem SHOW: pchly dull wht fluor, imm wht fluor ct, lt straw cut residue.


MW 9.4, Vis 85, PV 38, YP
13, Fil -, FC 0/1, AgNO3 1.2

7973.13' MD
7972.66' TVD
INC 0.91°
AZI 268.39°


SST : lt - med gy, lt tangy, frm - hd, vf gr, sb sph - sph, sb rnd - rnd, mod srt, sl calc, mod cem SHOW: pchly dull wht fluor, imm blu wht fluor ct.

SLTST : dk - med gy, dk brn gy, frm - hd, w srt, mod - w cmnt, v sl calc, occ intrbd lt gy - tan vf gr sst, tr tan tuff w dull mmrl fluor.





TF : lt gray - lt tan gray, Slt, amorph, vly
tx, wk calc, silt fritz with HCL.



SH : It gy - It brn gy, opaque, sb-eg - eg, sb ang - ang, sft - brittle, wavy laminations, wxy, scat tuff SHOW: very slight oil odor, trace oil stain, spotty brt yellow fluor with dull yellow overall fluor, slow brt yellow transp oil cut fluor, strong residue UV intensity, very pale straw res .

SH : SHOW: dull yellow overall fluor, immediate bright white oil cut fluor, strong residue UV intensity, It amber res .

TF : lt gray-of wht, sft-amor occ frm-fria, vari opq - trnsl, wxy, occ sl expsns, thn intrbd w/ Sh SHOW: brt yel-grn mmrl fluor, no strn, nil vis cut, slw watry-frt wht cut fluor.

8756.25' MD
8751.44' TVD
INC 9.65°
AZI 180.09°

SH : med gr- lt brwn gr, frm - mod
hd, pty- flky, abun thn lams,
com intrbd w wh tuff, SHOW: No
odor or sin, sct fluor f/tuff, no petro
fluor, nil vis cut, slw wht ct fluor, r
opq wht fluor strmr, dull wht - yel res
fluor, nil vis res.

008

Conn

SG 230 U

SG 183 U

GP 819 U

GP 1960 U

0068

Conn


GP 182 U

8850.66' MD
8844.71' TVD
INC 8.67°
AZI 176.28°

SH : med brn gy- lt brn gy, med gy,
mod frm, pty- flky, abun thn lams, tr
intrbd w crm tuff, SHOW: No odor or
sin, sct fluor f/tuff, no petro fluor, sl
pnpt wht cut, slw wht ct fluor, r opq
wht fluor strmr, dull wht - yel res
fluor.

8950.92' MD
8911.01' TVD
INC 7.22°
AZI 181.35°

SH : lt brn gy, med gy, mod frm - med
hd, pty- flky, abun thn lams, tr intrbd
w crm - wh tuff, pyritic, SHOW: No
odor or sin, fluor f/tuff, no petro fluor,
no cut, dull wht res fluor.



SH : lt brn gy, med gy, mod frm - mod
hd, plty- flky, tr thn lams, r crm - wh
tuff, SHOW: No odor or stn, flour f/
tuff, no petro fluor, no cut, dull wht res
flour.



SH : lt brn gy, med gy, mod frm - med
hd, plty - flky, tr thn lams, r crm - wh
tuff, SHOW: flour f/tuff, no petro fluor,
no cut, dull wht res flour.

9046.40' MD
9038.83' TVD
INC 6.24°
AZI 171.45°

LST : yel orng, frm - hd, occ fri, silty
 w/ com chky txt, com clean orng
 calcite, slw rxn to hcl, SHOW: vr vis
 strn, wk odor, nil smpl fluor, nil vis cut,
 slw wrtry wht cut w/ slw opq wht - blu
 strmrss

9143.03' MD
9135.00' TVD
INC 4.89°
AZI 174.66°

SLTST : Shy Sh, It gry - It brn gry, firm, plty - flky, occ sub resn lstr, tr dirty slytsd and loose sd, tr glauc, tr py. SHOW: nil petro fluor, nil vis cut, slw opq wht-blu fluor strmrss, wk odor, r stn on slytsd.




SST : trns - trns, frm - hd, f gr w tr med gr, sb sph - sph, rnd - sb rnd, w - mo srt, scat pyr, r glauc, abun mud add, abun silst, r clyst, tr tuff w mmrl flour, SHOW: wk odor, vr pnpt petro flour, slw pnpt strmg wh yel cut, brt wh blu res.

SLTST : med gy - med brn gy, firm - mod sft, tr pty - fily, occ blky, tr sly sd and loose sd, r glauc. SHOW: no odor, no petro fluor, sl strmg cldy wh yel cut, brt yel wh res.

SLTST : med gy - med brn gy, occ lt brn gy, mod firm - sft, tr pty, r blky, tr sly sh, tr tuff w mmrl flour SHOW: no odor, no petro fluor, vsl pnpt brt yel cut, brt wh blures.

9431.91' MD
9423.03' TVD
INC 3.88°
AZI 174.51°



SST : dbm sly Sst, trnsl - lt gr, occ brnsh gr hues, f gr w/ occ loose med gr, tr glauc, com pyr, com grdf/ dirty Sltst, SHOW: no odor, no vis stn, nil vis cut, com wht-yel fluor strmr, d yel - wht res fluor.

9719.33' MD
9709.96' TVD
INC 3.03°
AZI 174.83°

SLTST : medbrn gy - lt gy brn, frm fri - mod hd, pty - fly, sly - occ wy, occ sly Sh, tr lams, sct sly Sst, com glauc + pyr, SHOW: no petro odor or fluor, nil vis cut, wtry yel - wht cut, r wht - blu fluor strmr f/ sdy smpls.

MW 10.65, Vis 54, PV 23, YP
16, Fil 2.6, FC 1/2, pH 9.9,
CI 35000

9815.52' MD
9806.02' TVD
INC 2.75°
AZI 177.03°

SLTST : med brn gy - med brn - dsly yel brn, fria-frm, rnd-pty, crmbly, sly-gritty, sb resn lstr, com pyr, incrs org nc, com sly Sh, tr lams when shly, SHOW: no vis cut, vwk slw wtry wht-yel cut fluor.

CG 8573 U

0076

Conn

0086

CG 4321 U

0066

CG 1684 U

Conn

SH : com sly Sh, yelish brn- dkbrn gr, firm - md hd, pty rnd ctgs, sly tx, com lams, com pyr, gr dg f/ Sltst SHOW: vwk sheen + obr, dl yel fluor, nil vis ct, abd yel-wht fluor strmr, r strn.

Lower Kingak
9913 MD, 9903' TVD





26 July 2012 (9963' MD)

Drilled to 10015' MD - POOH for Core
Bit 26 July 2012
Core #2 10015'-10103' MD
0% Recovered

Bit #6 HDBS OT103
Jets: N/A, TFA: 0.4600
In: 10015' MD / 10005' TVD
Out: 10103' MD / 10093' TVD

28 July 2012 (10039' MD)

Bit #7 HDBS FX54
Jets: 5x11, TFA: 0.4640
In: 10103' MD / 10093' TVD
Out: 10574' MD / 10564' TVD
Grade: 0-0-NO-A-X-I-RR-CP



9912.28' MD
9902.68' TVD
INC 2.48°
AZI 181.36°

SLTST : med brn gy - med brn,
fria-frm-md hd, rnd-plty, crmbly-occ
fly, sly-grty, sb resn lstr, com pyr, r
glau, com grdg to slylam Sh.
SHOW: no vis cut, vfnl slw yel fluor
strmr, r stn.

SLTST : grish brn-dsk brn,
fria-frm, brit - crmbly-occ fly, sly-
grty, sb resn lstr, tr pyr, com as asly
Sh, tr lams slylams, com sprkls f/
mica, com Tf, poss slough. SHOW: tr
fluor f/ Tf, nil vis ct, nil to vtry wht ct
fluor, tr opq wht-blw slw fluor strmr,
dl wht resid fluor, no vis stn, no odor.

10064.19' MD
10054.46 TVD
INC 2.23°
AZI 194.12°

SH : lt gy - med gy, ooc blk, ooc lt brn
gy, frm - md hd, fria ip, plty - brit -
crmbly, sly txt, tr tuff w/ mrl flou,
SHOW: no odor, no petro flou, nil vis
ct.

SH : slySh, pl brn-md brn, w' com dskybrn + occ grybrn hues, frm - md hd, fria, pty - brit - crmby, slytx, sbrsn-sprkly, tr Pyr, vorgnc, tr lams. SHOW: no odor, no petro fluor, nil vis ct, vdl wtry yel-wht cut fluor.

10157.05' MD
10147.26' TVD
INC 1.64°
AZI 203.99°

SH : slySh, pl brn-md brn, w' com dskybrn + occ grybrn hues, frm - md hd, fria, pty - brit - crmby, slytx, sbrsn-sprkly, tr Pyr, vorgnc, tr lams. SHOW: no odor, no petro fluor, nil vis ct, vdl wtry yel-wht cut fluor.

Lower Kingak (K-1 Top)
10220' MD, 10210' TVD

10200

GP 792 U

10254.18' MD
10244.35 TVD
INC 1.67°
AZI 200.62°


SH : slySh, pl brn-md brn, w' com dskybrn + occ grybrn hues, frm - md hd, fria, pty - brit - crmby, slytx, sbrsn-sprkly, tr Pyr, tr lams. SHOW: no odor, no petro fluor, nil vis ct, vdl wtry yel-wht cut fluor.


10300

GP 850 U

10349.19' MD
10339.33' TVD
INC 1.60°
AZI 196.87°

SH : brn-md brn, w' com dskybrn + occ grybrn hues, frm - md hd, fria, pty - brit - crmby, slytx, sbrsn-sprkly, tr Pyr, tr lams. SHOW: no odor, no petro fluor, nil vis ct.





500	ROP ft/hr	0	Gas Max units	2K	Chromatograph Gas Analysis (ppm)	MW In ppg	Lithologic Descriptions
0	Gamma api	150	Gas Avg units	2K	Methane Ethane Propane Total Butane Total Pentane	9 12	Deviation Surveys
0	WOB lbs	40	Resistivity ohms	50	ECD ppg	9 12	Remarks
0	RPM rpm	200	Density 1 g/cc 3	10 100 1K 10K 100KM			
	Interpretative Lithology	DEPTH MD Slide	Cuttings				

WARRANTY: Halliburton Energy Services, Inc. will use its best efforts to furnish customers with accurate information and interpretations that are part of, and incident to, the services provided. However, Halliburton Energy Services, Inc. cannot and does not warrant the accuracy or correctness of such information and interpretations. Under no circumstances should any such information or interpretation be relied upon as the sole basis for any drilling, completion, production, or financial decision or any procedure involving any risk to the safety of any drilling venture, drilling rig or its crew or any other third party. The Customer has full responsibility for all drilling, completion and production operation. Halliburton Energy Services, Inc. makes no representations or warranties, either expressed or implied, including, but not limited to, the implied warranties of merchantability or fitness for a particular purpose, with respect to the services rendered. In no event will Halliburton Energy Services, Inc. be liable for failure to obtain any particular results or for any damages, including, but not limited to, indirect, special or consequential damages, resulting from the use of any information or interpretation provided by Halliburton Energy Services, Inc.

HALLIBURTON

DIRECTIONAL SURVEY REPORT

Great Bear Petroleum, LLC

Alcor 1

Exploration

North Slope Borough Alaska

USA

AK-XX-0009285348

All depths reference the driller's pipe tally.

Measured Depth (feet)	Inclination (degrees)	Direction (degrees)	Vertical Depth (feet)	Latitude (feet)	Departure (feet)	Vertical Section (feet)	Dogleg (deg/100ft)
0.00	0.00	0.00	0.00	0.00 N	0.00 E	0.00	TIE-IN
139.03	0.37	207.79	139.03	0.40 S	0.21 W	0.24	0.27
231.15	0.19	271.35	231.15	0.66 S	0.50 W	0.32	0.36
322.39	0.46	261.45	322.39	0.71 S	1.01 W	0.11	0.30
416.62	0.80	219.77	416.61	1.27 S	1.81 W	0.19	0.58
503.87	1.11	201.58	503.85	2.52 S	2.51 W	0.93	0.49
592.94	1.04	196.68	592.90	4.10 S	3.06 W	2.02	0.13
685.39	0.95	186.77	685.34	5.66 S	3.39 W	3.21	0.21
780.20	0.94	208.49	780.14	7.13 S	3.85 W	4.25	0.38
877.37	0.65	225.85	877.30	8.21 S	4.63 W	4.80	0.38
976.87	0.55	217.66	976.79	8.98 S	5.33 W	5.12	0.13
1070.52	0.84	233.02	1070.44	9.75 S	6.15 W	5.37	0.37
1161.77	0.84	184.97	1161.68	10.82 S	6.74 W	6.00	0.75
1259.04	0.65	208.98	1258.94	12.01 S	7.07 W	6.87	0.37
1355.56	0.78	205.42	1355.45	13.09 S	7.62 W	7.53	0.14
1451.70	0.70	209.13	1451.58	14.19 S	8.18 W	8.20	0.10
1547.61	0.87	214.97	1547.48	15.30 S	8.89 W	8.81	0.20
1642.98	0.86	205.66	1642.84	16.54 S	9.61 W	9.52	0.15
1739.38	0.64	193.71	1739.23	17.71 S	10.05 W	10.31	0.28
1836.78	0.69	209.38	1836.63	18.75 S	10.47 W	11.01	0.19
1931.60	0.71	175.26	1931.44	19.84 S	10.70 W	11.83	0.43

2028.33	0.48	183.94	2028.17	20.84 S	10.68 W	12.71	0.25
2123.91	0.46	205.20	2123.74	21.58 S	10.87 W	13.26	0.18
2217.21	0.50	180.79	2217.04	22.33 S	11.04 W	13.82	0.22
2312.62	0.53	181.16	2312.45	23.19 S	11.05 W	14.56	0.03
2409.08	0.22	169.25	2408.90	23.82 S	11.02 W	15.11	0.33
2463.32	0.57	179.55	2463.14	24.19 S	11.00 W	15.45	0.66
2510.66	0.67	119.99	2510.48	24.56 S	10.76 W	15.89	1.31
2606.45	1.05	112.70	2606.26	25.18 S	9.47 W	17.07	0.41
2700.00	0.12	96.30	2699.80	25.52 S	8.58 W	17.81	1.00
2799.23	0.18	69.63	2799.03	25.48 S	8.33 W	17.90	0.09
2894.32	0.50	111.12	2894.12	25.58 S	7.80 W	18.25	0.40
2990.67	0.53	133.19	2990.47	26.03 S	7.08 W	19.00	0.21
3084.68	0.88	117.17	3084.47	26.66 S	6.13 W	20.03	0.42
3180.11	0.85	116.51	3179.89	27.31 S	4.84 W	21.23	0.03
3275.33	0.61	141.14	3275.10	28.02 S	3.89 W	22.32	0.41
3372.36	0.83	141.77	3372.12	28.97 S	3.13 W	23.53	0.23
3468.66	0.65	129.82	3468.42	29.87 S	2.28 W	24.73	0.25
3560.34	1.00	128.73	3560.09	30.71 S	1.26 W	25.96	0.38
3656.27	0.94	157.86	3656.00	31.96 S	0.31 W	27.52	0.51
3755.14	0.94	121.17	3754.86	33.13 S	0.69 E	29.04	0.60
3851.82	0.94	107.39	3851.53	33.78 S	2.13 E	30.32	0.23
3948.95	0.63	109.99	3948.65	34.20 S	3.39 E	31.31	0.32
4043.92	0.19	103.09	4043.62	34.41 S	4.03 E	31.82	0.47
4140.04	0.15	126.06	4139.74	34.52 S	4.29 E	32.04	0.08
4236.56	0.32	102.08	4236.26	34.65 S	4.66 E	32.34	0.20
4331.54	0.29	159.75	4331.23	34.93 S	5.00 E	32.75	0.31
4425.85	0.62	116.22	4425.54	35.38 S	5.54 E	33.41	0.48
4523.07	0.27	149.90	4522.76	35.81 S	6.13 E	34.08	0.43
4618.45	0.53	131.14	4618.14	36.30 S	6.57 E	34.72	0.30
4710.67	0.31	184.86	4710.35	36.83 S	6.87 E	35.33	0.46
4808.64	0.68	180.96	4808.32	37.67 S	6.84 E	36.05	0.38
4903.55	0.33	180.86	4903.23	38.51 S	6.83 E	36.76	0.37
4999.95	0.55	168.26	4999.62	39.24 S	6.92 E	37.44	0.25
5095.22	0.47	204.56	5094.89	40.04 S	6.85 E	38.10	0.34
5190.87	0.69	179.59	5190.53	40.98 S	6.69 E	38.83	0.35
5286.20	0.26	183.07	5285.86	41.77 S	6.68 E	39.51	0.45
5382.80	0.32	212.82	5382.46	42.21 S	6.52 E	39.82	0.17
5476.87	0.51	208.96	5476.53	42.80 S	6.18 E	40.15	0.20
5573.78	0.60	174.46	5573.43	43.68 S	6.02 E	40.84	0.35
5669.61	0.39	169.03	5669.26	44.50 S	6.13 E	41.60	0.22
5764.88	0.46	176.14	5764.53	45.20 S	6.22 E	42.25	0.09
5860.77	0.50	196.81	5860.41	45.98 S	6.12 E	42.88	0.18
5956.68	0.61	212.35	5956.32	46.82 S	5.73 E	43.41	0.19
6054.74	0.58	217.79	6054.37	47.65 S	5.14 E	43.84	0.07
6149.17	0.43	229.35	6148.80	48.26 S	4.58 E	44.08	0.19
6241.53	0.53	187.93	6241.16	48.91 S	4.26 E	44.48	0.38
6336.73	0.44	156.77	6336.35	49.68 S	4.34 E	45.19	0.29
6388.96	0.51	174.23	6388.58	50.09 S	4.44 E	45.61	0.31
6437.33	0.65	159.50	6436.95	50.57 S	4.56 E	46.07	0.42
6534.86	0.49	172.94	6534.48	51.50 S	4.81 E	47.00	0.21
6630.89	0.45	184.45	6630.50	52.28 S	4.83 E	47.69	0.11
6726.83	0.44	180.68	6726.44	53.03 S	4.79 E	48.32	0.03
6822.44	0.40	162.88	6822.05	53.71 S	4.89 E	48.96	0.14
6918.13	0.56	174.04	6917.73	54.50 S	5.04 E	49.71	0.19
7011.46	0.32	185.63	7011.06	55.21 S	5.06 E	50.34	0.27
7109.41	0.54	204.95	7109.01	55.90 S	4.84 E	50.83	0.27
7205.30	0.45	211.55	7204.89	56.63 S	4.45 E	51.27	0.11
7301.43	0.57	216.27	7301.02	57.34 S	3.97 E	51.64	0.13
7394.03	0.88	237.89	7393.61	58.09 S	3.09 E	51.85	0.44
7492.35	1.06	248.06	7491.92	58.83 S	1.61 E	51.75	0.25
7589.06	0.64	283.13	7588.62	59.04 S	0.25 E	51.26	0.67
7684.78	0.72	280.36	7684.33	58.81 S	0.86 W	50.50	0.09
7779.85	0.64	297.13	7779.40	58.46 S	1.92 W	49.67	0.22
7877.15	0.79	282.23	7876.69	58.07 S	3.06 W	48.76	0.24
7973.13	0.91	268.39	7972.66	57.95 S	4.47 W	47.95	0.25
8066.71	1.07	262.34	8066.22	58.09 S	6.07 W	47.27	0.20
8163.21	1.06	183.52	8162.71	59.10 S	7.02 W	47.67	1.40
8256.61	2.03	187.48	8256.08	61.60 S	7.29 W	49.70	1.04
8276.71	2.22	188.14	8276.16	62.34 S	7.39 W	50.29	0.95
8360.29	3.67	182.39	8359.63	66.62 S	7.73 W	53.82	1.77
8396.65	4.99	183.01	8395.88	69.36 S	7.86 W	56.13	3.63
8428.91	5.96	184.13	8428.00	72.43 S	8.06 W	58.70	3.02
8457.38	6.62	184.77	8456.30	75.54 S	8.30 W	61.27	2.33
8491.89	7.22	186.53	8490.55	79.68 S	8.71 W	64.64	1.84
8525.32	8.06	186.68	8523.69	84.09 S	9.23 W	68.21	2.51
8554.46	8.67	185.91	8552.52	88.30 S	9.69 W	71.63	2.13

8554.46	8.07	183.51	8522.32	88.50 S	9.09 W	71.03	2.13
8598.25	9.50	184.77	8595.76	95.19 S	10.33 W	77.27	1.94
8659.65	10.12	183.80	8656.26	105.62 S	11.11 W	85.92	1.04
8693.51	9.83	182.61	8689.61	111.48 S	11.44 W	90.82	1.05
8723.57	9.80	181.00	8719.23	116.60 S	11.60 W	95.18	0.92
8756.25	9.65	180.09	8751.44	122.12 S	11.65 W	99.93	0.66
8790.22	8.91	178.99	8784.96	127.60 S	11.61 W	104.70	2.24
8825.57	8.56	177.37	8819.90	132.96 S	11.44 W	109.43	1.21
8850.66	8.67	176.28	8844.71	136.71 S	11.23 W	112.78	0.78
8950.92	7.22	181.35	8944.01	150.55 S	10.89 W	124.94	1.60
9046.40	6.24	171.45	9038.83	161.68 S	10.26 W	134.89	1.59
9143.03	4.89	174.66	9135.00	170.98 S	9.10 W	143.52	1.43
9240.11	4.61	172.51	9231.75	178.97 S	8.20 W	150.89	0.34
9335.90	4.22	173.94	9327.25	186.29 S	7.33 W	157.66	0.42
9431.91	3.88	174.51	9423.03	193.03 S	6.64 W	163.85	0.36
9527.21	3.48	174.68	9518.13	199.12 S	6.07 W	169.41	0.42
9622.34	3.07	176.04	9613.10	204.54 S	5.62 W	174.32	0.44
9719.33	3.05	174.83	9709.96	209.70 S	5.21 W	179.00	0.07
9815.52	2.76	177.03	9806.02	214.56 S	4.86 W	183.38	0.32
9912.28	2.50	181.36	9902.68	219.00 S	4.79 W	187.26	0.34
10064.19	2.23	194.12	10054.46	225.18 S	5.59 W	192.21	0.39
10157.05	1.66	203.99	10147.27	228.16 S	6.58 W	194.30	0.71
10254.18	1.66	200.62	10244.36	230.76 S	7.65 W	196.02	0.10
10349.19	1.60	196.87	10339.33	233.32 S	8.52 W	197.80	0.13
10447.17	1.59	196.11	10437.27	235.93 S	9.29 W	199.68	0.02
10539.87	1.20	196.93	10529.94	238.09 S	9.93 W	201.23	0.42
10731.66	0.57	144.06	10721.71	240.79 S	9.95 W	203.55	0.51
10778.66	0.52	224.28	10768.71	241.13 S	9.97 W	203.84	1.50
10812.00	0.52	224.28	10802.05	241.35 S	10.18 W	203.92	0.00

CALCULATION BASED ON MINIMUM CURVATURE METHOD

SURVEY COORDINATES RELATIVE TO WELL SYSTEM REFERENCE POINT
TVD VALUES GIVEN RELATIVE TO DRILLING MEASUREMENT POINT

VERTICAL SECTION RELATIVE TO WELL HEAD
VERTICAL SECTION IS COMPUTED ALONG A DIRECTION OF 150.00 DEGREES (TRUE)
A TOTAL CORRECTION OF 20.87 DEG FROM MAGNETIC NORTH TO TRUE NORTH HAS BEEN APPLIED

HORIZONTAL DISPLACEMENT IS RELATIVE TO THE WELL HEAD.
HORIZONTAL DISPLACEMENT(CLOSURE) AT 10812.00 FEET
IS 241.56 FEET ALONG 182.41 DEGREES (TRUE)

Date Printed: 28 August 2012