

cleaning

February 28, 2026

```
[1]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

# Load dataset
# data = pd.read_csv("datasets/family_anxiety_14_dataset.csv") # training
# dataset
data = pd.read_csv("datasets/enhanced_anxiety_dataset.csv") # testing dataset

# Display basic dataset information
print("DATASET DESCRIPTION")
print(f"Dataset shape: {data.shape[0]} rows, {data.shape[1]} columns")
print(f"Column names: {list(data.columns)}")
print(f>Data types:\n{data.dtypes}")
print(f"Missing values:\n{data.isnull().sum()}")

# Convert Yes/No columns to binary using map() instead of replace to avoid
# warning
yes_no_cols = ['Smoking', 'Family History of Anxiety', 'Dizziness',
               'Medication', 'Recent Major Life Event']
for col in yes_no_cols:
    data[col] = data[col].map({'Yes': 1, 'No': 0})

# Creating target column: Diagnosed if Anxiety Level > 4
data['Diagnosed'] = (data['Anxiety Level (1-10)'] > 4).astype(int)

print("NEW TARGET COLUMN DIAGNOSED")
print(data[['Anxiety Level (1-10)', 'Diagnosed']].head())
print(f"Diagnosed distribution: 0 = {sum(data['Diagnosed']==0)}, 1 =
      {sum(data['Diagnosed']==1)}")

# Features vs target
features = data.drop(columns=['Diagnosed'])
target = data['Diagnosed']
```

```

# Display min and max for numeric features after conversion
numeric_features = features.select_dtypes(include=[np.number])

print("NUMERIC FEATURES MIN AND MAX VALUES")
for col in numeric_features.columns:
    print(f"{col}: Min = {numeric_features[col].min()}, Max = {numeric_features[col].max()}")

# statistical summary
print("STATISTICAL SUMMARY OF NUMERIC FEATURES")
print(numeric_features.describe())

# OUTLIER DETECTION FOR CONTINUOUS COLUMNS
print("OUTLIER DETECTION FOR CONTINUOUS COLUMNS")

# Identify continuous columns
continuous_cols = ['Age', 'Anxiety Level (1-10)', 'Sleep Hours', 'Physical Activity (hrs/week)']

print(f"Continuous columns: {continuous_cols}")

# IQR Method for outlier detection
def detect_outliers_iqr(data, columns):
    outlier_summary = {}

    for col in columns:
        if col in data.columns:
            Q1 = data[col].quantile(0.25)
            Q3 = data[col].quantile(0.75)
            IQR = Q3 - Q1
            lower_bound = Q1 - 1.5 * IQR
            upper_bound = Q3 + 1.5 * IQR

            outliers = data[(data[col] < lower_bound) | (data[col] > upper_bound)]
            outlier_indices = outliers.index.tolist()

            outlier_summary[col] = {
                'Q1': Q1,
                'Q3': Q3,
                'IQR': IQR,
                'lower_bound': lower_bound,
                'upper_bound': upper_bound,
                'outlier_count': len(outliers),
                'outlier_percentage': (len(outliers) / len(data)) * 100,
                'outlier_indices': outlier_indices,
                'outlier_values': outliers[col].tolist()
            }

```

```

    }

    return outlier_summary

# Z-Score Method for outlier detection
def detect_outliers_zscore(data, columns, threshold=3):
    outlier_summary = {}

    for col in columns:
        if col in data.columns:
            mean = data[col].mean()
            std = data[col].std()
            z_scores = np.abs((data[col] - mean) / std)

            outliers = data[z_scores > threshold]
            outlier_indices = outliers.index.tolist()

            outlier_summary[col] = {
                'mean': mean,
                'std': std,
                'threshold': threshold,
                'outlier_count': len(outliers),
                'outlier_percentage': (len(outliers) / len(data)) * 100,
                'outlier_indices': outlier_indices,
                'outlier_values': outliers[col].tolist(),
                'max_zscore': z_scores.max()
            }

    return outlier_summary

# Detect outliers using both methods
iqr_outliers = detect_outliers_iqr(data, continuous_cols)
zscore_outliers = detect_outliers_zscore(data, continuous_cols)

# Display IQR method results
print("IQR METHOD OUTLIER RESULTS")
for col, stats in iqr_outliers.items():
    print(f"{col}: {stats['outlier_count']} outliers, {stats['outlier_percentage']:.2f}%")
    print(f" Bounds: [{stats['lower_bound']:.2f}, {stats['upper_bound']:.2f}]")
    if stats['outlier_count'] > 0:
        print(f" Outlier values: {stats['outlier_values']}")

# Display Z-Score method results
print("ZSCORE METHOD OUTLIER RESULTS")
for col, stats in zscore_outliers.items():

```

```

    print(f"{col}: {stats['outlier_count']} outliers_␣
↳({stats['outlier_percentage']:.2f}%)" )
    print(f"    Max ZScore: {stats['max_zscore']:.2f}")
    if stats['outlier_count'] > 0:
        print(f"    Outlier values: {stats['outlier_values']}")

# Box plots for visualizing outliers
fig, axes = plt.subplots(1, len(continuous_cols), figsize=(15, 5))
if len(continuous_cols) == 1:
    axes = [axes]

for i, col in enumerate(continuous_cols):
    axes[i].boxplot(data[col].dropna())
    axes[i].set_title(f'{col} Boxplot')
    axes[i].set_ylabel('Values')
plt.tight_layout()
plt.show()

# Numeric features correlation heatmap showing only high correlations
print("HIGH CORRELATIONS ABS > 0.2")
corr_matrix = numeric_features.corr(method='spearman')

# Create a mask for correlations with absolute value > 0.2
mask = np.abs(corr_matrix) > 0.2

# Remove diagonal
np.fill_diagonal(mask.values, False)

# Get pairs with high correlation
high_corr_pairs = []
for i in range(len(corr_matrix.columns)):
    for j in range(i+1, len(corr_matrix.columns)):
        if mask.iloc[i, j]:
            high_corr_pairs.append({
                'Feature 1': corr_matrix.columns[i],
                'Feature 2': corr_matrix.columns[j],
                'Correlation': corr_matrix.iloc[i, j]
            })

# Display high correlation pairs
if high_corr_pairs:
    high_corr_df = pd.DataFrame(high_corr_pairs)
    high_corr_df = high_corr_df.sort_values('Correlation', ascending=False)
    print(high_corr_df.to_string(index=False))
else:
    print("No correlations with absolute value > 0.2 found")

```

```

# Create heatmap only for high correlations
if high_corr_pairs:
    plt.figure(figsize=(10, 8))

    # Get unique features from high correlation pairs
    high_corr_features = list(set([item['Feature 1'] for item in
    ↪high_corr_pairs] +
                                [item['Feature 2'] for item in
    ↪high_corr_pairs]))

    # Filter correlation matrix for these features
    high_corr_matrix = corr_matrix.loc[high_corr_features, high_corr_features]

    sns.heatmap(high_corr_matrix, annot=True, fmt=".2f",
                cmap="coolwarm", center=0, linewidths=0.2, square=True)
    plt.title("High Correlations Only Absolute > 0.2", fontsize=16,
    ↪fontweight='bold')
    plt.tight_layout()
    plt.show()

# 1. ENHANCED TARGET DISTRIBUTION PLOT - with percentages and clear labels
plt.figure(figsize=(10, 5))
ax = sns.countplot(x=data['Diagnosed'], hue=data['Diagnosed'],
                  palette=['skyblue', 'salmon'], legend=False)
plt.title("Diagnosed Target Distribution", fontsize=14, fontweight='bold')
plt.xlabel("Diagnosis Status (0 = Non-Diagnosed, 1 = Diagnosed)")
plt.ylabel("Count")

# Add count and percentage labels on bars
total = len(data)
for p in ax.patches:
    count = int(p.get_height())
    percentage = count/total*100
    ax.annotate(f'{count}\n({percentage:.1f}%)',
                (p.get_x() + p.get_width()/2., p.get_height()),
                ha='center', va='bottom', fontsize=11)
plt.tight_layout()
plt.show()

# 2. OVERLAYED HISTOGRAMS - diagnosed vs non-diagnosed with mean lines
numeric_cols = numeric_features.columns.tolist()
n_cols = len(numeric_cols)
n_rows = (n_cols + 1) // 2

fig, axes = plt.subplots(n_rows, 2, figsize=(14, 5*n_rows))
axes = axes.flatten()

```

```

for i, col in enumerate(numeric_cols):
    ax = axes[i]

    # Getting data for diagnosed and non-diagnosed separately
    diagnosed_data = data[data['Diagnosed'] == 1][col]
    nondiagnosed_data = data[data['Diagnosed'] == 0][col]

    # Plotting histograms with transparency
    ax.hist(nondiagnosed_data, bins=15, alpha=0.6, color='skyblue',
            label=f'Non-Diagnosed (n={len(nondiagnosed_data)})',
    edgecolor='black', linewidth=0.5)
    ax.hist(diagnosed_data, bins=15, alpha=0.7, color='salmon',
            label=f'Diagnosed (n={len(diagnosed_data)})', edgecolor='black',
    linewidth=0.5)

    # Adding vertical lines for means
    ax.axvline(nondiagnosed_data.mean(), color='blue', linestyle='--',
               linewidth=2, label=f'Mean Non-Diagnosed: {nondiagnosed_data.
    mean():.2f}')
    ax.axvline(diagnosed_data.mean(), color='red', linestyle='--',
               linewidth=2, label=f'Mean Diagnosed: {diagnosed_data.mean():.
    2f}')

    ax.set_title(f'{col} Distribution by Diagnosis', fontsize=12,
    fontweight='bold')
    ax.set_xlabel(col)
    ax.set_ylabel('Frequency')
    ax.legend(loc='upper right', fontsize=8)
    ax.grid(True, alpha=0.3)

# Hide any unused subplots
for j in range(i+1, len(axes)):
    axes[j].set_visible(False)

plt.tight_layout()
plt.show()

# 3. DENSITY PLOTS
fig, axes = plt.subplots(n_rows, 2, figsize=(14, 5*n_rows))
axes = axes.flatten()

for i, col in enumerate(numeric_cols):
    ax = axes[i]

    # Create density plots for each group

```

```

    for diagnosis, color, label in [(1, 'salmon', 'Diagnosed'), (0, 'skyblue', 'Non-Diagnosed')]:
        subset = data[data['Diagnosed'] == diagnosis]
        sns.kdeplot(data=subset, x=col, ax=ax, color=color,
                    label=f'{label} (n={len(subset)})',
                    fill=True, alpha=0.4, linewidth=2)

    ax.set_title(f'{col} Density by Diagnosis', fontsize=12, fontweight='bold')
    ax.set_xlabel(col)
    ax.set_ylabel('Density')
    ax.legend(loc='upper right')
    ax.grid(True, alpha=0.3)

# Hide any unused subplots
for j in range(i+1, len(axes)):
    axes[j].set_visible(False)

plt.tight_layout()
plt.show()

# Skewness and kurtosis for numeric features
skew_kurt = pd.DataFrame({
    'Skewness': numeric_features.skew(),
    'Kurtosis': numeric_features.kurtosis()
}).sort_values(by='Skewness', key=abs, ascending=False)

print("SKEWNESS AND KURTOSIS OF FEATURES")
print(skew_kurt)

# Categorical features summary
categorical_features = features.select_dtypes(include=['object', 'category']).columns

print("CATEGORICAL FEATURES SUMMARY")
for col in categorical_features:
    print(f"Categorical Feature: {col}")
    print(f"Number of unique values: {data[col].nunique()}")
    print("Value counts top 10:")
    print(data[col].value_counts().head(10))

# Save cleaned dataset
# data.to_csv("training_dataset.csv", index=False) # save the training dataset
data.to_csv("testing_dataset.csv", index=False)
print("Dataset saved")
print(f"Final dataset shape: {data.shape[0]} rows, {data.shape[1]} columns")

```

DATASET DESCRIPTION

Dataset shape: 11000 rows, 19 columns

Column names: ['Age', 'Gender', 'Occupation', 'Sleep Hours', 'Physical Activity (hrs/week)', 'Caffeine Intake (mg/day)', 'Alcohol Consumption (drinks/week)', 'Smoking', 'Family History of Anxiety', 'Stress Level (1-10)', 'Heart Rate (bpm)', 'Breathing Rate (breaths/min)', 'Sweating Level (1-5)', 'Dizziness', 'Medication', 'Therapy Sessions (per month)', 'Recent Major Life Event', 'Diet Quality (1-10)', 'Anxiety Level (1-10)']

Data types:

Age	int64
Gender	object
Occupation	object
Sleep Hours	float64
Physical Activity (hrs/week)	float64
Caffeine Intake (mg/day)	int64
Alcohol Consumption (drinks/week)	int64
Smoking	object
Family History of Anxiety	object
Stress Level (1-10)	int64
Heart Rate (bpm)	int64
Breathing Rate (breaths/min)	int64
Sweating Level (1-5)	int64
Dizziness	object
Medication	object
Therapy Sessions (per month)	int64
Recent Major Life Event	object
Diet Quality (1-10)	int64
Anxiety Level (1-10)	float64

dtype: object

Missing values:

Age	0
Gender	0
Occupation	0
Sleep Hours	0
Physical Activity (hrs/week)	0
Caffeine Intake (mg/day)	0
Alcohol Consumption (drinks/week)	0
Smoking	0
Family History of Anxiety	0
Stress Level (1-10)	0
Heart Rate (bpm)	0
Breathing Rate (breaths/min)	0
Sweating Level (1-5)	0
Dizziness	0
Medication	0
Therapy Sessions (per month)	0
Recent Major Life Event	0
Diet Quality (1-10)	0

Anxiety Level (1-10) 0

dtype: int64

NEW TARGET COLUMN DIAGNOSED

	Anxiety Level (1-10)	Diagnosed
0	5.0	1
1	3.0	0
2	1.0	0
3	2.0	0
4	1.0	0

Diagnosed distribution: 0 = 7618, 1 = 3382

NUMERIC FEATURES MIN AND MAX VALUES

Age: Min = 18, Max = 64

Sleep Hours: Min = 2.3, Max = 11.3

Physical Activity (hrs/week): Min = 0.0, Max = 10.1

Caffeine Intake (mg/day): Min = 0, Max = 599

Alcohol Consumption (drinks/week): Min = 0, Max = 19

Smoking: Min = 0, Max = 1

Family History of Anxiety: Min = 0, Max = 1

Stress Level (1-10): Min = 1, Max = 10

Heart Rate (bpm): Min = 60, Max = 119

Breathing Rate (breaths/min): Min = 12, Max = 29

Sweating Level (1-5): Min = 1, Max = 5

Dizziness: Min = 0, Max = 1

Medication: Min = 0, Max = 1

Therapy Sessions (per month): Min = 0, Max = 12

Recent Major Life Event: Min = 0, Max = 1

Diet Quality (1-10): Min = 1, Max = 10

Anxiety Level (1-10): Min = 1.0, Max = 10.0

STATISTICAL SUMMARY OF NUMERIC FEATURES

	Age	Sleep Hours	Physical Activity (hrs/week) \
count	11000.000000	11000.000000	11000.000000
mean	40.241727	6.650691	2.942136
std	13.236140	1.227509	1.827825
min	18.000000	2.300000	0.000000
25%	29.000000	5.900000	1.500000
50%	40.000000	6.700000	2.800000
75%	51.000000	7.500000	4.200000
max	64.000000	11.300000	10.100000

	Caffeine Intake (mg/day)	Alcohol Consumption (drinks/week) \
count	11000.000000	11000.000000
mean	286.090000	9.701636
std	144.813157	5.689713
min	0.000000	0.000000
25%	172.000000	5.000000
50%	273.000000	10.000000
75%	382.000000	15.000000
max	599.000000	19.000000

	Smoking	Family History of Anxiety	Stress Level (1-10) \
count	11000.000000	11000.000000	11000.000000
mean	0.525364	0.531545	5.856364
std	0.499379	0.499027	2.927202
min	0.000000	0.000000	1.000000
25%	0.000000	0.000000	3.000000
50%	1.000000	1.000000	6.000000
75%	1.000000	1.000000	8.000000
max	1.000000	1.000000	10.000000

	Heart Rate (bpm)	Breathing Rate (breaths/min)	Sweating Level (1-5) \
count	11000.000000	11000.000000	11000.000000
mean	90.916000	20.957545	3.080636
std	17.325721	5.160107	1.398877
min	60.000000	12.000000	1.000000
25%	76.000000	17.000000	2.000000
50%	92.000000	21.000000	3.000000
75%	106.000000	25.000000	4.000000
max	119.000000	29.000000	5.000000

	Dizziness	Medication	Therapy Sessions (per month) \
count	11000.000000	11000.000000	11000.000000
mean	0.515636	0.515091	2.427818
std	0.499778	0.499795	2.183106
min	0.000000	0.000000	0.000000
25%	0.000000	0.000000	1.000000
50%	1.000000	1.000000	2.000000
75%	1.000000	1.000000	4.000000
max	1.000000	1.000000	12.000000

	Recent Major Life Event	Diet Quality (1-10)	Anxiety Level (1-10)
count	11000.000000	11000.000000	11000.000000
mean	0.511182	5.181818	3.929364
std	0.499898	2.895243	2.122533
min	0.000000	1.000000	1.000000
25%	0.000000	3.000000	2.000000
50%	1.000000	5.000000	4.000000
75%	1.000000	8.000000	5.000000
max	1.000000	10.000000	10.000000

OUTLIER DETECTION FOR CONTINUOUS COLUMNS

Continuous columns: ['Age', 'Anxiety Level (1-10)', 'Sleep Hours', 'Physical Activity (hrs/week)']

IQR METHOD OUTLIER RESULTS

Age: 0 outliers (0.00%)

Bounds: [-4.00, 84.00]

Anxiety Level (1-10): 322 outliers (2.93%)


Bounds: [-2.50, 9.50]

Outlier values: [2.6, 2.5, 2.9, 11.3, 10.4, 2.9, 2.9, 2.9, 2.6, 2.9, 2.3, 10.4, 2.6, 2.7, 10.4, 11.0, 2.7]

Physical Activity (hrs/week): 36 outliers (0.33%)



Max ZScore: 3.92


Outlier values: [8.7, 9.9, 8.5, 8.5, 8.5, 8.7, 8.7, 8.5, 8.9, 9.8, 10.0, 8.6, 8.7, 9.0, 9.4, 8.7, 8.7, 9.2, 8.5, 8.8, 9.3, 10.1, 9.2, 9.2, 10.0, 9.6, 9.0, 9.0, 9.0, 8.5, 8.6, 9.7, 8.7, 8.9, 8.8, 9.6]




HIGH CORRELATIONS ABS > 0.2

Feature 1	Feature 2	Correlation
Stress Level (1-10)	Anxiety Level (1-10)	0.721165
Family History of Anxiety Therapy Sessions (per month)	Anxiety Level (1-10)	0.581110
Therapy Sessions (per month)	Anxiety Level (1-10)	0.330756
Caffeine Intake (mg/day)	Anxiety Level (1-10)	0.282222
Sleep Hours	Anxiety Level (1-10)	-0.351404







SKEWNESS AND KURTOSIS OF FEATURES

	Skewness	Kurtosis
Anxiety Level (1-10)	1.043996	0.950054
Therapy Sessions (per month)	1.035117	0.586923
Physical Activity (hrs/week)	0.507010	-0.215078
Caffeine Intake (mg/day)	0.323941	-0.701446
Sleep Hours	-0.224472	-0.047568
Diet Quality (1-10)	0.161948	-1.228529
Stress Level (1-10)	-0.160872	-1.255731
Breathing Rate (breaths/min)	-0.141205	-1.171865
Family History of Anxiety	-0.126451	-1.984371
Heart Rate (bpm)	-0.119204	-1.192624
Smoking	-0.101599	-1.990039
Age	0.097336	-1.126341
Sweating Level (1-5)	-0.073929	-1.263226
Dizziness	-0.062585	-1.996446
Medication	-0.060399	-1.996715
Recent Major Life Event	-0.044745	-1.998361
Alcohol Consumption (drinks/week)	-0.023334	-1.159180

CATEGORICAL FEATURES SUMMARY

Categorical Feature: Gender

Number of unique values: 3

Value counts top 10:

Gender

Female 3730

Male 3657

Other 3613

Name: count, dtype: int64

Categorical Feature: Occupation

Number of unique values: 13

Value counts top 10:

Occupation

Musician 892

Artist 888

Student 878

Nurse 861

Chef 858

Doctor 842

Other 840

Freelancer 838

Engineer 833

Scientist 832

Name: count, dtype: int64

Dataset saved

Final dataset shape: 11000 rows, 20 columns