

Maintenance sheet version 9 for ablation area (tripod, one level)

Station name	SWC - old, SWC-L
People present	Jason Box, Adrien Werhule, Jakob Jakobsen
Purpose	Maintenance / installation / take-down / quick visit / emergency
Date	2/8-2022

Notes: Wose wiring on tripod bent legs?
we rotated wire box to S
radiometer 15° E of true south
solar pointing west.

AWS to do list		Check after maintenance			
Part	Shipped (Y/N)	Replaced? (Y/N)	Number shipped/arrival	Number departure	
Radiometer		N	202382		Clean? (Y) / N
Ablation hose assembly		N	50183		No air in hose and bladder half full? Y / (N) 1/5 full no air
Iridium modem IMEI number		N	24310		
Inclinometer/compass		N			Attached to the radiometer? (Y) / N
Satellite antenna		N			
Wind sensor		N			Black box pointing toward the radiometer (i.e. along the boom) (Y) / N changed to good
Temperature / humidity assembly					Fan spins? Y / N Sounds, OK? Y / N
HygroClip T/hum assembly		N			NB: Rotronics (Y / N) could have a 40 °C offset. New or old type? NB: Luft sensor (Y / N)
Sonic ranger on AWS		Y			Old sensor with new membrane? Y / N replaced whole unit
Sonic ranger on stake(s)					Old sensor with new membrane? Y / N NB: make sure not being buried next winter installed new, higher
Thermistor string		N			no spare. needs to be analog
Solar panel					Clean? (Y) / N NB: is not effective when partially covered
GPS antenna					At top of logger enclosure? (Y) / N was down moved to ok
Data logger					CR1000 or CR1000X?
Multiplexer					Clicking during measurement cycle? Y / N
Logger enclosure	!				Replaced (including everything inside)? Y / N New desiccant bags? Y / (N) none in
Battery box					New box? Y / N New desiccant bags? Y / N
Stakes					New one(s) drilled in? (Y) / N Length of new stake(s) 8 m? (Y) / N Bottom plugged to reduce melt-in? Y / (N)
Tripod					New tripod? Y / (N) New sensor boom? Y / (N)

rusty 3 legged

Metadata maintenance

	Arrival	Departure
Time difference between logger clock and UTC ($\pm$ mm:ss)	+2 hours 1-12 sec	0
Download data and/or change CF/SD Card (wait for green light)	Y/N	Y/N
Name of logger program	promiceV30.exe	
Screen dump of values in fast scan mode	Y/N	Y/N
Photos of tripod, sensors, logger box wiring etc. (more is better)	Y/N	Y/N
Mast tilt towards radiometer (- if tilting towards anemometer)	same °	1° pitch °
Mast tilt across boom looking from radiometer (- if clockwise)	°	-2.2 roll °
Boom direction relative to north	° true/magn.	° true/magn.
Box on wind sensor exactly towards mast? If not, measure.	Y/N	Y/N
Radiometer exactly aligned with inclinometer? If not, measure.	Y/N	Y/N
Temperature / humidity height (bottom of casing – surface)	cm	260 cm
Stake assembly standing?	Y/N / sort of	Y/N / sort of
Free length of stake (if 3: outer, holding boom with sonic ranger)	cm	cm
Free length of stake 2 (if 3: middle)	cm	cm
Free length of stake 3 (if 3: outer, without sonic ranger)	cm	cm
Height of ablation bladder fluid level above the ice surface	cm	cm
Vertical difference in surface height (at station – at hose) (approx.)	cm	cm
Length of thermistor string on surface from surface marking	cm	cm
Apparent damage to sensors? If yes, which?	Y/N	Y/N

Notes:

heading 1940
 radiometer height 247.5 cm bottom
 solar bottom - 140
 enc 96
 abl 50
 snow depth 53, 50, 46, 45, 50, 52
 50, 45, 45, 44

Must-do at next visit:

always bring probe w/ cm units
 is more effective to measure height

dessicant
 straight legs?