Introduction to Computer Vision

Lecture 8 - 3D Vision I

Prof. He Wang

Logistics

- Assignment 2:
  - released on 4/4 evening
  - due on 4/20 11:59PM (Saturday)

- If 1 day (0 - 24 hours) past the deadline, 15% off
- If 2 day (24 - 48 hours) past the deadline, 30% off
- Zero credit if more than 2 days.

Logistics

- Midterm: 4/24, in class
- One-page double-sided A4 cheatsheet
- Scope: from Lecture 1 - Lecture 9

UNet Structure



- Skip link between the feature maps from the encoder and the decoder with the same resolution.
- Now what needs to store in the bottleneck?

UNet Structure



- The skip link makes shortcut from the inputs to the outputs
- Bottleneck: no need to memorize the whole image but only provides global context

Summary of Semantic Segmentation

- A top-down approach

- Bottleneck structure:
  - Large receptive field and provides global context
  - Get rid of redundant information
  - Lower the computation cost

- Skip link:
  - Assist final segmentation
  - Avoid memorization

Evaluation Metrics: Pixel Accuracy

- Pixel accuracy: simply report the percent of pixels in the image which were correctly classified.

$$accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

- However, may be misleading when the class representation is small within the image, as the measure will be biased in mainly reporting how well you identify negative case (ie. where the class is not present).

Evaluation Metrics: Intersection over Union

- Intersection over Union

$$IoU = \frac{target \cap prediction}{target \cup prediction}$$



Alternative Loss: Soft IoU Loss

$$IoU = \frac{I(X)}{U(X)} .$$

where, $I(X)$ and $U(X)$ can be approximated as follows:

$$I(X) = \sum_{v \in V} X_v * Y_v .$$

$$U(X) = \sum_{v \in V} (X_v + Y_v - X_v * Y_v) .$$

Therefore, the IoU loss L_{IoU} can be defined as follows:

$$L_{IoU} = 1 - IoU = 1 - \frac{I(X)}{U(X)} .$$

Rahman, Md Atiqur, and Yang Wang. "Optimizing intersection-over-union in deep neural networks for image segmentation." International symposium on visual computing. Springer, Cham, 2016

Evaluation Metrics: mIoU

- For each class, we can compute the metrics above by finding the intersection between the ground truth and predicted one-hot encoded masks for each class.

- Metrics can be examined class-by-class, or by taking the average over all the classes, to get a mean IoU.

From 2D to 3D

Some slides are borrowed and modified from Stanford CS 231A

2D Image Representations

$$H \times W \times 3$$

Beyond Single Frame and Single View

Stereo images

Multiview images

Panoramic images

We Live in a 3D World.

From partial observations to aggregate complete 3D scenes.



“Building Rome in a day.” Sameer Agarwal, Noah Snavely, Ian Simon, Steven M. Seitz and Richard Szeliski International Conference on Computer Vision, 2009, Kyoto, Japan.

Visual Data Acquisition

- Different types of sensors and visual data

RGB camera

Depth camera

LiDAR



RGB image



Depth image



LiDAR point cloud

Robots Need 3D Vision!



- Industrial robots



- Autonomous driving

Both of them need accurate and robust 3D distance information!

Various Representations of 3D Data

Regular form



Multi-view images



Depth



Volumetric

Irregular form



Surface Mesh



Point Cloud

$$F(x) = 0$$

Implicit representation

Camera Model

Some slides are borrowed and modified from Stanford CS 231A

How do We See a World?



- Let's design a camera
  - Idea 1: put a piece of film in front of an object
  - Do we get a reasonable image?

Pinhole Camera



- Idea 2: Add a barrier to block off most of the rays
  - This reduces blurring
  - The opening known as the **aperture**

Pinhole Camera



f = focal length
o = aperture = pinhole = center of the camera

Pinhole Camera



$$P = \begin{bmatrix} x \\ y \\ z \end{bmatrix} \rightarrow P' = \begin{bmatrix} x' \\ y' \end{bmatrix}$$

$$\begin{cases} x' = f\,\dfrac{x}{z} \\ y' = f\,\dfrac{y}{z} \end{cases}$$

[Eq. 1]

Derived using similar triangles

Pinhole Camera





[Eq. 2]

$$\frac{x'}{f} = \frac{x}{z}$$

Pinhole Camera

Is the size of the aperture important?





Pinhole Camera

Shrinking aperture size





-What happens if the aperture is too small?

-Less light passes through

Adding lenses!

Camera and Lense



- A lens focuses light onto the film

Camera and Lense



- A lens focuses light onto the film
  - There is a specific distance at which objects are "in focus"
  - Related to the concept of depth of field

Camera and Lense

- A lens focuses light onto the film
  - There is a specific distance at which objects are "in focus"
  - Related to the concept of depth of field

Camera and Lense



- A lens focuses light onto the film
  - All rays parallel to the optical (or principal) axis converge to one point (the *focal point*) on a plane located at the *focal length f* from the center of the lens.
  - Rays passing through the center are not deviated

Paraxial Refraction Model



From Snell's law:

$$\begin{cases} x' = z' \dfrac{x}{z} \\ y' = z' \dfrac{y}{z} \end{cases} \quad \text{[Eq. 3]}$$

$$\begin{cases} x' = f \dfrac{x}{z} \\ y' = f \dfrac{y}{z} \end{cases} \quad \text{[Eq. 1]}$$



From Snell's law:

[Eq. 3]

$$\begin{cases} x' = z' \dfrac{x}{z} \\ y' = z' \dfrac{y}{z} \end{cases}$$

[Eq. 4]

$$z' = f + z_o$$

$$f = \frac{R}{2(n-1)}$$

[FP] sec 1.1, page 8

Issues with Lenses: Radial Distortion

- Deviations are most noticeable for rays that pass through the edge of the lens



No distortion

Pin cushion



Barrel (fisheye lens)



Image magnification decreases with distance from the optical axis

The Geometry of Pinhole Camera

- Intrinsics
  - The intrinsic properties of the camera
- Extrinsics
  - The pose of the camera (in the world reference frame)

Camera Model:Intrinsics

Pinhole Camera



$$P = \begin{bmatrix} x \\ y \\ z \end{bmatrix} \rightarrow P' = \begin{bmatrix} x' \\ y' \end{bmatrix} \qquad \begin{cases} x' = f\,\dfrac{x}{z} \\ y' = f\,\dfrac{y}{z} \end{cases} \qquad \Re^3 \xrightarrow{E} \Re^2$$

[Eq. 1]

f = focal length
o = center of the camera

From Retina Plane to Images



Coordinate Systems



1. Off set



$$(x, y, z) \rightarrow (f\frac{x}{z} + c_x, f\frac{y}{z} + c_y)$$

[Eq. 5]

Converting to Pixels





1. Off set
2. From metric to pixels

$$(x, y, z) \rightarrow (\underbrace{f\,k}_{\alpha}\frac{x}{z} + c_x, \underbrace{f\,l}_{\beta}\frac{y}{z} + c_y)$$

[Eq. 6]

Units: k,l : pixel/m

f : m

Non-square pixels

α, β : pixel

Projective Transformation



$$P = (x, y, z) \rightarrow P' = (\alpha \frac{x}{z} + c_x, \beta \frac{y}{z} + c_y)$$

[Eq. 7]



- Is this a linear transformation?
  No – division by z is nonlinear
- Can we express it in a matrix form?

Homogeneous Coordinate System

E→H

$$(x, y) \Rightarrow \begin{bmatrix} x \\ y \\ 1 \end{bmatrix}$$

homogeneous image coordinates

$$(x, y, z) \Rightarrow \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

homogeneous scene coordinates

- **Converting back *from* homogeneous coordinates**

H→E

$$\begin{bmatrix} x \\ y \\ w \end{bmatrix} \Rightarrow (x/w, y/w)$$

$$\begin{bmatrix} x \\ y \\ z \\ w \end{bmatrix} \Rightarrow (x/w, y/w, z/w)$$

Projective Transformation in H

$$P_h' = \begin{bmatrix} \alpha x + c_x z \\ \beta y + c_y z \\ z \end{bmatrix} = \begin{bmatrix} \alpha & 0 & c_x & 0 \\ 0 & \beta & c_y & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix} \quad P_h \qquad \text{[Eq.8]}$$

Homogenous Euclidian

$$P_h' \rightarrow P' = (\alpha \frac{x}{z} + c_x, \beta \frac{y}{z} + c_y)$$

$$M = \begin{bmatrix} \alpha & 0 & c_x & 0 \\ 0 & \beta & c_y & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix}$$

The Camera Matrix



Camera matrix K

[Eq.9]

$$P' = M\,P$$

$$= K\begin{bmatrix} I & 0 \end{bmatrix} P$$

$$P' = \begin{bmatrix} \alpha & 0 & c_x & 0 \\ 0 & \beta & c_y & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

Camera Skewness





$$P' = \begin{bmatrix} \alpha & -\alpha\cot\theta & c_x & 0 \\ 0 & \frac{\beta}{\sin\theta} & c_y & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

sec. 1.2.2 [FP] or sec. 6.2.4 [HZ]

Degree of Freedom of K





$$P' = \begin{bmatrix} \alpha & -\alpha\cot\theta & c_x & 0 \\ 0 & \frac{\beta}{\sin\theta} & c_y & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

How many degrees of freedom does K have?

5 degrees of freedom!

Camera Model:Extrinsics

World Reference Frame



- The mapping so far is defined within the camera reference system
- What if an object is represented in the world reference system?
- Need to introduce an additional mapping from world ref system to camera ref system

3D Translation of Points



$$T = \begin{bmatrix} T_x \\ T_y \\ T_z \end{bmatrix}$$

$$P' \rightarrow \begin{bmatrix} \mathbf{I} & T \\ 0 & 1 \end{bmatrix}_{4\times4} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

A translation vector in 3D has 3 degrees of freedom

3D Rotation of Points

Rotation around the coordinate axes, counter-clockwise:



$$R_x(\alpha) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos\alpha & -\sin\alpha \\ 0 & \sin\alpha & \cos\alpha \end{bmatrix}$$

$$R_y(\beta) = \begin{bmatrix} \cos\beta & 0 & \sin\beta \\ 0 & 1 & 0 \\ -\sin\beta & 0 & \cos\beta \end{bmatrix}$$

$$R_z(\gamma) = \begin{bmatrix} \cos\gamma & -\sin\gamma & 0 \\ \sin\gamma & \cos\gamma & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$R = R_x(\alpha)\, R_y(\beta)\, R_z(\gamma)$$

$$P' \rightarrow \begin{bmatrix} R & 0 \\ 0 & 1 \end{bmatrix}_{4\times4} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

A rotation matrix in 3D has 3 degrees of freedom

3D Rotation and Translations

$$R = R_x(\alpha)\ R_y(\beta)\ R_z(\gamma) \qquad T = \begin{bmatrix} T_x \\ T_y \\ T_z \end{bmatrix}$$

$$P' \rightarrow \begin{bmatrix} R & T \\ 0 & 1 \end{bmatrix}_{4\times4} \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$

World Reference System



In 4D homogeneous coordinates: $P = \begin{bmatrix} R & T \\ 0 & 1 \end{bmatrix}_{4\times4} P_w \leftarrow \begin{bmatrix} x_w \\ y_w \\ z_w \\ 1 \end{bmatrix}$

[Eq.9]

Internal parameters

External parameters (Camera pose)

$$P' = K\begin{bmatrix} I & 0 \end{bmatrix} P = K\begin{bmatrix} I & 0 \end{bmatrix}\begin{bmatrix} R & T \\ 0 & 1 \end{bmatrix}_{4\times4} P_w = K\begin{bmatrix} R & T \end{bmatrix} P_w$$

[Eq.11]

The Projective Transformation



$$P'_{3\times1} = M\,P_w = K_{3\times3}\begin{bmatrix} R & T \end{bmatrix}_{3\times4} P_{w4\times1} \qquad M = \begin{bmatrix} \mathbf{m}_1 \\ \mathbf{m}_2 \\ \mathbf{m}_3 \end{bmatrix}$$

$$= \begin{bmatrix} \mathbf{m}_1 \\ \mathbf{m}_2 \\ \mathbf{m}_3 \end{bmatrix} P_W = \begin{bmatrix} \mathbf{m}_1 P_W \\ \mathbf{m}_2 P_W \\ \mathbf{m}_3 P_W \end{bmatrix} \quad \text{E} \rightarrow \left(\frac{\mathbf{m}_1 P_w}{\mathbf{m}_3 P_w}, \frac{\mathbf{m}_2 P_w}{\mathbf{m}_3 P_w}\right) \quad \text{[Eq.12]}$$

Properties of Projective Transformations

- Points project to points
- Lines project to lines
- Distant objects look smaller

Exercise



$$M = K\begin{bmatrix} R & T \end{bmatrix} = K\begin{bmatrix} I & 0 \end{bmatrix} = \begin{bmatrix} f & 0 & 0 & 0 \\ 0 & f & 0 & 0 \\ 0 & 0 & 1 & 0 \end{bmatrix}$$

$$\rightarrow P'_E = \left(\frac{\mathbf{m}_1 P_w}{\mathbf{m}_3 P_w}, \frac{\mathbf{m}_2 P_w}{\mathbf{m}_3 P_w}\right) = \left(f\frac{x_w}{z_w}, f\frac{y_w}{z_w}\right) \qquad P_w = \begin{bmatrix} x_w \\ y_w \\ z_w \\ 1 \end{bmatrix}$$

Projective Camera



Weak Projective Camera

When the relative scene depth is small compared to its distance from the camera



Weak Projective Camera



$$\begin{cases} x' = \dfrac{f'}{z}x \\ y' = \dfrac{f'}{z}y \end{cases} \rightarrow \begin{cases} x' = \dfrac{f'}{z_0}x \\ y' = \dfrac{f'}{z_0}y \end{cases}$$

Magnification m

Weak Projective Camera



Projective (perspective) Weak perspective

$$M = K\begin{bmatrix} R & T \end{bmatrix} = \begin{bmatrix} \mathbf{A} & \mathbf{b} \\ \mathbf{v} & 1 \end{bmatrix} \rightarrow M = \begin{bmatrix} \mathbf{A} & \mathbf{b} \\ \mathbf{0} & 1 \end{bmatrix}$$

Perspective vs. Weak Perspective

$$P' = M\,P_w = \begin{bmatrix} \mathbf{m}_1 \\ \mathbf{m}_2 \\ \mathbf{m}_3 \end{bmatrix} P_W = \begin{bmatrix} \mathbf{m}_1 P_W \\ \mathbf{m}_2 P_W \\ \mathbf{m}_3 P_W \end{bmatrix} \qquad M = \begin{bmatrix} \mathbf{A} & \mathbf{b} \\ \mathbf{v} & \mathbf{1} \end{bmatrix} = \begin{bmatrix} \mathbf{m}_1 \\ \mathbf{m}_2 \\ \mathbf{m}_3 \end{bmatrix}$$

$$\xrightarrow{E} \left(\frac{\mathbf{m}_1 P_w}{\mathbf{m}_3 P_w}, \frac{\mathbf{m}_2 P_w}{\mathbf{m}_3 P_w}\right)$$

Perspective

$$P' = M\,P_w = \begin{bmatrix} \mathbf{m}_1 \\ \mathbf{m}_2 \\ \mathbf{m}_3 \end{bmatrix} P_W = \begin{bmatrix} \mathbf{m}_1 P_W \\ \mathbf{m}_2 P_W \\ 1 \end{bmatrix} \qquad M = \begin{bmatrix} \mathbf{A} & \mathbf{b} \\ \mathbf{0} & \mathbf{1} \end{bmatrix}$$

$$= \begin{bmatrix} \mathbf{m}_1 \\ \mathbf{m}_2 \\ \mathbf{m}_3 \end{bmatrix} = \begin{bmatrix} & \mathbf{m}_1 & \\ & \mathbf{m}_2 & \\ 0 & 0 & 0 & 1 \end{bmatrix}$$

$$\xrightarrow{E} (\mathbf{m}_1 P_w, \mathbf{m}_2 P_w)$$

magnification

Weak perspective

Orthographic (Affine) Projection

Distance from center of projection to image plane is infinite



$$\begin{cases} x' = \dfrac{f'}{z}x \\ y' = \dfrac{f'}{z}y \end{cases} \rightarrow \begin{cases} x' = x \\ y' = y \end{cases}$$

Orthographic Projection vs. Perspective Projection





Pros and Cons of the Camera Models

- Weak perspective results in much simpler math.
  - Accurate when object is small and distant.
  - Most useful for recognition.
- Pinhole perspective is much more accurate for modeling the 3D-to-2D mapping.
  - Used in structure from motion or SLAM.

One-Point Perspective



Masaccio, *Trinity*, Santa Maria Novella, Florence, 1425-28

il Canaletto The Piazzetta, Venice,

Weak Perspective Projection

The Kangxi Emperor's Southern Inspection Tour (1691-1698) by Wang Hui

Camera Calibration

Some slides are borrowed from Stanford CS231A.

Why Camera Calibration?

- Imagine how we picks up an object

  - Our eyes capture images of the object.
  - Our brain processes these images, finds the object, and tells our arms and hands where to go and how to pick up the object .
  - To connect the space from our eye and the space of our body, we need camera calibration.

https://blog.zivid.com/importance-of-3d-hand-eye-calibration

Camera Calibration in Robot-Camera System

- Hand-eye calibration: transfer the end-effector target pose from camera space to robot space.





Projective Camera

$$P' = M\,P_w = K\begin{bmatrix} R & T \end{bmatrix} P_w$$

Internal parameters

External parameters

$$\mathcal{M} = \begin{pmatrix} \alpha \boldsymbol{r}_1^T - \alpha\cot\theta \boldsymbol{r}_2^T + u_0 \boldsymbol{r}_3^T & \alpha t_x - \alpha\cot\theta t_y + u_0 t_z \\ \frac{\beta}{\sin\theta}\boldsymbol{r}_2^T + v_0 \boldsymbol{r}_3^T & \frac{\beta}{\sin\theta} t_y + v_0 t_z \\ \boldsymbol{r}_3^T & t_z \end{pmatrix}_{3\times 4}$$

$$K = \begin{bmatrix} \alpha & -\alpha\cot\theta & u_o \\ 0 & \frac{\beta}{\sin\theta} & v_o \\ 0 & 0 & 1 \end{bmatrix} \qquad R = \begin{bmatrix} \mathbf{r}_1^T \\ \mathbf{r}_2^T \\ \mathbf{r}_3^T \end{bmatrix} \qquad T = \begin{bmatrix} t_x \\ t_y \\ t_z \end{bmatrix}$$

Goal of Calibration

- Estimate camera intrinsics and extrinsic from one or multiple images

$$P' = M\,P_w = K\begin{bmatrix} R & T \end{bmatrix} P_w$$

$$\mathcal{M} = \begin{pmatrix} \alpha \boldsymbol{r}_1^T - \alpha\cot\theta\,\boldsymbol{r}_2^T + u_0\boldsymbol{r}_3^T & \alpha t_x - \alpha\cot\theta\, t_y + u_0 t_z \\ \frac{\beta}{\sin\theta}\boldsymbol{r}_2^T + v_0\boldsymbol{r}_3^T & \frac{\beta}{\sin\theta} t_y + v_0 t_z \\ \boldsymbol{r}_3^T & t_z \end{pmatrix}_{3\times 4}$$

$$K = \begin{bmatrix} \alpha & -\alpha\cot\theta & u_o \\ 0 & \frac{\beta}{\sin\theta} & v_o \\ 0 & 0 & 1 \end{bmatrix} \qquad R = \begin{bmatrix} \mathbf{r}_1^T \\ \mathbf{r}_2^T \\ \mathbf{r}_3^T \end{bmatrix} \qquad T = \begin{bmatrix} t_x \\ t_y \\ t_z \end{bmatrix}$$

Change notation:
$P = P_w$

$p = P'$

Calibration Problem



- $P_1 \ldots P_n$ with known positions in $[O_w, i_w, j_w, k_w]$

Calibration Problem



- $P_1 \ldots P_n$ with known positions in $[O_w, i_w, j_w, k_w]$
- $p_1, \ldots p_n$ known positions in the image

Goal: compute intrinsic and extrinsic parameters

Assuming known correspondence between P_n and p_n

Calibration Problem

- The degree of freedom of M: 5 + 3 + 3 = 11

- We need 11 equations
- Thus, 6 correspondence would suffice

$$p = K[R\ T]P$$

$$K = \begin{bmatrix} \alpha & -\alpha\cot\theta & u_o \\ 0 & \frac{\beta}{\sin\theta} & v_o \\ 0 & 0 & 1 \end{bmatrix} \qquad R = \begin{bmatrix} \mathbf{r}_1^T \\ \mathbf{r}_2^T \\ \mathbf{r}_3^T \end{bmatrix} \qquad T = \begin{bmatrix} t_x \\ t_y \\ t_z \end{bmatrix}$$

Calibration Problem



In practice, using more than 6 correspondences enables more robust results

Calibration Problem



$$P_i \rightarrow M\,P_i \rightarrow p_i = \begin{bmatrix} u_i \\ v_i \end{bmatrix} = \begin{bmatrix} \frac{m_1\,P_i}{m_3\,P_i} \\ \frac{m_2\,P_i}{m_3\,P_i} \end{bmatrix} \qquad M = \begin{bmatrix} m_1 \\ m_2 \\ m_3 \end{bmatrix}$$

in pixels

[Eq. 1]

Calibration Problem

[Eq. 1]

$$\begin{bmatrix} u_i \\ v_i \end{bmatrix} = \begin{bmatrix} \dfrac{\mathbf{m}_1\, P_i}{\mathbf{m}_3\, P_i} \\ \dfrac{\mathbf{m}_2\, P_i}{\mathbf{m}_3\, P_i} \end{bmatrix}$$

$$u_i = \frac{\mathbf{m}_1\, P_i}{\mathbf{m}_3\, P_i} \rightarrow u_i(\mathbf{m}_3\, P_i) = \mathbf{m}_1\, P_i \rightarrow u_i(\mathbf{m}_3\, P_i) - \mathbf{m}_1\, P_i = 0$$

$$v_i = \frac{\mathbf{m}_2\, P_i}{\mathbf{m}_3\, P_i} \rightarrow v_i(\mathbf{m}_3\, P_i) = \mathbf{m}_2\, P_i \rightarrow v_i(\mathbf{m}_3\, P_i) - \mathbf{m}_2\, P_i = 0$$

[Eqs. 2]

Calibration Problem

$$
\begin{cases}
u_1(\mathbf{m}_3\, P_1) - \mathbf{m}_1\, P_1 = 0 \\
v_1(\mathbf{m}_3\, P_1) - \mathbf{m}_2\, P_1 = 0 \\
\vdots \\
u_i(\mathbf{m}_3\, P_i) - \mathbf{m}_1\, P_i = 0 \\
v_i(\mathbf{m}_3\, P_i) - \mathbf{m}_2\, P_i = 0 \\
\vdots \\
u_n(\mathbf{m}_3\, P_n) - \mathbf{m}_1\, P_n = 0 \\
v_n(\mathbf{m}_3\, P_n) - \mathbf{m}_2\, P_n = 0
\end{cases}
\qquad \text{[Eqs. 3]}
$$

Calibration Problem

$$\begin{cases} -u_1(\mathbf{m}_3\ P_1)+\mathbf{m}_1\ P_1=0 \\ -v_1(\mathbf{m}_3\ P_1)+\mathbf{m}_2\ P_1=0 \\ \vdots \\ -u_n(\mathbf{m}_3\ P_n)+\mathbf{m}_1\ P_n=0 \\ -v_n(\mathbf{m}_3\ P_n)+\mathbf{m}_2\ P_n=0 \end{cases}$$



[Eq. 4]

Homogenous linear system

$$\mathbf{P} \overset{\text{def}}{=} \begin{pmatrix} \mathbf{P}_1^T & \mathbf{0}^T & -u_1\mathbf{P}_1^T \\ \mathbf{0}^T & \mathbf{P}_1^T & -v_1\mathbf{P}_1^T \\ & \vdots & \\ \mathbf{P}_n^T & \mathbf{0}^T & -u_n\mathbf{P}_n^T \\ \mathbf{0}^T & \mathbf{P}_n^T & -v_n\mathbf{P}_n^T \end{pmatrix}_{2n \times 12} \quad \text{1x4}$$

$$\boldsymbol{m} \overset{\text{def}}{=} \begin{pmatrix} \mathbf{m}_1^T \\ \mathbf{m}_2^T \\ \mathbf{m}_3^T \end{pmatrix}_{12\text{x}1} \quad \text{4x1}$$

Calibration Problem

Homogeneous M x N Linear Systems

M=number of equations = 2n
N=number of unknown = 11



Rectangular system (M>N)

- 0 is always a solution

Calibration Problem

- How do we solve this homogenous linear system?

$$Pm = 0$$

Calibration Problem

- How do we solve this homogenous linear system?

$$Pm = 0$$

- Add a constraint to **m** to avoid trivial solution: $|m|^2 = 1$
- Then we can solve the following minimization problem using SVD:

Minimize $|\mathbf{P}\,\mathbf{m}|^2$

under the constraint $|\mathbf{m}|^2 = 1$

Calibration Problem

$$\mathbf{P}\,\mathbf{m} = 0$$

SVD decomposition of P

$$\mathbf{U}_{2n\times 12}\,\mathbf{D}_{12\times 12}\,\mathbf{V}^{\mathrm{T}}_{12\times 12}$$

Last column of V gives $\boldsymbol{m}$ Why? See pag 592 of HZ*

$$\boldsymbol{m} \overset{\text{def}}{=} \begin{pmatrix} \mathbf{m}_1^{\mathrm{T}} \\ \mathbf{m}_2^{\mathrm{T}} \\ \mathbf{m}_3^{\mathrm{T}} \end{pmatrix}$$

Convert 1×12 into 3×4

$$\hat{M}$$

*: R. Hartley and A. Zisserman. Multiple View Geometry in Computer Vision. Cambridge University Press, 2003.

Calibration Problem

- Since $||\hat{M}||_F = 1$, we need to find a scale ρ to unnormalize it:

$$M = \rho\hat{M} = \begin{pmatrix} \alpha \boldsymbol{r}_1^T - \alpha \cot\theta \boldsymbol{r}_2^T + c_x \boldsymbol{r}_3^T & \alpha t_x - \alpha \cot\theta t_y + c_x t_z \\ \frac{\beta}{\sin\theta}\boldsymbol{r}_2^T + c_y \boldsymbol{r}_3^T & \frac{\beta}{\sin\theta} t_y + c_y t_z \\ \boldsymbol{r}_3^T & t_z \end{pmatrix} = \mathrm{K}\begin{bmatrix} \mathrm{R} & \mathrm{T} \end{bmatrix}$$

$$\mathrm{K} = \begin{bmatrix} \alpha & -\alpha\cot\theta & c_x \\ 0 & \frac{\beta}{\sin\theta} & c_y \\ 0 & 0 & 1 \end{bmatrix}$$

Note that we can also represent $\hat{M} = \left[\hat{A}_{3\times3}\ \hat{b}_{1\times3}\right]$, which satisfies $A = \rho\hat{A}, b = \rho\hat{b}$.

Calibration Problem

$$M = \rho\hat{M} = \begin{pmatrix} \alpha \boldsymbol{r}_1^T - \alpha\cot\theta \boldsymbol{r}_2^T + c_x \boldsymbol{r}_3^T & \alpha t_x - \alpha\cot\theta t_y + c_x t_z \\ \frac{\beta}{\sin\theta}\boldsymbol{r}_2^T + c_y \boldsymbol{r}_3^T & \frac{\beta}{\sin\theta} t_y + c_y t_z \\ \boldsymbol{r}_3^T & t_z \end{pmatrix} = \mathrm{K}\begin{bmatrix}\mathrm{R} & \mathrm{T}\end{bmatrix}$$

A $\quad$ $\mathbf{b}$

$$\mathrm{K} = \begin{bmatrix} \alpha & -\alpha\cot\theta & c_x \\ 0 & \frac{\beta}{\sin\theta} & c_y \\ 0 & 0 & 1 \end{bmatrix}$$

Box 1

$$\hat{\mathrm{A}} = \begin{bmatrix} \hat{\mathbf{a}}_1^{\mathrm{T}} \\ \hat{\mathbf{a}}_2^{\mathrm{T}} \\ \hat{\mathbf{a}}_3^{\mathrm{T}} \end{bmatrix} \qquad \hat{\mathrm{b}} = \begin{bmatrix} \hat{\mathrm{b}}_1 \\ \hat{\mathrm{b}}_2 \\ \hat{\mathrm{b}}_3 \end{bmatrix}$$

Estimated values from $\hat{M}$

Intrinsic

$$\rho = \frac{\pm 1}{|\hat{\mathbf{a}}_3|} \qquad c_x = \rho^2(\hat{\mathbf{a}}_1 \cdot \hat{\mathbf{a}}_3)$$

$$c_y = \rho^2(\hat{\mathbf{a}}_2 \cdot \hat{\mathbf{a}}_3)$$

$$\cos\theta = \frac{(\hat{\mathrm{a}}_2 \times \hat{\mathrm{a}}_3) \cdot (\hat{\mathrm{a}}_3 \times \hat{\mathrm{a}}_1)}{|\hat{\mathrm{a}}_2 \times \hat{\mathrm{a}}_3| \cdot |\hat{\mathrm{a}}_3 \times \hat{\mathrm{a}}_1|}$$

Theorem (Faugeras, 1993)

Let $\mathcal{M} = (\mathcal{A} \quad \boldsymbol{b})$ be a 3×4 matrix and let $\boldsymbol{a}_i^T$ $(i = 1, 2, 3)$ denote the rows of the matrix $\mathcal{A}$ formed by the three leftmost columns of $\mathcal{M}$.

- A necessary and sufficient condition for $\mathcal{M}$ to be a perspective projection matrix is that $\text{Det}(\mathcal{A}) \neq 0$.
- A necessary and sufficient condition for $\mathcal{M}$ to be a zero-skew perspective projection matrix is that $\text{Det}(\mathcal{A}) \neq 0$ and

$$(\boldsymbol{a}_1 \times \boldsymbol{a}_3) \cdot (\boldsymbol{a}_2 \times \boldsymbol{a}_3) = 0.$$

- A necessary and sufficient condition for $\mathcal{M}$ to be a perspective projection matrix with zero skew and unit aspect-ratio is that $\text{Det}(\mathcal{A}) \neq 0$ and

$$\begin{cases} (\boldsymbol{a}_1 \times \boldsymbol{a}_3) \cdot (\boldsymbol{a}_2 \times \boldsymbol{a}_3) = 0, \\ (\boldsymbol{a}_1 \times \boldsymbol{a}_3) \cdot (\boldsymbol{a}_1 \times \boldsymbol{a}_3) = (\boldsymbol{a}_2 \times \boldsymbol{a}_3) \cdot (\boldsymbol{a}_2 \times \boldsymbol{a}_3). \end{cases}$$

Calibration Problem

$$M = \rho \hat{M} = \begin{pmatrix} \alpha \boldsymbol{r}_1^T - \alpha \cot\theta \boldsymbol{r}_2^T + c_x \boldsymbol{r}_3^T & \alpha t_x - \alpha \cot\theta t_y + c_x t_z \\ \frac{\beta}{\sin\theta} \boldsymbol{r}_2^T + c_y \boldsymbol{r}_3^T & \frac{\beta}{\sin\theta} t_y + c_y t_z \\ \boldsymbol{r}_3^T & t_z \end{pmatrix} = \mathrm{K}[\mathrm{R} \quad \mathrm{T}]$$

A $\quad$ $\mathbf{b}$

$$\mathrm{K} = \begin{bmatrix} \alpha & -\alpha\cot\theta & c_x \\ 0 & \frac{\beta}{\sin\theta} & c_y \\ 0 & 0 & 1 \end{bmatrix}$$

Box 1

$$\hat{\mathrm{A}} = \begin{bmatrix} \hat{\mathbf{a}}_1^{\mathrm{T}} \\ \hat{\mathbf{a}}_2^{\mathrm{T}} \\ \hat{\mathbf{a}}_3^{\mathrm{T}} \end{bmatrix} \qquad \hat{\mathrm{b}} = \begin{bmatrix} \hat{\mathrm{b}}_1 \\ \hat{\mathrm{b}}_2 \\ \hat{\mathrm{b}}_3 \end{bmatrix}$$

Estimated values from $\hat{M}$

Intrinsic

$$\alpha = \rho^2 |\hat{\mathbf{a}}_1 \times \hat{\mathbf{a}}_3| \sin\theta$$

$$\beta = \rho^2 |\hat{\mathbf{a}}_2 \times \hat{\mathbf{a}}_3| \sin\theta$$

Calibration Problem

$$M = \rho\hat{M} = \begin{pmatrix} \alpha \boldsymbol{r}_1^T - \alpha\cot\theta \boldsymbol{r}_2^T + c_x \boldsymbol{r}_3^T & \alpha t_x - \alpha\cot\theta t_y + c_x t_z \\ \frac{\beta}{\sin\theta}\boldsymbol{r}_2^T + c_y \boldsymbol{r}_3^T & \frac{\beta}{\sin\theta} t_y + c_y t_z \\ \boldsymbol{r}_3^T & t_z \end{pmatrix} = \mathrm{K}[\mathrm{R} \quad \mathrm{T}]$$

$$A \qquad \mathbf{b}$$

$$\mathrm{K} = \begin{bmatrix} \alpha & -\alpha\cot\theta & c_x \\ 0 & \frac{\beta}{\sin\theta} & c_y \\ 0 & 0 & 1 \end{bmatrix}$$

Box 1

$$\hat{\mathrm{A}} = \begin{bmatrix} \hat{\mathbf{a}}_1^{\mathrm{T}} \\ \hat{\mathbf{a}}_2^{\mathrm{T}} \\ \hat{\mathbf{a}}_3^{\mathrm{T}} \end{bmatrix} \qquad \hat{\mathrm{b}} = \begin{bmatrix} \hat{\mathrm{b}}_1 \\ \hat{\mathrm{b}}_2 \\ \hat{\mathrm{b}}_3 \end{bmatrix}$$

Estimated values from $\hat{M}$

Extrinsic

$$\mathbf{r}_1 = \frac{(\hat{\mathbf{a}}_2 \times \hat{\mathbf{a}}_3)}{|\hat{\mathbf{a}}_2 \times \hat{\mathbf{a}}_3|} \qquad \mathbf{r}_3 = \frac{\pm \hat{\mathbf{a}}_3}{|\hat{\mathbf{a}}_3|}$$

$$\mathbf{r}_2 = \mathbf{r}_3 \times \mathbf{r}_1 \qquad \mathrm{T} = \rho\, \mathrm{K}^{-1}\hat{\mathbf{b}}$$

Calibration Problem: Degeneration Case



- P_i's cannot lie on the same plane!
- Points cannot lie on the intersection curve of two quadric surfaces

Camera Calibration with Radial Distortion

- Image magnification (in)decreases with distance from the optical axis
- Caused by imperfect lenses
- Deviations are most noticeable for rays that pass through the edge of the lens



No distortion

Pin cushion

Barrel

General Camera Calibration

$$\begin{bmatrix} u_i \\ v_i \end{bmatrix} = \begin{bmatrix} \frac{\mathbf{q}_1 \, \mathrm{P_i}}{\mathbf{q}_3 \, \mathrm{P_i}} \\ \frac{\mathbf{q}_2 \, \mathrm{P_i}}{\mathbf{q}_3 \, \mathrm{P_i}} \end{bmatrix} \quad i=1\ldots n \longrightarrow X = f(Q) \quad \text{[Eq .8]}$$

measurements

parameters

f( ) is the nonlinear mapping

- Reference:
  - Chapter 1 in D. A. Forsyth and J. Ponce. Computer Vision: A Modern Approach (2nd Edition). Prentice Hall, 2011.
  - Chapter 7 in R. Hartley and A. Zisserman. Multiple View Geometry in Computer Vision. Cambridge University Press, 2003.

Calibration Procedure



Camera Calibration Toolbox for Matlab
J. Bouguet – [1998-2000]

http://robots.stanford.edu/cs223b04/JeanYvesCalib/htmls/example.html

Calibration Procedure









Calibration Procedure



Calibration Procedure



Calibrating Intrinsics + Multiple Extrinsics



Calibrating Intrinsics + Multiple Extrinsics



Calibrating Intrinsics + Multiple Extrinsics



Visualization of Reproduction Errors



Depth Images

2D Image Representations

$$H \times W \times 3$$

Multi-View Images



- Multiple images from different viewpoints
- Contain 3D information
- Indirect, not a true 3D representation

Depth Image



- A single-channel image filled by depth values
- A 2.5D representation

True 3D representation should enable distance measurement between two points.

3D Data: from Sensors or Graphics

Real 3D data acquired by 3D sensing

Synthetic 3D data

Depth Sensors

- Depth sensors are a form of 3D range finder
- Measure multi-point distance information across a wide Field-of-View (FoV)



https://www.terabee.com/depth-sensors-precision-personal-privacy

Depth Image



- A single-channel image filled by depth values
- A 2.5D representation

True 3D representation should enable distance measurement between two points.

Stereo Sensors

- Mechanism: estimate correspondence, compute disparity and then turn it into depth.

Stereolabs Zed

Intel RealSense

Ensenso



Occipital Structure Core

Point Triangulation



Computing Depth



$$u - u' = \frac{B \cdot f}{z} = \text{disparity} \qquad \text{[Eq. 1]}$$

Note: Disparity is inversely proportional to depth

Disparity Maps

$$u - u' = \frac{B \cdot f}{z}$$

Stereo pair



Disparity map / depth map



Disparity map with occlusions

http://vision.middlebury.edu/stereo/

Advantages and Disadvantages of Stereo Sensors

Advantages:

1. Robust to the illumination of direct sunlight
2. Low implementation cost

Disadvantage:

Finding correspondences along $Image_L$ and $Image_R$ is hard and erroneous

Failure of correspondence search



Textureless surfaces

Occlusions, repetition

Non-Lambertian surfaces, specularities

Correspondence is Difficult

- Occlusions
- Fore shortening
- Baseline trade-off
- Homogeneous regions
- Repetitive patterns

Challenges

Changes of brightness/exposure



Changes in the mean and the variance of intensity values in corresponding windows!

Challenges

- Fore shortening effect



- Occlusions



Challenges

- Homogeneous regions

Challenges

- Repetitive patterns

Active Stereo



Replace one of the two cameras by a projector

- Single camera
- Projector geometry calibrated
- What's the advantage of having the projector? Correspondence problem solved!

Structured Light

- Belongs to active stereoscopic approaches
- One camera replaced by an infrared projection unit
- Generates a pattern by projecting on the imaged surface

Advantage:
1. Simplify the correspondence problem

Drawback:
1. Near field
2. Indoor





Structure Light

RealSense D415

RealSense D435

RealSense D455

- RGB camera, infrared projector, left and right infrared cameras.
- Captures video data in 3D under any ambient light conditions.

RGB image

Pattern of projected infrared points to generate a dense 3D image



Depth map

Structural Light



IR images



Right IR image



The observed scene



Left IR image

Stereo matching



Computed depth

Time-of-Flight (ToF) Sensors

Microsoft Kinect v2 (2013)

Microsoft Azure Kinect (2020)

iPad Pro 2019 LiDAR

iToF vs. dToF

- dToF (the future)
  - Direct time-of-flight
  - Pulse wave
  - Long range
  - Theoretically higher precision but currently lower resolution
  - Expensive (needs SPAD)



- iToF (Classic 3D imaging)
  - Indirect time-of-flight
  - Sin wave and solve for phase shift
  - Lower range
  - Lower precision but higher resolution
  - Cheaper



iPad Pro Front Structure Light vs. LiDAR



dToF in iPad Pro is not there yet.

Next Generation ToF

- Industrial level 3D sensor
- https://thinklucid.com/helios-time-of-flight-tof-camera/



Helios2 sensor from Lucid Vision Labs

Summary of Different Depth Sensors

CONSIDERATIONS	STEREO VISION	STRUCTURED-LIGHT	TIME-OF-FLIGHT (TOF)
Software Complexity	High	Medium	Low
Material Cost	Low	High	Medium
Compactness	Low	High	Low
Response Time	Medium	Slow	Fast
Depth Accuracy	Low	High	Medium
Low-Light Performance	Weak	Good	Good
Bright-Light Performance	Good	Weak	Good
Power Consumption	Low	Medium	Scalable
Range	Limited	Scalable	Scalable

Quickly improving!

Failure Cases in Depth Sensing

RGB



Depth



Point cloud



Next week: Lecture 9,
3D Vision II