

EXERCICIOS LISTA 3 CASA – GUILHERME FIUZA

1-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
int n=1;
```

```
while (n<=20)
```

```
{
```

```
    printf("O numero e: %i \n", n);
```

```
    n++;
```

```
}
```

```
return 0;
```

```
}
```

2-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
int n=20;
```

```
while (n>=1)
```

```
{
```

```
    if (n%2==0)
```

```
    {
```

```
        printf("O numero par e: %i \n", n);
```

```
    }
```

```
    n=n-1;
```

```
}
```

```
return 0;
```

```
}
```

3-

```
#include<stdio.h>

int main()
{
    int n=1;

    while (n<=20)
    {
        if (n%2==0)
        {
            printf("O numero par e: %i \n", n);
        }
        else printf("O numero impar e: %i \n", n);

        n++;
    }
    return 0;
}
```

4-

```
#include<stdio.h>

int main()
{
    int n;

    for ( n = 20; n >=1; n=n-1)
    {
        printf("%i \n", n);
    }

    return 0;
}
```

5-

```
#include<stdio.h>

int main()
{
    int n;
    for ( n = 1; n <= 20; n++)
    {
        if (n%2!=0)
        {
            printf("%i \n", n);
        }

    }
    return 0;
}
```

6-

```
#include<stdio.h>

int main()
{
    int n;
    for ( n = 20; n >= 1; n=n-1)
    {
        if (n%2==0)
        {
            printf("Pares: %i \n", n);
        }
        else printf("Impares: %i \n", n);

    }
    return 0;
}
```

7-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
    int i=1;
```

```
do
```

```
{
```

```
    printf("O numero e: %i \n", i);
```

```
    i++;
```

```
} while (i<=20);
```

```
return 0;
```

```
}
```

8-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
int n=1;
```

```
do
```

```
{
```

```
if(n%2==0)
```

```
{printf("O número par e: %i \n", n);}
```

```
n=n+1;
```

```
}
```

```
while(n<=20);
```

```
return 0;
```

```
}
```

9-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
int n=1;
```

```
do
```

```
{
```

```
if(n%2==0)
```

```
{printf("O número par e: %i \n", n);}
```

```
else printf("O número ímpar e: %i \n", n);
```

```
n=n+1;
```

```
}
```

```
while(n<=20);
```

```
return 0;
```

```
}
```

10-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
float x, a, b;
```

```
char operacao;
```

```
while (1)
```

```
{
```

```
printf("Digite o primeiro valor: ");
```

```
scanf("%f", &a);
```

```
printf("Digite o segundo valor: ");
```

```
scanf("%f", &b);
```

```
printf("Que operacao voce deseja fazer? (+,-,*,/,) ou S (Sair)");
```

```
scanf(" %c", &operacao);
```

```
if ( operacao == 'S') { printf("Programa encerrado"); break;}
```

```
if (operacao == '/' && b==0) { printf("Programa encerrado, operacao impossivel \n");}
```

```
else if ( operacao == '+' || operacao == '-' || operacao == '*' || operacao == '/' )
```

```
{
```

```
switch (operacao)
```

```
{
```

```
case '+': x= a+b; printf("O resultado e: %f \n ", x); break;
```

```
case '-': x= a-b; printf("O resultado e: %f \n ", x); break;
```

```
case '*': x= a*b; printf("O resultado e: %f \n ", x); break;
```

```
case '/': x= a/b; printf("O resultado e: %f \n ", x); break;
```

```
}
```

```
}
```

```
}
```

```
return 0;
```

```
}
```

11-

```
#include<stdio.h>
```

```
int main()
```

```
{
```

```
int r, t, cont=0;
```

```
printf("Que tabuada vc deseja saber? ");
```

```
scanf("%i", &t);
```

```
do
```

```
{ r = t * cont;
```

```
printf("Resultado e: %i * %i = %i \n", cont, t, r);
```

```
cont=cont+1;
```

```
} while (cont<=10);
```

```
return 0;
```

```
}
```