Playmaker Picks

Discord, website, research tools and API usage
Updated October 11, 2026

🚀 Start here and check your access

Run /start for private getting-started steps or /membership_status to check feature eligibility. Use the same Discord account linked to Whop. These commands do not buy, extend or grant access.

Access	Available features
Public / ROOKIE	Website settled results, capper directory, public sports scores and schedules, plus the configured free Discord channels. No unsettled premium selections.
Verified HIGHROLLER paid / eligible trial	Published current picks, member stats and Member Bet Vault when enabled. An eligible first-time trial lasts seven days; the prepaid paid pass is $19.99 for 30 days. No automatic paid conversion or renewal. Checkout and access require enabled launch settings; do not assume deployment alone opens enrollment.
OPERATOR / Owner	Team research: website Data Models and NFL Matchup Lab, and Discord /model in Laboratory. Paid/trial membership alone does not unlock these tools. Owner-only /api is a separate cache-refresh tool.

Features depend on current verification, configured channels and deployment. Adults must be 21+ or the higher local legal age. Playmaker provides analysis and tracking, not sportsbook wagering or guaranteed profits.

📷 Recording a play from an image

Cappers post personal betting-slip images in Capper_plays (1513186440278704178). Open the bot's review controls, check selections, odds and units, and use Edit bet or Enter units if needed. Press Confirm and record only after checking the extracted data. These plays credit the individual capper and feed that capper's website homepage, never the official team tracker.

Confirmation creates one tracked card in Capper_plays, normally replacing the upload. React on that card, not the deleted upload or review prompt. If reposting fails, a new card is published without deleting the upload; the new card is tracked. There is no extra official or confirmation-channel copy.

✍️ Recording a play manually

Use /play in Capper_plays when you have no image. You need the capper role and any configured official-role permissions. Follow the input form for units, selections and American odds; multi-leg plays collect the remaining legs and calculate combined odds. The resulting personal card stays in Capper_plays. Official plays cannot bypass ballot approval through this command.

⭐ Team ballots and official picks

Post a native single-choice Discord poll in Cappers_Ballet (1559647368650166322), with three choices beginning with Yes, No, and Pass. Attach the bet image or post it immediately afterward from the same account. Without an image, include the complete selection and American odds in the poll text or your immediately following message. Missing or ambiguous selections/odds require staff review; the bot never invents them.

Only finalized polls are evaluated, once per minute. Approval requires at least three Yes votes and strictly more Yes than No. Pass is ignored for approval: 3 Yes = 3 stars / 1u; 4 Yes = 4 stars / 2u; 5 Yes = 5 stars / 3u. Two or fewer Yes votes, ties and No-majorities are not posted. More than five Yes votes or malformed polls require staff review.

Approved picks are posted in Official_Playmaker_Plays (1560077460488458392) using only the bot's own name and avatar, never a capper's identity, and mention the HIGHROLLER role. The bet is written out even without an image. Official plays count toward the automatic team unit summary, not individual capper records.

Deployment requires the separate capper/ballot database migration and a bot restart. The first scan includes existing channel ballots; later scans resume a saved cursor. Durable claims prevent duplicate publication. Failed or interrupted publications alert staff and are not automatically retried: reconcile the saved play and any Discord post before changing the ballot state. Existing records remain classified as official; do not infer historical personal credit without reviewing original sources. Old automatic Top Playmakers messages are not updated or deleted; staff may remove them manually.

For a late image or correction, trusted staff can set capper_ballots.source_message_id to its message ID in the same ballot channel. This explicit association avoids guessing which older poll a later upload belongs to. Only reset a failed ballot to pending after reconciling any existing saved play/post.

The displayed tracking era starts October 14, 2026, at midnight Eastern. Team and capper stats, settled website ledgers, and current-pick displays exclude plays created before that time, even if they settle later. Historical records and Discord posts are retained. The persistent tracking_display_settings.starts_at setting controls this boundary; /tracker_start can further narrow Discord totals by settlement date but does not erase the retained archive.

✅ Settling a play with reactions

React directly on the tracked play card in Official_Playmaker_Plays or Capper_plays. A personal play's author or Discord Owner can settle by reaction; team plays are bot-owned, so a Discord Owner grades them by reaction. An OPERATOR role alone does not authorize settling another author's play. Officials can use the /settle picker. Reactions on unrelated messages/channels are ignored.

Icon	Result	What happens
✅	Win	Settles immediately and updates the card
❌	Loss	Settles immediately and updates the card
🅿️	Void	No change to your unit total
🌓	Partial	Not processed by reaction — use /settle instead

🛠️ Tracker and personal tools

Command	What it does
/update_tracker	Officials/moderators refresh the Unit Summary and reconcile missed reactions. The tracker also refreshes automatically every hour, Eastern Time.
/rankings	Posts the current team ranking summary.
/summary	Posts the official team unit summary only, without individual capper rankings. Use the configured team-stats channel.
/capper_tracker [capper:]	Privately requests individual capper totals and monthly breakdown, optionally for one capper. This tracker is never automatically displayed.
/play_results	Search published settled official team plays by Eastern date range, sport and grade. Browse ten per page; original-post links appear when accessible.
/mystats	Privately shows individual capper-play, Tail and Vault records. Use its share button to publish to the eligible Free or VIP Chat destination. Tail stats use the play's risk units, not your personal stake.
/vault_leaderboard	Shows this month's member Vault records. Vault results are separate from the official capper ledger.
/tracker_start date_value:show	Shows the date the tracker is currently counting from.

Commands for officials

Command	What it does
/settle	Opens a paginated list of open official plays. Select a play, then choose its result. Use this for partials or when the tracked message cannot be reacted to. The card's Play # identifies the record.
/regrade	Select a play from the last two days, then enter remaining legs, new American odds and an optional note. Regraded plays count as zero units.
/unsettle	Select a play settled in the last seven days to reopen an accidental or incorrect settlement. Confirm before applying it.
/edit_play	Select an open official play and edit units, team, selections and leg odds in a modal. Ownership and role checks still apply.
/recap	Officials/moderators preview the previous weekly or monthly recap privately; post:true sends it to the results channel. Scheduled recaps run at 10 AM Eastern on Mondays and on the first day of the month.
/request_insights	Staff can request author insight for up to 50 open picks missing an insight request. Insight is capper-written analysis, not automatically extracted slip text.
/test [image:]	Officials run system diagnostics or parse an attached slip without recording a play.

Automatic settlement suggestions

Every 15 minutes the bot checks supported full-game moneyline, spread and total legs against cached final scores. It posts a suggested WIN/LOSS/VOID in the confirmation channel. An authorized official/moderator must Confirm; Dismiss leaves the play unchanged. Props and unmatched or unsupported games require manual grading. A suggestion is not an automatic official settlement.

Member Bet Vault and Tail tracking

Eligible members submit in the configured Member Bet Vault channel: attach exactly one static JPEG, PNG or WebP betting-slip image, up to 10 MB. Put units in the caption when needed, then follow the confirmation and settlement controls. The channel is submission-only; read the response before completing your entry.

Use the Tail control under an official play to register a tail; use /mystats to see your record. Member Vault entries do not become official capper picks. Access failures, missing units or unclear slip data must be resolved before confirming.

Website: results, picks and profiles

Visit playmakersportsanalytics.com. The homepage and /results ledger show official team picks only, ten results per page with sport filters on the dedicated page. Individual capper homepage metrics and results use Capper_plays only. Published current picks include both team and personal plays with separate attribution. Test plays, open selections and private account data are excluded from the public settled ledger.

This guide is available on the website at /guide, through the Guide (team only) navigation link. Only verified OPERATOR/Owner accounts can open it; paid/trial access alone is insufficient. The page uses the same tab-session access checks as the research tools, and its content RPC checks current access on every fetch.

/cappers lists current verified OPERATOR cappers, with public profiles and settled performance. /picks contains published open picks for verified member/team access. Filter by sport or capper, and open the insight control where available.

On /account, sign in with Discord, complete age verification, check membership, edit your profile, choose sports/capper follows, and manage alert preferences. The personalized homepage uses those follows. A preference does not guarantee delivery of every alert.

Verified capper page owners can edit their own page appearance and their own open-pick insights. A verified Owner can edit all capper pages/insights. Available appearance controls include colors, heading font, bio, social links, avatar, banner

and section order. Saving or uploading can fail explicitly; verify the saved result.

Active website access is verified once per browser tab and retained across navigation/reloads until the tab closes. No 30-second or focus role refresh runs. Sign-out, account/profile changes and membership expiry invalidate it. A removed role blocks new protected database requests even if previously viewed content remains in the tab. The browser cache cannot grant server access.

Website sports center and NFL Matchup Lab

The public sports board and sport pages show cached schedules, scores and update times, with links to each sport center. Coverage varies; empty, unsupported and failed feeds are labeled. The browser reads Supabase caches, not API-Sports directly. A sync timestamp is not proof of an instant live score.

OPERATOR/Owner members can use /nfl/lab for matchup records, home/away splits, last-five form, scoring averages and rest context. NFL efficiency panels add nflverse offensive/defensive EPA per play and success rates over up to ten prior regular-season games; at least three are required. Same-day games are excluded from efficiency history.

Enter American odds, stake and an optional your estimated probability for implied/break-even probability, payout and conditional expected profit. The calculator is not a sportsbook odds feed. CSV exports include matchup summaries, game history and calculator data. NFL efficiency is descriptive: it does not recalibrate the score-only model.

Website Data Models: six competitions

Open /models with verified OPERATOR/Owner access. Choose NFL, NBA, MLB, NHL, NCAA Football or NCAA Men's Basketball, then choose an upcoming matchup. The NFL Lab link appears only under the NFL tab.

The page shows stored projections from the Playmaker ratings model (ratings-v2), refreshed by the bot every 30 minutes. A game stays listed until one hour after its scheduled start.

Ratings: every team carries offensive and defensive ratings that update after each game, adjusted for opponent strength and a learned home advantage, and partially regressed between seasons. At least three prior games per team and 30 league games are required; otherwise no projection is shown.

Learned adjustments: rest days and back-to-backs, travel distance between venues, and outdoor weather (temperature, wind and precipitation from Open-Meteo) for NFL, MLB, NHL and NBA venues. NCAA has no venue data, so it has no travel or weather adjustment. NFL play-by-play efficiency (EPA) is used only when it improves the backtest; it currently does not.

NFL injuries: players listed Out or Doubtful reduce their team's projection using fixed position weights (QB weighted most). This is a heuristic, not a depth-chart model.

Probabilities: hockey and baseball use a Poisson score model; football and basketball use a calibrated normal margin.

Market comparison: the consensus sportsbook moneyline (no-vig), spread and total are shown beside the model with the model edge, cover and over probabilities. Market prices are never inputs to the projection.

Track record: a walk-forward backtest projects each past game using only information available before it, tunes on the earlier half and reports the later half against the old score-only baseline (Brier score, log loss, accuracy, margin and total error, plus calibration buckets).

Unresolved provider teams and NFL preseason games are excluded. Duplicate fixtures are merged across provider IDs/seasons by teams and exact start time so selections and history count the matchup once. Scored finals take precedence over duplicate schedule rows; fresher data is preferred.

These are experimental estimates, not betting recommendations. Injury, weather and odds feeds can be incomplete; historical weather only covers the last 92 days; odds cannot be backtested. Read sample sizes, update times and the track record.

Laboratory /model: fresh league and game data

Current OPERATOR/Owner members run /model only in Laboratory, configured by CONFIRMATION_CHANNEL_ID=1328130555568455710. Paid/trial access alone is not enough.

1. Choose one of the six model leagues from the dropdown.

2. In the modal, enter a game date as YYYY-MM-DD in Eastern time and an optional team filter.

3. The bot refreshes the selected league's current and prior seasons from API-Sports, follows all reported pages and saves the refreshed games. This spends shared API allowance.

4. Choose a game from the paginated dropdown; use Previous/Next for more than 25 choices.

5. Type POST in the confirmation modal. The finished model is posted publicly in Laboratory; the picker remains private.

The report includes projected scores and win probability, the market comparison (consensus line, model edge, cover and over), inputs (rest, travel, weather, NFL injuries), prior-game samples, the league's backtest track record, provider refresh time and request count. It uses the same ratings model as the website. Snapshot/picker controls expire after three minutes and cannot publish twice. Roles, channel and picker owner are rechecked. If refresh fails, no stale cached model is posted as a success.

/league_model: every game in a league on one date

Run /league_model in Laboratory, choose the league from the dropdown, then pick a date from the suggestions (yesterday through the next two weeks, Eastern time) or type it as YYYY-MM-DD. The bot uses stored league history and stored model inputs (no API allowance), runs the ratings model and posts one model-card image per game as a regular Laboratory message. Each card shows the projection, market comparison, inputs and track record. Games without enough history show an explicit no-projection card.

Member stats commands: cached versus refreshed

Command	Purpose
/schedule sport: [team:]	Seven-day cached schedule, optionally filtered by team.
/results sport: [team:]	Recent provider game results, optionally filtered by team. This is not /play_results, which searches official betting-play settlements.
/teamstats sport: team:	Recent team form and scoring from available cached games, not guaranteed season standings.
/matchup sport: team: opponent:	Upcoming matchup context from the sports cache, not the Laboratory probability model.
/gamestats sport: league: game: [player:]	Choose league/game suggestions and optionally a player/driver for game-specific reports.
/playerstats sport: league: player:	Current/previous season player or driver reports; choose the league and name suggestions.

These commands reply privately and require verified paid/trial access or allowed staff access. Available sports, players and endpoints vary. Without refresh:true they use cached data only and show update times. With refresh:true, live calls require enabled refresh/budget settings and consume your member allowance; player/season lookups may need multiple calls. Previous-season player data can be reused from cache.

For /schedule, /results, /teamstats and /matchup, refresh:true updates today's UTC-date feed only; other dates stay cached. For /gamestats it refreshes the selected game's player snapshot; /playerstats uses current/previous-season scope. Neither refresh mode expands provider subscription coverage.

API reference for website and bot integrations

Website requests go to the configured Supabase project at /rest/v1/rpc/FUNCTION_NAME. Use the public publishable/anon key for the project and the signed-in user's access token for protected RPCs, never a service-role key. Functions with “public” in their names can still require team authorization.

Supabase RPC	Access and request body
public_settled_results	Public settled official ledger. No arguments: {}.
public_nfl_games / public_nfl_standings / public_nfl_data_status	Public NFL schedule, standings and freshness. No arguments: {}.
website_member_access	Signed-in account's verified membership/team access. No arguments: {}. This is an access check, not a role-grant endpoint.
member_current_picks	Verified member/team access; published open picks only. No arguments: {}.
public_nfl_model_games / public_nfl_team_efficiency	Verified OPERATOR/Owner research. No arguments: {}.
public_sport_model_events	Verified OPERATOR/Owner research. Example NBA body: {"p_sport_slug":"basketball","p_league_id":"12"}.
operator_sport_model_projections	Verified OPERATOR/Owner research. Stored ratings-model projections with market comparison and inputs. Body: {"p_competition":"nfl"}; other keys are basketball:12 (NBA), baseball:1 (MLB), hockey:57 (NHL), ncaa:2 (NCAA Football) and basketball:116 (NCAA Men's Basketball).
operator_sport_model_backtest	Verified OPERATOR/Owner research. The league's latest walk-forward backtest report. Body: {"p_competition":"hockey:57"}.
operator_user_guide	Verified OPERATOR/Owner guide content. No arguments: {}. Returns HTML text; the underlying content table is not accessible to browser accounts.

With the existing authenticated Supabase JavaScript client, an NBA model-history page is requested as:

supabase.rpc('public_sport_model_events', { p_sport_slug: 'basketball', p_league_id: '12' }).order('start_at').order('event_id').range(0, 999)

Check the returned error before using data. Fetch successive 1,000-row ranges until a raw page contains fewer than 1,000 rows; filtering unresolved teams must not determine whether another provider-history page exists.

Model competition	Server-side API-Sports GET request
NFL / NCAA Football	https://v1.american-football.api-sports.io/games · league=1 for NFL, league=2 for NCAA · season=YYYY.
NBA / NCAA Men's Basketball	https://v1.basketball.api-sports.io/games · league=12 for NBA, league=116 for NCAA · season=YYYY-YYYY.
MLB	https://v1.baseball.api-sports.io/games · league=1 · season=YYYY.
NHL	https://v1.hockey.api-sports.io/games · league=57 · season=starting year.

Bot requests authenticate with the server-only x-apisports-key header. Initial season calls omit page; subsequent calls add page only when paging is reported. Owner /api also uses leagues and teams directory endpoints, teams/statistics where supported, and per-game statistics endpoints. NFL/NCAA/basketball team detail uses games/statistics/teams?id=GAME_ID; NFL/NCAA player detail uses games/statistics/players?id=GAME_ID. Soccer uses fixtures and fixture-scoped statistics instead of games.

Use /model, /api or the enabled member refresh commands for normal operations. Ad-hoc direct provider calls bypass this application's reservation accounting and still consume provider quota. Do not expose the provider key in browser code.

Confirm provider licensing for public display and downloads before rollout.

Owner /api: refresh a team season cache

Only the Discord Owner role can run /api sport: season: in the configured server. Choose a sport and provider season, then choose a league and team by name from paginated dropdowns. This refreshes available team-season caches; it does not produce a /model prediction.

Provider formats differ: NFL/NCAA football/MLB use calendar-year seasons; NHL uses the starting year (2025 for 2025-26); basketball uses split-year text such as 2025-2026. Coverage depends on the selected sport and subscription.

The refresh loads the team directory, season schedule, available season-team summaries and supported per-game team/player statistics. NFL/NCAA have no season-summary endpoint in this tool. Other endpoints depend on coverage. Directory queries and detail calls spend shared quota too. Review the completion report: PARTIAL / FAILED means a complete refresh is not claimed. Pickers expire after three minutes; refresh work has a 12-minute interaction limit. Saved components remain cached after failure, but retrying starts again and spends quota again.

API calls, limits and freshness

Action	Provider calls and limits
Website browsing / CSV exports	Reads stored Supabase data; no direct API-Sports calls. It does not force a provider refresh.
Member stats without refresh	Cached only; no live provider request.
Member stats with refresh:true	Five requests per user per UTC day across products, 20 member requests per product/day, and a five-minute per-product cooldown. Multi-call lookups count each request, not just one command.
Staff /model, Owner /api and automated sync	Use the shared automated allowance, not the member five-request allowance. /model refreshes both seasons and every reported page; /api may call multiple endpoints. Only one /model refresh runs at a time.
Shared provider ceiling	7,500 reserved API-Sports requests per UTC day across all products and system/member usage. Existing usage counts. Bot restart does not reset it. Other apps using the same provider key are not counted by this bot.
Model inputs (automated)	Shared automated allowance. League odds refresh hourly for NBA, MLB, NHL and NCAA basketball (one paged league request); NFL and NCAA Football odds are one request per upcoming game every six hours. NFL injuries and rosters refresh every six hours for teams playing within eight days. Weather comes from Open-Meteo every three hours (not API-Sports quota). Backtests rerun daily at 6:45 AM Eastern.
nflverse NFL efficiency	Separate free nflreadpy/nflverse feed, not API-Sports quota. Bot synchronization updates the stored efficiency panels; feed availability still matters.

API-Sports calls reserve allowance before network access, so failed calls can still consume a reservation. The provider's own quota and subscription rules also apply. Daily budget resets at midnight UTC (8 PM Eastern during daylight time; 7 PM during standard time). Manual refresh does not guarantee that the source has newer data.

Automated history backfill resumes saved cursors; routine NFL and multi-sport syncs maintain caches. NFL score checks occur every 15 minutes only during cached game windows. Do not interpret every page load or command as a live provider poll.

Deployment checklist for staff

Keep API keys and the Supabase service-role key on the bot server only, never in website VITE variables. Configure GUILD_ID, the required role/channel settings, API_SPORTS_KEY and API_SPORTS_BUDGET_ENABLED=true. Set OPEN_METEO_API_KEY for model weather; without it, weather adjustments are skipped. MEMBER_STATS_REFRESH_ENABLED controls member on-demand refresh, not /model.

On the Linux bot host:

```
cd /opt/discord-bot
git pull
./.venv/bin/python3 -m pip install -r requirements.txt
systemctl restart discord-bot.service
journalctl -u discord-bot.service --since "2 minutes ago" --no-pager
```

Install dependencies only when requirements change or packages are missing, and always into the service's virtual environment. Use -r for requirements.txt; python3 is the server executable. nflreadpy>=0.1.5 is the supported minimum in the requirements.

In Supabase SQL Editor, apply the relevant migrations in order after their prerequisites: 20261011170000_sports_model_history.sql, 20261011180000_nflverse_team_efficiency.sql, 20261011193500_shared_api_daily_budget.sql, 20261011214000_operator_research_access.sql and 20261014120000_sport_model_projections.sql (model inputs, projections and backtests; then restart the bot so it fills them). Pulling Git does not execute SQL. Deploy the website separately; a bot restart does not publish frontend fixes.

For the protected website guide, apply 20261011230000_operator_user_guide.sql after the research-access migration. Its table stores this guide privately and its RPC checks current OPERATOR/Owner access. Deploy the frontend to expose /guide; no bot restart is needed for this page.

After restart, check the command-sync log for /model. Verify a live refresh in Laboratory and the website with a real eligible account. Automated tests do not prove production provider coverage, purchases or Discord role mappings.

🔑 Commands for operators and server managers

Command	What it does
/tracker_start date_value:YYYY-MM-DD	Counts only plays settled on or after this date, for example 2026-09-28. Everything earlier is hidden from the tracker but is never deleted.
/tracker_start date_value:clear	Counts every play again.
/testing enabled:true	Enables the automatic image test-channel flow, which parses without recording. Manual /play is not a database-free dry run.
/testing enabled:false	Returns to normal recording.

Both settings revert to their .env defaults when the bot restarts. Set TRACKER_START_DATE or TESTING in .env to make a change permanent.

📊 How units are scored

Wins pay the true price of the bet. Risking 2 units at +250 and winning returns +5 units; the same 2 units at −110 returns +1.82 units. A loss always costs the full amount risked. Voids and regrades count as zero. Your record displays as wins-losses, and the net unit figure reflects actual profit rather than a flat win count.

🚨 If something does not appear

Check the bot, role, channel, account identity and source update time. If a play will not settle by reaction, use the authorized /settle picker. Expired controls require rerunning the command. For website errors, deploy the latest frontend and reload; use Retry when offered.

Sports-data failure alerts name a job; check its traceback before retrying. A shared-allowance denial is not fixed by restarting. A model can legitimately have insufficient history or no matching game. Unresolved-team and duplicate counts are data-quality notices, not fabricated estimates. Provider or database errors must not be treated as empty successful results.

Key settings: GUILD_ID · OFFICIAL_CHANNEL_ID · IMAGE_INPUT_CHANNEL_ID · CONFIRMATION_CHANNEL_ID · MEMBER_BET_CHANNEL_ID · API_SPORTS_KEY · API_SPORTS_BUDGET_ENABLED · MEMBER_STATS_REFRESH_ENABLED · OPEN_METEO_API_KEY · TRACKER_START_DATE

Weather data by Open-Meteo.com, CC-BY 4.0.
nflverse data attribution: nflverse / nflreadpy, CC-BY 4.0.