Practical-9

Create Placement Dashboard using Data Controls & Reports

Create a database - PlacementDB

- Table Name – Students
- Column name – PlacementId,StudentId,CompanyName,JobRole,PackageLPA

Two – Web Forms

1. Default.aspx
2. Companies.aspx

Default.aspx

```
<%@ Page Language="C#" AutoEventWireup="true" CodeBehind="Default.aspx.cs"
Inherits="P9_PlacementDashboard.Default" %>

<!DOCTYPE html>

<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
    <title></title>
</head>
<body>
    <form id="form1" runat="server">

    <h1>Placement Dashboard</h1>
    <hr />
    <h3>Placement Summary</h3>

    <table border="1" cellpadding="8">
        <tr>
            <td>Total Students</td>
            <td><asp:Label ID="lblTotal" runat="server" /></td>
        </tr>
        <tr>
            <td>Placed Students</td>
            <td><asp:Label ID="lblPlaced" runat="server" /></td>
        </tr>
        <tr>
            <td>Unplaced Students</td>
            <td><asp:Label ID="lblUnplaced" runat="server" /></td>
        </tr>
        <tr>
```

```
        </tr>
        <tr>
            <td>Placement Percentage</td>
            <td><asp:Label ID="lblPercentage" runat="server" /></td>
        </tr>
        <tr>
            <td>Highest Package (LPA)</td>
            <td><asp:Label ID="lblHighestPackage" runat="server" /></td>
        </tr>
    </table>

    <h3>Student Placement Records</h3>

    <asp:GridView ID="gvPlacements" runat="server"    AutoGenerateColumns="True"
        EmptyDataText="No student records found.">
    </asp:GridView>
    <br />

    <asp:HyperLink ID="lnkCompanies" runat="server"  NavigateUrl="~/Companies.aspx">
        View Company Summary
    </asp:HyperLink>
    <br /><br />
    </form>
</body>
</html>
```

Default.aspx.cs

```
protected void Page_Load(object sender, EventArgs e)
{
    if (!IsPostBack)
    {
        LoadSummary();        LoadPlacements();
    }
}
1 reference
private void LoadSummary()
{
    using (SqlConnection con = new SqlConnection(cs))
    {
        con.Open();
        SqlCommand cmd = new SqlCommand(
            "SELECT COUNT(*) FROM Students", con);
        lblTotal.Text = cmd.ExecuteScalar().ToString();
```

```
cmd.CommandText =
    "SELECT COUNT(*) FROM Students WHERE IsPlaced = 1";
lblPlaced.Text = cmd.ExecuteScalar().ToString();
cmd.CommandText =
    "SELECT COUNT(*) FROM Students WHERE IsPlaced = 0";
lblUnplaced.Text = cmd.ExecuteScalar().ToString();
cmd.CommandText =
    "SELECT MAX(PackageLPA) FROM Placements";
object result = cmd.ExecuteScalar();
decimal highest = result == DBNull.Value ? 0
    : Convert.ToDecimal(result);
```

```
        lblHighestPackage.Text = highest.ToString("N2");
        int total = Convert.ToInt32(lblTotal.Text);
        int placed = Convert.ToInt32(lblPlaced.Text);

        decimal percentage = total == 0
            ? 0  : (decimal)placed * 100 / total;

        lblPercentage.Text =
            percentage.ToString("N2") + "%";
    }
}
```

```
        private void LoadPlacements()
        {
            using (SqlConnection con = new SqlConnection(cs))
            {
                string query = "SELECT * FROM Students";
                SqlDataAdapter da = new SqlDataAdapter(query, con);
                DataTable dt = new DataTable();
                da.Fill(dt);
                gvPlacements.DataSource = dt;
                gvPlacements.DataBind();
            }
        }
        0 references
        protected void btnReport_Click(object sender, EventArgs e)
        {
            Response.Redirect("~/Companies.aspx");
        }
    }
}
```

Companies.aspx

```
<body>
    <form id="form1" runat="server">
    <h3>Placement Records</h3>

<asp:Repeater ID="rptCompanies" runat="server">
    <HeaderTemplate>
        <table border="1" cellpadding="5">
            <tr>
                <th>Placement ID</th>
                <th>Student ID</th>
                <th>Company</th>
                <th>Job Role</th>
                <th>Package (LPA)</th>
            </tr>
    </HeaderTemplate>
```

```
    <ItemTemplate>
        <tr>
            <td><%# Eval("PlacementId") %></td>
            <td><%# Eval("StudentId") %></td>
            <td><%# Eval("CompanyName") %></td>
            <td><%# Eval("JobRole") %></td>
            <td><%# Eval("PackageLPA") %></td>
        </tr>
    </ItemTemplate>

    <FooterTemplate>
        </table>
    </FooterTemplate>
</asp:Repeater>
```

```
<h3>Company Details Using DataList</h3>

<asp:DataList ID="dlPlacements" runat="server">
    <ItemTemplate>
        <p>
            Company: <%# Eval("CompanyName") %><br />
            Job Role: <%# Eval("JobRole") %><br />
            Package: <%# Eval("PackageLPA") %> LPA
        </p>
        <hr />
    </ItemTemplate>
</asp:DataList>

    <br />
    <a href="Default.aspx">Back to Dashboard</a>
    </form>
</body>
</html>
```

Companies.aspx.cs

```
public partial class Companies : System.Web.UI.Page
{
    //connection string
    string cs = "";
    0 references
    protected void Page_Load(object sender, EventArgs e)
    {
        if (!IsPostBack)
        {
            LoadCompanies(); LoadPlacements();
        }
    }
    1 reference
    private void LoadCompanies()
    {
        using (SqlConnection con = new SqlConnection(cs))
        {
            string query = "SELECT * FROM Placements";
            SqlDataAdapter da = new SqlDataAdapter(query, con);
            DataTable dt = new DataTable();
            da.Fill(dt);
            rptCompanies.DataSource = dt;
            rptCompanies.DataBind();
        }
    }
```

```
        private void LoadPlacements()
        {
            using (SqlConnection con = new SqlConnection(cs))
            {
                string query = "SELECT * FROM Placements";
                SqlDataAdapter da = new SqlDataAdapter(query, con);
                DataTable dt = new DataTable();
                da.Fill(dt);
                dlPlacements.DataSource = dt;
                dlPlacements.DataBind();
            }
        }
    }
}
```