



*Virtual Summer School: Machine Learning in
Electron Microscopy Lecture 13*

Examples of DCNN in Electron Microscopy

Tommy Wong

Lecture Github:
[github.com/SergeiVKalinin/ML-
ElectronMicroscopy-
2023/tree/main/Lecture%2013](https://github.com/SergeiVKalinin/ML-ElectronMicroscopy-2023/tree/main/Lecture%2013)

Labeling this image took ~ 1 hr, DL
prediction took < 1 min.




About me

Tommy (Chun Yin) Wong

Advisors: Dr. Sergei Kalinin, Dr. Maxim Ziatdinov


- Research interests: deep learning & computer vision, electron microscopy, radiation damage
- 3rd year Ph.D. student in Energy Science & Engineering, Bredesen Center, University of Tennessee (joint program with ORNL)
- M.S. in Materials Science & Engineering '22, University of Tennessee
- B.S.E. in Nuclear Engineering & Radiological Sciences '20, University of Michigan




- cwong13@vols.utk.edu
- My Github:
github.com/tommycwong

Microstructural defects can be labeled for pixel-wise segmentation


- Segmentation: associating each pixel in an image with a class




Cavities (bubbles & voids)



Precipitates





Dislocation loops




Dislocation lines

Different labeling systems are required for different segmentation algorithms

- Important: labels are usually either 0 or 1




Precipitates






Voids

Semantic segmentation: one-hot encoding (U-Net)



[Class x y W H]

Object identification: bounding box (YOLO)




...


```
Dictionary{  
  'boxes': [x1 y1 x2 y2]  
  'labels': class  
  'masks': feature mask  
}
```

Instance segmentation: label encoding (Mask R-CNN)



Web-based GUI tools are used for labeling




CVAT



Roboflow



Labelbox



VIA

Labeling using Computer Vision Annotation Tool (CVAT)

cvat.ai

Documentation:

github.com/TaSeeMba/cvat/blob/master/cvat/apps/documentation/user_guide.md

CVAT labeling workflow

Important: before labeling, ensure all image data have the same dimensions e.g. 1024x1024



Creating a project and labeling tasks

The image displays three sequential screenshots of the CVAT (Computer Vision Annotation Tool) web interface, illustrating the process of creating a project and labeling tasks. Each screenshot is marked with an orange circle containing a number (1, 2, or 3) and an orange arrow pointing to a specific action.

Screenshot 1: Create a new project
The interface shows the 'Create a new project' form. The 'Name' field is filled with 'DL_for_Microscopy'. Under the 'Labels' section, 'Raw' is selected, and 'Bubble' is chosen as the label type. The 'Submit & Open' button is highlighted with an orange arrow.

Screenshot 2: Create a new task
The interface shows the 'Create a new task' form. The 'Name' field is filled with 'DL_for_Microscopy_eg_img'. The 'Project' field is set to 'DL_for_Microscopy'. The 'Subset' field is set to 'Input subset'. The 'Labels' section shows 'Project labels will be used'. The 'Select files' section shows 'My computer' selected. The 'Submit & Open' button is highlighted with an orange arrow.



Screenshot 3: Task details and jobs
The interface shows the task details for 'DL_for_Microscopy_eg_img'. The task is created by 'tommycwong' on 'June 5th 2023'. The 'Issue Tracker' is 'Not specified'. The 'Subset' is 'Input subset'. Below the task details, the 'Jobs' section shows a table with 0 of 1 jobs. The 'Job #180806' is highlighted with an orange arrow.

Job	Frames	Stage	State	Started on	Duration	Assignee
Job #180806	0-0	annotation	new	June 5th 2023 02:06	a few seconds	Select a user



Labeling using polygon and ellipse tools

Remember to click **Save**
Polygon tool

- Hold **Shift** to draw



Ellipse tool




Exporting and parsing labels

Export as .xml

Export job #180806 as a dataset ×

* Export format

 CVAT for images 1.1 ▼

☐ Save images

Custom name

DL_for_Microscopy_Train_eg_lab .zip

☒ Use default settings ⓘ

Cancel OK

Parsing labels using Python

```
get_imgs(train_img_names)
parse_anno_file(xml, train_img_filename)
get_unet_mask(annos)
get_maskrcnn_mask(annos)
get_maskrcnn_dataset(images=train_imgs,
labels=maskRcnn_masks)
```

```
<image id="0" name="DL_for_Microscopy_Train_eg_img.png" width="512" height="512">
  <ellipse label="Bubble" source="manual" occluded="0" cx="291.95" cy="334.99" rx="32.35" ry="30.94" z_order="0">
  </ellipse>
  <polygon label="Bubble" source="manual" occluded="0" points="282.22,131.08;289.47,135.54;295.61,142.23;300.07,1
  </polygon>
```

Additional notes on labeling

- Features typically should have a convex mask
 - Concave masks are likely occluded convex masks
- Don't leave holes between multiple overlapping masks
- Keep in mind output files: different parsing scripts needed for .xml, .json, etc.

Data Augmentation Techniques

Notebook: https://github.com/tommycwong/ML-ElectronMicroscopy-2023/blob/main/Lecture%2013/ML4EM_Summer2023_Data_Augmentation_supp.ipynb




THE UNIVERSITY OF
TENNESSEE
KNOXVILLE

Rationale: more varied data → less overfitting



Electron microscopy experiments yield (relatively) small datasets
∴ requires augmentation

Use a sliding window cropper to enhance the dataset




Rotate, flip, resize the image to increase variability


Original



Flipped/Mirrored




Rotated 180 degrees




Zoomed in

Adding noise to simulate noises during imaging


Original




Gaussian




Background noise




Poisson




Contrast




Jitter



Blur




Salt & pepper





Convolutional Neural Networks (CNN)



THE UNIVERSITY OF
TENNESSEE
KNOXVILLE



Semantic segmentation assigns class labels to each pixel




Augmented reality microscope [3]

Semantic segmentation of street views [1], [2]

- [1] G. Heinrich, "Image Segmentation Using DIGITS 5," NVIDIA Developer Blog, Nov. 10, 2016. <https://developer.nvidia.com/blog/image-segmentation-using-digits-5/> (accessed Feb. 25, 2021).
- [2] M. Cordts et al., "The Cityscapes Dataset for Semantic Urban Scene Understanding," in 2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), Las Vegas, NV, USA, Jun. 2016, pp. 3213–3223, doi: 10.1109/CVPR.2016.350.
- [3] P.-H. C. Chen et al., "Microscope 2.0: An Augmented Reality Microscope with Real-time Artificial Intelligence Integration," arXiv:1812.00825 [cs], Dec. 2018, doi: 10.1038/s41591-019-0539-7.


Convolutional Neural Network (CNN)



Activation function: ReLU (Wikipedia)

$$f(x_i, w_i) = \phi\left(\sum_i (w_i \cdot x_i)\right)$$

Artificial neuron and fully connected NN [9]



Convolutional Neural Network (CNN)

3 ₀	3 ₁	2 ₂	1	0
0 ₂	0 ₂	1 ₀	3	1
3 ₀	1 ₁	2 ₂	2	3
2	0	0	2	2
2	0	0	0	1

12.0	12.0	17.0
10.0	17.0	19.0
9.0	6.0	14.0

www.cs.toronto.edu/~lczhang/360/lec/w04/convnet.html


Normal convolution kernel

$$\begin{aligned}
 &(3 * 0 + 3 * 1 + 2 * 2) \\
 &+ (0 * 2 + 0 * 2 + 1 * 0) \\
 &+ (3 * 0 + 1 * 1 + 2 * 2) \\
 &= 12
 \end{aligned}$$

12	20	30	0
8	12	2	0
34	70	37	4
112	100	25	12

→ 2 × 2 Max-Pool →

20	30
112	37



Maxpooling

Deep learning lingo

- **Training data**—used for training
- **Validation data**—for predictions *during* training
- **Testing data**—for predictions *after* training
- **Ground truth**—actual true labels
- **Epoch**—1 training cycle
- **Batch size**—no. of training images each epoch
- **Hidden layer**—layers between input and output layers
- **Learning rate**—how big a step an optimizer goes each epoch

Deep learning lingo

Loss function


- Evaluates how close the predictions are to the ground truth → Minimize
- Binary cross entropy: (dis)similarity between prediction and GT

$$H_p(q) = -\frac{1}{N} \sum_{i=1}^N y_i \cdot \log(p(y_i)) + (1 - y_i) \cdot \log(1 - p(y_i))$$

<https://towardsdatascience.com/understanding-binary-cross-entropy-log-loss-a-visual-explanation-a3ac6025181a>

Optimizer

- Controls the *convergence* of a model (by minimizing loss func.)
- Step controlled by learning rate
- Adam optimizer




<https://www.jeremyjordan.me/nn-learning-rate/>

Semantic segmentation w/ U-Net

Look for salient features

Developed by Ronneberger et al. (2015) [11]




Adapted from Wong et al. (2021) <https://doi.org/10.1017/S1431927621007686>

U-Net demonstration

https://github.com/tommycwong/ML-ElectronMicroscopy-2023/blob/main/Lecture%2013/ML4EM_Summer2023_U_Net.ipynb




Instance segmentation w/ Mask R-CNN

Fast R-CNN



+ segmentation

Mask R-CNN



$$Loss = L_{class} + L_{box} + L_{mask}$$

Mask R-CNN demonstration

https://github.com/tommycwong/ML-ElectronMicroscopy-2023/blob/main/Lecture%2013/ML4EM_Summer2023_Mask_R_CNN.ipynb