

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

CS100 Recitation 8

GKxx

April 11, 2022

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
 - The Copy Constructor
 - The Copy-Assignment Operator
 - Synthesized Copy Operations
 - Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

When Copy Happens

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Point2d {  
    double x, y;  
public:  
    Point2d() : Point2d(0, 0) {}  
    Point2d(double a, double b) : x(a), y(b) {}  
};
```

Question

What member functions have been synthesized by the compiler?

When Copy Happens

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Point2d {  
    double x, y;  
public:  
    Point2d() : Point2d(0, 0) {}  
    Point2d(double a, double b) : x(a), y(b) {}  
};
```

When we have the class definition above, there are 3 ways of constructing an object:

```
Point2d p0;  
Point2d p1(3.14, 6.28);  
Point2d p2(p1); // same as Point2d p2 = p1;
```

When Copy Happens

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Point2d {  
    double x, y;  
public:  
    Point2d() : Point2d(0, 0) {}  
    Point2d(double a, double b) : x(a), y(b) {}  
};
```

We can also pass Point2d objects as arguments, or as return-values:

```
// BAD!! You should use reference-to-const.  
Point2d less_in_x(Point2d lhs, Point2d rhs) {  
    return lhs.get_x() < rhs.get_x() ? lhs : rhs;  
}
```

When Copy Happens

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

How many copies are created?

```
Point2d p3 = less_in_x(p0, p1);
```

When Copy Happens

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

How many copies are created?

```
Point2d p3 = less_in_x(p0, p1);
```

- Copy-initialize the parameters lhs and rhs.
- Copy-initialize a temporary object generated by the calling expression with the return value. (?)
- Copy-initialize p3. (not assignment!)

When Copy Happens

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

How many copies are created?

```
Point2d p3 = less_in_x(p0, p1);
```

- Copy-initialize the parameters lhs and rhs.
- Copy-initialize a temporary object generated by the calling expression with the return value. (?)
- Copy-initialize p3. (not assignment!)

Copying a return-value?

- Many compilers avoid such copying by **Return Value Optimization (RVO)**.
- Since C++11, a local object will be returned by **moving** instead of **copying**, if it is **move-constructible**.
- C++17 **guarantees** that such copying won't happen, even when the object is not move-constructible.

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- The Copy-Assignment Operator
- Synthesized Copy Operations
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

The Copy Constructor

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The

Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

The **copy ctor** defines the behavior of copy initializing an object.

```
class Point2d {  
    public:  
        Point2d(const Point2d &other)  
            : x(other.x), y(other.y) {}  
        // other members  
};
```

The Copy Constructor

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The

Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

The **copy ctor** defines the behavior of copy initializing an object.

```
class Point2d {  
public:  
    Point2d(const Point2d &other)  
        : x(other.x), y(other.y) {}  
    // other members  
};
```

- Can we define the parameter type as `Point2d` instead of reference-to-**const**?
- Can we define the parameter type as `Point2d &`?

The Copy Constructor

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {
    std::size_t m_size, m_capacity;
    int *m_data;
public:
    Vector(const Vector &other)
        : m_size(other.m_size),
          m_capacity(other.m_capacity),
          m_data(new int[m_capacity]{})) {
        for (std::size_t i = 0; i < m_size; ++i)
            m_data[i] = other.m_data[i];
    }
    // other members
};
```

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

**The
Copy-Assignment
Operator**

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- **The Copy-Assignment Operator**
- Synthesized Copy Operations
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

The Copy-Assignment Operator

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

The behavior of assignment like

```
Point2d p1, p2;  
p1 = p2;
```

is defined by the [copy-assignment operator](#). It is defined by [overloading](#) the assignment operator.

```
class Point2d {  
public:  
    Point2d &operator=(const Point2d &other) {  
        x = other.x;  
        y = other.y;  
        return *this;  
    }  
};
```

The Copy-Assignment Operator

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Point2d {  
public:  
    Point2d &operator=(const Point2d &other) {  
        x = other.x;  
        y = other.y;  
        // return reference to the object itself  
        return *this;  
    }  
};
```

Notice

You should make the overloaded operator behave as similar to the built-in one as possible.

The Copy-Assignment Operator

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

When an assignment happens, the left-hand operand is bound to the implicit `this`. The right-hand operand is passed as the parameter.

```
Point2d p1, p2;  
p1 = p2;  
p1.operator=(p2); // equivalent way
```


The Copy-Assignment Operator

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

When an assignment happens, the left-hand operand is bound to the implicit `this`. The right-hand operand is passed as the parameter.

```
Point2d p1, p2;  
p1 = p2;  
p1.operator=(p2); // equivalent way
```

Since the assignment operator returns the object on the left-hand side, we can chain assignments together:

```
p1 = p2 = p3;
```

Copy-Assignment of Vector

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {  
public:  
    Vector &operator=(const Vector &other) {  
        delete[] m_data;  
        m_size = other.m_size;  
        m_capacity = other.m_capacity;  
        m_data = new int[m_capacity];  
        for (std::size_t i = 0; i < m_size; ++i)  
            m_data[i] = other.m_data[i];  
        return *this;  
    }  
    // other members  
};
```

Copy-Assignment of Vector

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {  
public:  
    Vector &operator=(const Vector &other) {  
        delete[] m_data;  
        m_size = other.m_size;  
        m_capacity = other.m_capacity;  
        m_data = new int[m_capacity];  
        for (std::size_t i = 0; i < m_size; ++i)  
            m_data[i] = other.m_data[i];  
        return *this;  
    }  
    // other members  
};
```

- Anything wrong with this assignment operator?

Self-assignment Safety

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

- Should self-assignment happen, the data is **deleted** at first! It becomes a disaster.
- Exception-safety issue.

Self-assignment Safety

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

- Should self-assignment happen, the data is **deleted** at first! It becomes a disaster.
- Exception-safety issue.

Self-assignment may happen unnoticed and without a warning:

```
Vector v = some_value();  
Vector &rv = some_function(v);  
v = rv;
```

Notice

Assignment operator should always be **self-assignment-safe**.

The Correct Way

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {  
public:  
    Vector &operator=(const Vector &other) {  
        int *new_data = new int[other.m_capacity];  
        for (std::size_t i = 0; i < other.m_size; ++i)  
            new_data[i] = other.m_data[i];  
        m_size = other.m_size;  
        m_capacity = other.m_capacity;  
        delete[] m_data;  
        m_data = new_data;  
        return *this;  
    }  
};
```

Still Problematic Way

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
Vector &Vector::operator=(const Vector &other) {  
    // test self-assignment directly  
    if (this != &other) {  
        delete[] m_data;  
        m_size = other.m_size;  
        m_capacity = other.m_capacity;  
        m_data = new int[m_capacity];  
        for (std::size_t i = 0; i < m_size; ++i)  
            m_data[i] = other.m_data[i];  
    }  
    return *this;  
}
```

- This handles self-assignment correctly, but **still has exception-safety issue**.

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- The Copy-Assignment Operator
- **Synthesized Copy Operations**
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

Synthesized Copy Ctor

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

The compiler will synthesize a copy ctor if

- the copy ctor is not defined, and
- every member is **copy-constructible**.

The synthesized copy ctor will copy-initialize the members one-by-one, and has an empty function body.

Question

Is it ok for `Point2d` to use the synthesized copy ctor? What about `Vector`?

Synthesized Copy-Assignment Operator

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

The compiler will synthesize a copy-assignment operator if

- the copy-assignment operator is not defined, and
- every member is **copy-assignable**.

The synthesized copy-assignment operator will copy-assign the members one-by-one, and of course return ***this**.

Synthesized Copy-Assignment Operator

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

The compiler will synthesize a copy-assignment operator if

- the copy-assignment operator is not defined, and
- every member is **copy-assignable**.

The synthesized copy-assignment operator will copy-assign the members one-by-one, and of course return ***this**.

Question

Is it ok for `Point2d` to use the synthesized copy-assignment operator? What about `Vector`?

Copying Array Members

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

It is not allowed to copy arrays directly like

```
int a[100], b[100];  
a = b;
```

But if there's an array member, the synthesized copy operations will copy the elements in the array one-by-one. Don't worry!

Use =default

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

For a **default ctor**, a **copy ctor**, a **copy-assignment operator** or a **destructor**, we can explicitly require the compiler to synthesize one with defaulted behavior by `=default`:

```
class Point2d {  
    double x, y;  
public:  
    Point2d() = default;  
    Point2d(const Point2d &) = default;  
    Point2d &operator=(const Point2d &) = default;  
    ~Point2d() = default;  
    // other members  
};
```

The Rule of Three

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

Theorem (The Rule of Three)

If a class needs one of the three copy-controlling operations (copy-ctor, copy-assignment operator and destructor), it is highly possible that all of them are needed.

- Such idea was not so widely acknowledged when C++98 came out. Therefore, the compiler will still generate the others if you only define one or two of them.
- We will see changes in C++11 when we talk about **moving**.

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- The Copy-Assignment Operator
- Synthesized Copy Operations
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

Prevent Copying

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

Some class, like `std::istream`, should avoid copying. (Why?)

Question

Can we prevent copying by simply not defining the copy operations?

Prevent Copying

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

Some class, like `std::istream`, should avoid copying. (Why?)

Question

Can we prevent copying by simply not defining the copy operations?

Before C++11, people prevent copying by **declaring the copying operations as private, and not defining them.**

- Attempts to copy such an object outside the class and out of a friend will cause an error in access-level.
- Attempts to copy inside the class or in a friend will cause a linking error.

Deleted Functions

CS100
Recitation 8
GKxx

Copy Control

Copying an Object
The Copy
Constructor
The
Copy-Assignment
Operator
Synthesized Copy
Operations
Prevent Copying

More about Class

Constructors and
Type-casting
Friends
Constant Member
Functions Revisited

Since C++11, we can define a function as **deleted** by defining it to be `=delete`.

```
class Uncopyable {  
    public:  
        Uncopyable(const Uncopyable &) = delete;  
        Uncopyable &operator=(const Uncopyable &) = delete;  
};
```

Deleted Functions

CS100
Recitation 8
GKxx

Copy Control

Copying an Object
The Copy
Constructor
The
Copy-Assignment
Operator
Synthesized Copy
Operations
Prevent Copying

More about Class

Constructors and
Type-casting
Friends
Constant Member
Functions Revisited

Since C++11, we can define a function as **deleted** by defining it to be `=delete`.

```
class Uncopyable {  
    public:  
        Uncopyable(const Uncopyable &) = delete;  
        Uncopyable &operator=(const Uncopyable &) = delete;  
};
```

Use `=delete` to avoid copying in modern C++!

Deleted Functions

CS100
Recitation 8
GKxx

Copy Control

Copying an Object
The Copy
Constructor
The
Copy-Assignment
Operator
Synthesized Copy
Operations
Prevent Copying

More about Class

Constructors and
Type-casting
Friends
Constant Member
Functions Revisited

Since C++11, we can define a function as **deleted** by defining it to be `=delete`.

```
class Uncopyable {  
    public:  
        Uncopyable(const Uncopyable &) = delete;  
        Uncopyable &operator=(const Uncopyable &) = delete;  
};
```

Use `=delete` to avoid copying in modern C++!

Notice

If we define a special member function to be `=default` but the compiler cannot synthesize it, it is implicitly **deleted** and will not cause an error (but will generate a warning).

Recommended Reading Materials

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

- *Effective C++*, Item 5: Know what functions C++ silently writes and calls.
- *Effective C++*, Item 6: Explicitly disallow the use of compiler-generated functions you do not want.

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object
The Copy
Constructor
The
Copy-Assignment
Operator
Synthesized Copy
Operations
Prevent Copying

More about Class

Constructors and
Type-casting
Friends
Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- The Copy-Assignment Operator
- Synthesized Copy Operations
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

Constructors and Type-casting

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

A constructor also defines a type-casting:

```
void fun(std::string s) {  
    // do something  
}  
  
int main() {  
    fun("Hello world");  
    return 0;  
}
```

- `std::string` has a constructor that accepts a `const char *` parameter.
- When calling `fun("Hello")`, the initialization of the parameter could be seen as a **conversion** from `const char *` to `std::string`.

Constructors and Type-casting

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

Sometimes this will be confusing.

```
class Vector {  
    public:  
        Vector(std::size_t n)  
            : m_size(n), m_capacity(n),  
              m_data(new int[n]()) {}  
};  
int main() {  
    Vector v = 10; // What??  
    return 0;  
}
```


explicit Constructors

By defining a constructor as **explicit**, we disallow such conversion from happening implicitly.

```
class Vector {  
    public:  
        explicit Vector(std::size_t n)  
            : m_size(n), m_capacity(n),  
              m_data(new int[n]()) {}  
};  
  
int main() {  
    Vector v1 = 10; // Error  
    Vector v2(10);  // ok  
    return 0;  
}
```

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object
The Copy
Constructor
The
Copy-Assignment
Operator
Synthesized Copy
Operations
Prevent Copying

More about Class

Constructors and
Type-casting
Friends
Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- The Copy-Assignment Operator
- Synthesized Copy Operations
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- **Friends**
- Constant Member Functions Revisited

Friends

Code inside a **friend** of a class can access the private members of that class.

```
class Vector {  
    friend bool equal_to(const Vector &, const Vector &);  
    friend class SomeOtherClass;  
    // other members  
};  
  
inline bool equal_to  
    (const Vector &lhs, const Vector &rhs) {  
    if (lhs.m_size != rhs.m_size)  
        return false;  
    for (std::size_t i = 0; i < lhs.m_size; ++i)  
        if (lhs.m_data[i] != rhs.m_data[i])  
            return false;  
    return true;  
}
```

Friends

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

- A `friend` declaration is not a member of the class.
- Access-modifiers do not apply to `friend` declarations.
- `friends` are often declared together at the beginning or end of the class.

Contents

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

1 Copy Control

- Copying an Object
- The Copy Constructor
- The Copy-Assignment Operator
- Synthesized Copy Operations
- Prevent Copying

2 More about Class

- Constructors and Type-casting
- Friends
- Constant Member Functions Revisited

Access Elements of Vector

CS100

Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {  
public:  
    int &at(std::size_t n) {  
        return m_data[n];  
    }  
    // other members  
};
```

What will happen on a `const` object?

```
void print_vector(const Vector &v) {  
    for (std::size_t i = 0; i < v.size(); ++i)  
        std::cout << v.at(i) << " "; // Error!  
}
```

Access Elements of Vector

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {  
public:  
    int &at(std::size_t n) const {  
        return m_data[n];  
    }  
    // other members  
};
```

Access Elements of Vector

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

```
class Vector {  
public:  
    int &at(std::size_t n) const {  
        return m_data[n];  
    }  
    // other members  
};
```

Still problematic:

```
const Vector v = some_value();  
v.at(10) = 42;
```

Compilers may fail to detect such modification, but it is undefined behavior!

Correct Way

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

Const overloading.

```
class Vector {  
public:  
    int &at(std::size_t n) {  
        return m_data[n];  
    }  
    const int &at(std::size_t n) const {  
        return m_data[n];  
    }  
    // other members  
};
```

Calling a `const` member function is actually **adding low-level `const`** to the `this` pointer.

Bitwise `const` vs Logical `const`

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

- A member function is bitwise-`const` if it does not modify any data member.
- A member function is logical-`const` if it makes the object *appear* unchanged to users.
 - A logical-`const` member function should prevent potential modification.
 - A logical-`const` member function may modify some data member, but the object seems unchanged to users.

The compiler can only check bitwise constness.

Bitwise `const` vs Logical `const`

CS100
Recitation 8

GKxx

Copy Control

Copying an Object

The Copy
Constructor

The
Copy-Assignment
Operator

Synthesized Copy
Operations

Prevent Copying

More about
Class

Constructors and
Type-casting

Friends

Constant Member
Functions Revisited

Bitwise-`const` but not logical-`const` :

```
class Vector {  
    public:  
        int &at(std::size_t n) const {  
            return m_data[n];  
        }  
};
```

Directly returning a non-const reference to a data member is not allowed, but compilers may fail to detect this one.

mutable Member

What if we want to count how many times the function is called?

```
class Vector {
    int access_cnt;
public:
    int &at(std::size_t n) {
        ++access_cnt;
        return m_data[n];
    }
    const int &at(std::size_t n) const {
        ++access_cnt;    // Oops! It is not bitwise-const!
        return m_data[n];
    }
};
```

mutable Member

Define a member to be **mutable**, so that it is modifiable even in a **const** member function.

```
class Vector {  
    mutable int access_cnt;  
public:  
    int &at(std::size_t n) {  
        ++access_cnt;  
        return m_data[n];  
    }  
    const int &at(std::size_t n) const {  
        ++access_cnt;  
        return m_data[n];  
    }  
};
```