

API Reference

Request

Retrieve tracking information for a MAWB ID.

```
GET http://api.glslatina.it/mawb/${mawb-id}
```

This is an example:

```
GET https://api.glslatina.it/mawb/123-123456
```

HTTP Header	Type	Description
x-api-key	string	Required. Provided API key

REST Param	Type	Description
mawb-id	string	Required. ID of a valid MAWB e.g. 123-12345678

Response

Response is in **JSON** as shown in `resp_by_mawb_id.json` , it contains a `resp_status` key (the response message status) and the possible status codes are `HTTP` compliant as table below :

HTTP status code	resp_status
200	ok (request successfully completed)
400	bad params (e.g. missing <code>mawb-id</code>)
401	unauthorized (e.g. missing <code>x-api-key</code>)
404	not found (e.g. invalid <code>mawb-id</code>)
500	server error (e.g. internal server/db err)

Request

Retrieve tracking information for a tracking ID (GLS parcel ID).

```
GET http://api.glslatina.it/tracking/${tracking-id}
```

This is an example:

```
GET http://api.glslatina.it/tracking/LT642428350
```

HTTP Header	Type	Description
<code>x-api-key</code>	string	Required. Provided API key

REST Param	Type	Description
<code>tracking-id</code>	string	Required. ID of a valid tracking ID e.g. <code>LT641122059</code>

Response

Response is in **JSON** as shown in `resp_by_tracking_id.json` , it contains a `resp_status` key (the response message status) and the possible status codes are `HTTP` compliant as table below :

HTTP status code	resp_status
200	ok (request successfully completed)
400	bad params (e.g. missing <code>tracking-id</code>)
401	unauthorized (e.g. missing <code>x-api-key</code>)
404	not found (e.g. invalid <code>tracking-id</code>)
500	server error (e.g. internal server/db err)