Tutorial - GIT

Grupo de Linux da Universidade de Aveiro

2016

1 Introduction

Welcome to this tutorial. This is a brief introduction to version control software and GIT. This tutorial is separated in three parts:

- Introduction
- First steps
- Advanced commands

Introduction - we will talk about Version Control Systems and GIT.
First steps - we will talk about GIT's basic commands.
Advanced commands - we will talk about GIT's advanced commands.

1.1 What is a version control system?

A version control system (VCS) is a software that allows you to manage the changes in files, while retaining previous changes. It will also allow you to work with others more effectively, since it will track the changes for you.

1.2 Why use version control system?

Instead of using other kinds of systems, you can use **VCS** to track the changes in code and in file structure of your project. Just this aspect will allow you to focus in code production instead of always worrying if you have the right files or what others have changed in the files.

1.3 What is GIT?

GIT is one of the main VCS used for software development. GIT main goals are:

- Speed
- Data integrity
- Distributed
- Non-linear workflow

2 First steps

This is the beginning of a great journey for you. You will learn the basics of GIT, which will help until the end of your days as developer.

2.1 Create a local repository

First of all, lets create a new repository so you that you can start tracking all the changes in your project.

```
git init
touch README.md
git add README.md
git commit -m "Initial commit"
```

Lets dissecate each command:

- git init this command will initialize a local git repository in the folder you're in.
- touch README.md will create an empty file called README.md.
- git add README.md will make your local GIT repository start tracking your file.
- git commit -m "Initial commit" will set the actual state of the repository as the first snapshot taken.

2.2 Adding files

Lets create a few other files so we can start tracking them with GIT.

```
touch file_1
touch file_2
mkdir folder_1
touch folder_1/file_1
touch folder_1/file_2
```

Lets check what is the state of the local GIT repository with git status.

```
On branch master
Untracked files:
    (use "git add <file>..." to include in what will be committed)

file_1
file_2
folder_1/

nothing added to commit but untracked files present (use "git add" to track)
```

There are two ways of start tracking these files. You can add all files with one command or you can add them one by one. If you know that you want to add them all, you can use this command:

```
git add .
```

If you don't want to track all files, you can add them individually like this:

```
git add <file>
```

In this case, we want to add all files, so we will use **git add** . and know lets check the state of the local repository with **git status**.

```
On branch master

Changes to be committed:
    (use "git reset HEAD <file>..." to unstage)

new file: file_1
new file: file_2
new file: folder_1/file_1
new file: folder_1/file_2
```

2.3 Making commits

Now that we have added some new files and started tracking them in our repository, lets save this state. To save this changes in the repository, we need to make a commit of the changes. To commit the changes, we will use the following command:

```
git commit -m "A message relevant to the changes made in this commit"
```

Know that we know which command to use, lets use it but don't forget to add a meaningful message, so that when others check the commits to the repository can understand what or why you did those changes.

2.4 Checking the log

Lets check the log to see the changes we have made to our local repository. To check these changes, we will check the local repository log and to do that we must run the following command:

```
git log
```

After running this command, we will get an output similar to this:

```
commit 3070d3621b60b5ebe46b2d58ad6be2537069d79d
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:44:20 2016 +0000

Added initial files

commit 5814279838033e7b0f14a620c73202f52f11cf99
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:26:39 2016 +0000

Initial commit
```

What can we check in the log? Well, we can see the commits that were made to the repository, when were they made and the message that the author of the commit wrote for that change.

Now lets say you want to check what a specific commit made. You can verify this with this command:

```
git show <commit hash>
```

Where the **<commit hash>** is the number that appears after the commit word when using the **git log**.

2.5 Updating the remote server

2.6 Creating a branch

GIT supports branches. What are branches? Branches are places where code diverges, meaning that the code will have the same base, but it will differ from branch to branch. Every GIT repository has main branch, that is called master and if you don't branch all your commits will go there.

Now lets say you need to add a new feature. You don't want to break the master branch while you develop your new feature, so you will create a new branch so that you can work on code. To create the new branch, you will use the following command:

```
git branch  chranch name>
```

Lets create a new branch for our new feature called **feature-1**. After creating your new branch to work on you should check in which branch are you in, by running the following command **git branch**. And you will get the following result:

```
feature-1
* master
```

The star (*) before the name of the branch will tell you which in which branch you are and right now you should be in the master branch. But we want to develop our new feature, so we will need to change to the feature-1 branch. To do that we need to run the following command:

```
git checkout <branch name>
```

After we run this command you should check in which branch are you now and the result should be feature-1 as demonstrated in the following:

```
* feature-1 master
```

Now we can develop our feature in this branch, without changing the master branch.

Lets add a new file called feat_1 and lets add and commit our new feature to the repository. Lets do this by running the following commands:

```
echo "feature 1 developed" >> file_1
git add file_1
git commit -m "Feature 1 complete"
git log
```

And the output should be similar to this:

```
commit 43756632d9dedf6b8756e1dd393d877ee7c81a4d
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 16:55:18 2016 +0000

Feature 1 complete

commit 3070d3621b60b5ebe46b2d58ad6be2537069d79d
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:44:20 2016 +0000

Added initial files

commit 5814279838033e7b0f14a620c73202f52f11cf99
Author: John Doe <john.doe@example.com>
```

```
Date: Tue Nov 15 15:26:39 2016 +0000
```

Initial commit

So now our code in feature-1 branch as a new feature that the master branch doesn't have. Lets just check our master branch to check that the change that we made didn't made it to the master branch, by running the following commands:

```
git checkout master
git log
```

The result should be similar to this:

```
commit 3070d3621b60b5ebe46b2d58ad6be2537069d79d
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:44:20 2016 +0000

Added initial files

commit 5814279838033e7b0f14a620c73202f52f11cf99
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:26:39 2016 +0000
Initial commit
```

As we can see in the last output, the master branch didn't get changed, while the changes we did are saved in the feature-1 branch.

2.7 Merge vs Rebase

Run this code in your terminal so that the repository matches the next exercise:

```
git checkout master
git branch bug_fix_1
git checkout bug_fix_1
echo "this is a bug fix" >> file_1
git commit -a -m "Bug Fix 1 solved"
git checkout master
```

Now we want to do a lot of things with our repository. We have two things happening, we developed our feature 1 and one of our colleagues developed a bug fix for a bug found in the master branch. Our colleague did his bug fix on the branch bug_fix_1.

There are two kinds of operations:

- Merge this operation will join two commits from different branches in a new commit in the branch you are
- **Rebase** this operation will take the commits in one branch and apply them before the commits of the branch you are in

2.7.1 Merge

So now we want to merge the bug fix into the master branch because we want our master branch to have the less amount of bugs possible. To do this, first we must check if we are in the master branch and then merge the bug_fix_1 branch into the master branch. To check if we are in the correct branch we need to run **git branch** and the output is:

```
bug_fix_1
feature-1
* master
```

If this isn't your case you need to run git checkout master.

After doing all this, the last thing that we need to do to merge both branches is:

```
git merge bug_fix_1
```

Since we merged the two branches, both of them should be equal. To check that all the commits have made into master branch lets check the log, by running **git log**:

```
commit 3b820eeb454915a81373a569a8a4baf32a6725b1
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 21:31:43 2016 +0000

Bug fix 1 solved

commit 3070d3621b60b5ebe46b2d58ad6be2537069d79d
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:44:20 2016 +0000

Added initial files

commit 5814279838033e7b0f14a620c73202f52f11cf99
Author: John Doe <john.doe@example.com>
Date: Tue Nov 15 15:26:39 2016 +0000
```

Initial commit

And lets check if the last commit is the same in both branches, by running git branch -v:

```
bug_fix_1 3b820ee Bug fix 1 solved
feature-1 4375663 Feature 1 complete
* master 3b820ee Bug fix 1 solved
```

Now that the bug_fix_1 branch has been merged into the master branch, we don't need that branch anymore, so lets delete it. To do this run:

```
git branch -d bug_fix_1
```

And now lets check that we did in fact deleted the bug_fix_1 branch and that we didn't lose any information by running again **git branch -v**:

```
feature-1 4375663 Feature 1 complete
* master    3b820ee Bug fix 1 solved
```

- 2.7.2 Rebase
- 2.7.3 Difference between them
- 2.8 Reset
- 3 Advanced tricks
- 3.1 Cherry-pick
- 3.2 RefLog
- 3.3 Bisect
- 3.4