


# Networks, Internet and Protocols

Network Fundamentals, Network Services



**SoftUni**

**SoftUni Team**

**Technical Trainers**



**Software University**

<https://about.softuni.bg>

# Table of Contents

1. Basic networking concepts
2. OSI Model, MAC address, IP address, TCP and ports
3. Domains and DNS, WWW
4. HTTP, GET, POST
5. Browser DevTools
6. Email



# Have a Question?



sli.do

#qa-fund




# Network Fundamentals

OSI Model, MAC address, IP address, TCP and ports


# What is a Network Protocol?

- A **set of rules** that determine how data is transmitted between different devices in the same network
- Enable **standardized communication** between devices
- Govern aspects of **data transmission, addressing, routing, and error handling**
- Work in **conjunction** to facilitate communication



- **Organize** network protocols into a **structured framework**
- Facilitate the understanding, design, and management of **complex networks**
- **Simplifies** network communication and troubleshooting
- Encourages protocol **interoperability** and **modularity**
- **Examples:**
  - OSI Model
  - TCP/IP Model






# OSI Model

# OSI Model Overview


- The **OSI Model** /Open Systems Interconnection Model/
- Developed by the International Organization for Standardization (ISO) in the **1970s**
- **Framework** for understanding and designing network protocols and communication
- **7 layers**
- **Key concept** - Each layer adds **functionality** to the data transmitted






- **Physical Layer (Layer 1)**

- **Converts digital data** into electrical, radio, or optical signals for transmission
- **Devices** - Hubs, switches, routers, modems, network interface cards (NICs)
- **Standards** - Ethernet, Wi-Fi, Bluetooth, USB, DSL



- **Data Link Layer (Layer 2)**

- **Manages data transmission** between nodes, error detection / correction
- **MAC Address** - Unique identifier for network interfaces
- **Protocols** - Ethernet, Point-to-Point Protocol (PPP), Frame Relay
- **Devices** - Switches, bridges



- **Network Layer (Layer 3)**

- **Routing algorithms** - Shortest Path First (SPF), Distance Vector (DV), Link State (LS)
- **Devices** - Routers, Layer 3 switches
- **Protocols** - Internet Protocol (IP), Internet Control Message Protocol (ICMP), Ipsec



- **Transport Layer (Layer 4)**

- **Error checking**, flow control, congestion control, multiplexing
- **TCP** - Ensures data is received in order, guarantees delivery using ACKs and retransmissions
- **UDP** - Fast, best-effort delivery without connection setup or error recovery



- **Session Layer (Layer 5)**

- **Functions** - Dialog control, token management, synchronization
- **Protocols** - Remote Procedure Call (RPC), Session Initiation Protocol (SIP), Network File System (NFS)




- **Presentation Layer (Layer 6)**

- **Functions** - Data representation, encryption, decryption, compression, decompression
- **Standards** - Secure Sockets Layer (SSL), Transport Layer Security (TLS), ASCII, Unicode, JPEG, MPEG




- **Application Layer (Layer 7)**
  - **User interface** for networked applications
  - **Protocols**
    - Hypertext Transfer Protocol (**HTTP**)
    - File Transfer Protocol (**FTP**)
    - Simple Mail Transfer Protocol (**SMTP**)
    - Domain Name System (**DNS**)
    - Telnet
    - Secure Shell (**SSH**)





**TCP/IP Model**

- **Transmission Control Protocol / Internet Protocol Model**
- **Developed** by the Department of Defense (**DoD**) in the **1970s** as part of the ARPANET project, the precursor to the modern internet
- **4 layers** - **Simplified version** with fewer layers
- Designed with a **focus on robustness, resilience, and scalability**



- **Link Layer**

- Combines the **functionalities of OSI Physical and Data Link layers**
- Transmission and reception of data packets over a physical medium
- Management of data link connections

- **Internet Layer**

- **Corresponds to the OSI Network Layer**
- Handling the logical addressing and routing of data packets

- **Transport Layer**
  - Closely resembles the OSI Transport Layer
- **Application Layer**
  - Merges the functionalities of **OSI Session, Presentation, and Application layers**






**Mac, IP**

- **Media Access Control (MAC) address** is a unique hardware identifier assigned to network interface cards (NICs)
- **Facilitate communication** at the Data Link Layer (Layer 2) in the OSI Model and the Link Layer in the TCP/IP Model
- **Format**
  - 48-bit (6-byte) or 64-bit (8-byte) hexadecimal number
  - Typically represented as six pairs of hexadecimal digits separated by colons or hyphens (e.g., 01:23:45:67:89:AB)
- **Generally hardcoded** by the manufacturer
- Can be manually changed in some cases





- **Internet Protocol (IP) address** - numerical identifier assigned to devices in a network for routing and addressing purposes
- Facilitate the **identification and location** of devices on a network
- Used at the Network Layer (Layer 3) in the OSI Model and the Internet Layer in the TCP/IP Model
- Types:
  - **IPv4**: 32-bit addresses, four decimal numbers separated by periods
  - **IPv6**: 128-bit addresses
- Assigned **statically (manually)** or **dynamically (using DHCP)**






# Networking Summary

- Communication in Internet uses **networking protocols**
  - The **OSI model** defines 7 layers of networking protocols
  - The **TCP/IP** protocol suite



- **IP (Internet Protocol):** Handles addressing and communication between devices
- **TCP (Transmission Control Protocol):** Complements IP, focuses on the reliable transport of data packets; uses ports to distinguish connections
- **UDP (User Datagram Protocol):** Similar to TCP, connectionless, faster, has no error checking; uses ports for communication
- **ICMP (Internet Control Message Protocol):** Used by networking devices, e.g. routers for error reporting and diagnostics
- **QUIC (Quick UDP Internet Connections):** Developed by Google, TCP alternative, combines features of TCP and UDP to reduce latency and improve security; often used with HTTP

\* Brief list of commonly encountered protocols



# Ports

- **Numerical identifiers** used to distinguish specific processes or services running on a device within a network
- Facilitate end-to-end communication between applications on different devices
- **Types of Ports**
  - **TCP ports** - Used for connection-oriented communication, ensuring reliability and data integrity
  - **UDP ports** - Used for connectionless communication, providing faster data transmission with minimal overhead



# Port Numbers

- Used to **identify** a network service
- Network services registry in **/etc/services**
- Some of them are:
  - **22** – SSH, **53** – DNS, **80** – HTTP, **110** – POP3, **123** – NTP, **143** – IMAP

```
tcpmux      1/tcp
echo        7/tcp
echo        7/udp
discard     9/tcp      sink null
discard     9/udp      sink null
systat      11/tcp     users
```

Ports	Port Numbers
Well-known (or system) ports	0 – 1023
Registered (or user) ports	1024 – 49151
Dynamic (and / or private) ports	49152 – 65535






# Web Fundamentals

WWW, Domains, DNS, URL

- A **global, interconnected system** of documents, images, and other resources, accessed through the internet using web browsers
- Invented by Sir Tim Berners-Lee in 1989 at CERN
- How the **Web Works**
  - **Hyperlinks** - Connect resources across the web, allowing users to navigate between them
  - **Web Servers** - Host and serve resources, making them accessible to web browsers
  - **Web Browsers** - Retrieve and display resources, allowing users to interact with the web

- A **unique**, human-readable **name** that **identifies a website**
- **Simplify navigation** and accessibility to websites, making it easier to remember and share
- **Structure**
  - **Top-Level Domains (TLDs)** - domain extensions, e.g., .com, .org, .net, .us, .uk, .de
  - **Second-Level Domains (SLDs)** - website's name, e.g., "example" in example.com
  - **Subdomains** - additional sections of a website, e.g., "blog" in blog.example.com

- A hierarchical, distributed database that **translates domain names into IP addresses**
- Facilitates the resolution of human-readable domain names to machine-readable IP addresses



# What is a URL?

- A **URL**, short for a **uniform resource locator** is a web address pointing to a specific website, a web page, or a document on the internet.
- **Structure-wise**, a URL consists of multiple **elements**
  - Communication protocol
  - Subdomain
  - Domain name
  - Domain extension
  - Path to the resource
  - Parameters, etc.



# Uniform Resource Locator (URL) Example

`http://mysite.com:8080/demo/index.php?id=27&lang=en#slides`

Protocol

Host

Port

Path


Query string

Fragment

- **Network protocol** (`http`, `ftp`, `https`...) – HTTP in most cases
- **Host, Domain** or **IP** address (`softuni.org`, `gmail.com`, `127.0.0.1`, `web`)
- **Port** (the default port is `80`) – integer in the range [0...65535]
- **Path** (`/forum`, `/path/index.php`)
- **Query string** (`?id=27&lang=en`)
- **Fragment** (`#slides`) – navigate to some section in the page

# What is Web Service?

- **Web services** implement **communication** between software **systems** or **components** of over the **network**
  - Using standard **protocols**, such as HTTP, JSON and XML
  - Exchanging **messages**, holding data and operations









# HTTP Protocol – Basics


- **HTTP** (**H**yper**T**ext **T**ransfer **P**rotocol)
  - **Text-based** client-server protocol for the Internet
  - For transferring **Web resources** (HTML files, images, styles, etc.)
  - **Request-response** based



# Web Server Work Model









# Network Layers and HTTP



# HTTP Request Methods

- **HTTP request methods** specify the desired **action** to be performed on the requested resource (identified by URL)

Method		Description	Other Methods
GET		Retrieve a resource	
POST		Create / store a resource	
PUT		Update (replace) a resource	
DELETE		Delete (remove) a resource	
PATCH		Update resource partially (modify)	
HEAD		Retrieve the resource's headers	

**CRUD** == the four main functions of persistent storage

CONNECT
OPTIONS
TRACE


# HTTP Response Status Codes

Status Code	Action	Description	
200	OK	Successfully retrieved resource	} Success
201	Created	A new resource was created	
204	No Content	Request has nothing to return	
301 / 302	Moved	Moved to another location (redirect)	} Redirect
400	Bad Request	Invalid request / syntax error	} Error
401 / 403	Unauthorized	Authentication failed / access denied	
404	Not Found	Invalid resource requested	
409	Conflict	Conflict detected, e.g. duplicated email	
500 / 503	Server Error	Internal server error / service unavailable	



**HTTP Dev Tools**

# HTTP Developer Tools: Network Inspector



- Chrome Developer Tools
  - Press **[F12]** in Chrome
  - Open the [Network] tab
  - Inspect the HTTP traffic



- <https://api.zippopotam.us/us/90222>

The screenshot shows a web browser's developer tools. On the left, the 'Network' tab is active, displaying a list of requests. The first request, '90222', is selected, and its 'Headers' sub-tab is open. The 'Request URL' is 'https://api.zippopotam.us/us/90222', the 'Request Method' is 'GET', the 'Status Code' is '200', and the 'Remote Address' is '172.67.147.158:443'. On the right, the 'Elements' tab is active, showing the DOM tree. A JSON object is visible, representing the response data: 

```
{  "post code": "90222",  "country": "United States",  "country abbreviation": "US",  "places": [    {      "place name": "Compton",      "longitude": "-118.2357",      "state": "California",      "state abbreviation": "CA",      "latitude": "33.9099"    }  ]}
```

# Requests Demo (2)

## ■ <https://restcountries.com/v2/name/Bulgaria>

[

{

"name": "Bulgaria",

"topLevelDomain": [

".bg"

],

"alpha2Code": "BG",

"alpha3Code": "BGR",

"callingCodes": [

"359"

],

"capital": "Sofia",

"altSpellings": [

"BG",

"Republic of Bulgaria",

"Република България"

],

"subregion": "Eastern Europe",

"region": "Europe",

"population": 6927288,

"latlng": [

43,

Raw

Parsed

Elements

Console

Network

1

Preserve log

Disable cache

No throttling

Filter

Invert

Hide data URLs

All

Fetch/XHR

JS

CSS

Img

Media

Font

Doc

WS

Wasm

Manifest

Other

Has blocked cookies

Blocked Requests

3rd-party requests

100 ms

200 ms

300 ms

400 ms

500 ms

Name

Bulgaria/

single-file-hooks-fram...

content.min.css

Headers

Preview

Response

Initiator

General

Request URL: https://restcountries.com/v2/name/Bulgaria/

Request Method: GET

Status Code: 200 OK

Remote Address: 161.35.252.68:443


Referrer Policy: strict-origin-when-cross-or

igin




**Email**

# How does Email work?



- **SMTP** (Simple Mail Transfer Protocol)
- Sending and receiving email messages between servers
- Ensures message is delivered to the correct server / format readable by the recipient's email client
- SMTPS (secure SMTP) uses additional SSL or TLS cryptographic protocol for increased security




- **IMAP** (Internet Message Access Protocol)

- Retrieving email messages from servers
- Allows management of email messages on the server from different devices **/sync and delete/**
- More popular and flexible

- **POP** (Post Office Protocol)


- Once downloaded to a client, the message is removed from the server **/download and delete/**
- Difficult to access email messages from different devices or locations



- **Redirect** incoming emails to another email address
- Useful for managing multiple email accounts
  - **Server-based forwarding** - Servers configured to automatically forward incoming messages to another email address
  - **Client-based forwarding** - setting up email forwarding using email client settings
  - **Email filters** - setting up filters to forward messages that match specific criteria



- **Detect** and **filter** out unwanted or harmful email messages
- **Rule-based** filtering and **Machine learning-based** filtering
- Some filtering is usually conducted automatically by an SMTP
- **Reject**, **redirect**, or **quarantine** an email depending on the contents
- **Customizable** for individual needs and preferences
- Setting up rules to **block/allow** emails from specific senders or domains






- Basic **networking concepts**
- **Layer Models:** OSI Model, TCP/IP
- MAC address, IP address, Ports
- Domains and DNS, WWW
- **HTTP** requests - GET, POST
- Browser **Dev Tools** - Web Debugging
- How does an Email work? **SMTP/IMAP**



# Questions?



# SoftUni Diamond Partners

**SUPER  
HOSTING  
.BG**



**Coca-Cola HBC  
Bulgaria**



**POKERSTARS**  
POKER | CASINO | SPORTS  
a Flutter International brand

**INDEAVR**  
Serving the high achievers



**AMBITIONED**

 **DRAFT  
KINGS**



**SOFTWARE  
GROUP**

createX



**Postbank**

Решения за твоето утре




**BOSCH**

**DXC**  
TECHNOLOGY



**SmartIT**



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg/>
- © Software University – <https://softuni.bg>



- Software University – High-Quality Education, Profession and Job for Software Developers

- [softuni.bg](http://softuni.bg), [about.softuni.bg](http://about.softuni.bg)

- Software University Foundation

- [softuni.foundation](http://softuni.foundation)

- Software University @ Facebook

- [facebook.com/SoftwareUniversity](https://facebook.com/SoftwareUniversity)

- Software University Forums

- [forum.softuni.bg](http://forum.softuni.bg)

