



XXBX Device Under Test – XBD

XBD User Guide v1.0

Jens-Peter Kaps
jkaps@gmu.edu

March 26, 2018
George Mason University
Fairfax, Virginia



cryptography.gmu.edu



www.gmu.edu

Cryptographic Engineering Research Group

Department of Electrical and Computer Engineering George Mason University
3100 Engineering Building, 4400 University Drive, Fairfax, VA 22030-4444, USA
Voice: (703) 993-1561, Fax: (703) 993-1601

Contents

1	Introduction	3
2	Boot Loader	4
2.1	Overview	4
2.2	Hardware Abstraction Layer	4
2.3	Stack Usage Measurement	4
2.4	XBH-XBD Communication	4
2.4.1	I ² C Interface	4
2.4.2	XBH-XBD Protocol	4
2.4.3	General Purpose IO	4
2.4.4	Reset	4
3	Board Specific Changes	5
3.1	Texas Instruments MSP430	5
3.1.1	Memory Map	5
3.1.2	Flash	5
3.2	Texas Instruments MSP432	5
3.3	Texas Instruments Tiva C	5
3.4	ST Microelectronics Nucleo	5
4	Using AES Peripherals	6
A	XBH - XBD Protocol	7

1 Introduction

2 Boot Loader

2.1 Overview

2.2 Hardware Abstraction Layer

2.3 Stack Usage Measurement

2.4 XBH-XBD Communication

2.4.1 I²C Interface

2.4.2 XBH-XBD Protocol

2.4.3 General Purpose IO

2.4.4 Reset

3 Board Specific Changes

3.1 Texas Instruments MSP430

3.1.1 Memory Map

3.1.2 Flash

3.2 Texas Instruments MSP432

3.3 Texas Instruments Tiva C

3.4 ST Microelectronics Nucleo

4 Using AES Peripherals

A XBH - XBD Protocol