![Texas Instruments] **TEXAS INSTRUMENTS**
www.ti.com

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

Description

The TS5A3154 is a single-pole double-throw (SPDT) analog switch that is designed to operate from 1.65 V to 5.5 V. The device offers a low ON-state resistance and an excellent channel-to-channel ON-state resistance matching. The device has excellent total harmonic distortion (THD) performance and consumes very low power. These features make this device suitable for portable audio applications.

Applications

- Cell Phones
- PDAs
- Portable Instrumentation
- Audio and Video Signal Routing
- Low-Voltage Data-Acquisition Systems
- Communication Circuits
- Modems
- Hard Drives
- Computer Peripherals
- Wireless Terminals and Peripherals

Features

- **Specified Make-Before-Break Switching**
- **Low ON-State Resistance (0.9 Ω)**
- **Control Inputs Are 5.5-V Tolerant**
- **Low Charge Injection**
- **Excellent ON-State Resistance Matching**
- **Low Total Harmonic Distortion (THD)**
- **1.65-V to 5.5-V Single-Supply Operation**
- **Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II**
- **ESD Performance Tested Per JESD 22**
  - **2000-V Human-Body Model (A114-B, Class II)**
  - **1000-V Charged-Device Model (C101)**

Summary of Characteristics

$V_+ = 5$ V, $T_A = 25°C$

Configuration	Single Pole, Double Throw 2:1 Multiplexer/ Demultiplexer (SPDT)
Number of channels	1
ON-state resistance (r_{on})	0.9 Ω
ON-state resistance match (Δr_{on})	0.1 Ω
ON-state resistance flatness ($r_{on(flat)}$)	0.15 Ω
Turn-on/turn-off time (t_{ON}/t_{OFF})	8 ns/12.5 ns
Make-before-break time (t_{MBB})	12 ns
Charge injection (Q_C)	10 pC
Bandwidth (BW)	100 MHz
OFF isolation (O_{ISO})	–64 dB at 1 MHz
Crosstalk (X_{TALK})	–64 dB at 1 MHz
Total harmonic distortion (THD)	0.004%
Leakage current ($I_{COM(OFF)}/I_{NC(OFF)}$)	±20 nA
Power-supply current (I_+)	0.1 μA
Package option	8-pin SSOP, SOT, or DSBGA

SSOP OR SOT PACKAGE (TOP VIEW)

YEA, YEP, YZA, OR YZP PACKAGE (BOTTOM VIEW)

FUNCTION TABLE

$\overline{EN}$	IN	NC TO COM, COM TO NC	NO TO COM, COM TO NO
L	L	ON	OFF
L	H	OFF	ON
H	X	OFF	OFF

⚖ Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

NanoFree and NanoStar are trademarks of Texas Instruments.

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

TEXAS INSTRUMENTS
www.ti.com

ORDERING INFORMATION

T$_A$	PACKAGE[1]		ORDERABLE PART NUMBER	TOP-SIDE MARKING[2]
−40°C to 85°C	NanoStar™ – WCSP (DSBGA) 0.17–mm Small Bump – YEA	Tape and reel	TS5A3154YEAR	
	NanoFree™ – WCSP (DSBGA) 0.17-mm Small Bump – YZA (Pb-free)		TS5A3154YZAR	
	NanoStar™ – WCSP (DSBGA) 0.23-mm Large Bump – YEP		TS5A3154YEPR	
	NanoFree™ – WCSP (DSBGA) 0.23-mm Large Bump – YZP (Pb-free)		TS5A3154YZPR	
	SSOP – DCT (Pb-free)	Tape	TS5A3154DCTRE6	JCF___
	DCU (Pb-free)	Tape and reel	TS5A3154DCURE6	JCF___, ____

[1] Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.
[2] DBV/DCK: The actual top-side marking has one additional character that designates the assembly/test site.
YEP/YZP: The actual top-side marking has three preceding characters to denote year, month, and sequence code, and one following character to designate the assembly/test site. Pin 1 identifier indicates solder-bump composition (1 = SnPb, ● = Pb-free).

![Texas Instruments logo] TEXAS INSTRUMENTS
www.ti.com

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

Absolute Minimum and Maximum Ratings[1][2]

over operating free-air temperature range (unless otherwise noted)

			MIN	MAX	UNIT
V_+	Supply voltage range[3]		−0.5	6.5	V
V_{NC} V_{NO} V_{COM}	Analog voltage range[3][4][5]		−0.5	$V_+ + 0.5$	V
I_K	Analog port diode current	V_{NC}, V_{NO}, $V_{COM} < 0$ or V_{NC}, V_{NO}, $V_{COM} > V_+$	−50	50	mA
I_{NC} I_{NO} I_{COM}	On-state switch current	V_{NC}, V_{NO}, $V_{COM} = 0$ to V_+	−200	200	mA
	On-state peak switch current[6]		−400	400	
V_I	Digital input voltage range[3][4]		−0.5	6.5	V
I_{IK}	Digital input clamp current	$V_I < 0$	−50		mA
I_+	Continuous current through V_+			100	mA
I_{GND}	Continuous current through GND		−100	100	mA
θ_{JA}	Package thermal impedance[7]	DCT package		220	°C/W
		DCU package		227	
		YEA/YZA package		140	
		YEP/YZP package		102	
T_{stg}	Storage temperature range		−65	150	°C

[1] Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those specified is not implied.

[2] The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

[3] All voltages are with respect to ground, unless otherwise specified.

[4] The input and output voltage ratings may be exceeded if the input and output clamp-current ratings are observed.

[5] This value is limited to 5.5 V maximum.

[6] Pulse at 1-ms duration < 10% duty cycle.

[7] The package thermal impedance is calculated in accordance with JESD 51-7.

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

TEXAS INSTRUMENTS
www.ti.com

SCDS191 – MARCH 2005

Electrical Characteristics for 5-V Supply[1]

V_+ = 4.5 V to 5.5 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch									
Analog signal range	V_{COM}, V_{NO}, V_{NC}					0		V_+	V
Peak ON resistance	r_{peak}	$0 \le (V_{NO}$ or $V_{NC}) \le V_+$, I_{COM} = –100 mA,	Switch ON, See Figure 13	25 °C	4.5 V		0.9	1.1	Ω
				Full				1.3	
ON-state resistance	r_{on}	V_{NO} or V_{NC} = 2.5 V, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C	4.5 V		0.8	0.9	Ω
				Full				1.1	
ON-state resistance match between channels	Δr_{on}	V_{NO} or V_{NC} = 2.5 V, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C	4.5 V		0.05	0.1	Ω
				Full				0.1	
ON-state resistance flatness	$r_{on(flat)}$	$0 \le (V_{NO}$ or $V_{NC}) \le V_+$, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C	4.5 V		0.15		Ω
				Full					
		V_{NO} or V_{NC} = 1 V, 1.5 V, 2.5 V, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C			0.09	0.15	
				Full				0.15	
NC, NO OFF leakage current	$I_{NC(OFF)}$, $I_{NO(OFF)}$	V_{NC} or V_{NO} = 1 V, V_{COM} = 4.5 V, or V_{NC} or V_{NO} = 4.5 V, V_{COM} = 1 V,	Switch OFF, See Figure 14	25°C	5.5 V	–20	2	20	nA
				Full		–150		150	
	$I_{NC(PWROFF)}$, $I_{NO(PWROFF)}$	V_{NC} or V_{NO} = 0 to 5.5 V, V_{COM} = 5.5 V to 0,	Switch OFF, See Figure 14	25°C	0 V	–5	0.7	5	μA
				Full		–25		25	
NC, NO ON leakage current	$I_{NC(ON)}$, $I_{NO(ON)}$	V_{NC} or V_{NO} = 1 V, V_{COM} = Open, or V_{NC} or V_{NO} = 4.5 V, V_{COM} = Open,	Switch ON, See Figure 15	25°C	5.5 V	–20	2	20	nA
				Full		–150		150	
COM OFF leakage current	$I_{COM(OFF)}$	V_{COM} = 1 V, V_{NC} or V_{NO} = 4.5 V, or V_{COM} = 4.5 V, V_{NC} or V_{NO} = 1 V,	Switch OFF See Figure 14	25°C	5.5 V	–20	2	20	nA
				Full		–150		150	
	$I_{COM(PWROFF)}$	V_{NC} or V_{NO} = 0 to 5.5 V, V_{COM} = 5.5 V to 0,	Switch OFF, See Figure 14	25°C	0 V	–5	0.7	5	μA
				Full		–25		25	
COM ON leakage current	$I_{COM(ON)}$	V_{COM} = 1 V, V_{NC} or V_{NO} = Open, or V_{COM} = 4.5 V, V_{NC} or V_{NO} = Open	Switch ON, See Figure 15	25°C	5.5 V	–20	2	20	nA
				Full		–150		150	
Digital Control Inputs (IN, $\overline{EN}$)[2]									
Input logic high	V_{IH}			Full		2.4		5.5	V
Input logic low	V_{IL}			Full		0		0.8	V
Input leakage current	I_{IH}, I_{IL}	V_I = 5.5 V or 0		25°C	5.5 V	–100	25	100	nA
				Full		–100		100	

[1] The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

[2] All unused digital inputs of the device must be held at V_+ or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

![Texas Instruments logo] **TEXAS INSTRUMENTS**
www.ti.com

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

Electrical Characteristics for 5-V Supply[1] (continued)

V_+ = 4.5 V to 5.5 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic									
Turn-on time, IN or $\overline{OE}$	t_{ON}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	C_L = 35 pF, See Figure 17	25°C	5 V	1	5.2	8	ns
				Full	4.5 V to 5.5 V	1		9	
Turn-off time, IN or $\overline{OE}$	t_{OFF}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	C_L = 35 pF, See Figure 17	25°C	5 V	5	9.5	12.5	ns
				Full	4.5 V to 5.5 V	4		13.5	
Make-before-break time	t_{MBB}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	C_L = 35 pF, See Figure 18	25°C	5 V	4	6.3	12	ns
				Full	4.5 V to 5.5 V	4		13	
Charge injection	Q_C	$V_{GEN} = 0$, $R_{GEN} = 0$,	C_L = 1 nF, See Figure 22	25°C	5 V		10		pC
NC, NO OFF capacitance	$C_{NC(OFF)}$, $C_{NO(OFF)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch OFF,	See Figure 16	25°C	5 V		19		pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch ON,	See Figure 16	25°C	5 V		57		pF
COM OFF capacitance	$C_{COM(OFF)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 16	25°C	5 V		36		pF
COM ON capacitance	$C_{COM(ON)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 16	25°C	5 V		57		pF
Digital input capacitance	C_I	$V_I = V_+$ or GND,	See Figure 16	25°C	5 V		2		pF
Bandwidth	BW	$R_L = 50\ \Omega$, Switch ON,	See Figure 19	25°C	5 V		100		MHz
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, f = 1 MHz,	Switch OFF, See Figure 20	25°C	5 V		–64		dB
Crosstalk	X_{TALK}	$R_L = 50\ \Omega$, f = 1 MHz,	Switch ON, See Figure 21	25°C	5 V		–64		dB
Total harmonic distortion	THD	$R_L = 600\ \Omega$, C_L = 50 pF,	f = 20 Hz to 20 kHz, See Figure 23	25°C	5 V		0.004		%
Supply									
Positive supply current	I_+	$V_I = V_+$ or GND,	Switch ON or OFF	25°C	5.5 V		0.02	0.1	µA
				Full				0.5	

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

TEXAS INSTRUMENTS
www.ti.com

Electrical Characteristics for 3.3-V Supply[1]

V_+ = 3 V to 3.6 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch									
Analog signal range	V_{COM}, V_{NO}, V_{NC}					0		V_+	V
Peak ON resistance	r_{peak}	$0 \le$ (V_{NO} or V_{NC}) $\le V_+$, I_{COM} = –100 mA,	Switch ON, See Figure 13	25 °C	3 V		1.3	1.6	Ω
				Full				1.9	
ON-state resistance	r_{on}	V_{NO} or V_{NC} = 2 V, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C	3 V		1.2	1.5	Ω
				Full				1.7	
ON-state resistance match between channels	Δr_{on}	V_{NO} or V_{NC} = 2 V, 0.8 V, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C	3 V		0.08	0.15	Ω
				Full				0.15	
ON-state resistance flatness	$r_{on(flat)}$	$0 \le$ (V_{NO} or V_{NC}) $\le V_+$, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C	3 V		0.3		Ω
				Full					
		V_{NO} or V_{NC} = 2 V, 0.8 V, I_{COM} = –100 mA,	Switch ON, See Figure 13	25°C			0.09	0.15	
				Full				0.15	
NC, NO OFF leakage current	$I_{NO(OFF)}$, $I_{NC(OFF)}$	V_{NC} or V_{NO} = 1 V, V_{COM} = 3 V, or V_{NC} or V_{NO} = 3 V, V_{COM} = 1 V,	Switch OFF, See Figure 14	25°C	3.6 V	–20	2	20	nA
				Full		–50		50	
	$I_{NO(PWROFF)}$, $I_{NC(PWROFF)}$	V_{NC} or V_{NO} = 0 to 3.6 V, V_{COM} = 3.6 V to 0,	Switch OFF, See Figure 14	25°C	0 V	–1	0.2	1	µA
				Full		–15		15	
NC, NO ON leakage current	$I_{NC(ON)}$, $I_{NO(ON)}$	V_{NC} or V_{NO} = 1 V, V_{COM} = Open, or V_{NC} or V_{NO} = 3 V, V_{COM} = Open,	Switch ON, See Figure 15	25°C	3.6 V	–20	2	20	nA
				Full		–50		50	
COM OFF leakage current	$I_{COM(OFF)}$	V_{COM} = 1 V, V_{NC} or V_{NO} = 3 V, or V_{COM} = 3 V, V_{NC} or V_{NO} = 1 V,	Switch OFF, See Figure 14	25°C	3.6 V	–20	2	20	nA
				Full		–50		50	
	$I_{COM(PWROFF)}$	V_{COM} = 0 to 3.6 V, V_{NC} or V_{NO} = 3.6 V to 0,	Switch OFF, See Figure 14	25°C	0 V	–1	0.2	1	µA
				Full		–15		15	
COM ON leakage current	$I_{COM(ON)}$	V_{COM} = 1 V, V_{NC} or V_{NO} = Open, or V_{COM} = 3 V, V_{NC} or V_{NO} = Open	Switch ON, See Figure 15	25°C	3.6 V	–20	2	20	nA
				Full		–50		50	
Digital Control Inputs (IN, $\overline{EN}$)[2]									
Input logic high	V_{IH}			Full		2		5.5	V
Input logic low	V_{IL}			Full		0		0.8	V
Input leakage current	I_{IH}, I_{IL}	V_I = 5.5 V or 0		25°C	3.6 V	–100	25	100	nA
				Full		–100		100	

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

(2) All unused digital inputs of the device must be held at V_+ or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

Electrical Characteristics for 3.3-V Supply[1] (continued)

V_+ = 3 V to 3.6 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic									
Turn-on time	t_{ON}	V_{COM} = V_+, R_L = 50 Ω,	C_L = 35 pF, See Figure 17	25°C	3.3 V	3	6	10	ns
				Full	3 V to 3.6 V	2		10.5	
Turn-off time	t_{OFF}	V_{COM} = V_+, R_L = 50 Ω,	C_L = 35 pF, See Figure 17	25°C	3.3 V	5	10	15	ns
				Full	3 V to 3.6 V	4		17	
Make-before-break time	t_{MBB}	V_{COM} = V_+, R_L = 50 Ω,	C_L = 35 pF, See Figure 18	25°C	3.3 V	4	5.7	12	ns
				Full	3 V to 3.6 V	4		13	
Charge injection	Q_C	V_{GEN} = 0, R_{GEN} = 0,	C_L = 1 nF, See Figure 22	25°C	3.3 V			9	pC
NC, NO OFF capacitance	$C_{NC(OFF)}$, $C_{NO(OFF)}$	V_{NC} or V_{NO} = V_+ or GND, Switch OFF,	See Figure 16	25°C	3.3 V			19	pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or V_{NO} = V_+ or GND, Switch ON,	See Figure 16	25°C	3.3 V			57	pF
COM OFF capacitance	$C_{COM(OFF)}$	V_{COM} = V_+ or GND, Switch ON,	See Figure 16	25°C	3.3 V			36	pF
COM ON capacitance	$C_{COM(ON)}$	V_{COM} = V_+ or GND, Switch ON,	See Figure 16	25°C	3.3 V			57	pF
Digital input capacitance	C_I	V_I = V_+ or GND,	See Figure 16	25°C	3.3 V			2	pF
Bandwidth	BW	R_L = 50 Ω, Switch ON,	See Figure 19	25°C	3.3 V			100	MHz
OFF isolation	O_{ISO}	R_L = 50 Ω, f = 1 MHz,	Switch OFF, See Figure 20	25°C	3.3 V			–64	dB
Crosstalk	X_{TALK}	R_L = 50 Ω, f = 1 MHz,	Switch ON, See Figure 21	25°C	3.3 V			–64	dB
Total harmonic distortion	THD	R_L = 600 Ω, C_L = 50 pF,	f = 20 Hz to 20 kHz, See Figure 23	25°C	3.3 V			0.010	%
Supply									
Positive supply current	I_+	V_I = V_+ or GND,	Switch ON or OFF	25°C	3.6 V		0.01	0.1	µA
				Full				0.25	

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

TEXAS INSTRUMENTS
www.ti.com

Electrical Characteristics for 2.5-V Supply[1]

V_+ = 2.3 V to 2.7 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch									
Analog signal range	V_{COM}, V_{NO}, V_{NC}					0		V_+	V
Peak ON resistance	r_{peak}	$0 \le (V_{NO}$ or $V_{NC}) \le V_+$, I_{COM} = −8 mA,	Switch ON, See Figure 13	25 °C	2.3 V		1.9	2.5	Ω
				Full				2.7	
ON-state resistance	r_{on}	V_{NO} or V_{NC} = 1.8 V, I_{COM} = −8 mA,	Switch ON, See Figure 13	25°C	2.3 V		1.6	2.1	Ω
				Full				2.5	
ON-state resistance match between channels	Δr_{on}	V_{NO} or V_{NC} = 1.8 V, I_{COM} = −8 mA,	Switch ON, See Figure 13	25°C	2.3 V		0.12	0.2	Ω
				Full				0.2	
ON-state resistance flatness	$r_{on(flat)}$	$0 \le (V_{NO}$ or $V_{NC}) \le V_+$, I_{COM} = −8 mA,	Switch ON, See Figure 13	25°C	2.3 V		0.65		Ω
				Full					
		V_{NO} or V_{NC} = 0.8 V, 1.8 V, I_{COM} = −8 mA,	Switch ON, See Figure 13	25°C			0.5	1	
				Full				1	
NC, NO OFF leakage current	$I_{NO(OFF)}$, $I_{NC(OFF)}$	V_{NC} or V_{NO} = 0.5 V, V_{COM} = 2.3 V, or V_{NC} or V_{NO} = 2.3 V, V_{COM} = 0.5 V,	Switch OFF, See Figure 14	25°C	2.7 V	−20	2	20	nA
				Full		−50		50	
	$I_{NO(PWROFF)}$, $I_{NC(PWROFF)}$	V_{NC} or V_{NO} = 0 to 2.7 V, V_{COM} = 2.7 V to 0,	Switch OFF, See Figure 14	25°C	0 V	−1	0.1	1	μA
				Full		−10		10	
NC, NO ON leakage current	$I_{NC(ON)}$, $I_{NO(ON)}$	V_{NC} or V_{NO} = 0.5 V, V_{COM} = Open, or V_{NC} or V_{NO} = 2.3 V, V_{COM} = Open,	Switch ON, See Figure 15	25°C	2.7 V	−20	2	20	nA
				Full		−50		50	
COM OFF leakage current	$I_{COM(OFF)}$	V_{COM} = 0.5 V, V_{NC} or V_{NO} = 2.3 V, or V_{COM} = 2.3 V, V_{NC} or V_{NO} = 0.5 V,	Switch OFF, See Figure 14	25°C	2.7 V	−20	2	20	nA
				Full		−50		50	
	$I_{COM(PWROFF)}$	V_{COM} = 0 to 2.7 V, V_{NC} or V_{NO} = 2.7 V to 0,	Switch OFF, See Figure 14	25°C	0 V	−1	0.1	1	μA
				Full		−10		10	
COM ON leakage current	$I_{COM(ON)}$	V_{COM} = 0.5 V, V_{NC} or V_{NO} = Open, or V_{COM} = 2.3 V, V_{NC} or V_{NO} = Open,	Switch ON, See Figure 15	25°C	2.7 V	−20	2	20	nA
				Full		−50		50	
Digital Control Inputs (IN, $\overline{EN}$)[2]									
Input logic high	V_{IH}			Full		1.8		5.5	V
Input logic low	V_{IL}			Full		0		0.6	V
Input leakage current	I_{IH}, I_{IL}	V_I = 5.5 V or 0		25°C	2.7 V	−100	25	100	nA
				Full		−100		100	

[1] The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

[2] All unused digital inputs of the device must be held at V_+ or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

Electrical Characteristics for 2.5-V Supply[1] (continued)

V_+ = 2.3 V to 2.7 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic									
Turn-on time	t_{ON}	$V_{COM} = V_+$, R_L = 50 Ω,	C_L = 35 pF, See Figure 17	25°C	2.5 V	4	7.0	11.5	ns
				Full	2.3 V to 2.7 V	3.5		12	
Turn-off time	t_{OFF}	$V_{COM} = V_+$, R_L = 50 Ω,	C_L = 35 pF, See Figure 17	25°C	2.5 V	5	11.5	18.5	ns
				Full	2.3 V to 2.7 V	4		21	
Make-before-break time	t_{MBB}	$V_{COM} = V_+$, R_L = 50 Ω,	C_L = 35 pF, See Figure 18	25°C	2.5 V	4	6.3	15	ns
				Full	2.3 V to 2.7 V	4		16	
Charge injection	Q_C	V_{GEN} = 0, R_{GEN} = 0,	C_L = 1 nF, See Figure 22	25°C	2.5 V		7		pC
NC, NO OFF capacitance	$C_{NC(OFF)}$, $C_{NO(OFF)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch OFF,	See Figure 16	25°C	2.5 V		19		pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch ON,	See Figure 16	25°C	2.5 V		57		pF
COM OFF capacitance	$C_{COM(OFF)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 16	25°C	2.5 V		36		pF
COM ON capacitance	$C_{COM(ON)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 16	25°C	2.5 V		57		pF
Digital input capacitance	C_I	$V_I = V_+$ or GND,	See Figure 16	25°C	2.5 V		2		pF
Bandwidth	BW	R_L = 50 Ω, Switch ON,	See Figure 19	25°C	2.5 V		100		MHz
OFF isolation	O_{ISO}	R_L = 50 Ω, f = 1 MHz,	Switch OFF, See Figure 20	25°C	2.5 V		–64		dB
Crosstalk	X_{TALK}	R_L = 50 Ω, f = 1 MHz,	Switch ON, See Figure 21	25°C	2.5 V		–64		dB
Total harmonic distortion	THD	R_L = 600 Ω, C_L = 50 pF,	f = 20 Hz to 20 kHz, See Figure 23	25°C	2.5 V		0.020		%
Supply									
Positive supply current	I_+	$V_I = V_+$ or GND,	Switch ON or OFF	25°C	2.7 V		0.001	0.05	μA
				Full				0.15	

(1) The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

TEXAS INSTRUMENTS
www.ti.com

Electrical Characteristics for 1.8-V Supply[1]

V_+ = 1.65 V to 1.95 V, T_A = −40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Analog Switch									
Analog signal range	V_{COM}, V_{NO}, V_{NC}					0		V_+	V
Peak ON resistance	r_{peak}	$0 \leq (V_{NO}$ or $V_{NC}) \leq V_+$, I_{COM} = −2 mA,	Switch ON, See Figure 13	25 °C	1.65 V		5.5	25	Ω
				Full				30	
ON-state resistance	r_{on}	V_{NO} or V_{NC} = 1.5 V, I_{COM} = −2 mA,	Switch ON, See Figure 13	25°C	1.65 V		2.0	2.7	Ω
				Full				3.1	
ON-state resistance match between channels	Δr_{on}	V_{NO} or V_{NC} = 0.6 V, 1.5 V, I_{COM} = −2 mA,	Switch ON, See Figure 13	25°C	1.65 V		0.16	0.3	Ω
				Full				0.3	
ON-state resistance flatness	$r_{on(flat)}$	$0 \leq (V_{NO}$ or $V_{NC}) \leq V_+$, I_{COM} = −2 mA,	Switch ON, See Figure 13	25°C	1.65 V		3		Ω
		V_{NO} or V_{NC} = 0.6 V, 1.5 V, I_{COM} = −2 mA,	Switch ON, See Figure 13	25°C			3	20	
				Full				25	
NC, NO OFF leakage current	$I_{NO(OFF)}$, $I_{NC(OFF)}$	V_{NC} or V_{NO} = 0.3 V, V_{COM} = 1.65 V, or V_{NC} or V_{NO} = 1.65 V, V_{COM} = 0.3 V,	Switch OFF, See Figure 14	25°C	1.95 V	−20	1.5	20	nA
				Full		−50		50	
	$I_{NO(PWROFF)}$, $I_{NC(PWROFF)}$	V_{NC} or V_{NO} = 0 to 1.95 V, V_{COM} = 1.95 V to 0,	Switch OFF, See Figure 14	25°C	0 V	−1	0.1	1	μA
				Full		−10		10	
NC, NO ON leakage current	$I_{NC(ON)}$, $I_{NO(ON)}$	V_{NC} or V_{NO} = 0.3 V, V_{COM} = Open, or V_{NC} or V_{NO} = 1.65 V, V_{COM} = Open,	Switch ON, See Figure 15	25°C	1.95 V	−20	1.5	20	nA
				Full		−50		50	
COM OFF leakage current	$I_{COM(OFF)}$	V_{NC} or V_{NO} = 1.65 V, V_{COM} = 0.3 V, or V_{NC} or V_{NO} = 0.3 V, V_{COM} = 1.65 V,	Switch OFF, See Figure 14	25°C	1.95 V	−20	1.5	20	nA
				Full		−50		50	
	$I_{COM(PWROFF)}$	V_{NC} or V_{NO} = 1.95 V to 0, V_{COM} = 0 to 1.95 V,	Switch OFF, See Figure 14	25°C	0 V	−1	0.06	1	μA
				Full		−10		10	
COM ON leakage current	$I_{COM(ON)}$	V_{NC} or V_{NO} = Open, V_{COM} = 0.3 V, or V_{NC} or V_{NO} = Open, V_{COM} = 1.65 V,	Switch ON, See Figure 15	25°C	1.95 V	−20	1.5	20	nA
				Full		−50		50	
Digital Control Inputs (IN, $\overline{EN}$)[2]									
Input logic high	V_{IH}			Full		1.5		5.5	V
Input logic low	V_{IL}			Full		0		0.6	V
Input leakage current	I_{IH}, I_{IL}	V_I = 5.5 V or 0		25°C	1.95 V	−100	25	100	nA
				Full		−100		100	

[1] The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

[2] All unused digital inputs of the device must be held at V_+ or GND to ensure proper device operation. Refer to the TI application report, *Implications of Slow or Floating CMOS Inputs*, literature number SCBA004.

Electrical Characteristics for 1.8-V Supply[1] (continued)

V_+ = 1.65 V to 1.95 V, T_A = –40°C to 85°C (unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		T_A	V_+	MIN	TYP	MAX	UNIT
Dynamic									
Turn-on time	t_{ON}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	C_L = 35 pF, See Figure 17	25°C	1.8 V	5	10.5	20.5	ns
				Full	1.65 V to 1.95 V	4.5		21	
Turn-off time	t_{OFF}	$V_{COM} = V_+$, $R_L = 50\ \Omega$,	C_L = 35 pF, See Figure 17	25°C	1.8 V	7	16.5	27.5	ns
				Full	1.65 V to 1.95 V	5		30	
Break-before-make time	t_{BBM}	$V_{NC} = V_{NO} = V_+$, $R_L = 50\ \Omega$,	C_L = 35 pF, See Figure 18	25°C	1.8 V	4	8.3	15	ns
				Full	1.65 V to 1.95 V	4		16	
Charge injection	Q_C	$V_{GEN} = 0$, $R_{GEN} = 0$,	C_L = 1 nF, See Figure 22	25°C	1.8 V		5		pC
NC, NO OFF capacitance	$C_{NC(OFF)}$, $C_{NO(OFF)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch OFF,	See Figure 16	25°C	1.8 V		19		pF
NC, NO ON capacitance	$C_{NC(ON)}$, $C_{NO(ON)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch ON,	See Figure 16	25°C	1.8 V		57		pF
COM OFF capacitance	$C_{COM(OFF)}$	V_{NC} or $V_{NO} = V_+$ or GND, Switch OFF,	See Figure 16	25°C	1.8 V		36		pF
COM ON capacitance	$C_{COM(ON)}$	$V_{COM} = V_+$ or GND, Switch ON,	See Figure 16	25°C	1.8 V		57		pF
Digital input capacitance	C_I	$V_I = V_+$ or GND,	See Figure 16	25°C	1.8 V		2.0		pF
Bandwidth	BW	$R_L = 50\ \Omega$, Switch ON,	See Figure 19	25°C	1.8 V		100		MHz
OFF isolation	O_{ISO}	$R_L = 50\ \Omega$, f = 1 MHz,	Switch OFF, See Figure 20	25°C	1.8 V		–64		dB
Crosstalk	X_{TALK}	$R_L = 50\ \Omega$, f = 1 MHz,	Switch ON, See Figure 21	25°C	1.8 V		–64		dB
Total harmonic distortion	THD	$R_L = 600\ \Omega$, C_L = 50 pF,	f = 20 Hz to 20 kHz, See Figure 23	25°C	1.8 V		0.060		%
Supply									
Positive supply current	I_+	$V_I = V_+$ or GND,	Switch ON or OFF	25°C	1.95 V		0.001	0.05	µA
				Full				0.1	

[1] The algebraic convention, whereby the most negative value is a minimum and the most positive value is a maximum

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

SCDS191 – MARCH 2005

TEXAS INSTRUMENTS
www.ti.com

TYPICAL PERFORMANCE

Figure 1. r_{on} vs V_{COM}


Figure 2. r_{on} vs V_{COM} (V_+ = 3 V)


Figure 3. r_{on} vs V_{COM} (V_+ = 5 V)


Figure 4. Leakage Current vs Temperature (V_+ = 5.5 V)


Figure 5. Charge Injection (Q_C) vs V_{COM}


Figure 6. t_{ON} and t_{OFF} vs Supply Voltage

![Texas Instruments logo] **TEXAS INSTRUMENTS**
www.ti.com

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER
SCDS191 – MARCH 2005

TYPICAL PERFORMANCE

Figure 7. t_{ON} and t_{OFF} vs Temperature (V_+ = 5 V)

Figure 8. Logic-Level Threshold vs V_+

Figure 9. Bandwidth (V_+ = 5 V)

Figure 10. OFF Isolation and Crosstalk (V_+ = 5 V)

Figure 11. Total Harmonic Distortion (THD) vs. Frequency

Figure 12. Power Supply Current vs Temperature (V_+ = 5 V)

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

TEXAS INSTRUMENTS
www.ti.com

SCDS191 – MARCH 2005

PIN DESCRIPTION

PIN NUMBER	NAME	DESCRIPTION
1	COM	Common
2	$\overline{\text{EN}}$	Enable control input
3	GND	Digital ground
4	GND	Digital ground
5	IN	Digital control to connect COM to NO or NC
6	NO	Normally open
7	NC	Normally closed
8	V_+	Power supply

PARAMETER DESCRIPTION

SYMBOL	DESCRIPTION
V_{COM}	Voltage at COM
V_{NC}	Voltage at NC
V_{NO}	Voltage at NO
r_{on}	Resistance between COM and NC or COM and NO ports when the channel is ON
r_{peak}	Peak on-state resistance over a specified voltage range
Δr_{on}	Difference of r_{on} between channels in a specific device
$r_{on(flat)}$	Difference between the maximum and minimum value of r_{on} in a channel over the specified range of conditions
$I_{NC(OFF)}$	Leakage current measured at the NC port, with the corresponding channel (NC to COM) in the OFF state under worst-case input and output conditions
$I_{NC(PWROFF)}$	Leakage current measured at the NC port during the power-off condition, $V_+ = 0$
$I_{NO(OFF)}$	Leakage current measured at the NO port, with the corresponding channel (NO to COM) in the OFF state under worst-case input and output conditions
$I_{NO(PWROFF)}$	Leakage current measured at the NO port during the power-off condition, $V_+ = 0$
$I_{NC(ON)}$	Leakage current measured at the NC port, with the corresponding channel (NC to COM) in the ON state and the output (COM) open
$I_{NO(ON)}$	Leakage current measured at the NO port, with the corresponding channel (NO to COM) in the ON state and the output (COM) open
$I_{COM(ON)}$	Leakage current measured at the COM port, with the corresponding channel (COM to NO or COM to NC) in the ON state and the output (NC or NO) open
$I_{COM(OFF)}$	Leakage current measured at the COM port, with the corresponding channel (COM to NO or COM to NC) in the OFF state and the output (NC or NO) open
$I_{COM(PWROFF)}$	Leakage current measured at the COM port during the power-off condition, $V_+ = 0$
V_{IH}	Minimum input voltage for logic high for the control input (IN, $\overline{\text{EN}}$)
V_{IL}	Maximum input voltage for logic low for the control input (IN, $\overline{\text{EN}}$)
V_I	Voltage at the control input (IN, $\overline{\text{EN}}$)
I_{IH}, I_{IL}	Leakage current measured at the control input (IN, $\overline{\text{EN}}$)
t_{ON}	Turn-on time for the switch. This parameter is measured under the specified range of conditions and by the propagation delay between the digital control (IN) signal and analog output (COM, NC, or NO) signal when the switch is turning ON.
t_{OFF}	Turn-off time for the switch. This parameter is measured under the specified range of conditions and by the propagation delay between the digital control (IN) signal and analog output (COM, NC, or NO) signal when the switch is turning OFF.
t_{MBB}	Make-before-break time. This parameter is measured under the specified range of conditions and by the propagation delay between the output of two adjacent analog channels (NC and NO) when the control signal changes state.
Q_C	Charge injection is a measurement of unwanted signal coupling from the control (IN) input to the analog (NC, NO, or COM) output. This is measured in coulomb (C) and measured by the total charge induced due to switching of the control input. Charge injection, $Q_C = C_L \times \Delta V_{COM}$, C_L is the load capacitance, and ΔV_{COM} is the change in analog output voltage.

PARAMETER DESCRIPTION (continued)

SYMBOL	DESCRIPTION
$C_{NC(OFF)}$	Capacitance at the NC port when the corresponding channel (NC to COM) is OFF
$C_{NO(OFF)}$	Capacitance at the NO port when the corresponding channel (NO to COM) is OFF
$C_{NC(ON)}$	Capacitance at the NC port when the corresponding channel (NC to COM) is ON
$C_{NO(ON)}$	Capacitance at the NO port when the corresponding channel (NO to COM) is ON
$C_{COM(ON)}$	Capacitance at the COM port when the corresponding channel (COM to NC or COM to NO) is ON
$C_{COM(OFF)}$	Capacitance at the COM port when the corresponding channel (COM to NC or COM to NO) is OFF
C_I	Capacitance of control input (IN, $\overline{EN}$)
O_{ISO}	OFF isolation of the switch is a measurement of OFF-state switch impedance. This is measured in dB in a specific frequency, with the corresponding channel (NC to COM or NO to COM) in the OFF state.
X_{TALK}	Crosstalk is a measurement of unwanted signal coupling from an ON channel to an OFF channel (NC to NO or NO to NC). This is measured in a specific frequency and in dB.
BW	Bandwidth of the switch. This is the frequency in which the gain of an ON channel is −3 dB below the DC gain.
THD	Total harmonic distortion describes the signal distortion caused by the analog switch. This is defined as the ratio of root mean square (RMS) value of the second, third, and higher harmonic to the absolute magnitude of the fundamental harmonic.
I_+	Static power-supply current with the control (IN, $\overline{EN}$) pin at V_+ or GND

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

TEXAS INSTRUMENTS
www.ti.com

SCDS191 – MARCH 2005

PARAMETER MEASUREMENT INFORMATION

The box shows:

Channel ON

$$r_{on} = \frac{V_{COM} - V_{NO} \text{ or } V_{NC}}{I_{COM}} \; \Omega$$

$V_I = V_{IH}$ or V_{IL}

Figure 13. ON-State Resistance (r_{on})

OFF-State Leakage Current
Channel OFF
$V_I = V_{IH}$ or V_{IL}

Figure 14. OFF-State Leakage Current ($I_{NC(OFF)}$, $I_{NO(OFF)}$, $I_{COM(OFF)}$, $I_{NO(PWROFF)}$, $I_{COM(PWROFF)}$)

ON-State Leakage Current
Channel ON
$V_I = V_{IH}$ or V_{IL}

Figure 15. ON-State Leakage Current ($I_{COM(ON)}$, $I_{NC(ON)}$, $I_{NO(ON)}$)

Figure 16. Capacitance (C_I, $C_{COM(OFF)}$, $C_{COM(ON)}$, $C_{NC(OFF)}$, $C_{NO(OFF)}$, $C_{NC(ON)}$, $C_{NO(ON)}$)

| TEST	R_L	C_L	V_{COM}
t_{ON}	50 Ω	35 pF	V_+
t_{OFF}	50 Ω	35 pF	V_+

(1) All input pulses are supplied by generators having the following characteristics: PRR ≤ 10 MHz, Z_O = 50 Ω, t_r < 5 ns, t_f < 5 ns.
(2) C_L includes probe and jig capacitance.

Figure 17. Turn-On (t_{ON}) and Turn-Off Time (t_{OFF})

TS5A3154
0.9-Ω SPDT ANALOG SWITCH
5-V/3.3-V SINGLE-CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER

TEXAS INSTRUMENTS
www.ti.com

SCDS191 – MARCH 2005

(1) All input pulses are supplied by generators having the following characteristics: PRR $\leq$ 10 MHz, Z_O = 50 Ω, t_r < 5 ns, t_f < 5 ns.
(2) C_L includes probe and jig capacitance.

Figure 18. Make-Before-Break Time (t_{MBB})

**Figure 19. Bandwidth (BW)**

Figure 20. OFF Isolation (O_{ISO})

**Figure 21. Crosstalk (X$_{TALK}$)**

(1) All input pulses are supplied by generators having the following characteristics: PRR $\leq$ 10 MHz, Z_O = 50 Ω, t_r < 5 ns, t_f < 5 ns.
(2) C_L includes probe and jig capacitance.

Figure 22. Charge Injection (Q$_C$)

(1) C_L includes probe and jig capacitance.

Figure 23. Total Harmonic Distortion (THD)

PACKAGING INFORMATION

Orderable Device	Status [1]	Package Type	Package Drawing	Pins	Package Qty	Eco Plan [2]	Lead/Ball Finish	MSL Peak Temp [3]
TS5A3154DCUR	ACTIVE	US8	DCU	8	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
TS5A3154DCURE4	ACTIVE	US8	DCU	8	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
TS5A3154DCURE6	PREVIEW	US8	DCU	8	3000	TBD	Call TI	Call TI
TS5A3154DCURG4	ACTIVE	US8	DCU	8	3000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM
TS5A3154YZPR	ACTIVE	WCSP	YZP	8	3000	Green (RoHS & no Sb/Br)	SNAGCU	Level-1-260C-UNLIM

[1] The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

[2] Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

[3] MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

DCU (R−PDSO−G8)   PLASTIC SMALL−OUTLINE PACKAGE (DIE DOWN)

4200503/F 07/05

NOTES: A.   All linear dimensions are in millimeters.
         B.   This drawing is subject to change without notice.
         C.   Body dimensions do not include mold flash or protrusion. Mold flash and protrusion shall not exceed 0.15 per side.
         D.   Falls within JEDEC MO−187 variation CA.

YZP (R−XBGA−N8)   DIE−SIZE BALL GRID ARRAY

0,95 / 0,85

A
B

1,95 / 1,85

Pin A1 Index Area

0,50
0,25

D
C
B
A

1   2

Bottom View

1,50
0,25
0,50

8X ⌀ 0,25 / 0,21

⌖ ⌀ 0,05 Ⓜ C A B
⌀ 0,05 Ⓜ C

0,50 Max

0,19 / 0,15

0,05 C

Seating Plane

C

4204741−4/C 08/2006

NOTES: A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M−1994.
        B. This drawing is subject to change without notice.
        C. NanoFree™ package configuration.
        D. This package is lead−free. Refer to the 8 YEP package (drawing 4204725) for tin−lead (SnPb).

NanoFree is a trademark of Texas Instruments.

TEXAS INSTRUMENTS
www.ti.com

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		**Applications**	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
Low Power Wireless	www.ti.com/lpw	Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless

Mailing Address: Texas Instruments
                     Post Office Box 655303 Dallas, Texas 75265

Copyright © 2006, Texas Instruments Incorporated