

Plastic TSOP

Package Code: T (Type II)



Notes:

- Controlling dimension: millimieters, unless otherwise specified.
- 2. BSC = Basic lead spacing between centers.
- Dimensions D and E1 do not include mold flash protrusions and should be measured from the bottom of the package.
- Formed leads shall be planar with respect to one another within 0.004 inches at the seating plane.



Plastic TSOP (T - Type II)													
	Millimeters		Inche	Inches		Millimeters		Inches		Millimeters		Inches	
Symbol	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max	
Ref. Std.													
No. Leads (N)		32			44			50					
Α	_	1.20	_	0.047	_	1.2044	_	0.047	_	1.20	_	0.047	
A1	0.05	0.15	0.002	0.006	0.050	0.150	0.002	0.0059	0.05	0.15	0.002	0.006	
b	0.30	0.52	0.012	0.020	0.30	0.45	0.012	0.018	0.30	0.45	0.012	0.018	
С	0.12	0.21	0.005	0.0083	0.12	0.21	0.005	0.0083	0.12	0.21	0.005	0.0083	
D	20.82	21.08	0.820	0.830	18.313	18.517	0.721	0.729	20.82	21.08	0.820	0.830	
E1	10.03	10.29	0.391	0.400	10.03	10.29	0.395	0.405	10.03	10.29	0.395	0.405	
Е	11.56	11.96	0.451	0.466	11.56	11.96	0.455	0.471	11.56	11.96	0.455	0.471	
е	1.27 BSC		0.050 E	0.050 BSC		0.800 BSC		0.0315 BSC		0.80 BSC		0.031 BSC	
L	0.40	0.60	0.016	0.024	0.406	0.597	0.016	0.0235	0.40	0.60	0.016	0.024	
ZD	0.95	REF.		0.805 REF.		REF.			0.875 REF.				
α	0°	5°	0°	5°	0°	5°	0°	5°	0°	5°	0°	5°	